

| BK | NUM | ANS | QUESTION  | ANSWER A  | ANSWER B  | ANSWER C   | ANSWER D  | ILLUST  |
|----|-----|-----|---|---|---|--|---|---------|
| 13 | 1   | D   | A bridge gage is normally used to determine turbine .   | bearing oil clearance                                 | diaphragm tip clearance   | blade axial clearance  | bearing wear  |         |
| 13 | 2   | B   | Coast Guard Regulations (46 CFR) requires machinery driving the fuel oil transfer and fuel oil service pumps to be fitted with a remote means of stopping that machinery .  | within the space concerned                            | outside of the space concerned                                  | at the throttle station  | within the fireroom   |         |
| 13 | 3   | D   | If a ship is to be laid up for an indefinite period, the saltwater side of the main condenser should be .   | left filled with saltwater with the sea valves closed | left filled with saltwater with the sea valves open             | drained and refilled with saltwater after closing the sea valves | drained and dried out after closing the sea valves                |         |
| 13 | 4   | D   | According to U.S. Coast Guard Regulations (46 CFR), which of the following pumps is required to have a pressure gage provided on the discharge side of the pump?  | Fire pump   | Boiler Feed pump  | Fuel oil transfer pump   | All of the above  |         |
| 13 | 5   | D   | Assume that steam has formed in a boiler in which all of the steam stop valves are closed, and the water level is held constant. When there is an increase in the temperature of the steam and water in the boiler, which of the following effects will occur on the pressure and the specific volume of the steam? | The steam pressure and volume will remain constant.   | The pressure will increase and the volume will remain constant. | The pressure will remain constant and the volume will increase.  | The pressure will increase and the specific volume will decrease. |         |
| 13 | 6   | B   | When a mixture of steam and water in a boiler has reached the point at which NO further change in state can occur with the addition of heat, the mixture is considered to have reached its .  | supercritical end point                               | critical end point  | vaporization end point   | saturation end point  |         |
| 13 | 7   | D   | Which symbol shown in the illustration is used to identify a stop-check valve on a drawing?   | A   | B   | C  | D   | SG-0014 |
| 13 | 8   | D   | If the water level cannot be seen in the lower part of the boiler gage glass, which of the following actions must be carried out immediately?   | Increase the feedwater going to the boiler.           | Check the DC heater water level.                                | Blowdown the boiler.   | Secure the boiler fires.  |         |

|    |    |   |   |   |  |  |   |         |
|----|----|---|---|---|--|--|---|---------|
| 13 | 9  | D | The item labeled "C" in the illustration, is the _____ .  | low pressure drain connection                               | high pressure drain connection                             | low pressure vent connection   | low pressure steam supply connection                                | SG-0025 |
| 13 | 10 | D | Fuel oil solenoid valves at the burner fronts should be of the manual reset type to _____ .   | permit the operator to secure each burner during a blackout | permit the operator to secure each burner after a blackout | prevent the furnace filling with oil during a power failure                        | prevent the furnace filling with oil after restoration of power     |         |
| 13 | 11 | C | Axial movement in a gear-type flexible coupling is provided for by _____ .  | each gear sliding on its shaft between retaining collars    | the variable oil clearance in the quill shaft              | gear teeth on the floating member sliding between internal teeth on the shaft ring | adjusting the pitch of the teeth on the pinion and high speed gears |         |
| 13 | 12 | B | A sectional (sinuous) header boiler is classified as which of the listed boiler types?  | Bent tube   | Straight tube  | Express  | D-type  |         |
| 13 | 13 | D | Which of the listed order of valves represents the proper installation of the main feedwater supply line to a marine propulsion boiler?       | Regulator, stop, stop-check                                 | Stop-check, stop, regulator                                | Stop, regulator, stop-check  | Stop-check, regulator, stop   |         |
| 13 | 14 | B | Which of the following fuel oil characteristics establishes the danger point when transferring, pumping, and firing procedures are concerned? | Fire point  | Flash point  | Specific gravity   | Viscosity   |         |
| 13 | 15 | C | When condenser tube ends are rolled into both tube sheets, the different rates of material expansion is compensated for by utilizing _____ .  | belled joints at both tube ends                             | threaded brass ferrules on the tube ends                   | expansion joints in the condenser shell  | metallic packing pressed around the tube ends                       |         |
| 13 | 16 | A | The Butterworth heater shown in the illustration receives steam at approximately _____ .  | 130 psi   | 170 psi  | 205 psi  | 850 psi   | SG-0005 |
| 13 | 17 | B | The BTU value of fuel oil is determined by a/an _____ .   | open cup test   | calorimeter  | hydrometer   | viscosimeter  |         |
| 13 | 18 | B | The variable capacity pressure atomizing fuel oil burner functions to _____ .   | maintain a constant fuel temperature                        | provide a wide range of combustion                         | provide a constant fuel return pressure  | maintain smokeless fuel oil atomization                             |         |
| 13 | 19 | D | As the pH of the boiler water approaches zero, the water becomes increasingly _____ .   | soft  | alkaline   | neutral  | acidic  |         |

|    |    |   |   |  |   |  |   |  |
|----|----|---|---|--|---|--|---|--|
| 13 | 20 | B | A combustion control system diaphragm type air flow transmitter receives its high pressure signal from the boiler .   | fan discharge  | windbox   | furnace  | smoke box   |  |
| 13 | 21 | C | Concerning the classification of steam turbines, a cross compound designed unit .   | consists of reaction stages and a dummy piston                                   | consists of one Curtis stage and reaction blading   | consists of a high pressure turbine, crossover pipe, and low pressure turbine            | is made up of a varied assortment of impulse and reaction staging                             |  |
| 13 | 22 | B | A sectional (sinuous) header boiler is classified as a/an .   | bent tube type   | straight tube type  | "A" type   | "D" type  |  |
| 13 | 23 | D | The required number of pounds of steam generated per hour to develop contract shaft horsepower and maintain the specified pressures and temperatures in the plant, when divided by the number of installed boilers, will give the . | overload capacity for each boiler  | efficiency of each boiler   | efficiency of each fireroom  | full power capacity of each boiler  |  |
| 13 | 25 | D | Condensate return lines from tank heating coils are led to the .  | atmospheric drain tank   | main condenser  | DC heater  | contaminated drain system   |  |
| 13 | 26 | A | In which of the listed components is chemical energy converted to thermal energy with regards to boiler operation?  | Furnace  | Superheater   | Steam drum   | Economizer  |  |
| 13 | 27 | A | Coast Guard Regulations (46 CFR) regarding hydrostatic testing of main steam piping state that .  | the hydrostatic test shall be applied from the boiler drum to the throttle valve | not less than fifty percent of the lagging shall be removed each time the hydrostatic test is applied | the hydrostatic test pressure must be maintained on the piping for a minimum of one hour | a pipe with a nominal size of six inches or more is not required to be hydrostatically tested |  |
| 13 | 28 | A | If the water level in a steaming boiler is dropping rapidly and cannot be kept at the normal level by standard practices, you should .  | secure the fires and then secure the steam stop                                  | secure the steam stop and then secure the fires   | blowdown the guage glass to find the true water level                                    | speed up the feed pump to raise the water to normal   |  |

|    |    |   |  |  |   |  |   |  |
|----|----|---|--|--|---|--|---|--|
| 13 | 29 | C | The total heating surface of any steam generating unit is comprised of which of the listed surfaces?   | Those parts of a boiler which are exposed on one side to only the water being heated and on the other side to the combustion gases, such as the economizer surfaces. | Those parts of a boiler which are exposed on one side to only the steam being heated and on the other side to the combustion gases, such as the superheater surfaces. | Those parts of a boiler which are exposed on one side to the water or steam being heated, and on the other side to the combustion gases. | Those parts of a boiler which are exposed on one side to only the water being heated and on the other side being directly exposed to the furnace flame. |  |
| 13 | 30 | C | A combustion control system, diaphragm-type, air volume regulator receives its low pressure signal from the boiler .   | windbox  | casing  | furnace  | smoke pipe  |  |
| 13 | 31 | A | In a cross-compound main propulsion unit, the astern turbine is usually installed at the .   | low pressure end of the low pressure turbine   | high pressure end of the low pressure turbine   | low pressure end of the high pressure turbine  | high pressure end of the high pressure turbine  |  |
| 13 | 32 | A | The purpose of a 'peep' hole in the boiler casing is to .  | examine the condition of the flame   | check the operation of the soot blowers   | check for excess smoke in the stack  | examine the condition of the refractory cones   |  |
| 13 | 33 | B | Which of the listed characteristics is determined by calculating the amount of heat absorbed by the water and steam, then dividing by the available heat in the total pounds of fuel oil burned? | Fireroom efficiency  | Boiler efficiency   | Plant efficiency   | Each of the above   |  |
| 13 | 34 | C | If a centrifugal main feed pump were operated at shutoff head with the recirculating line closed, which of the following conditions could occur?   | A decreased water level in the DC heater.  | An increased water level in the steam drum.   | Flashing at the suction side of the pump.  | Excessive diaphragm seal wear in the feedwater regulator.   |  |
| 13 | 35 | D | If a vessel is steaming at a steady rate, and the water level has dropped out of sight in the boiler gage glass, the FIRST corrective action should be to .                                      | open the feedwater bypass regulator  | blowdown the boiler guage glass   | slow down the engines  | cut out the fires   |  |

|    |    |   |   |   |   |  |  |  |
|----|----|---|---|---|---|--|--|--|
| 13 | 36 | A | Which of the stated pressure conditions identifies the boiler design pressure?  | The pressure specified by the manufacturer as a criteria for boiler design. | A pressure lower than boiler operating pressure.              | The same pressure as the boiler operating pressure at full power capacity. | The pressure at which a boiler is operated during overload conditions.         |  |
| 13 | 37 | B | Coast Guard Regulations require safety and relief valves for steam or air service to be provided with a substantial lifting device, capable of lifting the disc from its seat at what percentage of the set pressure? | 50%   | 75%   | 110%   | 125%   |  |
| 13 | 38 | D | The process of breaking up fuel oil into fine particles to ensure good combustion is called _____.  | settling  | straining   | pumping  | atomization  |  |
| 13 | 39 | C | Depending upon the design of the boiler, the constant pressure maintained at the steam drum or the superheater outlet is known as the _____.  | design pressure   | overload pressure   | operating pressure   | output pressure  |  |
| 13 | 40 | C | In the event of a failure of the pneumatic control system, a multi-element feedwater regulator is designed to operate as a _____.   | constant-pressure regulator   | constant-volume feedwater regulator                           | manually controlled feedwater regulator                                    | thermo-hydraulic feedwater regulator   |  |
| 13 | 41 | A | An efficient seal is obtained between the upper and lower halves of a turbine casing by _____.  | precision metal-to-metal contact  | copper gaskets  | asbestos gaskets   | flexible steel seal strips   |  |
| 13 | 42 | D | Which of the listed systems would be a potential source for the high pressure drain system?   | Galley steam tables   | Laundry steam pressing machines                               | Fuel oil tank heating coils  | Steam systems operating in excess of 150 psi                                   |  |
| 13 | 43 | C | How is boiler water forced to circulate faster in accelerated natural circulation boilers, than in free natural circulation boilers?  | Increasing the density of the water.  | Installing a water circulating pump, such as a hydro-kineter. | Increasing the inclined angle of the generating tubes.                     | Increasing the surface area of the economizer exposed to the combustion gases. |  |

|    |    |   |   |  |  |  |  |  |
|----|----|---|---|--|--|--|--|--|
| 13 | 44 | D | During initial starting of the standby turbine-driven boiler feed pump, which of the listed valves should remain closed?  | Turbine exhaust valve                        | Turbine steam supply valve                               | Pump suction valve                           | Pump discharge check valve                                       |  |
| 13 | 45 | A | The temperature of the fuel oil received during bunkering operations is critical in determining the _____.  | expansion space to leave in a tank           | flash point at which the fuel will burn                  | temperature to which the fuel must be heated | rate at which the fuel can be pumped during transfer operations  |  |
| 13 | 46 | D | A natural circulation water-tube boiler, with one or more water drums, would be classified as a/an _____.   | accelerated natural circulation boiler       | controlled circulation boiler                            | header-type boiler                           | drum-type boiler   |  |
| 13 | 47 | C | The flash point of a residual fuel oil should be used to determine the highest temperature to which the oil may be heated _____.  | for atomizing                                | for centrifuging   | in a storage tank                            | in the recirculating line  |  |
| 13 | 48 | C | In addition to a nozzle, a fuel oil atomizer uses which of the listed parts?  | Ignition electrode                           | Burner cone  | Sprayer plate                                | Air cone   |  |
| 13 | 49 | C | The major heat loss in a marine boiler is from the heat _____.  | used in the economizer and air heater        | passing through the boiler casing                        | carried away by combustion gases             | required to change water into steam                              |  |
| 13 | 50 | C | That portion of the steam drum, containing a manhole for internal access to the drum, for the purpose of cleaning, inspecting, and carrying out repairs, is called the _____. | end plate                                    | wrapper sheet  | drumhead                                     | tube sheet   |  |
| 13 | 51 | A | Carbon ring packing segments are secured in a turbogenerator gland by means of _____.   | garter springs                               | centering rings  | steam pressure                               | labyrinth rings  |  |
| 13 | 52 | C | Which of the following statements represents the major difference between a boiler drum and a header?   | The temperatures at which they are operated. | The number of tubes permitted to enter a drum or header. | The size of each is significantly different. | The size of the tubes permitted to penetrate the drum or header. |  |
| 13 | 53 | B | In a single furnace boiler, where is the steam typically cooled for use as auxiliary steam?   | Superheater                                  | Desuperheater  | Condenser                                    | Air ejector  |  |

|    |    |   |  |  |   |  |   |  |
|----|----|---|--|--|---|--|---|--|
| 13 | 54 | B | To prevent pulsations from developing in the feedwater lines the discharge side of a reciprocating feed pump is equipped with a/an _____ .                                       | feedwater regulator  | air chamber   | relief valve   | reed valve  |  |
| 13 | 55 | B | When the boiler is operating at high firing rates, in addition to the generating tubes, which of the following tubes will also function as generating tubes?                     | Downcomers and water wall tubes                                    | Superheater support, water screen, and water wall tubes                             | Water screen, superheater support, and economizer tubes  | Water wall, water screen, and economizer tubes  |  |
| 13 | 56 | D | The main feed pump aboard ship can handle high temperature water without becoming vapor bound because the _____ .  | pump operates at a high discharge pressure                         | constant-pressure governor controls the discharge pressure                          | area above the impeller eye is vented to the main condenser  | required net positive suction pressure is designed into the system                    |  |
| 13 | 57 | C | The flash point of a residual fuel oil should be used to determine the _____ .   | highest temperature to which the oil may be heated for atomization | minimum temperature to which the oil should be heated for transferring              | highest temperature to which the oil may be heated in a storage tank                               | minimum temperature to which the oil should be heated in the fuel oil heater          |  |
| 13 | 58 | D | In order for a maximum number of boiler generating and circulating tubes to be installed without weakening the tube sheet, which of the listed procedures should be carried out? | All rows of tubes should be bent at the same angle.                | All rows of tubes should be installed horizontal to the drum.                       | Different rows of tubes should be bent to enter the drum at any convenient angle.                  | All tubes should be installed normal to the drum surfaces.                            |  |
| 13 | 59 | D | The main feed pump discharge pressure is controlled by the admission of steam to the turbine. The admission of steam is normally regulated by a _____ .                          | flyweight controlled regulating valve                              | nozzle arrangement  | speed-limiting governor  | constant-pressure governor  |  |
| 13 | 60 | D | As found in a basic pneumatic automatic combustion control system, the function of a standardizing relay is to _____ .   | provide a backup means for manual control of the system            | control the boiler drum water level within acceptable limits regardless of the load | mechanically position valves or dampers in accordance with the amount of control pressure received | introduce a control for maintaining constant steam pressure regardless of boiler load |  |

|    |    |   |   |  |   |  |  |  |
|----|----|---|---|--|---|--|--|--|
| 13 | 61 | A | Which of the following methods is used to counter axial thrust in a single flow reaction turbine?   | A dummy piston and cylinder at the turbine inlet end   | Pressure equalizing holes in the individual rotor wheels  | Labyrinth packing  | Carbon packing   |  |
| 13 | 62 | C | Corrosion due to electrolytic action in modern water-tube boilers is uncommon because _____.  | boiler water is a strong electrolytic  | alkalinity control treatment prevents electrolytic action   | boiler components are generally constructed of similar metals  | electrolytic action cannot occur at high pressure                                    |  |
| 13 | 63 | A | Which of the following statements describes those portions of the piping maintained under positive pressure when a pressure-closed feed system is in operation? | All condensate and feed piping except for a short section between the condenser and condensate pump. | Only the section between the condensate pump and deaerating feed tank.  | Only the section between the deaerating feed tank and the boiler.  | Only the section between the condenser and the condensate pump.                      |  |
| 13 | 64 | A | Recirculation of the feedwater ensures a flow of water through the _____.   | main feed pump   | economizer  | standby feed pump suction line   | third stage heater   |  |
| 13 | 65 | B | Which of the listed components would be considered the dividing line separating the condensate system from the feedwater system?                                | Main condenser   | Deaerating feed tank  | Main air ejectors  | Boiler drum  |  |
| 13 | 66 | B | Which of the following statements describes what effect, if any, the change in temperature or pressure may have upon dissolved oxygen?                          | It slows the corrosive effect when both pressure and temperature are increased.                      | It speeds the corrosive effect with increased pressure and slows its corrosive effect with increased temperature. | It speeds the corrosive effect with lowered pressure and speeds its corrosive effect with increased temperature. | Temperature and pressure have no effect on the corrosive effect of dissolved oxygen. |  |
| 13 | 67 | D | When heating fuel oil used in main propulsion boilers aboard ship, the flash point may be exceeded only when _____.   | it is necessary to transfer the fuel   | the boiler is being fired under maximum load  | the superheater temperature has been higher than normal  | it is required for proper atomization  |  |

|    |    |   |   |  |   |   |   |  |
|----|----|---|---|--|---|---|---|--|
| 13 | 68 | C | The primary purpose of the sprayer plate in a mechanical atomizing oil burner is to _____.  | completely mix air with the fuel                   | assist in mixing atomizing steam with the fuel            | produce a fine, swirling, uniform fuel mist                   | prevent primary air mixing with the fuel                          |  |
| 13 | 69 | B | The amount of sodium phosphate in treated boiler water can be measured by a/an _____.   | alkalinity test                                    | phosphate test  | chloride test   | sodium phosphorous test   |  |
| 13 | 70 | D | If a ship with an automated engine room system develops a 'high' boiler water level at half speed, the _____.   | main feedwater stop valve will automatically close | main feed pump recirculating line will automatically open | surface blow valve will automatically open to lower the level | throttle will be automatically prevented from opening any further |  |
| 13 | 71 | D | Which of the following types of main propulsion turbines is most likely to require a dummy piston or cylinder arrangement to counterbalance axial thrust? | Double flow impulse turbine                        | Multistage impulse turbine                                | Double flow reaction turbine                                  | Single flow reaction turbine                                      |  |
| 13 | 72 | C | Longitudinal expansion of a boiler water drum is permitted by the _____.  | tubes  | casing  | foundation  | refractory  |  |
| 13 | 73 | B | Why is it necessary to have a relief valve protect the deaerating feed tank from internal pressure?   | Because the tank receives auxiliary exhaust.       | Because the tank receives high pressure drains.           | Because the tank receives large amounts of water.             | Because the tank receives small amounts of water.                 |  |
| 13 | 74 | C | Which of the components listed prevents water from flowing back into the auxiliary exhaust line if the deaerating feed tank becomes flooded?              | Exhaust piping                                     | Pumps   | Check valve   | Reverse-acting relief valve                                       |  |
| 13 | 75 | D | Air removed from the main condenser is vented to the atmosphere through the _____.  | vacuum breaker                                     | vent condenser  | atmospheric drain tank  | aftercondenser  |  |
| 13 | 76 | C | Which of the pumps listed operates at constant speed and delivers water to the deaerating feed tank at a nearly constant pressure?                        | Main feed booster pump                             | Main feed pump  | Main condensate pump  | Main circulating pump   |  |
| 13 | 77 | A | Which characteristic of fuel oil is the most significant when determining the temperature to which the fuel oil must be heated for proper atomization?    | Viscosity  | Flash point   | Pour point  | Specific gravity  |  |

|    |    |   |   |  |   |   |  |         |
|----|----|---|---|--|---|---|--|---------|
| 13 | 78 | A | The purpose of the relief valve in a fuel oil service system is to _____ .  | protect the service pump from high discharge pressure                  | regulate the atomizer oil pressure  | control the oil pressure regulators                                     | supply constant pressure to the burner combustion control valves     |         |
| 13 | 79 | B | Condensate pumps have distinctly noticeable characteristics and are recognized by their _____ .   | speed-limiting governors and closed impellers                          | large suction chambers and impeller eyes  | multiple impellers and pump shaft positions                             | open impellers and power ends  |         |
| 13 | 80 | C | Which of the devices listed is used to keep overheated condensate from flowing to the deaerating feed tank?   | Saltwater cooler   | Freshwater cooler   | Recirculating line to the main condenser                                | Recirculating line to the main feed pump                             |         |
| 13 | 81 | A | The purpose of the reaction turbine dummy piston is to _____ .  | counteract axial thrust toward the turbine low pressure end            | act in conjunction with gland seal steam to balance turbine thrust  | assist in maintaining radial clearances                                 | eliminate axial thrust caused by velocity increases in moving blades |         |
| 13 | 82 | B | Which of the following statements represents the purpose of boiler sliding feet?  | To ensure an airtight seal between the boiler inner and outer casings. | To accommodate the changing length of the water drum as it expands or contracts with temperature changes. | To compensate for deflection of the hull in way of the boiler supports. | To allow for unequal expansion between the wrapper and tube sheets.  |         |
| 13 | 84 | A | The net positive suction head of a boiler centrifugal feed pump should be calculated over and above the _____ .   | feedwater vapor pressure   | speed of the impeller   | pump capacity in gpm  | impeller ratio of the pump   |         |
| 13 | 85 | D | To combat galvanic corrosion, condensers utilizing copper-nickel waterboxes are usually fitted with _____ .   | bonding straps   | iron or steel anodes  | protective coatings   | all of the above   |         |
| 13 | 86 | B | In the illustrated hydraulically operated turbine gland seal regulator, the exhaust dump valve is closed as a result of the piston being actuated by a/an _____ . | bellows at "I"   | spring at "F"   | vacuum at "G"   | pressure at "A"  | SE-0019 |

|    |    |   |  |   |  |  |  |         |
|----|----|---|--|---|--|--|--|---------|
| 13 | 87 | C | Modern fuel oil temperature control devices are regulated to obtain a desired viscosity rather than a specific fuel oil temperature because .                    | residual fuel oils have the same viscosity characteristics regardless of where they are refined | the temperature of the fuel oil varies with the flow rate through the heater | the relationship between temperature and viscosity varies with different fuels | viscosity regulation eliminates the need for close control of the fuel/air ratio |         |
| 13 | 88 | A | In the hydraulically operated turbine gland seal regulator, illustrated, the device used as the gland seal pressure sensing unit is called a/an .                | bellows   | manifold   | pilot valve  | pivot rods and block   | SE-0019 |
| 13 | 89 | C | A test of boiler water for chloride content indicates the amount of .  | suspended matter present  | dissolved gases present  | seawater contamination present   | all of the above   |         |
| 13 | 90 | D | The boiler feedwater control valve varies the unity relationship between steam and water flow during periods of .  | minimum boiler load   | steady boiler load   | overload operation   | load change  |         |
| 13 | 91 | A | In a multistage reaction turbine, the dummy piston and cylinder function to .  | reduce axial thrust   | dynamic balance of the rotating rotor  | eliminate the pressure drop across the blades                                  | provide a means of measuring axial clearances                                    |         |
| 13 | 92 | B | A common type of air heater used in sectional header marine boilers is the .   | direct contact type   | gas tubular type   | Harrison crossflow type  | parallel flow type   |         |
| 13 | 93 | C | Gland sealing steam is used during steam turbine operation to prevent the loss of .  | oil   | air  | vacuum   | temperature  |         |
| 13 | 94 | D | Low pressure steam is used to keep air from leaking into turbine casing along the turbine shaft. For this purpose, which of the following steam systems is used? | Direct admission of 35 psi (241.3 kPa) auxiliary steam  | Superheated steam system   | Gland leakoff steam system   | Gland sealing steam system   |         |
| 13 | 95 | C | In a closed feed and condensate system, the drain from the second stage air ejector returns directly to the .  | auxiliary condenser   | loop seal  | atmospheric drain tank   | deaerating feed tank   |         |

|    |     |   |  |   |   |   |  |  |
|----|-----|---|--|---|---|---|--|--|
| 13 | 96  | B | Which of the water supplies listed below is typically used as a cooling medium for the gland exhaust condenser, intercondenser, and aftercondenser of an air ejector unit? | Seawater  | Condensate  | Potable water   | Evaporator distillate  |  |
| 13 | 97  | C | The viscosity of a residual fuel oil is measured in Saybolt _____.   | Milliliters Universal   | Millimeters Universal   | Seconds Furol   | Minutes Universal  |  |
| 13 | 98  | A | Relief valves in the fuel oil service system discharge to either the service pump suction or the _____.  | settling tanks  | recirculating line  | simplex fuel oil strainer                                 | slop retention tank  |  |
| 13 | 99  | D | Testing boiler water for chloride content will indicate the amount of _____.   | total alkalinity in the water   | phosphates present in the water   | methyl orange that should be added                        | dissolved salts from sea contamination                                       |  |
| 13 | 100 | D | If the entire pneumatic control to a multi-element feedwater regulator fails, the feedwater valve is controlled by _____.  | constant pump pressure regulator  | remote manual control regulator   | single-element feedwater regulator                        | local manual control   |  |
| 13 | 101 | A | One stage in an impulse turbine consists of a set of nozzles in which _____.   | a single pressure drop occurs followed by one or more rows of moving blades | a single velocity drop occurs followed by one row of moving blades  | steam expands and impinges on the row of reversing blades | velocity decreases and pressure increases followed by a row of moving blades |  |
| 13 | 102 | C | One advantage of installing water wall tubes in a boiler furnace is to _____.  | increase furnace size   | reduce furnace temperature  | decrease refractory maintenance                           | reduce combustion rates  |  |
| 13 | 103 | A | Which statement listed represents a vital function of the main condenser?  | The recovery of feedwater for reuse.  | Cooling of the exhaust steam from the auxiliary exhaust system before it enters the deaerating feed tank. | Storage of feedwater for immediate use in the boilers.    | Condensing of the exhaust steam from the main feed turbine pumps.            |  |

|    |     |   |  |   |   |   |   |         |
|----|-----|---|--|---|---|---|---|---------|
| 13 | 104 | D | Which of the listed conditions aids in directing gland leakoff steam from the low pressure propulsion turbine to pass through the gland exhaust condenser? | Steam pressure from the low pressure turbine.   | Steam pressure from the high pressure turbine.    | Compressed air in the air pilot.  | The use of a gland exhaust fan.   |         |
| 13 | 105 | D | Heat introduced to the condenser by exhausting steam is removed by the circulation of _____.   | reserve feedwater                               | cold condensate                                   | low pressure drains   | seawater  |         |
| 13 | 106 | C | What unit, or factor creates most of the vacuum within a tight and adequately cooled main condenser once the main engine is in operation?                  | Main condensate pump                            | Main air ejector                                  | Condensation of turbine exhaust steam   | Counterflow of seawater over the surface of the tubes with the flow of exhaust steam in the tubes |         |
| 13 | 107 | C | In what positions will the air-operated regulating valves, shown in the illustration, be in when the steam in the gland seal supply line is excessive?     | Both valves are open.                           | Both valves are closed.                           | The excess steam unloading valve is open and the supply pressure control valve is shut. | The excess steam unloading valve is shut and the supply pressure control valve is open.           | SE-0020 |
| 13 | 108 | C | The primary objective of the auxiliary exhaust system is to supply steam to the _____.   | main condenser                                  | main feed pumps                                   | deaerating feed tank  | soot blowers  |         |
| 13 | 109 | A | You should blow down a gage glass periodically to _____.   | remove any sediment from the glass              | maintain the proper water level in the steam drum | provide water samples for the second assistant  | test the feedwater stop-check valve   |         |
| 13 | 110 | C | Fine adjustments to a boiler combustion control system, to bring about near perfect combustion, should be made by manually adjusting the _____.            | fuel oil back pressure                          | air volume regulators                             | fuel/air ratio knob   | forced draft fan dampers  |         |
| 13 | 111 | D | An impulse-reaction turbine is characterized by which of the following arrangements?   | Impulse diaphragms with reaction rotor blading. | Stationary nozzles with impulse rotor blading.    | Reaction stages followed by velocity-compounded blading.                                | Velocity-compounded stages followed by reaction blading.  |         |

|    |     |   |   |  |  |   |   |         |
|----|-----|---|---|--|--|---|---|---------|
| 13 | 112 | D | The advantage of installing water wall tubes in a boiler furnace is to .  | increase the flow of gases through the furnace   | decrease the flow of gases through the furnace   | increase heat transfer to the mud drum  | permit higher combustion rates  |         |
| 13 | 113 | B | Steam drum water level indicators must be calibrated to compensate for density differences between the indicated drum water level, and the actual drum water level. If no compensation is made, the indicator will show a . | lower level than exists in the drum with the error becoming greater as the drum pressure decreases | lower level than exists in the drum with the error becoming greater as the drum pressure increases | higher level than exists in the drum with the error becoming greater as the drum pressure decreases | higher level than exists in the drum with the error becoming greater as the drum pressure increases |         |
| 13 | 114 | D | When vapor is in contact with and remains at the same temperature as the boiling liquid from which it was generated, the vapor and liquid are said to be in a/an .  | latent contact   | critical state   | sensible contact  | equilibrium contact   |         |
| 13 | 115 | A | The main condensate pump in a steam propulsion plant discharges directly to the .   | air ejector intercondenser   | main condenser hotwell   | air ejector aftercondenser  | DC heater vent condenser  |         |
| 13 | 116 | A | The set point pressure at which the first boiler safety valve is to lift is the .   | maximum steam drum pressure  | boiler overload capacity   | operating design pressure   | boiler full-power capacity  |         |
| 13 | 117 | A | The items labeled "D" in the illustration are the .   | low pressure drain connections   | high pressure drain connections  | low pressure vent connections   | low pressure steam supply connections   | SG-0025 |
| 13 | 118 | A | Which of the boiler components listed receives feedwater and serves as an area for the accumulation of saturated steam?   | Steam drum   | Headers  | Water drum  | Superheater headers   |         |
| 13 | 119 | D | Which of the listed boiler components is used to equalize the distribution of water to the generating tubes and provide an area for the accumulation of loose scale and other solid matter present in the boiler water?     | Downcomer  | Steam drum   | Water drum only   | Water drum and headers  |         |

|    |     |   |   |   |  |  |  |         |
|----|-----|---|---|---|--|--|--|---------|
| 13 | 120 | C | When firing a boiler in local manual control, an increase in boiler load must be accompanied by a/an .  | increase in the fuel oil flow before an increase in the forced draft pressure | decrease in the forced draft air pressure before a decrease in the fuel oil flow | increase in the forced draft air pressure before an increase in the fuel oil flow  | increase or a decrease in the fuel oil flow and forced draft air pressure simultaneously |         |
| 13 | 121 | B | Design characteristics of a velocity-compounded impulse turbine include the utilization of .  | one or more nozzles with one row of rotating blades                           | a single pressure stage with two or more velocity stages                         | a low velocity steam jet from a nozzle   | two or more simple impulse stages  |         |
| 13 | 122 | C | Rows of tubes installed along the walls, floor, and roof of the furnace are called .  | screen tubes  | downcomers   | water walls  | water headers  |         |
| 13 | 123 | B | The connection labeled "B" in the illustration is used to .   | maintain a vacuum in the shell of the feed water heater                       | provide a point of admission for the steam air heater drains                     | provide a point of admission for the L.P. bleed steam                              | drain condensate from the feed water heater to the main condenser                        | SG-0025 |
| 13 | 124 | C | Which of the tube types listed can be considered to serve as downcomers at low firing rates, and as generating tubes at high firing rates on some boilers?  | Water screen tubes  | Water wall tubes   | Superheater support tubes  | Riser tubes  |         |
| 13 | 125 | B | Which of the following actions should be taken to reestablish a 'blown' air ejector loop seal?  | Increase the condensate flow through the air ejector.                         | Momentarily close the valve in the loop seal line, then reopen slowly.           | Shut off the steam to the second stage air ejector momentarily then open it again. | Decrease the steam pressure to the air ejector nozzles.                                  |         |
| 13 | 126 | D | The life of the furnace lining can be affected by .   | the quality of installation   | the service environment  | the proper application of inspection criteria                                      | all of the above   |         |
| 13 | 127 | A | In most marine boilers, the primary reason the first few rows of generating tubes, called screen or furnace row tubes, are made larger in diameter than the rest of the generating tubes is because . | they require more water flow since they are exposed to the greatest heat      | they must screen the superheater from the direct radiant heat of the burners     | they must act as downcomers to ensure proper circulation                           | their main function is to retard combustion gas flow for maximum heat transfer rates     |         |

|    |     |   |   |  |  |  |  |  |
|----|-----|---|---|--|--|--|--|--|
| 13 | 128 | A | Boiler refractories previously baked out and fired are more sensitive to .  | rapid cooling  | sustained high furnace temperature   | rapid heating  | shock and vibration  |  |
| 13 | 129 | A | A unit of measure used to express the chloride content of boiler water is .   | PPM  | Micro-Farads   | pH   | Micro-Ohms   |  |
| 13 | 130 | D | Which of the following devices can be used to secure or hold furnace refractory in position?  | Brick bolts  | Boiler tubes   | Anchor strips  | All of the above   |  |
| 13 | 131 | B | When turbine rotor shafts extend through the casing, an external source of sealing steam is used in conjunction with labyrinth packing to . | maintain the rotor journal temperature   | seal the casing during periods of low casing pressure                              | seal the casing during periods of high casing pressure               | provide a constant flow to the gland leak off condenser                  |  |
| 13 | 132 | A | A corbel in the furnace of a water-tube boiler is a fillet of plastic refractory used as a .  | means of excluding slag from the joints at the furnace floor, walls, and corners   | preformed burner arch section  | foundation for refractory anchor bolts                               | set of gas baffles in the screen tubes                                   |  |
| 13 | 133 | C | Nichrome wire is used when patching boiler furnaces for .   | anchoring plastic refractory only  | reinforcing castable and plastic refractory  | anchoring castable refractory only                                   | anchoring castable and plastic refractory                                |  |
| 13 | 134 | C | Which of the following statements is correct regarding the start-up operation of a noncondensing turbine-driven feed pump?                  | Keep the steam exhaust valve closed until steam is applied to ensure that the auxiliary exhaust line pressure does not drop. | Keep the pump casing vent valve closed until flow is established through the pump. | Open the pump suction valve prior to admitting steam to the turbine. | Secure all drains prior to admitting any steam to avoid damage to traps. |  |
| 13 | 135 | A | In a main propulsion steam turbine installation, the condensate pump initially discharges to the .  | air ejector condenser  | deaerating feed tank   | first stage heater   | distillate tank  |  |
| 13 | 136 | A | Slagging of boiler furnaces is a slow progressive action which is accelerated by .  | fuel oils having high ash content  | low firing rates   | prolonged feedwater contamination of fuel oil                        | burning diesel fuel  |  |
| 13 | 137 | A | Which constituent of fuel oil determines the specific heat?   | Hydrocarbons   | Oxygen   | Nitrogen   | Sulphur  |  |

|    |     |   |  |   |   |  |  |  |
|----|-----|---|--|---|---|--|--|--|
| 13 | 138 | B | Which of the listed refractory materials is capable of providing structural stability?       | Chrome castable   | Firebrick   | Insulating brick   | Insulating block   |  |
| 13 | 139 | A | Boiler water samples should be circulated through a cooling coil prior to analysis because . | this keeps the water from flashing into steam as it is drawn from the higher pressure of the boiler to the lower pressure of the fireroom | it reduces the amount of suspended matter that frequently finds its way into the dead end lines | the cool sample has a higher conductivity measurement and the total dissolved solids in the water are easier to identify | the degree of acidity as measured on the pH recorder is amplified by cool water temperatures |  |
| 13 | 140 | D | Which of the following statements represents the function of insulating brick?               | Provides structural stability.  | Acts as a gas-side layer at high temperature areas in D-type boilers.                           | Provides the first layer at the inside of inner casing.  | Acts as backup insulation behind firebrick, plastic refractory, or castable refractory.      |  |
| 13 | 141 | A | Metallic packing rings are installed in turbine diaphragms to prevent .                      | interstage steam leakage along the shaft  | air from entering the turbine casing  | pressure buildup on both sides of the diaphragm  | steam from escaping to the atmosphere  |  |
| 13 | 142 | B | A corbel in the furnace of a water-tube boiler is a .  | preformed burner arch section   | fillet of plastic refractory  | formation of soot on furnace floor   | type of refractory anchor bolt   |  |
| 13 | 143 | B | Which of the following statements represents the function of insulation block?               | It is used to protect firebrick from maximum temperatures.  | It is generally used as the first layer on the inside of inner casings.                         | It is used to provide structural stability.  | Typically used as a gas-side layer at low temperature areas in D-type boilers.               |  |
| 13 | 144 | A | When operating with the auxiliary feed line, feedwater flow is controlled .                  | manually by throttling the auxiliary feed stop-check valve  | automatically by the main feedwater regulator   | manually by adjustment of the auxiliary feedwater regulator spring setting   | automatically by the economizer bypass   |  |
| 13 | 145 | C | Serious tube leaks in the air ejector condenser assembly will cause .                        | clogged steam strainers   | fouled nozzles  | loss of vacuum   | faulty steam pressure  |  |

|    |     |   |  |  |  |  |  |  |
|----|-----|---|--|--|--|--|--|--|
| 13 | 146 | D | The primary purpose of refractory mortar is .  | to seal brickwork joints                             | to seal tile installation joints         | to provide cushioning of individual pieces against concentrated stresses | all of the above                                   |  |
| 13 | 147 | C | Which of the following refractory materials contains a hydraulic-setting binder and develops strength without needing to be heated in a manner similar to concrete?                          | Plastic fireclay                                     | Plastic chrome ore                       | Castable fireclay  | Refractory mortar                                  |  |
| 13 | 148 | A | Pumps normally used for fuel oil service are .   | positive displacement rotary pumps                   | two-stage centrifugal pumps              | explosion proof gear pumps   | nonvented plunger pumps                            |  |
| 13 | 149 | B | A sample of boiler water can be chemically tested by initially adding a few drops of a specific color indicator, then slowly titrating a standard solution into the water sample until the . | burette reading is zero and the sample color changes | sample undergoes a definite color change | desired pH has been attained in the sample                               | desired amount of standard solution has been added |  |
| 13 | 150 | C | A major difference between the two element and the three element feedwater regulator control systems, is that a three element system will additionally measure and incorporate the .         | drum water level to the feedwater regulator          | steam flow to the feedwater regulator    | feedwater flow as sensed variable  | fuel oil flow to the feedwater regulator           |  |
| 13 | 151 | D | Labyrinth seals used to reduce leakage around a turbine shaft are constructed of .   | spring bound carbon segments                         | braided asbestos covered core segments   | staged rubber composition seal stripping                                 | machined metallic packing strips or fins           |  |
| 13 | 152 | A | A corbel is used in a boiler furnace to .  | protect the expansion joints                         | reduce gas turbulence                    | direct the flow of gases   | contain the furnace heat                           |  |
| 13 | 153 | A | Which of the following refractory materials is preferred for small repairs, particularly where standard size brick or tile cannot be used?   | Castable fireclay                                    | Plastic fireclay                         | Plastic chrome ore   | Chrome castable                                    |  |
| 13 | 154 | B | Which system should be tested by raising the water level in the idle boiler?   | Chemical feed  | Auxiliary feed                           | Auxiliary fuel oil system  | All of the above                                   |  |

|    |     |   |  |  |                                 |                                  |   |  |
|----|-----|---|--|--|---------------------------------|----------------------------------|---|--|
| 13 | 155 | C | The cooling water flow from an air ejector intercondenser and aftercondenser is discharged directly into the .                                 | main condenser hotwell                   | auxiliary condenser hotwell     | condensate and feed system       | atmospheric drain tank                          |  |
| 13 | 156 | D | As a general rule, for proper results castable fireclay must be air cured for .  | 12 hours                                 | 18 hours                        | 24 hours                         | 48 hours or longer                              |  |
| 13 | 157 | B | Which of the significant combustible elements of fuel oil is a major source of boiler corrosion?   | Oxygen                                   | Sulphur                         | Hydrogen                         | Carbon  |  |
| 13 | 158 | B | Which of the pumps listed is normally used in fuel oil service systems?  | Two-stage centrifugal                    | Positive displacement rotary    | Explosion proof gear             | Nonvented plunger                               |  |
| 13 | 159 | B | Phenolphthalein is used as an indicator to test boiler water for .   | hardness                                 | alkalinity                      | hydrazine                        | chloride content                                |  |
| 13 | 161 | D | Where are moisture shields located in a main propulsion steam turbine?   | Around throttle valve stems              | At the steam strainer inlet     | At the inner stage diaphragms    | After the last stage of the ahead rotor blading |  |
| 13 | 162 | A | Boiler refractory firebrick is secured to the casing by .  | slots in the brick engaging anchor bolts | high strength tensile fasteners | studding on the water wall tubes | fast drying plastic refractory mortar           |  |
| 13 | 163 | B | Which of the listed refractory materials will develop required strength only after being heated at a temperature of 1095°C (2000°F) or higher? | Castable fireclay                        | Plastic fireclay                | Castable insulation              | Chrome castable                                 |  |
| 13 | 164 | D | Makeup feedwater is brought into an operating closed feed system via the .   | main feed pump                           | auxiliary feed pump             | feed booster pump                | condenser vacuum drag line                      |  |
| 13 | 165 | D | Steam condensed in the air ejector intercondenser, drains to the .   | atmospheric drain tank                   | aftercondenser drain tank       | vent condenser drain tank        | main condenser through the loop seal            |  |
| 13 | 166 | D | Due to of the curing characteristics of plastic refractory, its use should be avoided in .   | high temperature areas                   | burner fronts                   | small repairs                    | low temperature areas                           |  |
| 13 | 167 | D | Which of the significant combustible elements of fuel oil is a major source of air pollution?  | Hydrogen                                 | Nitrogen                        | Vanadium                         | Sulphur   |  |

|    |     |   |  |   |  |   |  |  |
|----|-----|---|--|---|--|---|--|--|
| 13 | 168 | C | What is indicated by the code number 32Y20 stamped on a burner sprayer plate?  | Sprayer plate orifice area is 0.32 square inch.   | Sprayer plate requires a size 20 tip.  | Sprayer plate orifice was made with a size 32 drill.                              | Sprayer plate requires a minimum of 20 psi fuel pressure.  |  |
| 13 | 169 | B | Phenolphthalein indicator is used in the boiler water test for .   | dissolved oxygen  | alkalinity   | chloride content  | hardness   |  |
| 13 | 170 | C | Which of the listed refractory materials can be used as a substitute for insulating brick and insulating block in certain boiler walls construction? | Insulating cement   | Castable fireclay  | Castable insulation   | None of the above  |  |
| 13 | 171 | A | Which of the following statements represents the function the nozzle assembly performs in an impulse turbine?  | Converts the steam's thermal energy into kinetic energy by increasing its velocity and directing it against the rotor blades. | Provides an area where the steam is prevented from expanding prior to being directed against the rotor blades. | Increases the velocity of the steam without a pressure drop across the diaphragm. | Converts the potential energy of steam into thermal energy by increasing its velocity and directing it against the turbine blades. |  |
| 13 | 172 | A | Boiler refractory anchor bolts are secured to the casing by .  | hooked ends inserted into pads welded to the casing   | slots in the firebrick   | high strength tensile fasteners   | furnace mortar   |  |
| 13 | 173 | D | Which of the listed refractory materials is a suitable substitute for insulating block only?   | Insulating brick  | Insulating cement  | Castable insulation   | None of the above  |  |
| 13 | 174 | B | Which of the listed conditions will always result in dissolved oxygen being carried over from the main condenser?                                    | Priming in the boiler.  | Taking on makeup feed.   | Dumping auxiliary exhaust steam to the main condenser.                            | Excessive DC heater temperature.   |  |
| 13 | 175 | B | The loop seal connected to the main condenser returns the drains from the .  | vent condenser  | intercondenser   | aftercondenser  | all of the above   |  |

|    |     |   |  |  |  |   |  |  |
|----|-----|---|--|--|--|---|--|--|
| 13 | 176 | C | Which of the listed refractory materials would NOT be suitable for use in a wall previously provided with 2-inch thick insulation block, or in the construction of floors, or as a gas-side layer? | Firebrick                              | Insulating brick   | Castable insulation   | All of the above   |  |
| 13 | 177 | C | A desirable property of boiler fuel oil is _____.  | low carbon content per pound of fuel   | high sulphur content for complete combustion               | high BTU content per pound of fuel                                  | low residual acid after combustion   |  |
| 13 | 178 | A | Which of the following statements represents the advantage of castable insulation over either insulating brick or insulating block installations?  | The speed and economy of installation. | Its resistance to high temperatures.                       | Its high comparative strength.                                      | Its comparative greater insulating value.  |  |
| 13 | 179 | A | A sodium sulfite test is performed on a boiler water sample to determine if _____.   | there is any excess sulfite present    | the pH of the boiler water is within the prescribed limits | the dissolved oxygen in the boiler water is within tolerable limits | the hardness factor is maintained as close to zero as possible                                   |  |
| 13 | 180 | A | Which of the listed refractory materials is composed of wool fibers and clay binders?  | Insulating cement                      | Castable fireclay  | Chrome castable ore   | All of the above   |  |
| 13 | 181 | C | Nozzle diaphragms are installed in pressure-compounded impulse turbines to _____.  | support moving blades                  | support shrouding  | hold the nozzles of the stage and admit steam to moving blades      | eliminate blade and nozzle losses  |  |
| 13 | 182 | C | When heated, brickwork in a boiler is kept from buckling by the installation of _____.   | anchor bolts                           | sliding saddles  | expansion joints  | insulating blocks  |  |
| 13 | 183 | D | The primary purpose of insulating cement is _____.   | to seal joints in brickwork            | to anchor insulating block to the casing                   | to cushion the pieces against concentrated stresses                 | to fill voids in the insulation block layers at missing corners or at cutouts for anchor devices |  |

|    |     |   |   |  |   |   |  |  |
|----|-----|---|---|--|---|---|--|--|
| 13 | 184 | B | Under EMERGENCY operating conditions, the proper valve positions for controlling feedwater to the boiler should be the .                      | auxiliary stop-check valve fully open and the auxiliary stop valve used to regulate the amount of flow | auxiliary stop valve fully open and the auxiliary stop-check valve used to regulate the amount of flow                    | auxiliary stop and stop-check valves fully open and the feed pump speed used to regulate the amount of flow | auxiliary stop-check valve fully open and the auxiliary stop valve regulated by the feedwater regulator        |  |
| 13 | 185 | D | Which statement is true concerning two-stage air ejector assemblies?  | Air is removed from the condensate as it passes through the tubes.                                     | In the aftercondenser the air ejector motivating steam is condensed and returned to the main condenser via the loop seal. | The first stage air ejector takes suction on the second stage to increase vacuum.                           | The steam/air mixture from the main condenser is discharged by the first stage jet pump to the intercondenser. |  |
| 13 | 186 | B | Which of the following refractory materials can provide a straight backing surface for insulation block where minor casing warp has occurred? | Castable insulation  | Insulating cement   | Castable fireclay   | Chrome castable  |  |
| 13 | 187 | D | The presence of sulphur in fuel oil will most likely cause .  | a decrease in the ability of the oil to be properly atomized   | an excessive heat content per unit volume   | heavy slag formation on the refractory  | corrosion on the firesides of the boiler   |  |
| 13 | 188 | B | Which atomizing sprayer plate has the largest capacity?   | 4309   | 2909  | 2 PCRS 3509   | 3009   |  |
| 13 | 189 | C | Which of the listed refractory materials may be used with other machinery insulation arrangements outside of the boiler?                      | Castable fireclay  | Refractory mortar   | Insulating cement   | Castable insulation  |  |
| 13 | 190 | A | Brick bolts, tile bolts, and pennant anchors are attached to the inner casing by .  | retaining clips  | fillet welds  | tack welds  | All of the above are correct.  |  |
| 13 | 191 | C | A pressure-velocity compounded impulse turbine consists of .  | velocity compounding with reaction pressure compounding  | several rows of moving blades attached to diaphragms  | two or more stages of velocity compounding  | two or more rows of nozzles in which no pressure drop exists   |  |

|    |     |   |  |  |  |   |   |  |
|----|-----|---|--|--|--|---|---|--|
| 13 | 192 | A | Which of the listed refractory materials can be used in an area directly exposed to the highest heat in the furnace?             | Firebrick                                      | Insulating brick   | Insulating block                                | Baffle mix                                  |  |
| 13 | 193 | D | Which of the following statements represents the primary function of handholes used on a boiler?                                 | To allow access into the steam and water drum. | To allow access for cleaning in the stack.               | To provide access for cleaning out the firebox. | To allow access into the headers.           |  |
| 13 | 194 | A | If manual control of the water level in a steaming boiler is required, the proper method of control is with the auxiliary feed . | stop-check valve                               | stop valve   | pump speed control                              | pump pressure control                       |  |
| 13 | 195 | C | In the condensate system, the automatic recirculating valve can be actuated by the .   | DC heater water level                          | superheater steam flow                                   | condensate temperature                          | condensate pump discharge pressure          |  |
| 13 | 196 | B | The primary source of steam to the auxiliary exhaust system is typically supplied directly from .                                | the main engine LP bleed                       | turbine driven and reciprocating steam pumps             | the turbine gland exhaust system                | all of the above                            |  |
| 13 | 197 | B | The most harmful slag forming compounds found in fuel oils are .   | iron and sulphur                               | vanadium and sodium                                      | potassium and nickel                            | calcium and silica                          |  |
| 13 | 198 | A | Which group of numbers would indicate the largest fuel capacity for a sprayer plate in a mechanical fuel oil atomizer?           | 2909   | 3509   | 43709   | 3 PCRS 4309                                 |  |
| 13 | 199 | B | Normally a boiler water sample should be taken .   | after the boiler has been blown down           | before the boiler has been blown down or chemicals added | when the boiler has been refilled with makeup   | from the highest point in the feed system   |  |
| 13 | 200 | C | The contaminated drain system normally receives drains that may be exposed to .  | salt water contamination                       | spoiled food contamination                               | oil contamination                               | water contamination due to boiler treatment |  |
| 13 | 201 | D | Which of the devices listed is found on an LP main propulsion steam turbine casing?  | Duplex set of relief valves                    | Sliding beam   | HP turbine bypass valve                         | Sentinel valve                              |  |
| 13 | 202 | B | In a steam propulsion plant, the primary source of auxiliary exhaust steam is from the .   | main condenser                                 | main feed pump   | distilling plant                                | air heaters                                 |  |

|    |     |   |  |  |   |  |  |  |
|----|-----|---|--|--|---|--|--|--|
| 13 | 203 | D | Auxiliary steam at full operating pressure is supplied directly from the boiler to the _____ .   | turbogenerator   | main air ejectors   | distilling plant   | soot blowers   |  |
| 13 | 204 | A | Which of the operating principles listed would apply to a single-element, thermo-hydraulic, feedwater regulator?   | A failure of the regulator pressure actuating system closes the valve. | The regulator maintains a constant water level throughout the boiler load range.  | The cooling fins on the generator prevent the formation of steam in the closed system. | The pressure in the inner tube acts upon the bellows of the regulator. |  |
| 13 | 205 | C | Main condensate recirculating systems are primarily intended to _____ .  | prevent excessive overheating of the condensate pumps                  | balance and control condensate temperatures at full load                          | provide adequate cooling water for the air ejector condensers                          | vent accumulated vapors from the condensate pump discharge             |  |
| 13 | 206 | B | Which of the casualties listed is apt to occur immediately after a high water casualty?  | Massive tube failure   | Water carryover to the turbines   | Excessive steam pressure   | Excessive superheater temperature                                      |  |
| 13 | 207 | D | Heavy slagging and high temperature corrosion of boiler tubes can result from using a fuel oil with high amounts of _____ .  | ash  | sodium chloride salts   | vanadium salts   | all of the above   |  |
| 13 | 208 | B | Which precaution should be observe to prevent damage to the fuel oil service pump when warming up the fuel service system?   | Strip all water from the fuel oil settlers.                            | Close the recirculating valve when the proper atomization temperature is reached. | Heat the fuel oil in the settlers to the atomization temperature.                      | Bypass the fuel oil meter so that recirculating oil does not register. |  |
| 13 | 209 | C | The last two digits stamped on a fuel oil atomizer sprayer plate represents the cross-sectional area ratios of the tangential slots and orifice. This ratio determines the _____ . | density of the oil spray   | degree of atomization   | angle of the cone  | capacity of the atomizer   |  |
| 13 | 210 | B | In a water-tube boiler, circulation is caused by the difference in the _____ .   | area and length of the water-tubes                                     | densities within the circulating water  | heights of the boiler drum   | angle of inclination of the tubes                                      |  |
| 13 | 211 | C | Shrouding on impulse turbine blading is held in place by _____ .   | seal welding   | circumferential dovetails   | peening the tenons   | locking keys   |  |

|    |     |   |   |   |   |   |  |  |
|----|-----|---|---|---|---|---|--|--|
| 13 | 212 | B | The means of circulation commonly found in water-tube boilers is _____ .  | compound  | accelerated natural   | cross-compound  | integral   |  |
| 13 | 213 | A | High pressure and low pressure drain systems are part of the _____ .  | fresh water drain system  | auxiliary turbine drain system  | contaminated drain system   | boiler drain system  |  |
| 13 | 214 | C | Which of the following statements is true concerning the operation of a boiler thermo-hydraulic feedwater regulator?  | A failure in the regulator pressure actuating system opens the feed valve wide. | The regulator maintains constant water level throughout all boiler load ranges. | The inner tube of the generator is open to the steam and water in the steam drum. | The outer tube of the generator transfers heat to the inner tube of the closed system. |  |
| 13 | 215 | A | The DC Heater functions to _____ .  | store, heat, and deaerate feedwater   | chemically treat feedwater to remove carbonic gas                               | ensure recirculation in the feedwater system                                      | remove the major amount of noncondensable gases from the main condenser                |  |
| 13 | 216 | C | The high pressure steam drain system is normally collected by the _____ .   | atmospheric drain tank  | contaminated drain inspection tank  | deaerating feedwater heater   | main condenser   |  |
| 13 | 217 | D | A lower than normal boiler stack gas temperature usually indicates _____ .  | dirty firesides   | dirty watersides  | fuel high sulfur content  | incomplete combustion  |  |
| 13 | 218 | A | The number '29' on a fuel oil burner sprayer plate marked '2909' indicates the _____ .                                | orifice size  | cross-sectional area ratio  | whirling chamber size   | slot cross-sectional area  |  |
| 13 | 219 | A | Eight (8) ounces of oxygen, dissolved in 500,000 pounds of water, is a concentration of _____ .                       | 1.0 ppm   | 4.0 ppm   | 8.0 ppm   | 16.0 ppm   |  |
| 13 | 220 | B | The steam separator as used in conjunction with a steam whistle normally drains to which of the listed drain systems? | Low pressure  | High pressure   | Main turbine  | Contaminated   |  |
| 13 | 221 | C | Allowance for axial expansion of the steam turbine due to temperature changes is provided for by the use of _____ .   | casing flexible joints  | rotor position indicators   | a deep flexible I beam support  | pivoted-shoe type thrust bearings  |  |

|    |     |   |  |  |   |  |   |
|----|-----|---|--|--|---|--|---|
| 13 | 222 | A | Which of the following statements concerning boiler steam drum surface blow piping is correct?                         | Usually the surface blow pipe is perforated with holes along its top surface; however, when a scum pan is also employed, the holes are located along the bottom of the pipe surface. | The centerline of the pipe is normally situated at a distance from the bottom of the steam drum equal to approximately one fourth the diameter of the drum. | To ensure adequate blowdown, the aggregate cross sectional area of these perforated holes must be equal to approximately twice the cross sectional area of the pipe. | All of the above.   |
| 13 | 223 | C | Clean low pressure steam drains are collected in the _____.  | deaerating feedwater heater  | contaminated drain inspection tank  | atmospheric drain tank   | main condenser hotwell  |
| 13 | 224 | A | In a single-element feedwater regulator, the amount of valve opening and closing is controlled by the _____.           | water level in the drum  | steam pressure in the drum  | steam flow from the boiler   | feedwater flow to the boiler                                    |
| 13 | 225 | B | Which statement is true concerning drain inspection tanks?   | Inspection tanks collect all HP drains.  | Inspection tanks provide for a visual examination of condensate which could be oil contaminated.  | They are discharged to the condensate system just forward of the feed pump.  | They collect condensate from the cargo tank heating coils only. |
| 13 | 226 | D | From which of the areas listed are condensate drains normally collected and returned to the low pressure drain system? | Steam whistle separator/trap   | Each main feed pump steam supply line   | Steam systems operating in excess of 150 psi   | Main and auxiliary air ejector aftercondensers                  |
| 13 | 227 | C | Economy and efficiency in the operation of a marine boiler have traditionally been characterized by _____.             | a clear stack (invisible stack gases)  | maintaining the fuel oil temperature as high as possible  | a light brown haze from the stack  | a slight wisp of white smoke from the stack                     |
| 13 | 228 | B | When warming up a fuel oil service system, you should open the steam supply to the fuel oil heaters _____.             | before you start the fuel oil service pump   | after you start the fuel oil service pump   | only if the settlers are incapable of heating the oil  | before you open the recirculating valve                         |

|    |     |   |   |  |   |   |  |  |
|----|-----|---|---|--|---|---|--|--|
| 13 | 229 | C | A dissolved oxygen concentration of 8.0 ppm represents .  | 8 lbs of oxygen dissolved in 1,000,000 tons of water | 8 tons of oxygen dissolved in 1,000,000 pounds of water             | 8 ounces of oxygen dissolved in 1,000,000 ounces of water | 80 ounces of oxygen dissolved in 100,000 ounces of water |  |
| 13 | 230 | B | The level in the atmospheric drain tank is normally maintained by the use of a/an .   | overflow to the bilges                               | float-type regulator  | vacuum drag to the air ejector condenser                  | overflow to a distillate tank                            |  |
| 13 | 231 | C | The forces of expansion developed within a propulsion turbine casing are accommodated by .  | expansion bolts at the base of the steam line        | an expansion loop in the exhaust line                               | supporting the forward end on a deep flexible I-beam      | corrugations in the steam chest                          |  |
| 13 | 232 | C | In a boiler equipped with a convection type superheater, the superheater tubes are located .  | in the path of the radiant heat of combustion        | between the downtake nipple and circulator tube                     | in a position screened from the furnace                   | between the economizer and generating tubes              |  |
| 13 | 233 | D | The primary function of the contaminated drain inspection tank is to .  | store contaminated drains                            | separate the oil and water by using a series of filters and baffles | only cool down the contaminated drains                    | serve as a means for visually examining the drains       |  |
| 13 | 234 | B | Single-element automatic feedwater regulators are controlled by the .   | temperature in the steam drum                        | water level in the steam drum                                       | pressure in the steam drum                                | feedwater flow to steam drum                             |  |
| 13 | 235 | D | The DC heater functions to .  | remove air from feedwater                            | heat feedwater  | store feedwater   | all of the above   |  |
| 13 | 236 | B | If live steam is supplied directly to the tank heating coils, the collected drains in the 'clean' section of the contaminated drain inspection tank are removed directly to the . | main and/or auxiliary condenser                      | atmospheric drain tank  | deaerating feedwater heater                               | makeup feedwater tank                                    |  |
| 13 | 237 | B | A light brown haze issuing from the boiler smoke stack generally indicates .  | dirty fuel atomizers                                 | good fuel combustion  | too much fuel pressure                                    | a high firing rate                                       |  |
| 13 | 238 | B | The complete unit housing the burner, air scoop, air doors and bladed cone is correctly called the .  | burner assembly                                      | register assembly   | atomizer assembly   | air duct assembly  |  |

|    |     |   |  |  |  |   |   |  |
|----|-----|---|--|--|--|---|---|--|
| 13 | 239 | B | If it should become necessary to abandon a compartment because of the danger of a large steam leak on a boiler, which of the following actions represents the best avenue of escape? | Escape through another compartment on a higher level.            | Escape through another compartment on a lower level.             | Escape by way of a fireroom ladder to the outer deck. | Use fireroom elevator to an upper deck.     |  |
| 13 | 240 | C | The percentage by weight of steam in a mixture of steam and water is called the _____.   | moisture percentage  | moisture quality   | quality of steam                                      | heat effectiveness                          |  |
| 13 | 241 | D | The correct radial clearances between the rotor and the casing in a propulsion turbine are maintained by the turbine _____.  | interstage packing   | thrust bearing   | diaphragms  | journal bearings                            |  |
| 13 | 242 | A | In a boiler equipped with a convection type superheater, the superheater tubes are located _____.  | in a position screened from the furnace                          | in the direct path of radiant heat flow                          | in a separately fired convection furnace              | on the fireside of the screen tubes         |  |
| 13 | 243 | A | Excessive water flow beyond the design limits of a feedwater heater, will be indicated by a/an _____.  | increase in the pressure drop between the water inlet and outlet | decrease in the pressure drop between the water inlet and outlet | excessive gas liberation from the waterside vents     | high steam temperature at the heater outlet |  |
| 13 | 244 | B | A two-element boiler feedwater regulator is controlled by _____.   | steam flow and feedwater flow                                    | steam flow and drum water level                                  | drum water level and feedwater flow                   | drum water level and drum pressure          |  |
| 13 | 245 | B | A high water level in a deaerating feed heater will cause the automatic dump valve to drain condensate to the _____.   | atmospheric drain tank   | reserve feed tank  | auxiliary condenser                                   | main condenser                              |  |
| 13 | 246 | C | As steam accomplishes work in an engine or turbine, the pressure of the steam is reduced because it _____.   | diminishes in volume   | becomes saturated again  | expands in volume                                     | becomes superheated again                   |  |
| 13 | 247 | A | The greatest single overall efficiency loss in a marine propulsion steam plant cycle results from _____.   | heat lost in the main condenser                                  | poor heat transfer in feedwater heaters                          | mechanical losses in the atomization process          | heat loss required for fuel oil heating     |  |
| 13 | 248 | D | The most serious fireside burning of the boiler superheater tubes is the result of _____.  | combustion gases impinging on the tubes                          | fuel droplets striking the hot tubes                             | carbon steel tubes being heated above 750°F           | the tubes becoming steam bound or dry       |  |

|    |     |   |  |   |   |  |   |         |
|----|-----|---|--|---|---|--|---|---------|
| 13 | 249 | B | If the theoretical quantity of dry air required to burn one pound of fuel oil is 13.75 pounds, what weight of air will be necessary to burn one pound of fuel to operate a boiler at 10% excess air? | 14.44 pounds  | 15.13 pounds  | 15.81 pounds   | 16.50 pounds  |         |
| 13 | 250 | B | As steam accomplishes work in an engine or turbine, it expands and _____.  | increases in superheat  | decreases in superheat  | decreases in volume  | decreases in moisture content                                     |         |
| 13 | 252 | B | The purpose of the division plates installed in boiler superheater headers is to _____.  | limit the maximum temperature rise of the superheater outlet to 15°F            | ensure proper steam flow, thus preventing 'short circuiting' of superheater loops | provide a means of controlling steam passage in response to throttle demands | all of the above  |         |
| 13 | 253 | C | The connection labeled "C" in the illustration, is used to _____.  | maintain a vacuum in the shell of the feed water heater                         | provide a point of admission for the steam air heater drains                      | provide a point of admission for the L.P. bleed steam                        | drain condensate from the feed water heater to the main condenser | SG-0025 |
| 13 | 254 | D | A two-element feedwater regulator responds directly to changes in _____.   | feedwater flow to the boiler  | feedwater pump discharge pressure   | DC heater water level  | steam flow from the boiler  |         |
| 13 | 255 | D | The DC heater automatic level dump valve is used to _____.   | divert the flow of condensate from the first stage heater to the vent condenser | maintain a proper condensate level in the condenser hotwell                       | recirculate condensate to the atmospheric drain tank                         | drain excess feedwater to the distilled water tank                |         |
| 13 | 256 | A | Which of the following conditions in a water-tube boiler generating tube could cause tube failure, even if the water gage glass shows the proper level?  | Film boiling  | low dissolved oxygen content  | Decreased superheat  | A film of soot  |         |
| 13 | 257 | B | Efficient combustion in a boiler is indicated by a _____.  | white haze  | brown haze  | yellow haze  | black haze  |         |

|    |     |   |  |   |   |  |  |         |
|----|-----|---|--|---|---|--|--|---------|
| 13 | 258 | B | When seated, the disc of a safety valve has an area of 0.75 square inches (1.9 sq cm). When the valve lifts the area is increased by 10%. If the valve lifts at 300 psig (2170 kPa), at approximately what pressure will the valve reseal? | 262 psig (1907 kPa)   | 273 psig (1983 kPa)   | 284 psig (2059 kPa)  | 295 psig (2135 kPa)  |         |
| 13 | 259 | D | When a boiler water test indicates a pH value of 6, you should _____.  | check the DC heater for possible malfunction  | begin a continuous boiler blowdown  | chemically treat to lower the pH to normal level   | chemically treat to raise the pH to normal level   |         |
| 13 | 262 | B | In a D-type boiler, which of the tubes listed would be located in the generating tube bank?  | Water walls   | Superheater support tubes   | Downcomer tubes  | Recirculating tubes  |         |
| 13 | 263 | A | If water hammer develops while opening the valve in a steam line, which of the following actions should be taken?  | Shut the steam valve at once, open the drain valves until all moisture is drained, shut the drain line valves, and slowly open the steam valve again. | Continue to fully open the steam valve as the drain line valves are opened until all moisture is drained, shut the drain line valves. | Stop opening the steam valve, open the drain line valves, resume opening the steam valve slowly, and shut the drain line valves after the steam valve is open fully. | Increase the speed of opening the steam valve to rapidly heat the line to stop the water hammer. |         |
| 13 | 264 | A | Two-element feedwater regulators operate by sensing _____.   | boiler water level and steam flow   | boiler water level and steam pressure   | boiler water level and feedwater flow  | feedwater flow and steam pressure  |         |
| 13 | 265 | A | High pressure steam drains are normally discharged to the _____.   | DC heater   | atmospheric drain line  | reserve feed tank  | drain and inspection tank  |         |
| 13 | 266 | A | Identify the system shown in the illustration.   | Bleed steam   | Auxiliary steam   | High pressure drains   | Auxiliary condensate   | SG-0024 |
| 13 | 267 | C | The major heat loss in an oil fired boiler is the heat _____.  | used in the economizer and air heater   | passing through the boiler casing   | going up the stack   | required to change water into steam  |         |
| 13 | 268 | C | Which of the systems or components shown in the illustration, are supplied by auxiliary exhaust steam?   | Air ejectors  | Intermediate pressure bleed steam system  | Boiler air heaters   | Low pressure bleed steam system  | SG-0024 |

|    |     |   |  |   |   |  |  |         |
|----|-----|---|--|---|---|--|--|---------|
| 13 | 269 | B | When securing a boiler, the burner registers are to be left open for a few minutes to _____.   | cool the furnace                                    | purge the furnace                         | cool the uptakes   | kill steam generation                                |         |
| 13 | 270 | B | The auxiliary exhaust system shown in the illustration can be supplied by steam from the _____.  | fuel oil heaters                                    | IP bleed system                           | main steam system  | distilling plant                                     | SG-0024 |
| 13 | 271 | C | In modern reaction turbines, thin tipping is a procedure designed to _____.  | allow for axial expansion                           | increase blade strength and rigidity      | reduce tip leakage                                       | maintain radial clearances                           |         |
| 13 | 272 | A | Boiler screen tubes are used to protect which of the listed components from high furnace temperature?  | Superheater   | Refractory                                | Wall tubes   | Steam drum   |         |
| 13 | 273 | A | The best conductor of heat in a marine boiler is _____.  | steel   | water                                     | steam  | brick  |         |
| 13 | 274 | A | A two-element feedwater regulator reacts to changes in the steam drum water level and the _____.   | steam flow from the boiler                          | main feed pump speed                      | water flow to the boiler                                 | signal from the flame scanner                        |         |
| 13 | 276 | C | Damage to deck machinery from water hammer developing in the steam lines can be prevented by _____.  | installing a steam strainer in all exhaust lines    | opening machinery throttle valves rapidly | draining the steam piping before operating any machinery | ensuring that all drain lines are properly insulated |         |
| 13 | 277 | A | If the theoretical quantity of dry air required to burn one pound of fuel oil is 13.75 pounds, what is the weight of air per pound of fuel when operating a boiler at 5% excess air? | 14.44 pounds  | 15.13 pounds                              | 15.81 pounds   | 16.50 pounds   |         |
| 13 | 278 | C | The boiler fuel oil system 'hot' strainers are also known as _____.  | coarse strainers                                    | magnetic strainers                        | discharge strainers                                      | cestus strainers                                     |         |
| 13 | 279 | A | A practical ceiling on boiler efficiency with regard to heat absorption is the requirement to _____.   | maintain uptake gas temperature above the dew point | maintain an excess of CO                  | protect the safety valves from excessive temperature     | prevent excess air density                           |         |

|    |     |   |  |   |   |   |  |         |
|----|-----|---|--|---|---|---|--|---------|
| 13 | 280 | D | If a main condenser were operating with a vacuum of 28.09 in. Hg, a condensate discharge temperature of 95°F, a seawater inlet temperature of 64°F and an overboard temperature of 72°F, which of the following would represent the condensate depression? | 0.3 in. Hg                                      | 0.5 in. Hg                                | 5.5°F   | 3.24°F   | SG-0026 |
| 13 | 281 | C | Turbine casing flanges are sometimes provided with a system of joint grooving to .   | form a labyrinth seal between the casing halves | ensure perfect alignment of casing halves | inject sealing compound between the casing halves | increase contact pressure between the casing halves' flanges |         |
| 13 | 282 | D | A convection type superheater in a D-type boiler is protected from radiant heat by .   | generator tubes                                 | convection currents                       | control desuperheaters                            | water screen tubes   |         |
| 13 | 283 | C | With reference to the chart, if a boiler generates saturated steam at 385.3 psig, how much heat per pound was required to change the water into steam if the feedwater temperature was initially 104.5°C?  | 96.85 BTU                                       | 97.15 BTU                                 | 1016.40 BTU                                       | 1196.45 BTU  | SG-0004 |
| 13 | 284 | B | One of the operating conditions sensed by a two-element feedwater regulator is .   | feedwater flow                                  | steam flow                                | fuel pressure                                     | steam pressure   |         |
| 13 | 285 | D | The cooling water supplied to the vent condenser in a DC heater is .   | seawater  | fresh water                               | potable water                                     | condensate   |         |
| 13 | 286 | C | In the boiler steam and water system, pressure is highest in the .   | steam stop                                      | dry pipe                                  | feed line   | mud drum   |         |
| 13 | 287 | C | If the theoretical quantity of dry air required to burn one pound of fuel oil is 13.75 pounds, what will be the weight of the air necessary to burn one pound of fuel when operating a boiler at 15% excess air?   | 14.44 pounds                                    | 15.13 pounds                              | 15.81 pounds                                      | 16.50 pounds   |         |
| 13 | 288 | A | The boiler fuel oil system suction strainers are also known as the .   | 'cold' strainer                                 | 'hot' strainer                            | 'fine' strainer                                   | magnetic strainer  |         |

|    |     |   |  |   |   |   |  |         |
|----|-----|---|--|---|---|---|--|---------|
| 13 | 289 | C | On an automatically fired boiler, the loss of forced draft fan will result in which of the listed actions to be carried out?   | Stopping of the feed pump                                     | Stopping of the fuel oil service pump   | Closing of the master fuel oil cutoff                       | All of the above.  |         |
| 13 | 291 | D | After one year of operating the bearing shown in the illustration, the reading obtained at point "A" would always be equal to the _____.   | reading stamped on the gage only                              | designed oil clearance  | designed oil clearance plus the stamped bridge gage reading | stamped bridge gage reading plus the bearing wear                  | SE-0017 |
| 13 | 292 | C | A boiler superheater support tube differs from a standard generating tube in that the _____.   | direction of flow of the steam and water mixtures differ      | metals from which they are fabricated differ                                    | outside diameters and wall thicknesses differ               | method of heat transfer in the tube differs                        |         |
| 13 | 293 | A | Scavenging air is supplied to steam soot blowers to _____.   | prevent the backup of combustion gases into soot blower heads | provide cooling air when soot blower elements are rotating through blowing arcs | prevent the escape of steam into the inner casing           | prevent warping of the cams when exposed to high temperature steam |         |
| 13 | 294 | B | A two-element feedwater regulator not only responds to changes in water level, but is also designed to react to _____.   | feedwater flow  | steam flow  | fuel flow   | steam pressure   |         |
| 13 | 295 | B | The leakage of air into the pump casing by way of the packing gland of a condensate pump, is prevented by _____.   | special packing in the stuffing box                           | a water seal line to the packing gland  | an air seal line from the compressed air line               | the vacuum in the pump suction                                     |         |
| 13 | 296 | B | Which of the piping systems listed is shown in the illustration?   | Auxiliary exhaust   | Auxiliary steam   | Butterworth   | Main feed  | SG-0005 |
| 13 | 297 | D | If the theoretical quantity of dry air required to burn one pound of fuel oil is 13.75 pounds, what will be the weight of the air necessary to burn one pound of fuel to operate a boiler at 20% excess air? | 14.44 pounds  | 15.13 pounds  | 15.81 pounds  | 16.50 pounds   |         |
| 13 | 298 | B | Strainers are installed in boiler fuel oil service lines to _____.   | absorb contaminants   | remove solids   | decrease viscosity  | adsorb water   |         |

|    |     |   |   |   |  |   |   |         |
|----|-----|---|---|---|--|---|---|---------|
| 13 | 299 | D | Ferrous sulfate tends to go into solution in boiler water when the value of the hydrogen ion concentration increases. Consequently, the boiler water of a 900 psi plant should be . | pure with neutral pH                                      | pure and treated to a pH of 4.0 to 4.5                       | maintained at a pH of 7.0   | pure and treated to a pH of 10.5 to 11.0                                    |         |
| 13 | 300 | B | Under constant boiler load, the superheated steam temperature may rise above normal for the existing load if .  | excess air is too low                                     | feedwater temperature is too low                             | boiler water level is too high  | combustion air is excessively hot   |         |
| 13 | 301 | C | A turbine diaphragm functions to .  | support moving blades and shrouding in an impulse turbine | provide support for interstage packing in a reaction turbine | support the nozzles and guide the flow of steam in an impulse turbine | decrease steam velocity in the nozzles of an impulse turbine                |         |
| 13 | 302 | A | Which of the methods listed would be most effective in repairing a steam cut on a seating surface of a superheater handhole plate?  | Filling the cut by welding and then grinding it smooth.   | Filling the cut with iron cement or plastic steel.           | Grinding the seating surface and installing an oversized gasket.      | Refacing the surface and over torquing the handhole plate.                  |         |
| 13 | 303 | A | The concentration of total dissolved solids in boiler water could increase as a result of .   | infrequent bottom blows                                   | zero water hardness  | dissolved oxygen deaeration   | priming and carryover   |         |
| 13 | 304 | C | Which type of feedwater regulator listed provides the MOST effective regulation of boiler water level under all operating conditions?   | Single-element  | Double-element   | Triple-element  | Monothermonic   |         |
| 13 | 305 | D | Flooding of the DC heater, due to the addition of excessive makeup feed, is normally corrected by the use of .  | a condensate pressure regulating valve                    | a thermostatic steam regulating valve                        | the feed pump recirculating line                                      | a manual or automatic dump valve to the reserve feed tank or distilled tank |         |
| 13 | 306 | D | If a boiler generates saturated steam at 125.3 psig, how much heat is required to change the water into steam if the feedwater temperature is 240°F?                                | 30.5 Btu/lb   | 116.5 Btu/lb   | 582.7 Btu/lb  | 983.4 Btu/lb  | SG-0004 |
| 13 | 307 | A | Excess air must be provided to an operating boiler to allow for .   | complete combustion of fuel                               | fluctuations in boiler steam demand                          | heat losses up the stack  | all of the above  |         |

|    |     |   |   |  |  |   |   |  |
|----|-----|---|---|--|--|---|---|--|
| 13 | 308 | D | Strainers are installed in boiler fuel oil service lines to _____ .   | absorb contaminants                              | collect water                                | decrease viscosity                                      | remove solids                                 |  |
| 13 | 309 | C | A boiler with a water capacity of 10 tons, generates steam at the rate of 30 tons per hour. If the feedwater quality is 0.5 ppm, the concentration of solids will increase 1.5 ppm every hour. What would be the increase in the concentration of solids within 24 hours? | 12 ppm   | 24 ppm                                       | 36 ppm  | 48 ppm  |  |
| 13 | 310 | D | Air accumulated in the aftercondenser of the air ejector unit is discharged directly to the _____ .   | intercondenser                                   | high pressure turbine                        | main condenser  | atmosphere                                    |  |
| 13 | 311 | B | In what type of turbine is the moving blading and the intervening fixed rows of blading shaped so as to form convergent-divergent nozzles?  | Impulse  | Reaction                                     | Impulse-reaction  | Curtiss                                       |  |
| 13 | 312 | B | In a boiler water gage glass, a ball check valve is installed on the _____ .  | top connection only                              | bottom connection only                       | top and bottom connection                               | drain valve                                   |  |
| 13 | 313 | D | Should the superheater outlet thermometer indicate an excessively high temperature on a single furnace boiler, the cause could be _____ .   | dirty steam generating tube surfaces             | too much excess air                          | the fuel oil being too viscous                          | all of the above                              |  |
| 13 | 314 | B | In an automatically fired boiler, the steam pressure regulator controls the supply of fuel oil to the burners by responding to variations in the _____ .  | steam drum water level                           | steam header pressure                        | master fuel oil solenoid valve position                 | burner flame intensity                        |  |
| 13 | 315 | C | Vent condensers are usually an integral part of deaerating feed heaters and serve to condense _____ .   | only steam vented from high pressure steam traps | steam vented from high pressure steam glands | the steam vapor entrained with the noncondensable gases | the gases liberated by the deaeration process |  |
| 13 | 317 | D | Too much excess air in a steaming boiler may be indicated by _____ .  | a white burner flame                             | a clear stack                                | white smoke   | all of the above                              |  |
| 13 | 318 | B | Strainers are installed in boiler fuel oil service lines to _____ .   | collect water                                    | remove solids                                | decrease viscosity                                      | absorb contaminants                           |  |

|    |     |   |  |   |  |  |   |  |
|----|-----|---|--|---|--|--|---|--|
| 13 | 319 | D | The concentration of total dissolved solids in the boiler water can increase as a result of _____ .                            | frequent surface blows                          | dissolved oxygen deaeration            | zero water hardness                                      | insufficient blowdown                           |  |
| 13 | 320 | C | The greatest deterrent to heat transfer from the fireside to the waterside of a boiler is _____ .                              | water film                                      | water eddies                           | gas film   | gas eddies                                      |  |
| 13 | 321 | A | For a large main propulsion turbine, the most commonly used turbine thrust bearing is the _____ .                              | pivoted segmental shoe                          | overhung turbine wheel                 | self-aligning shell                                      | self-oiling sleeve                              |  |
| 13 | 322 | A | The minimum feedwater inlet temperature to a boiler economizer is determined by the _____ .                                    | dew point temperature of the stack gas          | superheater outlet temperature         | surface area of the third stage heater                   | radiant heat transfer in the furnace            |  |
| 13 | 323 | B | In automated boiler operations, a dirty flame scanner will most likely result in _____ .                                       | increased fuel oil consumption                  | securing fuel oil to the burner        | loss of forced draft air                                 | incomplete purge cycle                          |  |
| 13 | 324 | B | The two-element feedwater regulator functions similarly to the three-element feedwater regulator, but does not utilize _____ . | steam flow measurement                          | feedwater flow measurement             | water level  | drum pressure                                   |  |
| 13 | 325 | C | The purpose of the recirculating line between the turbine driven feed pump and the DC heater is to _____ .                     | ensure a steady boiler water level at all loads | seal the labyrinth packing on the pump | ensure sufficient flow through the feed pump at low load | cool the vent condenser                         |  |
| 13 | 326 | C | If a quantity of saturated steam consists of 90 percent steam and 10 percent moisture, the quality of the mixture is _____ .   | 10%   | 80%                                    | 90%  | 100%  |  |
| 13 | 327 | B | When too much excess air is supplied to an operating boiler, the _____ .   | heat loss will be reduced                       | heat loss will be excessive            | flame will impinge on the burner cone                    | flame will be a deep red color                  |  |
| 13 | 328 | A | Which of the listed types of strainers are installed between the fuel oil heater and the burner manifold?                      | Duplex  | Magnetic                               | Simplex  | Self-cleaning                                   |  |
| 13 | 329 | B | Dissolved and suspended solids in boiler water are kept at minimum levels by _____ .   | using only volatile chemicals                   | frequently blowing down the boiler     | treating the boiler water with phosphates                | the introduction of oxygen scavenging chemicals |  |

|    |     |   |  |  |  |  |  |         |
|----|-----|---|--|--|--|--|--|---------|
| 13 | 330 | D | Which of the listed devices may trip due to total flame failure in both boilers of an automated plant?   | Individual burner solenoids                        | Main fuel header solenoids                   | Main turbine throttle valve                      | All of the above   |         |
| 13 | 331 | C | The astern element of a main propulsion turbine is usually .   | multiple entry, helical flow                       | single entry, double flow                    | impulse staged                                   | reaction staged  |         |
| 13 | 332 | A | Bi-color water level indicators, connected directly to the boiler drum, operate on the principle of .  | different refractive properties of steam and water | special insoluble indicating fluids          | different chemical properties of steam and water | different densities which result from the comparison of the varying steam pressure in the drum |         |
| 13 | 333 | B | The difference between the temperature of the condensate discharge and the temperature corresponding to the vacuum being maintained at the exhaust inlet to the main condenser is defined as . | main circulator loss                               | condensate depression                        | condensate recession                             | absolute condenser temperature   |         |
| 13 | 334 | B | If the bellows in a thermo-hydraulic feedwater control valve ruptures, the boiler water level will .   | increase only                                      | decrease only                                | increase initially and then decrease             | decrease initially and then increase   |         |
| 13 | 335 | C | Feedwater heaters are used aboard steam vessels to reduce thermal shock to the boiler and to .   | increase plant mechanical efficiency               | act as a heat sink for turbine bleed steam   | improve thermal efficiency                       | reduce back pressure in the auxiliary exhaust line   |         |
| 13 | 336 | B | Which line on the graph indicates the Latent Heat of Fusion?   | Line 1   | Line 2                                       | Line 3   | Line 4   | SG-0001 |
| 13 | 337 | D | As the percentage of CO2 in the stack gas decreases, you can assume that .   | the fuel to air ratio is increasing                | fuel is being burned with increasing economy | you are approaching secondary combustion         | excess air is increasing   |         |
| 13 | 338 | A | The valve located between the fuel oil header and the burner valve is known as the .   | root valve   | return valve                                 | header valve                                     | register valve   |         |
| 13 | 339 | C | The end product of reactions occurring when boiler water is chemically treated, remain in the boiler and increase the need for .   | acid cleaning                                      | makeup feed                                  | boiler blowdown                                  | waterside corrosion treatment  |         |

|    |     |   |   |  |   |  |  |  |
|----|-----|---|---|--|---|--|--|--|
| 13 | 340 | B | Why is superheated steam used in the main propulsion turbines instead of saturated steam?                         | Less specific energy available per pound of steam.         | Greater heat energy available per pound of steam.                                       | Higher pressure available than saturated steam.  | Lower required specific volume than saturated steam. |  |
| 13 | 341 | C | Reduction gear bearing bridge gage readings should be taken after .   | rotating the journal to the point of minimum oil clearance | all bearing caps and all bearing halves are removed                                     | rotating the bearing shell so that the point of maximum bearing wear is directly at the bottom | All of the above are correct.                        |  |
| 13 | 342 | C | The purpose of the mica used in a boiler water gage glass assembly is to prevent .                                | overheating of the glass                                   | light refraction in the glass   | etching of the glass   | leakage from the glass                               |  |
| 13 | 343 | C | When the flame scanner senses flame failure during boiler operation, which of the listed events will occur FIRST? | The fuel oil service pump is stopped.                      | The automatic purge cycle commences.  | The fuel oil solenoid valve is de-energized.   | The 'trial for ignition' period commences.           |  |
| 13 | 344 | D | Improper boiler feedwater deaeration could be directly linked to .  | operating with excessive condensate depression             | fluctuating deaerating feed tank level as a result of taking on makeup feed too rapidly | fluctuating condensate pressure due to not maintaining proper hotwell level                    | all of the above                                     |  |
| 13 | 345 | A | In a closed feedwater system, the greatest deaeration of condensate occurs in the .                               | DC heater  | atmospheric drain tank  | air ejector condenser  | vent condenser                                       |  |
| 13 | 346 | B | Most marine boilers are designed to produce .   | superheated steam only                                     | saturated and superheated steam   | saturated steam only   | superheated and supercritical steam                  |  |
| 13 | 347 | A | Excessive combustion air in a boiler is indicated by the flame ends appearing as a/an .                           | shower of sparks   | orange colored flame  | dull red or black flame  | light brown flame                                    |  |
| 13 | 348 | D | Fuel oil atomizers are used in boilers to .   | control the temperature of fuel entering the furnace       | control the amount of air entering the furnace  | mix air and fuel together  | break fuel oil into a fine spray                     |  |

|    |     |   |   |   |  |   |  |         |
|----|-----|---|---|---|--|---|--|---------|
| 13 | 349 | A | A continuous blow is used to _____ .  | regulate the density or salinity of boiler water  | remove scum from the surface of boiler water   | permit air to escape while raising steam in a cold boiler   | remove sludge from the bottom of the water drum                              |         |
| 13 | 350 | B | Which of the following statements is true concerning the information tabulated in the table?                        | At 185.3 psig (1366.4 kPa), the saturation temperature of a mixture of water and steam is 377.51°F (192°C). | When one pound of water changes to one pound of steam at 200 psia (1378.8 kPa), its volume increases 124.41 times. | If one pound of steam at 250 psia (1723.5 kPa) condenses to one pound of water it will give up 843 BTU's (889.4 kJ) while changing state. | All of the above.  | SG-0004 |
| 13 | 351 | C | Which of the following statements is correct regarding axial thrust in a high pressure velocity-compounded turbine? | Most of the thrust produced is counter balanced by the action of a dummy piston.                            | Only a small portion of the thrust produced is counter balanced by the action of a dummy piston.                   | The thrust is minimized by equalizing holes drilled in the turbine wheels.  | The thrust is transmitted to and absorbed by the high speed pinion and gear. |         |
| 13 | 352 | C | Where is the 'dry pipe' located in a boiler?  | At the superheater outlet   | Behind the superheater screen tubes  | In the top of the steam drum  | Below the generation tube bank   |         |
| 13 | 353 | D | The weight of saturated steam is a factor dependent upon its _____ .  | density   | temperature  | pressure  | All of the above   |         |
| 13 | 354 | C | The pressure in the feedwater system must exceed boiler steam drum pressure in order to _____ .                     | prevent water hammer in the lines   | prevent air leakage into the feedwater system  | force the feedwater into the boiler   | remove the steam from the steam drum   |         |
| 13 | 355 | B | Feedwater is deaerated to prevent _____ .   | cavitation in the feed pump   | corrosion in the boiler  | loss of system vacuum   | all of the above   |         |
| 13 | 356 | A | Steam line water hammer can be best prevented by _____ .  | keeping lines drained and insulated   | replacing all 90°Elbows with capped tees   | always opening steam valves rapidly   | keeping steam temperature below the saturation point                         |         |

|    |     |   |  |   |  |   |   |  |
|----|-----|---|--|---|--|---|---|--|
| 13 | 357 | D | White smoke coming from the stack of a main propulsion boiler indicates .  | too much excess air   | partially burned fuel particles are leaving the stack                                    | excessive air velocity through the air registers                                | all of the above  |  |
| 13 | 358 | D | In a marine boiler equipped with mechanically atomized burner assemblies, proper combustion depends on the .                                 | design and mechanical construction of the atomizers   | speed of the forced draft fan and quantity of excess air                                 | centrifugal force imparted to the oil in the atomizer                           | all of the above  |  |
| 13 | 359 | D | Which of the following statements is true concerning the use of hydrazine in boiler water treatment?   | A reserve is maintained by continually adding it to the feedwater rather than the boiler water. | It removes free oxygen from the boiler without increasing total dissolved solid content. | It aids in maintaining the pH of the boiler water within the prescribed limits. | All of the above.   |  |
| 13 | 360 | A | The photoelectric cell installed as part of the combustion safety controls of an automatically fired boiler will .                           | sense light from the burner flame   | control the modulating pressure control circuit  | open the control circuit upon sensing an intense flame                          | close the control circuit upon sensing a flame failure  |  |
| 13 | 361 | C | Steam passing through a multistage impulse turbine does not impart any appreciable axial thrust to the rotor. This is primarily due to the . | pressure drop taking place in the moving blades   | dummy piston and cylinder arrangement  | equalizing holes provided in the turbine wheel                                  | steam passing through the blades only once with the largest pressure drop taking place in the first-stage |  |
| 13 | 362 | B | The glass used in a flat-type boiler water gage is protected from the hot steam and water by a/an .  | asbestos gasket   | mica shield  | felt cushion  | copper insulator  |  |
| 13 | 363 | B | In a given weight of steam, four-fifths is vapor and one-fifth is moisture. The steam in this mixture is best described as .                 | 20% quality   | 80% quality  | dry saturated   | superheated   |  |
| 13 | 364 | C | Increasing the temperature of the feedwater entering the steam drum will ultimately result in a/an .   | increase in stack gas temperature   | increase in fuel consumption   | decrease in the degree of superheat   | decrease in the quality of steam entering the superheater   |  |

|    |     |   |  |   |  |  |   |  |
|----|-----|---|--|---|--|--|---|--|
| 13 | 365 | C | Condensate is pumped from the condenser to the DC heater instead of directly to the boiler because .                                     | boiler feed pumps must operate with a negative suction head   | suspended solids in the condensate must be eliminated        | condensate should be deaerated before entering the boiler                | condensate at condensing temperature is too hot and will cause thermal stress in the boiler |  |
| 13 | 366 | C | In what section of a boiler would you find a steam quality of 90%?   | Superheater outlet  | Desuperheater outlet   | Steam drum   | Last pass of the superheater  |  |
| 13 | 367 | B | Increased dry gas loss and reduced boiler efficiency result from carrying too much excess air because excess air .                       | varies with the degree of deposits on heat absorbing surfaces | increases the amount of stack gas weight and temperature     | effects the amount of volatile matter and ash content of the fuel        | reduces the amount of harmful impurities produced by burning residual fuel                  |  |
| 13 | 368 | A | Fuel oil viscosity to the atomizer can be reduced by .   | increasing the fuel oil heater steam supply                   | mixing heavier oil with the fuel                             | changing the atomizer orifice size                                       | increasing fuel oil pressure  |  |
| 13 | 369 | A | The atmospheric drain tank is normally evacuated by .  | vacuum drag to the main and/or auxiliary condenser            | overflow to the bilges                                       | vacuum drag to the main and/or auxiliary air ejector condenser           | overflow to a distillate tank   |  |
| 13 | 370 | A | A flame scanner installed in modern boiler combustion control systems, functions to .  | cut off the fuel supply when the fires go out                 | monitor the stack for soot fires                             | regulate the fuel oil pressure   | sample the stack gases  |  |
| 13 | 371 | D | To minimize axial thrust in an impulse turbine, equalizing holes are located .   | between the steam inlet and the front of the dummy piston     | between the exhaust outlet and the front of the dummy piston | in each casing diaphragm   | in each rotor wheel   |  |
| 13 | 372 | D | If the low water level alarm sounds on an automatically fired boiler, and the low water cutout fails to function, you must immediately . | blowdown the gage glass to determine where the water level is | increase the feedwater supply to maintain the water level    | start the emergency feedwater injector to restore the normal water level | secure the fires to minimize damage to the boiler tubes                                     |  |

|    |     |   |   |   |  |  |   |  |
|----|-----|---|---|---|--|--|---|--|
| 13 | 373 | A | Combustion control systems on automatic boilers are designed to prevent immediate burner ignition after a normal or safety shutdown in order to allow time for .        | the furnace to be purged                          | electric charge buildup in the igniter                           | the fuel pump to start   | the drum level to equalize  |  |
| 13 | 374 | D | When it is necessary to operate a turbine driven main feed pump at shut off head, or at 20% or less of its rated capacity, what will prevent the pump from overheating? | Throttling of the steam supply valve.             | Throttling of the liquid discharge valve.                        | A bypass or recirculating line led back to the pump impeller eye or suction.                     | A bypass or recirculating line led back to the source of suction supply.      |  |
| 13 | 375 | B | Discharging an excessive amount of cold water into the DC heater during normal steaming conditions could cause .  | flashing at the feed pump suction                 | excess oxygen in the feedwater                                   | water hammer in the economizer   | increased back pressure   |  |
| 13 | 376 | C | The turndown ratio an automatic combustion control system is the ratio .  | of air to fuel for a given firing rate            | of forced draft fan speed to feedwater flow                      | between the highest and lowest oil pressure at which the burner will remain lit                  | between fuel oil pressure and atomizing steam pressure at a given firing rate |  |
| 13 | 377 | D | In a properly designed boiler, which of the end points should be reached first?   | Carryover   | Circulation  | Evaporation  | Combustion  |  |
| 13 | 378 | A | To obtain the best mixing of air and fuel with a fuel oil atomizer, you need to adjust the .  | atomizer position using the distance piece        | diffuser to the desired flow                                     | primary and secondary air cones for desired air flow   | total air volume admitted to the boiler furnace                               |  |
| 13 | 379 | D | Dissolved oxygen can be removed from the boiler water by .  | frequent surface and bottom blows                 | dumping and refilling the boiler weekly                          | passing the water through absorbent filters  | treating the water with chemical scavengers                                   |  |
| 13 | 380 | C | Which of the following statements is true concerning a photocell flame scanning system?   | The photocell requires a large amount of voltage. | The scanner head must be adjusted to sight the sensitivity link. | The scanner works in conjunction with the burner fuel oil (solenoid controlled) shut off valves. | The scanner window must be isolated from the forced draft fan air.            |  |

|    |     |   |   |  |   |   |   |  |
|----|-----|---|---|--|---|---|---|--|
| 13 | 381 | C | When a turbine is in operation, a rotor position micrometer is used to determine any change in rotor _____ .  | radial position relative to the casing                               | radial position relative to the micrometer                  | axial position relative to the casing           | axial position relative to the micrometer                                   |  |
| 13 | 382 | C | How is the nozzle in a nozzle reaction safety valve held in place?  | Press fit  | Lock nut  | Machine threads                                 | Spot weld   |  |
| 13 | 383 | A | If the control air pressure for an automatic combustion control system is lost during maneuvering, you should immediately _____ .   | switch to manual control   | blowdown the air receiver                                   | attempt to restart the air compressor           | secure the boilers  |  |
| 13 | 384 | A | A turbine-driven centrifugal feed pump used for boiler feed service should normally be stopped by _____ .   | hand activating the overspeed trip                                   | closing off the steam via the excess pressure pump governor | slowly closing the manual throttle              | opening wide the recirculating valve and then manually closing the throttle |  |
| 13 | 385 | C | To provide emergency feedwater supply to a steaming boiler if it becomes necessary to secure the DC heater, suction should be taken on the distilled water tank using the _____ . | emergency injector discharge   | feed booster pump   | main feed pump                                  | main condensate pump  |  |
| 13 | 386 | D | In addition to monitoring flame quality, flame scanners are used in combustion control systems to _____ .   | regulate the air/fuel ratio controller for more efficient combustion | secure the forced draft fans upon flame failure             | automatically open the fuel oil solenoid valves | secure the fuel supply in the event of a flame failure                      |  |
| 13 | 387 | C | In a properly designed boiler, which end point is most likely to occur first?   | Evaporation  | Circulation   | Combustion                                      | Moisture carryover  |  |
| 13 | 388 | C | Fuel oil passing through the burners is divided into fine particles by the _____ .  | diffuser   | air register  | sprayer plate                                   | air foils   |  |
| 13 | 389 | D | Although accurate tests of boiler water for dissolved oxygen are difficult to obtain on board ship, you can be fairly certain of proper oxygen removal by _____ .                 | testing frequently for total dissolved solids                        | maintaining low boiler water pH                             | giving the boiler frequent surface blows        | testing boiler water for excess scavenging agents                           |  |

|    |     |   |  |  |   |   |  |  |
|----|-----|---|--|--|---|---|--|--|
| 13 | 390 | B | If an automatically fired burner ignites, but repeatedly goes out within two seconds, the cause could be a/an .  | faulty pressure signal to the time delay relay circuit | dirty flame scanner window                                    | burned out solenoid coil in the low fire oil valve  | excessively high fuel oil temperature                                |  |
| 13 | 391 | A | Where reaction turbine blading is fitted with shrouding of "end tightened" design, which of the following conditions will be the most critical to efficient turbine operation? | Rotor axial position                                   | Diaphragm clearance position                                  | Limiting the use of LP bleed steam  | Operation through critical speed ranges                              |  |
| 13 | 392 | A | On a boiler safety valve, the blowdown adjusting ring is locked in place by a .  | set screw  | locknut   | wire seal   | cotter pin   |  |
| 13 | 393 | A | Flame scanners are used with boiler combustion control systems to monitor flame quality and to .   | shut off the fuel supply if flame failure is detected  | secure the fuel oil service pump in the event of a floor fire | secure the forced draft fan in the event of a flame failure                                       | regulate the fuel/air ratio controller for more efficient combustion |  |
| 13 | 394 | D | Fuel oil settling tanks are used to .  | store oil for immediate use                            | separate water and solids from the fuel                       | make stripping of sludge and water from fuel oil easier   | all of the above   |  |
| 13 | 395 | D | Which of the DC heater operations listed will result in excessive dissolved oxygen in boiler water?  | Excessively high water level in the heater.            | Conical baffles carrying away.                                | Operating the heater with a closed air vent.  | All of the above.  |  |
| 13 | 396 | C | Ultraviolet light sensing flame scanners installed on an automated main propulsion boiler, are designed so they .  | might be misled by glowing brickwork                   | will be sensitive to the outer portion of flames              | are sensitive only to the center of the ultraviolet portion of the flame from a particular burner | cannot be used with steam atomizing burners                          |  |
| 13 | 397 | C | Which of the boiler end points should be reached first?  | Water circulation                                      | Moisture carryover  | Combustion  | Atomization  |  |
| 13 | 398 | B | The amount of oil atomized by a straight mechanical fuel oil burner depends on the sprayer plate size and the .  | oil return pressure                                    | fuel oil pressure   | forced draft pressure   | furnace air pressure   |  |

|    |     |   |  |   |  |  |  |  |
|----|-----|---|--|---|--|--|--|--|
| 13 | 399 | A | What are the two most common gases that dissolve in boiler water and cause corrosion on the internal parts of the boiler?                        | Oxygen and carbon dioxide   | Oxygen and carbon monoxide   | Oxygen and ammonia   | Oxygen and nitrogen  |  |
| 13 | 400 | A | Which of the following represents a significant system limitation to be aware of when a burner management system is operated in the 'HAND' mode? | Some boiler safety interlocks are bypassed when the boiler is 'HAND' fired. | The burner is not capable of maintaining a high firing rate when the boiler is in the 'HAND' mode. | The flame failure alarm cannot function when the boiler is 'HAND' fired. | The burner sequence control is fully automatic even in the 'HAND' mode.              |  |
| 13 | 401 | B | What happens to the steam as it moves across the moving blades in a reaction turbine?  | It gains velocity at constant pressure.                                     | It creates an axial thrust in the direction of the steam flow.                                     | It loses velocity at constant pressure.                                  | It creates an axial thrust opposing the direction of steam flow.                     |  |
| 13 | 402 | D | An advantage of using boiler furnace studded water wall tubes packed with refractory is that .   | thinner tubes can be used   | thicker tubes are required   | lower quality steel can be used  | the use of dense firebricks is not required  |  |
| 13 | 403 | B | If the water level in the boiler water gage glass is not in sight, and the automatic feedwater regulator is in the closed position, the .        | safety valve should be lifted by hand                                       | fires should be shut off   | boiler water gage is faulty  | bottom blow should be opened   |  |
| 13 | 404 | B | Which of the following systems is designed to use auxiliary exhaust steam?   | Steam fuel oil atomizers  | Deaerating feedwater heater  | Air ejectors   | Standby lube oil pumps   |  |
| 13 | 405 | A | During cold ship start-up, you should open the feedwater outlet and condensate valves to a DC heater in order to .                               | avoid running the feed pump 'dry'   | expel noncondensable vapors from the vent  | thoroughly atomize incoming condensate                                   | prevent excessive pressure   |  |
| 13 | 406 | C | In a boiler automation system, if a burner fuel oil solenoid valve continually trips closed under normal steaming conditions, you should .       | wedge the valve in the open position and report it to the chief engineer    | bypass the solenoid valve and enter the fact in the logbook  | secure the burner and determine the cause of the valve failure           | wedge the valve in the open position and reduce the fuel oil pressure at that burner |  |

|    |     |   |   |   |  |   |  |  |
|----|-----|---|---|---|--|---|--|--|
| 13 | 407 | D | The 'end point for combustion' for a boiler furnace is reached whenever .   | the amount of heat being transferred to the tubes reaches a maximum no matter how much the firing rate is increased | panting of the furnace accompanied with black smoke takes place                          | the maximum rate at which the boiler can generate steam | the capacity of the sprayer plates at the designed pressure for the system is attained |  |
| 13 | 408 | D | The degree of fuel oil atomization is dependent upon the .  | boiler furnace size and shape   | air pressure at the furnace  | air supply temperature                                  | atomizer design  |  |
| 13 | 409 | D | Chemicals are added to boiler feedwater to .  | reduce the frequency of blowdowns   | prevent precipitation of sludge  | retard heat transfer                                    | prevent oxygen corrosion   |  |
| 13 | 410 | B | While your vessel is steaming with one boiler, the automatic combustion control system sensing line for the idle boiler is accidentally opened. How will this effect the steaming boiler? | The steam pressure will drop.   | The steam pressure will rise.  | The water level will rise.                              | The water level will drop.   |  |
| 13 | 411 | C | Packing rings installed on auxiliary turbines are lubricated by .   | separate lube oil lines   | a water leak off line  | moisture in the turbine steam                           | a salt water service line  |  |
| 13 | 412 | C | When the automatic combustion control fails, what should you do to control the air supply to a boiler?  | Reduce the firing rate.   | Open the forced draft fan crossover damper.  | Manually control the fan discharge damper position.     | Manually control the fan inlet damper position.  |  |
| 13 | 413 | C | When conducting a routine hydrostatic test on a water-tube boiler, you should .   | raise the temperature of the boiler water to 180°F  | apply hydrostatic pressure equal to the maximum allowable working pressure of the boiler | have gags installed on all safety valves                | bypass the economizer  |  |
| 13 | 414 | A | Under normal operating conditions, a drop in the steam temperature leaving an uncontrolled interdeck superheater could be caused by a .   | decrease in combustion gas velocity through the superheater   | decrease in steam velocity through the superheater                                       | drop in the feedwater temperature                       | badly fouled economizer  |  |

|    |     |   |   |   |  |  |   |         |
|----|-----|---|---|---|--|--|---|---------|
| 13 | 415 | C | If the boiler water and condenser hotwell levels are normal, but the DC heater level is only 30% of full, you should .                          | increase the speed of the condensate pump                         | open the feed pump recirculating valve wide                | open the makeup feed                         | bypass the vent condenser and third-stage feed heater           |         |
| 13 | 416 | C | Auxiliary exhaust steam can generally be used as a supply for the .   | air ejectors  | steam atomizers  | air heater supply                            | fuel oil heaters  |         |
| 13 | 417 | C | Reaching which of the boiler end points listed could cause the most damage to a boiler?   | Combustion  | Moisture carryover   | Circulation                                  | Heat transfer   |         |
| 13 | 419 | A | High salinity can be reduced in a steaming boiler by adding caustic soda, phosphate, and then .   | using the continuous blowdown                                     | steaming at a low firing rate for 24 hours                 | adding hydrazine to control dissolved oxygen | adding calcium carbonate to precipitate solids                  |         |
| 13 | 420 | B | The main purpose of the boiler steam drum component shown in the illustration is to .   | permit expansion during pressure surges                           | prevent thermal shock                                      | reduce vibration                             | reduce the possibility of priming                               | SG-0006 |
| 13 | 421 | B | In a cross-compounded turbine propulsion plant, steam enters the .  | high pressure, intermediate and low pressure units simultaneously | high pressure unit and then flows to the low pressure unit | high and low pressure units simultaneously   | high pressure unit and then flows to another high pressure unit |         |
| 13 | 422 | A | Which normally closed valve would have to be at least partially open prior to actually lighting off a cold boiler as shown in the illustration? | J   | F  | D  | C   | SG-0009 |
| 13 | 423 | B | Which of the following systems can normally be supplied by auxiliary exhaust steam?   | Main feed pump  | Low pressure evaporator                                    | Air ejectors                                 | Boiler steam atomizers  |         |
| 13 | 424 | A | Under normal conditions, the rate of heat transfer in a feedwater heater is most greatly affected by the .                                      | temperature differential between the steam and feedwater          | density of the feedwater                                   | pH of the feedwater                          | speed of the main feed pump                                     |         |
| 13 | 426 | D | Which set of boiler end points listed is considered to be the normal order of occurrence?   | Circulation, combustion, carryover                                | Combustion, circulation, carryover                         | Circulation, carryover, combustion           | Combustion, carryover, circulation                              |         |

|    |     |   |   |  |  |   |  |         |
|----|-----|---|---|--|--|---|--|---------|
| 13 | 427 | A | Which of the listed characteristics of fuel oil establishes the danger point as far as transferring, pumping, and firing procedures are concerned?      | Flash point                                    | Fire point   | Viscosity   | Specific gravity   |         |
| 13 | 428 | D | Which of the terms listed represents the ratio between the highest and lowest fuel oil pressure at which the burners will remain ignited?               | Air/fuel ratio                                 | Modulating band ratio  | Firing range ratio  | Turndown ratio   |         |
| 13 | 429 | B | If a routine boiler water test indicates high salinity, you should blowdown the boiler to reduce salinity and then .                                    | add carbonates to control sludging             | treat the boiler water with phosphates                       | reduce the firing rate to prevent scaling                         | increase the firing rate to prevent foaming  |         |
| 13 | 430 | D | The steam soot blower piping should be thoroughly drained before operating to prevent .   | accidental flameout                            | feedwater losses   | nozzle plugging   | erosion of refractory  |         |
| 13 | 431 | A | In a cross-compounded turbine operating at full load, the total available steam energy is approximately divided between the HP and LP in the ratio of . | 1:01   | 2:01   | 3:01  | 4:01   |         |
| 13 | 432 | D | The turbogenerator steam stop is located between the superheater outlet and the main steam stop valve to .  | provide for easier access                      | provide higher quality steam for the turbogenerators         | provide a flow of cooling steam through the control desuperheater | allow the use of superheated steam in the turbogenerator without pressurizing the larger main steam line |         |
| 13 | 433 | C | The component shown in the illustration depicts a/an .  | safety valve escape pipe expansion joint       | spray attemperator with a thermal sleeve                     | internal feed pipe and shell connection                           | dry pipe and shell connection  | SG-0006 |
| 13 | 434 | B | An increase in the pressure drop between the inlet and outlet of the feedwater heater waterside, not due to a waterside obstruction, would indicate .   | insufficient water velocity through the heater | a water flow rate higher than feedwater heater design limits | fouling of the heater steam side                                  | an accumulation of noncondensable gases in the steam circuit   |         |

|    |     |   |  |   |   |  |   |         |
|----|-----|---|--|---|---|--|---|---------|
| 13 | 435 | C | Which of the drains listed could be led directly to a DC heater operating at 35 psig (343 kPa)?  | Drain inspection tank overflow only.  | Contaminated evaporator relief valve drain only.  | An auxiliary steam line drain.   | Only those steam drains which operate at 35 psig (343 kPa) or less.   |         |
| 13 | 436 | C | Which of the following systems can be supplied by the auxiliary exhaust system?  | Main feed pump  | High pressure evaporator  | Boiler air heaters   | Boiler steam atomizers  |         |
| 13 | 437 | A | The connections labeled "A" in the illustration, are used to .   | maintain a vacuum in the shell of the feed water heater   | provide a point of admission for the steam air heater drains  | provide a point of admission for the L.P. bleed steam  | drain condensate from the feed water heater to the main condenser   | SG-0025 |
| 13 | 438 | A | Under normal operating conditions, a drop in the steam temperature leaving an interdeck-type superheater can be caused by a decrease in the velocity of the .                            | combustion gas flowing around the superheater tubes   | steam flowing through the superheater tubes   | steam flowing through the desuperheater  | steam entering the dry pipe   |         |
| 13 | 439 | B | In addition to the repeated use of surface blow to control boiler water chemistry, caustic soda may be used to treat high salinity, as well as .   | calcium chromate, for oxygen control  | phosphate, to aid in scale prevention   | calcium carbonate, to assist in precipitating solids   | calcium sulfate to reduce priming   |         |
| 13 | 440 | A | Upon taking over the watch, while the vessel is at sea speed, you find the following conditions to exist. Which condition should be attended to first and why should this step be taken? | Excessive recirculation of condensate. Failure to properly adjust may cause an increase in condenser level leading to a decrease in condenser vacuum. | Salted up evaporator dumping to bilge. Must immediately be restarted to prevent insufficient quantities of distilled and potable water. | High level in fuel oil sludge tank. Necessary to pump contents to settler to prevent overflow of tank into the bilges. | Leaking air line to auxiliary exhaust live steam makeup valve actuator. Repair or place in bypass control to insure proper pressures in the auxiliary exhaust steam system. |         |

|    |     |   |  |  |   |  |   |         |
|----|-----|---|--|--|---|--|---|---------|
| 13 | 441 | B | A turbine assembly in which steam flows in series through a high pressure turbine and then on to a low pressure turbine, with both turbines driving a common reduction gear through separate shafts, is classed as _____ . | dual series  | cross-compound  | tandem-compound  | tandem, double flow   |         |
| 13 | 442 | C | The main steam stop valve on a "D" type marine boiler is located at the _____ .  | desuperheater outlet   | desuperheater inlet   | superheater outlet   | superheater inlet   |         |
| 13 | 443 | A | Dirty generating tube surfaces may cause higher than normal superheater outlet temperatures because _____ .  | the boiler must be overfired to maintain the required rate of steam generation | the temperature of the gas leaving the generating banks will be lower than normal | the screen tubes absorb excessive heat and transfer the increased temperature to the superheater | gas laning will result causing overheating of the superheater       |         |
| 13 | 444 | C | If there is a sudden drop in the outlet temperature of an uncontrolled superheater, you should _____ .   | increase the firing rate   | bypass the air heater   | check for high water level in the drum   | reduce the forced draft fan speed                                   |         |
| 13 | 445 | C | In a modern high pressure steam plant, most feedwater deaeration takes place in the _____ .  | atmospheric drain tank   | air ejector condenser   | DC heater  | vent condenser  |         |
| 13 | 446 | A | The feed water heater shown in the illustration is actually comprised of three separately functioning heat exchangers. These heat exchangers are identified as the _____ .   | first stage heater, gland exhaust condenser, and drain cooler                  | first stage heater, inter condenser, and after condenser                          | inter condenser, after condenser, and gland exhaust condenser                                    | drain cooler, distillate condenser, and fresh water drain collector | SG-0025 |
| 13 | 447 | D | The limiting factor in determining the end point for combustion is usually the _____ .   | shape of the burner  | size of only the sprayer plates   | fuel oil pressure as the only concern  | ability of the forced draft fan to supply combustion air            |         |
| 13 | 448 | D | Improper atomization can be caused by _____ .  | low draft air pressure   | using the same size burner tips in all burners                                    | using small sprayer plates   | dirty sprayer plates  |         |
| 13 | 449 | D | In a steaming boiler most dissolved chlorides tend to concentrate at or near the _____ .   | tube joints  | feed pipe   | mud drum   | water surface   |         |

|    |     |   |  |   |  |  |  |         |
|----|-----|---|--|---|--|--|--|---------|
| 13 | 450 | D | The upper section of the feed water heater indicated by "G" in the illustration is used as the _____.  | drain cooler  | gland exhaust condenser  | after condenser  | first stage heater   | SG-0025 |
| 13 | 451 | B | In an impulse turbine, the fixed blades function to _____.   | decrease steam velocity   | change the direction of steam flow   | equalize pressure differences  | prevent steam turbulence   |         |
| 13 | 452 | B | The main steam stop bypass valve is used to _____.   | isolate the main steam stop for repairs while steaming                              | gradually increase the pressure and temperature of the main steam piping when warming up | cross-connect two steaming boilers   | supply auxiliary steam when the main steam stop is closed                            |         |
| 13 | 453 | B | The mid section of the feed heater, indicated by "F" in the illustration is used as the _____.   | drain cooler  | gland exhaust condenser  | after condenser  | first stage heater   | SG-0025 |
| 13 | 454 | A | The lower section of the feed heater, labeled "E" in the illustration is used as the _____.  | drain cooler  | gland exhaust condenser  | after condenser  | first stage heater   | SG-0025 |
| 13 | 455 | D | Under normal conditions, steam to the DC heater is supplied directly from which of the systems listed?   | Main steam  | 600 psi auxiliary steam  | 150 psi auxiliary steam  | Auxiliary exhaust steam  |         |
| 13 | 456 | B | A slight vacuum is maintained in the shell of the first stage heater that is part of the feed water heater shown in the illustration. The primary reason for the vacuum is to _____. | provide a low pressure area to guarantee feed water flow to the heater              | maintain a positive flow of steam supplied by main engine bleed system                   | force the use of the main condenser as the drain cooler                          | avoid the necessity of having to use the condensate pumps                            | SG-0025 |
| 13 | 457 | B | Insufficient combustion air supply to the furnace would cause _____.   | the fires to sputter  | low superheater outlet temperature   | high stack temperature   | high feedwater consumption   |         |
| 13 | 458 | B | Which of the following statements is correct concerning the operation of the level or drain regulator associated with the feed water heater shown in the illustration is correct?    | The regulator maintains the flow of steam into the first stage heater of this unit. | The regulator controls the level of condensate collected in the drain cooler section.    | The regulator controls the flow rate of condensate leaving the feedwater outlet. | The regulator controls the volume of condensate leaving the gland exhaust condenser. | SG-0025 |

|    |     |   |   |   |  |   |  |         |
|----|-----|---|---|---|--|---|--|---------|
| 13 | 459 | C | The feedwater heater shown in the illustration was designed to maintain the required feedwater outlet temperature with an approximate 10" (25.4 cm) Hg shell vacuum. If the shell vacuum is increased to approximately 16" (40.64 cm) Hg vacuum, the .                                      | overall plant operating efficiency will increase  | vacuum in the main condenser will drop as the feed heater shell vacuum increases     | feedwater outlet temperature will decrease  | flow rate of condensate to the feed heater will increase | SG-0025 |
| 13 | 460 | D | The feedwater heater shown in the illustration was designed to maintain the required feedwater outlet temperature with an approximate 10" Hg shell vacuum. If the shell vacuum is decreased to approximately 8" Hg vacuum, the .  | overall plant efficiency will increase  | vacuum in the main condenser will increase as the feed heater shell vacuum increases | flow rate of condensate to the feed heater will decrease                          | feedwater outlet temperature will increase               | SG-0025 |
| 13 | 461 | D | The designed function of fixed blades in an impulse turbine is to .   | prevent steam turbulence  | decrease steam velocity  | equalize pressure differences   | change the direction of steam flow                       |         |
| 13 | 462 | B | The bottom blow valve on a water-tube boiler is usually attached to the .   | steam and water drum  | boiler mud drum  | external downcomers   | floor tubes  |         |
| 13 | 463 | C | Which of the following statements is true concerning the piping system shown in the illustration?   | A "Y" strainer is utilized downstream of the Butterworth heater regulating valve to guard against foreign matter entering the heater tube bundle. | All high pressure piping connections are to have welded ends.                        | A moisture separator is installed before the steam whistle.                       | All of the above.  | SG-0005 |
| 13 | 464 | B | If the drain regulator used in the operation of the combined L.P. feed water heater, shown in the illustration, is incorrectly set to maintain too high of a level (condensate level covers approximately the lower half of tubes in the first stage heater) the resulting operation will . | cause no adverse operating effect   | cause the feed water outlet temperature to decrease                                  | cause the feedwater temperature to increase above the designed outlet temperature | cause the automatic make-up feed valve to cycle open     | SG-0025 |

|    |     |   |  |   |   |   |   |         |
|----|-----|---|--|---|---|---|---|---------|
| 13 | 465 | C | During normal operation the steam flow from the auxiliary exhaust line to the DC heater is a function of .   | spring pressure of the spray valves                       | water level in the DC heater reservoir                      | rate of condensation in the DC heater                         | rate of evaporation in the DC heater  |         |
| 13 | 466 | D | The connections labeled "D" in the illustration .  | maintain a vacuum in the shell of the feed water heater   | provide a point of admission of the steam air heater drains | provide a point of admission of the L.P. bleed steam          | drain condensate from the feed water heater to the main condenser                             | SG-0025 |
| 13 | 467 | A | Insufficient combustion air supply to a boiler furnace can cause .   | low superheater temperature                               | high stack temperature                                      | high superheater temperature                                  | sputtering fires  |         |
| 13 | 468 | A | A burner atomizer improperly positioned in the distance piece, may cause .   | oil impingement on furnace walls                          | slag formation on the screen tubes                          | erosion of the screen tube baffles                            | the ends of the flame, farthest from the atomizers, to be a yellowish orange, or golden shade |         |
| 13 | 469 | A | Calcium minerals in boiler water are precipitated out of solution by the use of which of the listed chemicals?   | Sodium phosphate  | Sodium hydroxide  | Phenolphthalein   | Caustic soda  |         |
| 13 | 470 | C | A boiler internal feed pipe is perforated to .   | provide positive flow to the downcomers                   | create a slight turbulence in the steam drum                | distribute water evenly throughout the steam drum             | reduce the weight of the steam drum internals   |         |
| 13 | 471 | A | Gland sealing steam is used on propulsion turbines to prevent .  | air leakage into the turbine                              | steam leakage through the casing drains                     | overheating of the labyrinth packing                          | reversed steam flow at interstage bleeds  |         |
| 13 | 472 | B | Boiler fuel savings gained by the use of an economizer can amount to .   | three percent for each 5°F rise in feed water temperature | one percent for each 10°F rise in feed water temperature    | one half percent for each 15°F rise in feed water temperature | three percent for each 20°F rise in feed water temperature                                    |         |
| 13 | 473 | D | A photoelectric cell is installed in an oil fired boiler safeguard system to introduce proper resistance values to the electronic control circuit. This device is primarily sensitive to . | light emitted from the back wall incandescent brickwork   | light emitted from the front wall incandescent brickwork    | the orange portion of the flame spectrum                      | the blue portion of the flame spectrum  |         |

|    |     |   |  |                                |                                   |   |   |  |
|----|-----|---|--|--------------------------------|-----------------------------------|---|---|--|
| 13 | 474 | D | Treatment of boiler feedwater for the control of hardness is necessary to prevent _____.   | excessive feedwater alkalinity | foaming                           | carryover                                       | waterside scale deposits                |  |
| 13 | 475 | B | In a DC heater, which source of steam is commonly used to heat and deaerate condensate?  | Root steam                     | Auxiliary exhaust steam           | Main steam                                      | Auxiliary steam                         |  |
| 13 | 476 | C | Low steam pressure in a steaming boiler can be caused by _____.  | low steam demand               | high feedwater temperature        | low water level                                 | large sprayer plates                    |  |
| 13 | 477 | C | Which of the following boiler stack (smoke color) conditions indicates efficient combustion?   | Black haze                     | White haze                        | Brown haze                                      | Yellow haze                             |  |
| 13 | 478 | C | If the temperature of the fuel oil entering an atomizer is too low, the burner will _____.   | dribble fuel and smoke white   | require more fuel for atomization | produce heavy black smoke at any load condition | require more excess air for combustion  |  |
| 13 | 479 | C | Of the impurities commonly found in marine lubricating oil, which of the following can NOT be removed by a centrifugal purifier at normal operating temperatures?  | Water                          | Carbon particles                  | Soluble sludge                                  | Metal particles                         |  |
| 13 | 480 | A | If the boiler water level of one boiler drops out of sight while your vessel is steaming, and the burners have been secured, you should _____.   | slow down the main engine      | close the main steam stop         | start the standby feed pump                     | blowdown the gage glass                 |  |
| 13 | 481 | C | When a high pressure turbine is operating at sea speed, the pressure of the steam leaking through the shaft gland packing may be slightly higher than the pressure setting of the gland seal regulator. In this situation, the excess steam at the regulator is directed to the _____. | gland exhaust condenser        | excess steam condenser            | main condenser                                  | auxiliary exhaust system                |  |
| 13 | 482 | A | The phrase 'boiler water column' as defined in the regulations, refers to the _____.   | water level indicator          | vertical water leg                | pressure head to the feedwater pump suction     | pressure gauge reading in feet of water |  |

|    |     |   |   |   |   |   |   |         |
|----|-----|---|---|---|---|---|---|---------|
| 13 | 483 | C | Which of the following statements best describes the actions occurring to the oil as it flows through a disk type centrifugal purifier?       | The purified oil is only thrown outward and away from the spindle of the machine. | Water, along with most of the dirt and sludge, is discharged past the discharge ring, located at the top of the bowl. | Most of the dirt and sludge is forced to accumulate on the vertical surfaces of the bowl. | As the dirty oil flows down through the distribution holes in the disks, the high centrifugal force causes the water to move outward. |         |
| 13 | 484 | D | Coast Guard Regulations (46 CFR) permit copper pipe used in steam service to be subjected to a maximum pressure and temperature of _____.     | 350 psi and 460°F (2413 kPa and 237.7°C)  | 350 psi and 406°F (2413 kPa and 207.8°C)  | 250 psi and 460°F (1723 kPa and 237.7°C)  | 250 psi and 406°F (1723 kPa and 207.8°C)  |         |
| 13 | 485 | B | Dissolved oxygen in the condensate can result from _____.   | steam leaks into the gland leakoff  | air leaks through the turbine glands  | improper operation of the gland exhauster   | vapor lock in the condensate pump   |         |
| 13 | 486 | A | Coast Guard Regulations (46 CFR) permit repairs to boiler safety valves while installed on a main propulsion boiler and may be made by _____. | the chief engineer in an emergency  | any competent person on the ship  | an approved repair facility only  | only the safety valve manufacturer  |         |
| 13 | 487 | B | Incomplete combustion due to insufficient air yields an excess amount of _____.   | carbon dioxide  | carbon monoxide   | nitrogen oxide  | sulfur dioxide  |         |
| 13 | 488 | B | If a burner were inserted too far into the boiler furnace, it could cause carbon deposits on the _____.                                       | furnace opening   | burner tip  | air cone  | register doors  |         |
| 13 | 489 | D | To minimize metal corrosion, boiler water is best kept _____.   | fairly acidic   | slightly acidic   | neutral   | alkaline  |         |
| 13 | 490 | C | In a disk type centrifugal purifier, the bowl is mounted on the upper end of the _____.   | worm wheel  | radial thrust bearing   | bowl spindle  | friction clutch   |         |
| 13 | 491 | B | Bridge gage readings are to be taken on the bearing shown in the illustration. You would use the indicated 3 3/4"R to _____.                  | identify the bearing by radius  | center the bearing load point   | center the bridge gauge   | measure the angle to bridge gauge   | SE-0017 |
| 13 | 493 | C | A centrifuge should satisfactorily remove which of the listed substances from lube oil?   | Fuel oil  | Gasoline  | Water   | Diesel fuel   |         |

|    |     |   |  |  |  |  |   |  |
|----|-----|---|--|--|--|--|---|--|
| 13 | 494 | A | A sulfite test is performed on boiler water to determine the amount of .   | excess sulfite present   | excess nitrate present   | dissolved iodate present   | carbon dioxide present  |  |
| 13 | 495 | A | Which of the following statements represents the function of a turbine gland exhaust condenser?                              | Assists in preheating the condensate before it enters the DC heater.           | Recovers condensate formed at the gland seal exhaust leak off.                                       | Directs the gland exhaust from the turbine sealing glands to the air ejector suction.        | Recovers condensate from the gland leakage around the ahead and astern throttle valves. |  |
| 13 | 496 | C | Coast Guard regulations require that the relieving capacity of boiler safety valves must be checked .                        | at least once a year   | at least once every 4 years  | when the generating capacity of the boiler is increased                                      | when repairs have been made to the safety valves  |  |
| 13 | 497 | C | Insufficient air for combustion in a boiler furnace could result in a .  | white incandescent flame   | high flame temperature   | black stack smoke emission   | 0% carbon monoxide level  |  |
| 13 | 498 | A | Which of the following represents the function of the diffuser used with a mechanical atomizing oil burner?                  | Provide flame stability at the atomizer tip.                                   | Control the amount of secondary combustion air.  | Complete the vaporization of the fuel for combustion.  | Finely divide the fuel particles into a cone-shaped spray.                              |  |
| 13 | 499 | D | A sulfite test is conducted on boiler water to check for .   | nitrates   | sulfates   | phosphates   | excess oxygen scavenging agents   |  |
| 13 | 500 | A | One function of the disks, in a disk-type centrifugal purifier, is to divide the bowl space into many separate passages to . | minimize agitation of the oil-water mixture                                    | increase hydraulic head needed for proper circulation  | completely filter out suspended particles  | prevent bowl spindle vibration  |  |
| 13 | 501 | D | The main propulsion shaft turning gear usually connects to the free end of the high-speed high pressure pinion because the . | lubricating oil from the high-speed pinion can easily supply the turning gears | turning gears are double reduction worm type and cannot mate with the low pressure high-speed pinion | arrangement allows for the use of a muff type coupling for flexibility and smooth engagement | greatest gear ratio between the turning gear motor output and bull gear can be obtained |  |
| 13 | 502 | A | A boiler feed stop-valve must be mounted .   | between the feed check valve and the boiler drum                               | between the feed pump and the feed check valve   | upstream of the feedwater regulator  | at or near the engine room operating platform   |  |

|    |     |   |  |  |  |   |  |  |
|----|-----|---|--|--|--|---|--|--|
| 13 | 503 | B | A boiler internal feed pipe is perforated to _____.  | provide positive downward circulation at high loads                | distribute the feedwater throughout the steam drum | reduce back pressure in the feedwater piping  | reduce the overall weight of the drum internals            |  |
| 13 | 504 | A | When the flow of oil admitted to a disk-type centrifugal purifier is in excess of its designed capacity, which of the following conditions will usually occur? | The oil will be discharged through the heavy phase discharge port. | The speed of the centrifuge will increase.         | All water will be retained by the purified oil being discharge.                         | Oil will be present in the water sealing line to the bowl. |  |
| 13 | 505 | B | The gland exhaust fan draws steam and noncondensable vapors from the gland exhaust condenser and discharges to the _____.                                      | atmospheric drain tank   | atmosphere   | main condenser  | vent condenser   |  |
| 13 | 506 | B | The water level in a steaming boiler has risen to within 2 inches of the top of the top gage glass. Your immediate action should be to _____.                  | secure the fires   | reduce the feedwater flow to the boiler            | secure the feedwater flow to the boiler   | open the surface blow line                                 |  |
| 13 | 507 | C | Insufficient combustion air supply will cause an atomizer flame to appear as a _____.  | ragged flame   | pointed flame                                      | dull red flame with black streaks   | light yellow flame with white streaks                      |  |
| 13 | 508 | C | The purpose of the diffuser in a boiler burner assembly is to _____.   | break up fuel oil into a fine spray                                | assist combustion by heating incoming air          | shield the flame from the incoming air blast while allowing some mixing of fuel and air | diffuse flame to all corners of the furnace                |  |
| 13 | 510 | B | Prior to relieving the watch you should first check the fireroom status by verifying the boiler steam drum level and _____.                                    | lube oil temperature   | fuel pressure to the burners                       | water drum level  | steam atomization temperature to the mechanical atomizers  |  |
| 13 | 511 | C | A nozzle in an impulse turbine functions to _____.   | reverse steam flow direction                                       | guide the steam through the fixed blades           | convert the steam's thermal energy to kinetic energy                                    | convert the steam's kinetic energy to thermal energy       |  |
| 13 | 512 | B | Steam baffles are used in the steam drum of a water-tube boiler to _____.  | support the drum safety valve nozzles                              | reduce the possibility of carryover                | extend the internal feed pipe   | remove boiler water dirt deposits                          |  |
| 13 | 513 | C | Which of the following chemicals is used in an Orsat apparatus to absorb carbon dioxide?   | Cuprous chloride   | Pyrogallic acid                                    | Potassium hydroxide   | Potassium chromate   |  |

|    |     |   |   |   |  |  |   |  |
|----|-----|---|---|---|--|--|---|--|
| 13 | 514 | A | Any feedwater testing done on a routine basis would normally include testing for .  | chloride  | phosphate  | electrical conductivity (total dissolved solids)                       | all of the above  |  |
| 13 | 515 | B | When raising vacuum on an auxiliary condenser, which of the following steps is necessary?   | Close the makeup feed drag line to raise hotwell level. | Open the auxiliary condensate recirculation valve from the auxiliary air ejector condenser outlet. | Rotate turbine with hand jacking gear while applying gland seal steam. | Close condensate pump vent line to eliminate air leaks. |  |
| 13 | 516 | B | When operating under constant load, the superheated steam temperature may rise above normal if the .  | excess air is too low                                   | feedwater temperature is too low   | feedwater temperature is too high                                      | boiler is priming                                       |  |
| 13 | 517 | A | Assuming all burners are clean and the fuel oil is at the correct temperature, it is considered good practice to adjust the excess air until a light brown haze is obtained. With the aid of a chemical based flue gas analyzer, the percentage readings (not necessarily in order) should indicate . | no CO, low O2, and high CO2                             | low CO2, no O2, and high CO  | high CO, high CO2, and no O2   | high O2, low CO, and low CO2                            |  |
| 13 | 518 | B | The measured gap between the face of the burner atomizer tip nut and the diffuser plate, is determined by the setting of the .  | atomizer tip nut  | distance piece   | sprayer plate  | diffuser plate  |  |
| 13 | 519 | D | Chemicals are added to boiler water by injecting them .   | as a powder into the mud drum                           | as a powder into the steam drum  | in solution into the main feed line                                    | in solution through the chemical feed pipe              |  |
| 13 | 520 | D | The size of the discharge ring used in a lube oil purifier is determined by the oil's .   | viscosity   | moisture content   | sediment content   | specific gravity  |  |

|    |     |   |   |  |  |  |   |  |
|----|-----|---|---|--|--|--|---|--|
| 13 | 521 | C | A factor in determining the minimum steam temperature required at the turbine inlet is the _____.   | horsepower of the turbine  | vacuum in the condenser  | moisture content in the steam at the LP end of the turbine | specific volume of the steam in the low pressure end of the turbine |  |
| 13 | 522 | D | Combustion gases can leak into the fireroom through _____.  | desuperheater seals  | fouled burner registers  | idle burner assemblies                                     | soot blower swivel tube packing glands                              |  |
| 13 | 523 | C | Coast Guard Regulations (46 CFR) prohibit which of the following pipe fittings from being installed in fuel oil service discharge piping? | Pipe unions  | Screwed bonnet valves  | Street ells  | Bolted flange joints  |  |
| 13 | 524 | A | Natural circulation in a marine boiler is a result of _____.  | the difference in the densities of the fluid in the downcomer and riser circuits | the fact that the specific weight of steam is greater than water | the velocity imparted to the feedwater by the feed pump    | the turbulence of high pressure feedwater entering the steam drum   |  |
| 13 | 525 | A | While vacuum is being raised on the main unit and the turbine warmed, condensate is recirculated to the main condenser to _____.          | ensure the condensation of air ejector steam                                     | cool the main condenser shell for better vacuum                  | provide a condenser vacuum seal                            | maintain a proper DC heater water level                             |  |
| 13 | 526 | C | Why should a boiler furnace be purged before the first burner is lit off?   | To control air pressure in the windbox.  | To ensure a proper fuel to air ratio.                            | To clear the furnace of any explosive gases.               | To make the fires easier to light.                                  |  |
| 13 | 527 | A | White stack smoke could indicate _____.   | excessive air leakage through the inner casing                                   | low atomizer fuel temperature                                    | insufficient air for combustion                            | excessive furnace combustion temperature                            |  |
| 13 | 528 | C | The diffuser of a burner register assembly _____.   | acts as a shield to prevent flare back   | shapes the fuel particles into a cone                            | serves to make the air mix evenly with the oil             | adds heat to the fuel particle cone                                 |  |
| 13 | 529 | B | Which of the following precautions should be observed when adding treatment chemicals to the boiler compound tank?                        | Cool the feedwater before it enters the tank.                                    | Ensure there is no pressure on the tank before opening it.       | Raise the boiler water level before adding chemicals.      | All of the above.   |  |

|    |     |   |   |  |   |  |  |  |
|----|-----|---|---|--|---|--|--|--|
| 13 | 530 | A | Scavenging air is supplied to steam soot blower elements to _____ .   | prevent back up of combustion gases into soot blower heads | provide cooling air when soot blower elements are rotating through blowing arcs | prevent build up of soot on the element                | prevent overheating of adjacent tubing                             |  |
| 13 | 531 | C | When a turbine rotor is not rotating during maneuvering, the heat tends to be concentrated at the _____ .   | turbine bleed lines  | exhaust trunk   | top of the turbine                                     | casing joints  |  |
| 13 | 532 | A | Which of the valves listed should be closed before lighting off a boiler?                                   | Economizer drain valve                                     | Air cock valve  | Superheater vent valve                                 | Superheater drain valve  |  |
| 13 | 533 | B | The bulk of the solid material entering a centrifugal purifier with lube oil is _____ .                     | discharged with the water                                  | trapped in the bowl   | trapped in the filter                                  | forced out the overflow  |  |
| 13 | 534 | A | Excess free oxygen in the boiler feedwater can be the result of _____ .                                     | improper operation of the DC heater                        | steam leaks through the turbine glands  | improper operation of the gland exhauster              | vapor lock in the boiler feed pump                                 |  |
| 13 | 535 | B | In a marine condenser designed with a reheating hotwell, the hotwell is reheated by _____ .                 | recirculation of condensate                                | steam lanes in the condenser  | a branch line from the air ejector steam supply        | submerged heating coils supplied with auxiliary exhaust steam      |  |
| 13 | 536 | D | To properly use a tube expander, the expander should be placed in the tube to be rolled so that the _____ . | bellling section is flattened against the tube sheet       | rollers bear on the portion of the tube which needs bellling                    | mandrel is in direct contact with the inner-tube sheet | rollers bear on the portion of the tube which is in the tube sheet |  |
| 13 | 537 | B | Black smoke issuing from the boiler stack can be caused by an improper fuel/air ratio and by _____ .        | excessively high fuel pressure                             | low fuel temperature  | high fuel temperature                                  | low fuel pressure  |  |
| 13 | 538 | D | When used as a separator, a centrifugal purifier may lose its seal and cause _____ .                        | water to contaminate the lube oil                          | the purifier pump to lose suction   | water flow from the oil discharge                      | oil flow from the water discharge                                  |  |
| 13 | 539 | D | In a water-tube boiler, sludge is most likely to collect in the _____ .                                     | generating tubes   | downcomer tubes   | screen tubes   | floor tubes  |  |
| 13 | 540 | C | Longitudinal expansion of a boiler water drum is allowed for at the boiler _____ .                          | tube sheet   | casing joints   | foundation sliding feet                                | refractory expansion joint   |  |

|    |     |   |   |   |  |   |   |  |
|----|-----|---|---|---|--|---|---|--|
| 13 | 541 | D | Before placing the jacking gear in operation on a main turbine unit, you must always _____ .  | start the gland seal steam                              | start the main circulating pump  | line up the condensate system                                     | line up and start the lube oil system   |  |
| 13 | 542 | A | Slag buildup on boiler furnace refractory is undesirable because it causes _____ .  | peeling or spalling of the brickwork                    | excessive cooling of the brickwork   | shrinking of the brickwork  | fracturing of the anchor bolts  |  |
| 13 | 543 | B | A boiler is to be secured in port. After the burners have been secured, the forced draft fan and air registers should be secured _____ .  | immediately after carrying out the former procedures    | after any oil on the furnace floor has been burned off and cleared of combustion gases | after 30 minutes has elapsed, after carrying out these procedures | after at least 1 hour has elapsed, after carrying out these securing procedures |  |
| 13 | 544 | B | The major reason dissolved gases are removed from boiler feedwater is because they may cause _____ .  | condenser vacuum loss                                   | corrosive conditions in the boiler   | a false boiler water level  | vapor lock in the feed pumps  |  |
| 13 | 545 | B | The main condenser is designed with a reheating hotwell. What will occur if the condensate level rises above the top of the hotwell, yet remains below the bottom row of tubes? | Vacuum will decrease.                                   | Condensate temperature will decrease.  | Condensate temperature will increase.                             | The air ejectors will overheat.   |  |
| 13 | 546 | B | Water-tube boiler screen tubes protect which of the listed components from high furnace temperatures?   | Saturated steam tube bank                               | Superheater tube bank  | Water drum  | Refractory  |  |
| 13 | 547 | D | If the boiler uptake periscope appears completely dark, this could indicate _____ .   | too much air  | too little air   | a burned out light bulb   | All of the above are correct.   |  |
| 13 | 548 | B | Any abnormal condition or emergency occurring in the fireroom must be immediately reported to the _____ .   | oiler on watch  | engineer on watch  | first assistant engineer  | U. S. Coast Guard   |  |
| 13 | 549 | D | What boiler water chemistry is necessary to ensure the precipitation of hard scale forming calcium?   | Hydrazine concentrations should be at the proper level. | Boiler water hardness should be high.  | Boiler water should be slightly acidic.                           | Boiler water should have a reserve of phosphates.                               |  |
| 13 | 550 | D | Prior to lighting a burner in a cold boiler, you should _____ .   | close the superheater vent                              | blowdown the mud drum  | open the surface blow valve                                       | thoroughly purge the furnace  |  |
| 13 | 551 | B | The jacking gear on main propulsion turbines can be used to _____ .   | provide propulsion in emergencies                       | provide reduction gear tooth inspection  | reduce turbine speed during maneuvering                           | lift the reduction gear casing  |  |

|    |     |   |   |   |  |  |  |  |
|----|-----|---|---|---|--|--|--|--|
| 13 | 552 | A | Repeated priming in a steaming boiler can cause damage to the _____ .   | superheater   | desuperheater  | economizer   | internal feed pipe   |  |
| 13 | 553 | D | Water is best removed from lubricating oil by _____ .   | silica gel cartridges   | pressure filters   | paper edge filters   | centrifuging   |  |
| 13 | 554 | A | Excessive water loss from the main feed system can be caused by _____ .   | an atmospheric drain tank trap frozen in the closed position                  | excessive recirculation of condensate from the outlet of the air ejector condenser to the main condenser                         | a vapor bound main condensate pump   | a leak in the desuperheater internal gasket  |  |
| 13 | 555 | A | With the steam control valve wide open during normal operation, the rate of steam flow from the auxiliary exhaust steam line to the DC heater is actually a function of _____ . | rate of condensation in the DC heater   | spring pressure of the spray valves  | water level in the DC heater reservoir   | rate of evaporation in the DC heater   |  |
| 13 | 556 | B | Water circulation in a water-tube boiler is a result of the _____ .   | difference between the area and length of the water-tubes                     | differences in water density in boiler tubes   | velocity added to the water by the feed pump   | siphon action of steam leaving the drum  |  |
| 13 | 557 | B | If a boiler is smoking black and increasing the boiler front air box pressure does not reduce the smoke, the cause can be _____ .   | forced draft fan failure  | dirty atomizers  | heavy soot on tubes  | high ambient air temperature   |  |
| 13 | 558 | B | To safely reduce a high water level in a steaming boiler, you should _____ .  | use the bottom blow   | use the surface blow   | secure the boiler fires  | open the superheater drain   |  |
| 13 | 559 | B | The primary difference between sludge and scale deposits in boiler tubes is _____ .   | scale forms only on the cooler boiler tubes whereas sludge forms on all tubes | scale forms as the result of the crystallization of salts, whereas sludge may consist of reaction products from boiler treatment | sludge is hard and nonadherent at operating temperatures, whereas scale can be deposited at any boiler temperature range | scale is heavier than water and forms in lower drums and headers, whereas sludge is more likely to form along the steam drum waterline |  |

|    |     |   |   |   |  |  |  |  |
|----|-----|---|---|---|--|--|--|--|
| 13 | 560 | B | If the gage glass water level remains constant in a steaming boiler while maneuvering, the most probable cause is a .                   | broken feedwater regulator  | restricted gage glass                                  | properly operating feed pump                           | high water level   |  |
| 13 | 561 | C | The jacking gear is used in preparation for starting a marine turbine and reduction gear unit to .                                      | allow the rotor to cool evenly  | allow a film of oil to form on the spring bearings     | prevent the gland seal steam from distorting the rotor | listen for rubbing noises from the gland seal condenser                              |  |
| 13 | 562 | A | Severe priming in a boiler can cause damage to the .  | superheater   | steam drum internals                                   | feedwater regulating valve                             | control desuperheater  |  |
| 13 | 563 | D | In accordance with Coast Guard Regulations (46 CFR), the normal operating pressure of a water-tube boiler must be stamped on the .      | burner front  | lower header   | name plate   | drum head  |  |
| 13 | 564 | C | Which of the following represents one of the most important considerations in the design and location of the boiler internal feed pipe? | Water must be directed toward the downcomers.                                 | Feedwater must be directed to the swash baffles.       | Thermal shock to the boiler drum must be avoided.      | Holes must be drilled in both the upper and lower portion of the internal feed pipe. |  |
| 13 | 565 | C | Zincs are installed in the main and auxiliary condenser waterboxes to .   | reduce turbulence   | prevent air pockets                                    | reduce the effects of electrolysis                     | prevent scaling  |  |
| 13 | 566 | D | The possibility of a flareback in a boiler will be reduced if you .   | rotate the soot blower elements one complete revolution prior to lighting off | maintain the fuel oil to the burner at the flash point | supply a minimum of excess air                         | purge the furnace with fresh air prior to lighting off                               |  |
| 13 | 567 | D | Boiler stack gas temperature could be higher than normal if .   | leakage exists in the inner and outer casing                                  | defects exist in the burner cone refractory            | fuel oil temperature is excessively high               | secondary combustion occurs in the gas passages                                      |  |
| 13 | 568 | A | Which ring dam arrangement should be used for centrifugal purification?   | The largest inside diameter ring without loss of oil.                         | The largest outside diameter ring without loss of oil. | The smallest inside diameter ring without loss of oil. | The smallest outside diameter ring without loss of oil.                              |  |

|    |     |   |   |   |   |   |   |  |
|----|-----|---|---|---|---|---|---|--|
| 13 | 569 | A | Scale prevention in boiler water is accomplished by adding treatment chemicals to _____.  | precipitate scale forming salts as sludge                       | solidify the scale as powder                                    | increase boiler water acidity   | cause the water to be neutral   |  |
| 13 | 570 | B | When a boiler has been secured and is being initially cooled, the water level showing in the steam drum gage glass should be _____.   | allowed to drop naturally                                       | maintained at the normal level                                  | maintained at a full glass  | allowed to go out of sight  |  |
| 13 | 571 | B | If steam is admitted to the main propulsion turbine with the jacking gear engaged, which of the following problems can occur?   | Uneven warming of the turbine.                                  | Destruction of the jacking gear.                                | A possibility of shearing the jacking gear flexible coupling.               | Excessive tooth stress on the high pressure first reduction pinion.         |  |
| 13 | 573 | D | High boiler water level can cause carryover and _____.  | damage to the economizer  | warped screen tubes   | warped water wall tubes   | damage to the propulsion turbine  |  |
| 13 | 574 | A | In a boiler, water flows downward in tubes furthest from the fires and flows upward in tubes nearest the fires because _____.   | water is denser in the tubes farthest from the fires            | water is less dense in the tubes farthest from the fires        | tubes farthest from the fires have a greater diameter                       | tubes farthest from the fires have a smaller diameter                       |  |
| 13 | 575 | C | Air trapped within the main condenser shell is harmful because it will _____.   | decrease the turbine exhaust steam temperature                  | cause the turbine casing to warp and bow                        | decrease the vacuum in the main condenser                                   | cause heat to be transferred too rapidly                                    |  |
| 13 | 576 | A | When an oil purification centrifuge loses a portion of its seal, the oil can then be discharged through the heavy phase discharge port. This is partly a result of greater _____. | centrifugal force being developed on the oil near the interface | centripetal force being developed on the oil near the interface | centrifugal force being developed on the water seal at the side of the bowl | centripetal force being developed on the water seal at the side of the bowl |  |
| 13 | 577 | C | In a steaming boiler, higher than normal stack gas temperature can be caused by _____.  | low steam demand  | excessively high fuel oil temperature                           | too much excess air   | delayed burning due to inadequate excess air                                |  |
| 13 | 578 | D | After restoring the normal water level in a boiler following a high water casualty, you should _____.   | immediately put the boiler on the line                          | immediately drain the economizer                                | blowdown the water gage glass   | completely drain the superheater  |  |
| 13 | 579 | D | The most effective way to eliminate sludge from the water drum of a boiler is to _____.   | frequently use the surface blow                                 | chemically treat the boiler water                               | wash the boiler watersides  | give the boiler a bottom blow   |  |

|    |     |   |  |  |  |  |   |  |
|----|-----|---|--|--|--|--|---|--|
| 13 | 580 | D | The water seal in a centrifuge, operating at normal speed, prevents the lube oil from discharging from the water outlet. Another function of the seal is to .                          | develop permanent emulsions with the lube oil                      | provide a means of 'washing' the oil as it passes through the bowl | keep the bowl at a temperature below that of the lube oil input    | provide an area for separated water to pass and create a path to remove the water from the bowl |  |
| 13 | 581 | D | The axial position of a turbine rotor is normally adjusted by varying the thickness of the .   | thrust bearing shoes   | journal bearing shims  | labyrinth packing fins   | thrust bearing filler piece   |  |
| 13 | 582 | A | Which of the actions listed should be carried out immediately after securing the fires in one boiler of a two boiler ship?   | Relieve all fuel oil service pressure to that boiler.              | Open the air registers wide to cool the furnace.                   | Drain and refill the boiler with cold water.                       | Secure the main feed pump.  |  |
| 13 | 583 | C | If the fires to a steaming boiler have been accidentally extinguished, you should not relight any burner until .   | all burning embers in the furnace are extinguished                 | the furnace refractory has cooled below ignition temperature       | the boiler furnace has been thoroughly purged                      | all fuel has been recirculated from the burners   |  |
| 13 | 584 | C | During the operation of a lube oil centrifuge, a thin emulsion interface occurs between the lube oil and seal. The position of this interface is determined by the .                   | number of disks in the disk stack                                  | outside diameter of the discharge ring                             | inside diameter of the ring dam                                    | initial volume of seal water admitted to the bowl   |  |
| 13 | 585 | B | Which of the condensers listed is cooled by sea water?   | Air ejector condenser  | Main condenser   | Vent condenser   | Gland exhaust condenser   |  |
| 13 | 586 | C | Which of the following statements is true concerning lube oil coolers?   | The temperature of the oil is less than that of the cooling water. | The pressure of the oil is less than that of the cooling water.    | The pressure of the oil is greater than that of the cooling water. | Magnets are installed in the tube sheets to remove metal particles.                             |  |
| 13 | 587 | A | A higher than normal stack gas temperature could indicate .  | dirty firesides or watersides                                      | inner or outer casing leakage                                      | eroded water screen tube walls                                     | defects in burner cone refractory   |  |
| 13 | 588 | C | The original bridge gage reading for a reduction gear bearing was measured as .008 inches. A year later, the bridge gage reading for the same bearing is .010 inches. This indicates . | bearing wear is .010 inch  | oil clearance is .002 inch   | bearing wear is .002 inch  | oil clearance has increased .010 inch   |  |

|    |     |   |   |  |   |  |  |         |
|----|-----|---|---|--|---|--|--|---------|
| 13 | 589 | D | The intermediate pressure bleed steam system, shown in the illustration, is used to supply steam at approximately .   | 35.0 psig  | 13.6 psig   | 13.6 psia  | 67.0 psig  | SG-0024 |
| 13 | 591 | A | When preparing to get underway and the jacking gear has been disengaged, the main unit should NOT remain stationary for more than 3 to 5 minutes, because . | uneven heating from gland seal steam can distort the rotor | the turbine drain lines can fill with condensate          | main condenser vacuum will drop rapidly without steam flow through the main unit | with no rotor movement, the journal bearings may overheat due to reduced lube oil flow |         |
| 13 | 592 | B | The steam drum air cock is normally opened when cooling down a boiler to .  | relieve any residual air pressure in the drum              | prevent a vacuum forming in the steam drum                | reduce the pressure in the drum more rapidly                                     | protect the superheater  |         |
| 13 | 593 | D | In order to obtain the best performance with a lube oil purifier, the lube oil inlet temperature should .   | never exceed the highest main engine bearing temperature   | be equal to the normal lube oil cooler outlet temperature | be equal to main lube oil sump temperature                                       | be maintained in a temperature range of 160°F to a maximum of 180°F                    |         |
| 13 | 594 | D | Chamfers, located at the parting edges of horizontal split sleeve type bearings, are used to facilitate oil storage and distribution. They are machined .   | radially the full length of the bearing                    | axially the full length of the bearing                    | radially, to within 45 degrees of the normal bearing surface                     | axially, approaching but not extending to the end of the bearing                       |         |
| 13 | 595 | A | After the steam leaves the low pressure turbine, it enters the .  | main condenser   | feed and filter tank                                      | first-stage feedwater heater   | turbine extraction valve manifold  |         |
| 13 | 596 | C | To allow for water drum expansion or contraction, the boiler is fitted with .   | U-bend tubes   | expansion joints  | sliding feet   | spring supported pipe hangers  |         |
| 13 | 597 | B | If the stack temperature is higher than normal, this could indicate .   | low fuel oil back pressure                                 | too much excess air                                       | high feedwater pressure  | external boiler casing leakage   |         |
| 13 | 598 | B | The maximum lube oil temperature leaving a large, main propulsion steam turbine bearing should .  | be 130° F  | never exceed 180°F  | never exceed the inlet temperature by more than 55°F                             | not exceed the normal lube oil outlet temperature from the centrifugal purifier        |         |

|    |     |   |   |  |   |   |  |         |
|----|-----|---|---|--|---|---|--|---------|
| 13 | 599 | D | In a marine boiler, maximum heat transfer rates can be obtained by _____ .  | maintaining the recommended boiler water pH                                      | treating the boiler water with oxygen scavenging chemicals  | maintaining the feedwater temperature 212°F in the economizer   | keeping the watersides free from scale deposits        |         |
| 13 | 600 | D | The illustrated device is designed as a _____ .   | water and steam separator  | oil and water separator   | liquid eductor  | steam whistle  | GS-0099 |
| 13 | 601 | B | The jacking gear must be engaged as quickly as possible when securing the main turbines in order to _____ .           | permit rapid cooling of the reduction gears                                      | prevent uneven cooling of the turbine rotors  | maintain a constant supply of lube oil to the main unit   | prevent the stern tube bearing from overheating        |         |
| 13 | 602 | D | After a boiler has been taken off the line and is cooling, the air cock is opened to _____ .                          | purge all air from the steam drum  | allow even cooling of the steam drum  | guard against entrapped gas pockets in the superheater  | prevent the formation of a vacuum within the boiler    |         |
| 13 | 603 | B | Which of the following conditions is true concerning the boiler water drum foundations?                               | All saddles are a rigid support and are welded directly to the ship's framework. | In a typical installation, the water drum is secured solidly to the ship's foundation on one end and free to move on the other. | Good preventive maintenance practice includes chipping the sliding feet and phosphorous bronze chocks to remove all rust and corrosion to insure free movement. | All of the above.                                      |         |
| 13 | 604 | C | The maximum lube oil temperature leaving the lube oil cooler of a main steam turbine propulsion system should _____ . | be about 180°F   | never be more than 60°F below the lube oil inlet temperature  | never exceed 130°F  | be dictated only by the existing sea water temperature |         |
| 13 | 605 | B | Proper vacuum must be maintained in the main condenser to _____ .   | run auxiliary machinery  | maintain plant efficiency   | utilize circulating seawater  | cool the lube oil supply                               |         |

|    |     |   |   |  |  |  |   |         |
|----|-----|---|---|--|--|--|---|---------|
| 13 | 606 | D | Item "Q" in the illustration is used to .   | guide the oil to be cleaned along the inside of the bowl for discharge                                   | balance the force distribution of the three wing device  | assist in breaking down surface tension and thereby increase separation of solids and liquids from the oil | establish the position of the three wing within the bowl  | GS-0124 |
| 13 | 607 | C | Which of the types of superheaters listed has the flattest superheat temperature curve? | Radiant  | Convection   | Radiant-convection   | Conduction-convection   |         |
| 13 | 608 | D | Carbon deposits in a boiler furnace, as a result of oil impingement, can be caused by . | excessive fuel temperature   | defective sprayer plates   | excessive oil pressure   | all of the above  |         |
| 13 | 609 | A | Chemicals are added to boiler water in order to .                                       | reduce oxygen corrosion  | reduce the total dissolved solids content  | decrease the necessity for blowdowns   | eliminate dissolved chlorides   |         |
| 13 | 610 | A | Before lighting any burner in a cold boiler you should always .                         | purge the furnace with air   | open the furnace peephole cover  | close off the burner register  | reduce the forced draft pressure  |         |
| 13 | 611 | C | The main propulsion turbine should be operated with the .                               | lowest practical chest pressure and the minimum number of nozzles required to maintain the desired speed | lowest practical chest pressure and the maximum number of nozzles possible to maintain the desired speed | highest practical chest pressure and the minimum number of nozzles required to maintain the desired speed  | highest practical chest pressure and the maximum number of nozzles possible to maintain the desired speed |         |
| 13 | 612 | A | The internal feed pipe in a D-type marine boiler .                                      | distributes feedwater evenly throughout the steam drum   | guides the feedwater toward the downcomer tubes  | is located well above the normal steam drum water level to assist in deaeration of feedwater               | is drilled with holes to provide even distribution of boiler feedwater chemicals                          |         |

|    |     |   |   |   |  |  |   |
|----|-----|---|---|---|--|--|---|
| 13 | 613 | C | On an automated vessel steaming at full sea speed, which of the following engine room responses will automatically be actuated by changing the bridge throttle control from full ahead to slow ahead? | Main turbine extraction valves will open.           | Scoop injection valve will open.                       | Condensate recirculating valve will open.  | First-stage feedwater heater will be bypassed.                        |
| 13 | 614 | C | Burning fuel with entrained saltwater, will cause a glassy slag formation on furnace refractory. This slag will   | form a protective coating thus increasing its life  | seal refractory joints thereby improving its function  | expand at a different rate and result in damaged refractory  | increase the furnace efficiency because of reduced firebox turbulence |
| 13 | 615 | B | While underway, vacuum in the main condenser is primarily caused by the   | suction drawn by the condensate pump                | condensing of the exhausting steam                     | main air ejector   | aftercondenser loop seal  |
| 13 | 616 | B | The dirty oil inlet on centrifugal lube oil purifiers is located at the   | top of the tubular bowl type                        | bottom of the tubular bowl type                        | top or bottom of the disk type depending upon whether the unit is to be operated as a separator or clarifier | bottom only of the disk type  |
| 13 | 617 | C | Boiler stack gas temperatures will be higher than normal when   | fuel temperature at the burners is excessively high | not enough excess air is being supplied for combustion | secondary combustion is occurring in the gas passages  | internal water wall refractory baffles have failed                    |
| 13 | 618 | B | What is the quickest way to shutoff the boiler fuel oil supply from inside the fireroom?  | Closing the settling tank suction valves.           | Trip the quick-closing fuel valve.                     | Close the double bottom suction valves.  | Open the oil recirculating valves.                                    |
| 13 | 619 | C | Chemicals are added to boiler water to  | eliminate the need for blowdowns                    | stabilize feedwater if a boiler becomes salted up      | prevent scale forming deposits   | maintain an acidic condition in the feedwater                         |
| 13 | 620 | D | To avoid acid corrosion of the economizer tubes when blowing tubes  | raise boiler pressure                               | lower boiler pressure                                  | lower water level  | drain the soot blowers headers  |

|    |     |   |  |  |  |  |  |  |
|----|-----|---|--|--|--|--|--|--|
| 13 | 621 | A | Maintaining low pressure in a condensing turbine exhaust trunk .   | enables better utilization of available heat energy to perform work                | eliminates creep problems in the exhaust trunk during maneuvering              | reduces condensate depression with low seawater temperature                                | prevents steam turbulence in the exhaust trunk due to steam laning                   |  |
| 13 | 622 | D | The maximum, safe, upper limit temperature of lubricating oil discharged from the purifiers is .   | 150°F  | 160°F  | 170°F  | 180°F  |  |
| 13 | 623 | A | Which of the following methods is used to securely fasten the babbitt lining of a reduction gear bearing to its shell?   | The babbitt is centrifugally spun into the bearings or cast under a pressure head. | The babbitt is relieved in way of the split and held in place by locking pins. | The babbitt is securely bonded to the shell by the pressure of the hydrodynamic oil wedge. | The babbitt has a crescent shaped pocket cast symmetrically about the bearing split. |  |
| 13 | 624 | C | In a "D" type marine boiler, operating under constant load, which of the following conditions could cause the superheated steam temperature to rise above normal?                    | High feedwater temperature   | Insufficient combustion air  | Low feedwater temperature  | DFT excessive vapor pressure   |  |
| 13 | 625 | C | In which of the following types of condensers would you find the cooling water passing through tubes with the turbogenerator exhaust steam directed around the outside of the tubes? | Jet  | Barometric   | Surface  | Collins  |  |
| 13 | 626 | B | A poorly cleaned lube oil purifier bowl may result in .  | insufficient oil supply to the gravity tank  | improper separation  | excessive lube oil consumption   | excessive water discharge rate   |  |
| 13 | 627 | B | Low stack gas temperatures due to light boiler loads should be avoided in order to reduce the .  | percentage of carbon monoxide in the stack gas                                     | formation of dew point sulfuric acid   | heat loss through the uptakes  | accumulation of soot   |  |
| 13 | 628 | A | You can secure the fuel supply to the boilers from outside the fireroom by .   | operating the remote shutoff   | operating the double bottom sluice valves with the reach rod                   | closing the master oil valve with the reach rod  | closing the oil recirculating valve with the remote control                          |  |

|    |     |   |   |   |   |   |   |         |
|----|-----|---|---|---|---|---|---|---------|
| 13 | 629 | C | The end products of reactions occurring when boiler water is chemically treated, remain in the boiler and increase the need for _____ . | makeup feed   | acid cleaning   | boiler blowdown   | waterside corrosion treatment   |         |
| 13 | 630 | B | Water removed through centrifugal force in the illustrated unit is displaced from the bowl through _____ .                              | K   | N   | V   | X   | GS-0124 |
| 13 | 631 | D | Proper vacuum must be maintained during prolonged astern operation to _____ .   | eliminate leaving loss in the ahead blading   | minimize any appreciable amount of condensate depression                        | ensure proper action of the condenser sentinel valve or back pressure trip  | prevent overheating of the ahead blading  |         |
| 13 | 632 | B | While raising steam on a cold boiler, the air cock is to be closed after _____ .  | the boiler is cut in on the line  | steam has formed and all air is vented  | the economizer drain is closed  | all burners have been lit and firing normally                                     |         |
| 13 | 633 | A | Which of the following statements is true regarding lube oil coolers used for main steam propulsion systems?                            | Regulating the inlet water flow to a lube oil cooler may result in air binding of the water side. | A lube oil cooler is typically constructed as a cross-flow type heat exchanger. | If an automatically controlled bypass valve controls the lube oil temperature, it will be used to regulate the lube oil flow out of the cooler. | The lube oil usually flows thru the tubes and the cooling water around the tubes. |         |
| 13 | 634 | A | The term 'separation' as used in oil purification refers to the removal of _____ .  | two liquids from each other   | solids from lube oil  | acid contaminants from oil  | oil from its additives  |         |
| 13 | 635 | B | A main condenser utilizing a scoop for the circulation of seawater must be constructed as a _____ .                                     | two-pass heat exchanger   | single-pass heat exchanger  | counterflow heat exchanger  | parallel flow heat exchanger  |         |
| 13 | 636 | A | Under normal firing rates, a reduction of the steam outlet temperature from an uncontrolled superheater could be caused by _____ .      | high feedwater temperature  | too much excess air   | dirty generating tubes  | fouled economizer tubes   |         |
| 13 | 637 | B | Low stack gas temperature should be avoided to reduce _____ .   | economizer thermal stress   | sulfuric acid formation   | back pressure in the uptakes  | air heater thermal stress   |         |

|    |     |   |  |   |   |  |  |         |
|----|-----|---|--|---|---|--|--|---------|
| 13 | 638 | C | All fuel oil service pumps are equipped with a _____.  | relief valve on the suction side  | combustion control valve on the discharge side                                      | remote means of stopping the pump  | direct suction to the double bottom tanks                          |         |
| 13 | 639 | B | One of the purposes of chemically treating boiler water is to _____.   | reduce blowdown frequency   | reduce scale formation  | eliminate waterside cleaning   | constantly decrease alkalinity                                     |         |
| 13 | 640 | C | Sound is produced by the illustrated device by the _____.  | vertical vibrating movement of "E"  | high speed rotation of "B"  | rapid oscillation of "B"   | rapid input of steam or air through "I"                            | GS-0099 |
| 13 | 641 | C | Why is it important to maintain good vacuum in a main turbine unit while operating astern?   | Reduces windage loss in the astern section.   | Prevents the ahead element from operating backwards.                                | Maintains proper temperatures in the ahead stage.                            | Limits the amount of time necessary to operate astern.             |         |
| 13 | 642 | D | The purpose of the boiler drum air cock is to _____.   | admit air when the boiler is being emptied  | permit escape of air when the boiler is being filled                                | permit escape of air when steam is forming in the drum after lighting off    | all of the above   |         |
| 13 | 643 | B | Which of the following statements concerning the operation of a lube oil purifier is correct?  | They should be operated as clarifiers for optimum moisture removal.   | They should be operated at maximum design speed and recommended operating capacity. | They should be operated as slowly as possible to ensure a long service life. | They should not be primed with water when operated as a separator. |         |
| 13 | 644 | C | In order to maintain the required lube oil temperature leaving a lube oil cooler, where an automatic bypass valve is not provided, which of the following operations is correct? | The cooling water to the lube oil cooler is directly regulated to maintain the proper lube oil temperature. | The quantity of lube oil to the cooler is regulated.                                | The cooling water discharge leaving the cooler is directly regulated.        | The lube oil velocity from the cooler is regulated.                |         |
| 13 | 645 | B | Excessive soot deposits on the heating surfaces of a boiler uncontrolled interdeck superheater would be indicated by _____.  | decreased fuel oil and air requirements   | increased stack temperature   | increased desuperheated steam temperature                                    | increased superheater outlet temperature                           |         |

|    |     |   |  |   |   |  |  |  |
|----|-----|---|--|---|---|--|--|--|
| 13 | 646 | D | Lube oil is preheated before centrifuging in order to _____.   | boil off water  | prevent corrosion   | reduce friction of the rotating components of the centrifuge               | improve purification   |  |
| 13 | 647 | A | Which of the following represents the proper color of the flame end farthest from the boiler burner during normal operations?                | Bright yellow or orange   | Dark brown  | Light brown haze   | Dazzling white   |  |
| 13 | 648 | D | The relief valve on the discharge side of the fuel oil service pump may discharge directly to the suction side of the pump, or to the _____. | fuel oil heater inlet   | oil header return line  | double bottom fuel tank  | fuel oil settling tank   |  |
| 13 | 649 | D | What is the purpose of chemically treating boiler water?   | To reduce formation of scale on the waterside of the boiler.          | To reduce to a minimum corrosion of boiler metal.                   | To reduce foaming and moisture carryover.                                  | All of the above.  |  |
| 13 | 650 | D | Which of the following would contribute to the formation of an oil and water emulsion, in addition to acid formation?                        | Aeration, agitation, and heat   | Solid insoluble particles, aeration, and heat                       | Water and solid insoluble particles  | Water, agitation, and heat   |  |
| 13 | 651 | A | The FIRST step in breaking vacuum on a main turbine unit should be to _____.   | secure the steam to the main air ejector                              | secure the steam to the gland seal system                           | stop the main circulating pump   | stop the main condensate pump                                      |  |
| 13 | 652 | A | Which of the following is the best reason for opening the air cock when draining a water-tube boiler?  | With the air cock open, the boiler drains without producing a vacuum. | Water flows out of the boiler too rapidly with the air cock closed. | Air mixed with the water will create a cleansing effect in the tubes.      | Air coming into the boiler will help dry out the boiler's surface. |  |
| 13 | 653 | C | The peeling of boiler refractory associated with slagging, is caused by the _____.   | shrinkage of brickwork adjacent to slag coated refractory             | chemical action of the slag on the firebrick surface                | difference in the rate of expansion between the firebrick and slag coating | uneven heating of the brickwork during boiler warm up              |  |

|    |     |   |   |   |  |  |   |  |
|----|-----|---|---|---|--|--|---|--|
| 13 | 654 | D | The purpose of the cam-actuated steam valve used in a boiler soot blower system, is to _____ .  | rotate the element through a predetermined blowing arc      | automatically blow the elements in the proper sequence | automatically secure steam to the blower head any time the element stops turning | prevent steam from entering the soot blower when the element holes are directed toward the refractory |  |
| 13 | 655 | D | If the pressure becomes excessive in the auxiliary exhaust system, the excess steam will be dumped to the _____ .   | deaerating feed tank  | vent condenser   | reduced steam system   | main condenser  |  |
| 13 | 656 | B | A cause of high superheater outlet temperature is _____ ,   | high feedwater temperature                                  | low feedwater temperature                              | excessive fuel oil temperature at the settlers                                   | insufficient excess air   |  |
| 13 | 657 | D | Which color burner flame would indicate too much excess air?  | Orange red  | Yellowish orange                                       | Bright red   | Incandescent white  |  |
| 13 | 658 | B | The relief valve on the discharge side of the fuel oil service pump may discharge directly to the settler, or to the _____ .                                    | fuel oil heater inlet                                       | suction side of the pump                               | oil header return line   | double bottom fuel tank   |  |
| 13 | 659 | C | An increase in the concentration of total dissolved solids in boiler water can result from _____ .  | zero water hardness   | dissolved oxygen deaeration                            | routine treatment with phosphates  | frequent prolonged surface blows  |  |
| 13 | 660 | D | A centrifuge will satisfactorily remove which of the listed substances from lube oil?   | Diesel fuel   | Gasoline   | Fuel oil   | Carbon particles  |  |
| 13 | 661 | D | To raise vacuum on the main turbine unit, you should _____ .  | start the lube oil pump after starting the jacking gear     | warm up and drain the main steam lines                 | pump the main condenser hotwell dry  | admit gland sealing steam to the turbine glands   |  |
| 13 | 662 | D | A nozzle reaction safety valve will lift at a pressure lower than required if the _____ .   | adjusting ring is set too low                               | blowdown is set too low                                | nozzle ring has come adrift  | spring compression is insufficient  |  |
| 13 | 663 | C | Under otherwise normal operating conditions, a drop in the steam temperature leaving an uncontrolled interdeck-type superheater could be caused by a/an _____ . | increase in combustion gas velocity through the superheater | decrease in steam velocity through the superheater     | increase in feedwater temperature  | badly fouled economizer   |  |

|    |     |   |  |  |  |  |  |  |
|----|-----|---|--|--|--|--|--|--|
| 13 | 664 | C | In a tubular-bowl type centrifugal lube oil purifier, any solids separated from the oil are _____.   | discharged with the water                  | removed through the waste drain                                | retained in the bowl   | solidified on the upper cover  |  |
| 13 | 665 | B | In a closed feed and water cycle, which of the conditions listed could prevent vacuum from reaching the desired level?                               | Steam leaking from the turbine glands.     | Marine growth on the cooling water side of the main condenser. | Condensate recirculating back to the condenser during maneuvering. | Steam pressure to air ejectors maintained at 10 psig above designed supply pressure. |  |
| 13 | 666 | D | Coast Guard Regulations (46 CFR) require unfired pressure vessels with manholes to be hydrostatically tested _____.                                  | every 4 years                              | every 8 years  | at each certification inspection                                   | at the discretion of the marine inspector  |  |
| 13 | 667 | D | An incandescent white flame in a boiler firebox would indicate _____.  | efficient combustion                       | low fuel oil temperature                                       | excessive fuel oil pressure  | too much excess air  |  |
| 13 | 668 | D | The recirculating valve provided in a straight mechanical boiler fuel oil service system, should be opened when _____.                               | going into maneuvering conditions          | the service pump relief valve lifts                            | bypassing one bank of fuel oil heaters                             | preparing to light off a cold boiler   |  |
| 13 | 669 | A | An adequate phosphate reserve should be maintained in boiler water to _____.   | prevent hard scale formation               | reduce the blowdown frequency                                  | maintain a pH of 7   | remove dissolved oxygen concentrations   |  |
| 13 | 670 | A | Main steam turbine bearings are lined with _____.  | babbitt                                    | steel  | cast-iron  | ferrous oxide  |  |
| 13 | 671 | A | Raising vacuum on a main turbine unit without using the turning gear will result in _____.   | uneven heat distribution in the rotor unit | excessive time being required to raise vacuum                  | scoring of the rotor in way of the labyrinth packing               | overheating of the second-stage air ejector  |  |
| 13 | 672 | D | Babbitt is a metal alloy commonly used for lining _____.   | saltwater piping                           | valve seats  | shim stock   | precision bearings   |  |
| 13 | 673 | B | Heated lube oil will begin to break down if mixed with water and _____.  | allowed to stand idle                      | is thoroughly agitated   | thoroughly centrifuged   | discharged through a finite filter   |  |
| 13 | 674 | C | Under normal operating conditions, a drop in the steam temperature at the outlet of an interdeck superheater could be caused by a decrease in _____. | steam velocity through the superheater     | the feedwater temperature                                      | combustion gas velocity through the superheater                    | the pressure differential across the fuel oil strainers                              |  |

|    |     |   |   |   |  |  |   |  |
|----|-----|---|---|---|--|--|---|--|
| 13 | 675 | B | Waterboxes on condensers are vented to .  | prevent excessive pressure on tube sheets                   | liberate air pockets and reduce waterside oxidation                          | assure positive flow to the lube oil coolers             | prevent vapor binding of the circulating pump                 |  |
| 13 | 676 | B | In order to determine the effectiveness of the lube oil centrifuge in removing water, the engineer in charge should .   | have the centrifuge cleaned only once every 30 days         | take lube oil samples each week and place in clear containers for inspection | maintain the lube oil input at a maximum of 155°F        | maintain the rotating speed of a disk-type bowl at 15,000 RPM |  |
| 13 | 677 | A | If an analysis of boiler flue gas determines there is 50% excess air for combustion, you should expect the nitrogen content of the flue gas to be approximately . | 79.00%  | 33.00%   | 21.00%   | 14.00%  |  |
| 13 | 678 | B | Steam assist fuel atomizers are converted to straight mechanical atomizers in order to .  | raise steam on the idle boiler                              | cold start a boiler with diesel oil  | meet minimum boiler steam demands                        | provide the best fuel economy                                 |  |
| 13 | 679 | B | Phosphates are used in the chemical treatment of boiler water to .  | control alkalinity and neutralize vanadium                  | convert scale forming salts to relatively harmless sludges                   | neutralize the harmful effects of hydrogen embrittlement | decrease dissolved oxygen content                             |  |
| 13 | 680 | D | A lube oil sample taken from the main engine lube oil system has a dark yellow opaque color. This is the result of .  | water contamination   | mixing oils of two widely different viscosities                              | overheating  | aeration  |  |
| 13 | 681 | B | Prolonged astern operation of a turbine will cause .  | overheating of the stern gland                              | overheating of the ahead stages  | improper functioning of the air ejectors                 | loss of suction at the condensate pump                        |  |
| 13 | 682 | B | The primary operational difference between a huddling chamber type safety valve and a nozzle reaction type safety valve is the .                                  | manner in which steam pressure causes initial valve opening | principle by which blowdown is accomplished                                  | difference in valve relieving capacities                 | manner in which lifting pressure is adjusted                  |  |

|    |     |   |   |  |  |   |   |  |
|----|-----|---|---|--|--|---|---|--|
| 13 | 683 | D | Which of the following statements is correct regarding the selection of the proper size ring dam for a tubular-type lube oil purifier?                                | The size ring dam used depends on the viscosity of the oil being purified. | While all ring dams have the same inside diameter, the outside diameters vary. | Ring dams of larger sizes are indicated by smaller numbers. | Satisfactory purification is obtained when the ring dam is the largest size possible, and no oil is present at the water discharge. |  |
| 13 | 684 | A | A lube oil sample is taken from the main engine lube oil system and visually inspected. Which of the following would indicate water contamination?                    | A milky-white color  | A clear, amber color   | A black color   | A reddish-orange color  |  |
| 13 | 685 | C | When main condenser tubes are rolled into both tube sheets, the effects due to differential expansion rates are minimized by the use of _____.                        | a bellows tube sheet   | condenser supports   | shell expansion joints                                      | a brass wearing strip   |  |
| 13 | 686 | A | Under normal firing rates, which of the conditions listed could result in a low superheater outlet temperature?   | High feedwater temperature   | Too much excess air  | Dirty generating tubes                                      | Fouled economizer tubes   |  |
| 13 | 687 | D | If an analysis of boiler flue gas determines there is no excess air for combustion, you should expect the nitrogen content of the flue gas to be approximately _____. | 10.50%   | 14.00%   | 21.00%  | 79.00%  |  |
| 13 | 688 | D | In a disk-type purifier which component is used to separate lube oil into thin layers and create shallow settling distances?  | A discharge ring   | A three-wing device  | A tubular bowl  | A series of cone-shaped plates  |  |
| 13 | 689 | A | Boiler water hardness in modern high pressure boilers should be kept as close to 'zero' as possible by chemically treating with _____.                                | trisodium phosphate  | soda ash   | caustic soda  | all of the above  |  |

|    |     |   |  |  |  |  |   |         |
|----|-----|---|--|--|--|--|---|---------|
| 13 | 690 | C | A sudden unexplainable drop has occurred in the outlet temperature of an uncontrolled interdeck superheater on a boiler carrying a higher than normal TDS (total dissolved solids) reading. Which of the actions listed is required? | Immediate increase in the firing rate.                         | Reduction in the forced draft fan speed.                                   | Lowering the steam drum water level.                     | Raising the feedwater temperature.                |         |
| 13 | 691 | B | The purpose of the sentinel valve installed on a turbine casing is to .  | warn the engineer of back flow of steam from the exhaust trunk | warn the engineer of excessive pressure in the low pressure turbine casing | relieve excess pressure to the turbine extraction points | vent excess steam to the main condenser           |         |
| 13 | 692 | A | What is the primary operational difference between a nozzle reaction safety valve and a huddling chamber safety valve?   | The principle by which blowdown is accomplished.               | The manner in which steam pressure causes initial valve opening.           | The difference in valve relieving capacities.            | The manner in which lifting pressure is adjusted. |         |
| 13 | 693 | D | In a disk type lube oil purifier, heavy impurities collect mostly .  | at the bottom of the unit                                      | along the center shaft   | at the water discharge                                   | on the inside surfaces of the bowl                |         |
| 13 | 694 | A | The lube oil coolers installed in a gravity lubricating oil system are located between the .   | lube oil pumps and gravity tanks                               | gravity tanks and main units   | gravity tanks and lube oil sump                          | lube oil sump and lube oil pumps                  |         |
| 13 | 695 | D | The recommended vacuum should be maintained in the main condenser to .   | condense turbine exhaust steam                                 | recover latent heat from turbine exhaust steam                             | recover sensible heat from turbine exhaust steam         | utilize the greatest possible amount of energy    |         |
| 13 | 696 | B | What type of lube oil cooler is shown in the illustration?   | Self venting   | Shell-and-tube   | Bundle and stack   | Plate type  | GS-0122 |
| 13 | 697 | C | If an analysis of boiler flue gas determines there is 100% excess air for combustion, you should expect the flue gas to have a nitrogen content of approximately .   | 21.00%   | 33.00%   | 79.00%   | 87.00%  |         |
| 13 | 698 | A | Which of the fuel atomizers listed has the greatest firing range or turndown ratio?  | Steam assist   | Rotary cup   | Return flow  | Straight-through flow                             |         |

|    |     |   |   |  |   |   |   |         |
|----|-----|---|---|--|---|---|---|---------|
| 13 | 699 | B | In the prevention of moisture carryover from a marine boiler, one important consideration is to _____.  | properly treat the boiler water with hydrazine                                 | control the amount of boiler water solids                                     | maintain a high boiler water level  | add foaming agents to the boiler water  |         |
| 13 | 700 | C | The items labeled "A" in the illustration are the _____.  | low pressure drain connections   | high pressure drain connections   | low pressure vent connections   | low pressure steam supply connections   | SG-0025 |
| 13 | 701 | B | The sentinel valve located on the low pressure turbine casing is designed to _____.   | bypass exhaust steam to the main condenser                                     | warn the engineer of excessive pressure in the L.P. casing                    | control steam flow to the LP unit   | relieve excess pressure when the astern throttle is opened                    |         |
| 13 | 702 | A | When excessive static boiler pressure has resulted in the initial lift of the valve disc, a huddling chamber safety valve will continue to lift open as a result of _____.                  | steam pressure acting on the enlarged area of projecting lip or ring           | the resulting reactive force created by the rapid expansion of escaping steam | an increase in steam velocity through an adjustable orifice ring  | steam pressure transmitted through a pipe connected to the superheater outlet |         |
| 13 | 703 | D | While standing your engine room watch at sea, you notice the D.C. heater level dropping rapidly as indicated by the remote level indicator. Which of the following actions should be taken? | Immediately stop the main engine.  | Do nothing in particular as this is a common occurrence aboard this vessel.   | It is only necessary to immediately open the automatic make-up feed bypass valve.                                   | Open the make-up feed valve bypass and check the condenser level immediately. |         |
| 13 | 704 | A | Prior to relieving the watch you should first check the fireroom status by verifying the boiler steam drum level and _____.   | inspecting the fires and burners   | preparing to blow tubes   | stack temperature   | port and starboard settling tank levels                                       |         |
| 13 | 705 | A | One of the basic rules applying to the operation of a single-pass main condenser, is that the _____.  | cooling water overboard should be about 10°F higher than the inlet temperature | vacuum must be maintained at 29.92" of Hg. under all operating conditions     | quantity of reheating steam flow through the condenser must be maintained at maximum under all operating conditions | condensate temperature must never be allowed to drop below 104°F              |         |

|    |     |   |  |  |   |   |  |  |
|----|-----|---|--|--|---|---|--|--|
| 13 | 706 | D | While trying to light off a burner on a semi-automated boiler, you note that the fuel oil solenoid valve at the burner will not stay open. Which of the following conditions could cause this problem? | The fuel oil pressure at that burner is too high.            | The flame scanner is adjusted for excessive time delay in the ignition trial circuit. | The solenoid coil is energized causing the valve to remain closed.                                | The forced draft air supply has failed.                      |  |
| 13 | 707 | B | A flue gas analysis is performed to determine the _____.   | percentage of nitrogen by volume                             | correct fuel/air ratio for efficient combustion                                       | carbon content of the fuel being burned   | specific heat of combustion products                         |  |
| 13 | 708 | A | An advantage of steam atomization compared to mechanical atomization is _____.   | its greater turndown ratio                                   | improved heat transfer in the boiler  | the ability of the system to maintain the proper ratio of fuel and air at all rates of combustion | bleed steam is utilized thereby increasing plant efficiency  |  |
| 13 | 709 | A | Carryover in a marine boiler can be caused by _____.   | boiler water contaminants                                    | low boiler water alkalinity   | a high concentration of hydrazine in the boiler water   | overfiring the boiler to the end point of combustion         |  |
| 13 | 710 | B | If contaminated lube oil were allowed to settle undisturbed in a tank, into which layers would the contaminants separate?  | Sediment on the bottom, oil in the middle, and water on top. | Sediment on the bottom, water in the middle, and oil on top.                          | Water on the bottom, oil in the middle, and sediment on top.                                      | Water on the bottom, sediment in the middle, and oil on top. |  |
| 13 | 711 | A | The purpose of shroud bands secured to the tips of the turbine blades is to _____.   | stiffen the blades to reduce vibration                       | increase blade resistance to moisture in steam  | assist in maintaining radial clearances   | strengthen the blade root fastenings                         |  |
| 13 | 712 | A | In a huddling chamber type safety valve, initial valve opening is caused by static pressure acting on the _____.   | valve disk   | nozzle ring   | adjusting ring  | compression screw  |  |
| 13 | 713 | C | To determine the extent of lube oil system contamination you would _____.  | watch for variations in the lube oil pump discharge pressure | observe the oil flow in the sight glasses   | inspect the purifier for separated foreign matter   | maintain a close watch on bearing temperatures               |  |
| 13 | 714 | C | Which of the following types of bearing lubrication schemes can carry the highest unit loading?  | Ring lubricated  | Disk lubricated   | Pressure lubricated   | Oil whip lubricated  |  |

|    |     |   |  |  |  |  |  |  |
|----|-----|---|--|--|--|--|--|--|
| 13 | 715 | D | While making a round of the engine room, the oil in all of the main engine bearing sight glasses appears to be milky. The probable cause is _____.   | cold running of the bearing  | collapse of the oil wedge  | air leakage into the bearing   | water contamination of the lube oil                          |  |
| 13 | 716 | C | Which of the following would cause the dowel or locking lip of a split-type, precision insert, main bearing to shear and allow the bearing to rotate with the journal?   | Unequal torque to any two adjacent bearing bolts                                 | Excessive bearing bolt torque                                    | Insufficient bearing crush   | Short periods of above normal operating speeds               |  |
| 13 | 717 | D | A chemical based analysis of boiler stack gases is taken to _____.   | determine the volume of the SO2 products of combustion                           | estimate the amount of noncombustible solids present in fuel oil | estimate the BTU content of a quantity of fuel oil   | measure the percentage volume of CO2                         |  |
| 13 | 718 | C | While at sea, during your watch in the engine room of a steam turbine driven vessel, you notice the main lube oil pump suction strainer vacuum differential has been increasing. To correct this you should _____. | open drain line prior to changing over strainers to decrease vacuum differential | back flush the strainer baskets                                  | stop the main engine prior to removing the lube oil suction strainer covers, if simply changing over strainers has not proved satisfactory | rotate the knife edge cleaning device                        |  |
| 13 | 719 | D | If boiler water chemicals are decreasing in one boiler and increasing in the other boiler, while both are steaming at normal rates, a leak probably exists in the _____.   | economizer tubes   | superheater tubes  | feedwater crossover line   | internal desuperheater flange                                |  |
| 13 | 720 | B | The most practical method of determining the condition of a shaft bearing while the shaft is in operation is to _____.   | visually inspect the bearing   | check the lube oil temperature                                   | check the lube oil viscosity   | perform a carbon blot test on an oil sample from the bearing |  |
| 13 | 721 | B | Steam supplied to the main propulsion turbines is _____.   | saturated steam  | superheated steam  | desuperheated steam  | wet steam  |  |

|    |     |   |   |   |  |   |  |  |
|----|-----|---|---|---|--|---|--|--|
| 13 | 722 | D | In a huddling chamber safety valve, the initial valve opening is caused by .  | static pressure acting on the compression screw                   | steam pressure acting on the increased surface area of the projecting feather                                  | steam flow passing through the calibrated adjusting ring                          | steam pressure acting on the exposed bottom area of the valve disk                   |  |
| 13 | 723 | B | During the routine inspection of an operating centrifugal lube oil purifier, you notice oil discharging through the water discharge port. Which of the following actions should be taken? | Do nothing as this is normal.                                     | Add water to seal the bowl.  | Increase the bowl speed to balance the water and oil discharges.                  | Decrease the temperature of the entering oil to lower the specific gravity.          |  |
| 13 | 724 | C | One limiting problem of lube oil filters restricting their use in large lube oil systems is .   | they easily rupture at normal working pressures                   | as the oil temperature fluctuates during load changes their effectiveness changes inversely to the temperature | the associated large pressure drop across the filter                              | the need to centrifuge the oil in addition to the use of the filter                  |  |
| 13 | 725 | B | A condensate recirculating line is provided to the main condenser in a closed feedwater system to .   | prevent excessively cooled distillate from entering the DC heater | provide adequate cooling water to the air ejector inter and after condensers                                   | assure a positive flow through the main feed pump                                 | prevent flashing in the main feed pump   |  |
| 13 | 726 | C | In a tubular bowl centrifugal purifier, lube oil is rotated at the same speed as the bowl by the .  | ring dam  | bowl boss  | three-wing device   | flexible spindle   |  |
| 13 | 727 | D | Which of the stack emissions listed represents a heat loss from the furnace?  | Nitrogen  | Excess air   | Superheated water vapor   | All of the above are correct.  |  |
| 13 | 728 | D | Boilers equipped with steam atomizers can operate over a wide load range without cutting burners in and out because .   | steam maintains the oil at the fire point temperature             | atomizing steam pressure is held constant for all load ranges  | it is not necessary to regulate fuel oil pressure at the burners with this system | steam velocity aids in the atomizing of fuel oil over a wide range of fuel pressures |  |

|    |     |   |   |  |  |   |   |         |
|----|-----|---|---|--|--|---|---|---------|
| 13 | 729 | B | The unit shown in the illustration is used as the _____.  | high pressure feed heater  | combined low pressure feed heater  | butterworth feed heater   | flash evaporator salt water feed heater         | SG-0025 |
| 13 | 730 | D | The vessel is currently operating at sea. Despite troubleshooting the system, the engineers of the vessel have been unable to transfer fuel to the settler. As the settler level is becoming dangerously low, they should now _____.  | repeat all the steps they have taken   | call out all hands for assistance  | utilize a rubber impeller portable pump   | reduce the vessel's speed and other plant loads |         |
| 13 | 731 | D | Which of the steam losses listed would be associated with a multistage impulse turbine rather than a multistage reaction turbine?   | Radiation loss   | Leaving loss   | Blade and nozzle loss   | Diaphragm packing loss                          |         |
| 13 | 732 | B | Why is it occasionally necessary to verify the accuracy of the distilled water make-up feed tank level remote indicator?  | It is possible to lose vacuum if the level rises above the make-up feed piping connection. | A false high reading may contribute to an increase in condenser absolute pressure. | The tank may overflow in the engine space causing unnecessary damage to all electrical equipment. | All of the above are correct.                   |         |
| 13 | 733 | D | While standing your engine room watch at sea, you notice the D.C. heater level is dropping below normal as indicated by the remote level indicator. The boiler drum level is observed to be normal, as is the main condensate pump discharge pressure. Therefore, you should _____. | increase the boiler firing rates   | decrease the boiler firing rates   | reduce the feedwater level set point  | open the make-up feed bypass valve              |         |

|    |     |   |   |   |  |  |   |  |
|----|-----|---|---|---|--|--|---|--|
| 13 | 734 | D | While on watch aboard a 900 psi steam vessel, you suddenly hear a loud, piercing, high-pitched noise. Which of the following actions should you take? | Vacate everyone from the engine room immediately, as this is the preliminary signal that the steam smothering system is about to be released. | Rapidly move towards the direction of the noise to investigate the probable source.      | Cautiously move towards the source of the noise, sweeping the beam of your flash light ahead of you. | Move away from the noise to find a broom, then cautiously advance, sweeping the handle ahead of you to locate the source. |  |
| 13 | 735 | C | Which steam plant watch operating condition will require priority attention over the other conditions listed?   | High level main condenser   | High level lube oil storage tank   | Low water level main boiler  | Deaerating tank pressure 2 psig above normal  |  |
| 13 | 736 | B | The terms 'swell' and 'shrink' relate to a change in boiler water level which .   | results when the feed rate becomes erratic during maneuvering   | is due to the volumetric change in the size of the steam bubbles below the water surface | result in a rapid change in fuel oil viscosity   | indicates a high chloride concentration in the boiler water   |  |
| 13 | 737 | B | Which of the flue gas components listed contributes to the greatest heat loss in a boiler?  | Carbon monoxide   | Nitrogen   | Carbon dioxide   | Superheated water vapor   |  |
| 13 | 738 | B | Boilers equipped with steam atomized burners can be operated without changing burner tips because steam atomization .                                 | maintains the oil at ignition temperature   | finely atomizes fuel oil over a band of fuel oil system pressures                        | automatically cleans the burner tips and eliminates fouling  | regulates itself by responding to the position of the main engine throttles   |  |
| 13 | 739 | C | The inability to maintain proper boiler water alkalinity, phosphate, or pH levels in a steam boiler, indicates a leak in the .                        | economizer drain line   | DC heater  | desuperheater  | superheater drain line  |  |

|    |     |   |   |   |   |  |  |         |
|----|-----|---|---|---|---|--|--|---------|
| 13 | 740 | D | Upon taking over the watch while vessel is operating at sea speed you find the D.C. heater level to be dropping slowly. Which components should be checked immediately?   | Auxiliary condenser recirculation valve. Failure to properly set may prevent proper flow through the condensate line. | Makeup feed valve. Improper operation may prohibit the necessary addition of distilled water to the system. | D.C. heater spill valve. If this bypass is opened, large amounts of water may be directed to the distilled water tank. | All of the above are correct and together provide the necessary means to control the water levels throughout the condensate and feedwater systems. |         |
| 13 | 741 | D | In comparison to a reaction turbine, a steam loss specific to an impulse turbine is known as _____.   | radiation loss  | leaving loss  | blade and nozzle loss  | diaphragm packing loss   |         |
| 13 | 742 | B | The function of a safety valve on a marine boiler is to prevent the pressure in the boiler from rising above _____.   | design test pressure  | maximum allowable working pressure  | the pressure used in the accumulation test   | the hydrostatic test pressure  |         |
| 13 | 743 | B | The term 'swell' relates to a change in boiler water level which _____.   | results when the feed rate becomes erratic during maneuvering   | is due to the steam bubbles below the surface occupying a larger volume                                     | is due to a rapid change of steam temperature during maneuvering operations  | indicates a high chloride concentration in the boiler water  |         |
| 13 | 744 | C | Upon assuming the in port watch of a tank vessel while cargo operations are in progress, with the main engine and reduction gear secured you notice a substantial rise in the reduction gear lube oil sump level. Which components or conditions should be checked immediately? | Inspect proper line-up of lube oil service pump bypass system.  | Confirm with the deck officer that there has been a change in the vessel's trim.                            | Verify that there is no rotation of the propulsion equipment and the gravity tank is empty.                            | All of the above are correct.  |         |
| 13 | 745 | D | Which of the listed parts shown, in the illustration of the turbogenerator governing system, provides the follow-up motion to prevent the nozzle valves from cycling between the fully open and fully closed positions with each variation in turbine speed?                    | Synchronizer  | Operating cylinder  | Main speed governor  | Restoring linkage  | SE-0009 |

|    |     |   |  |   |   |   |  |  |
|----|-----|---|--|---|---|---|--|--|
| 13 | 746 | C | Slag caused by water in the fuel oil will .  | form a protective coating thus increasing its life              | seal refractory joints thereby improving its function | expand at a different rate and result in damaged refractory | increase the furnace efficiency because of reduced firebox turbulence                                |  |
| 13 | 747 | C | A high carbon monoxide content in the flue gases of a boiler indicates .   | complete combustion   | too much excess air                                   | incomplete combustion                                       | a high carbon content fuel   |  |
| 13 | 748 | B | In most installations, the firing rate of a boiler using steam atomization is indicated by the .   | burner register opening   | fuel oil supply pressure                              | fuel oil return pressure                                    | steam atomization temperature  |  |
| 13 | 749 | C | While your vessel is steaming at a constant rate, the alkalinity in one of the boilers is decreasing steadily without requiring the use of extra makeup feedwater. This condition could be caused by a leak in the . | economizer  | condenser   | desuperheater   | superheater  |  |
| 13 | 750 | B | The property of a fuel oil which is a measurement of its available energy, is known as its .   | cetane number   | heating value   | carbon number   | cetane index   |  |
| 13 | 751 | A | In securing the main turbines, steam to the second stage air ejectors should be left on for a while in order to .  | dry out the main turbines                                       | insure equal cooling of the main turbine bearings     | prevent excessive condensate depression                     | remove the excessive amount of noncondensable vapors which accumulated during maneuvering operations |  |
| 13 | 752 | B | A boiler safety valve must be capable of .   | remaining open until all pressure in the steam drum is relieved | remaining open until a preset pressure drop occurs    | opening gradually above a designated pressure               | closing with a chattering motion to free scale deposits from the seats                               |  |
| 13 | 753 | B | Lube oil cannot be efficiently filtered if its .   | viscosity index is too low                                      | temperature is too low                                | pump discharge pressure is higher than the system pressure  | pump capacity is greater than the system's needs   |  |

|    |     |   |   |  |   |   |  |         |
|----|-----|---|---|--|---|---|--|---------|
| 13 | 754 | C | What will occur if the level of the atmospheric drain tank, (fresh water drain collector) is permitted to continuously rise while the vessel is underway?   | The tank will overflow causing a significant loss of potable water.        | The pressure of the contaminated steam system will rise when the tank becomes full. | There is a definite possibility of the tank overflowing, causing loss of distilled water. | There will be an increase of vacuum in the main condenser within a short period of time. |         |
| 13 | 755 | B | Despite troubleshooting the system, the watch engineer has been unable to transfer fuel to the settler while underway. As the settler level is becoming dangerously low, the engineer should now .  | repeat all the steps he has taken  | call out other engineers for assistance   | utilize a portable rubber impeller transfer pump  | secure each propulsion boiler  |         |
| 13 | 756 | A | The purpose of the relief valve in a fuel oil service system is to .  | protect the system from high discharge pressure                            | regulate the atomizer oil pressure  | control the oil pressure regulators   | supply constant pressure to the burner combustion control valves                         |         |
| 13 | 757 | D | A high percentage of carbon dioxide in boiler flue gases indicates .  | carbonized burner tips   | too much excess air   | contaminated fuel oil   | nearly complete combustion of fuel oil   |         |
| 13 | 758 | C | With an increase in the saturation pressure of a fluid, the value represented by line "5" on the graph will .   | decrease the number of BTU's per pound per change in degree of temperature | increase the number of BTU's per pound, per change in degree of temperature         | remain virtually the same   | represent an increase in the latent heat of condensation                                 | SG-0001 |
| 13 | 759 | C | A basic comparison can be made between a low pressure evaporator operation and a main condenser with regards to the removal of noncondensable gases. The vacuum drag line for the main condenser is specifically connected in which area? | main tube bank   | steam lane  | air cooler section  | hotwell  |         |

|    |     |   |   |   |  |  |  |         |
|----|-----|---|---|---|--|--|--|---------|
| 13 | 760 | B | The purpose of the pressure control disk installed in the soot blower illustrated is to .   | control the velocity and distance of the steam valve passing from the soot blower element | reduce the steam supply pressure to the soot blower element                      | control the amount of arc during rotation of the soot blower element | assist in the initial opening of the valve at the beginning of the soot blower operation | SG-0023 |
| 13 | 761 | B | For a period of time immediately after being secured, turbines should be rotated slowly to avoid .  | damage to the reduction gear teeth  | distortion of the rotor shaft  | excessive strain on the quill shaft flexible coupling                | seizure of the main bearing  |         |
| 13 | 762 | B | A boiler accumulation test is used to measure the .   | lifting pressure of the boiler safety valves  | total relieving capacity of the boiler safety valves                             | steam generating capacity of the boiler                              | blowdown pressure of the boiler  |         |
| 13 | 763 | C | The steam soot blower piping should be thoroughly drained before operating to prevent .   | accidental flameout   | feedwater losses   | nozzle/elements eroding  | erosion of the corbel  |         |
| 13 | 764 | D | The level of the contaminated drain inspection tank continually decreases when steam is admitted to a fuel oil double bottom tank. You can expect . | a plugged heating coil  | higher than normal return temperatures   | a leaking makeup feed regulator                                      | a perforated heating coil  |         |
| 13 | 765 | D | The function of item "E" shown in the illustration is to .  | pulse supply steam or air to chamber "M"  | allow steam/condensate or air to be evacuated from the unit as sound is produced | act as a reed to enable the production of sound                      | control the admission of steam into chamber "M" as part of the process to produce sound  | GS-0099 |
| 13 | 766 | C | The best indication that a bearing is being properly lubricated is by the .   | oil pressure at the lube oil pump discharge   | lube oil strainer condition during cleaning and inspection                       | oil temperature indicated by the bearing thermometer                 | oil temperature leaving the lube oil cooler  |         |
| 13 | 767 | A | If the flue gas oxygen content is too high, you should .  | adjust the combustion control system  | adjust the fuel oil service system   | increase the forced draft fan speed                                  | increase the fuel oil temperature  |         |

|    |     |   |  |   |   |   |   |         |
|----|-----|---|--|---|---|---|---|---------|
| 13 | 768 | B | The firing range of a steam assisted fuel atomizer is regulated to cope with changes in the steam demand by varying the _____.           | fuel oil return pressure                              | fuel oil supply pressure  | steam atomization temperature   | shape of the atomized fuel cone   |         |
| 13 | 769 | D | Which steam plant watch operating condition will require priority attention over the other conditions listed?                            | High level hydrazine dosing tank                      | High level lube oil storage tank  | Low sewage tank chlorination section level  | Low lube oil level in the operating feed pump   |         |
| 13 | 770 | B | Oil discharged from the illustrated device has a milky-white appearance which is due to _____.   | proper operation of the centrifuge                    | insufficient tension being maintained by "H"  | excessive tension provided by "Q"   | slightly worn item "V"  | GS-0124 |
| 13 | 771 | B | In a reaction turbine, the fixed blades function to _____.   | decrease steam velocity                               | increase steam velocity   | prevent turbulence  | produce turbulence  |         |
| 13 | 772 | B | Which of the conditions listed will provide 'blowdown' after the safety valve has lifted?  | The valve is held open by a pressure pilot line.      | Once the valve has opened, the existing steam pressure acts on an enlarged area creating an opening force greater than that which opened the valve. | Once the valve lifts, the set opening pressure changes.                               | The safety valve opens gradually but with decreasing lift during the blowdown period. |         |
| 13 | 773 | B | In accordance with Coast Guard Regulations (46 CFR), all vessels having oil fired main propulsion boiler(s) must be equipped with _____. | only one positive displacement type fuel service pump | duplex strainers, each for suction and discharge  | one fuel oil heater if shown that the normally used fuel oil will be of low viscosity | all of the above  |         |
| 13 | 774 | C | The three wing device in the unit illustrated is maintained in its position by item _____.   | O   | P   | Q   | R   | GS-0124 |
| 13 | 775 | D | In the illustrated device, what would be a reason for oil being discharged from port "N" ?   | The device being operated as a clarifier.             | The ring dam size is too small.   | This would be normal for the operation.   | The ring dam size is too large.   | GS-0124 |
| 13 | 777 | C | Which of the following items should be checked each time the firing rate or forced draft pressure is adjusted?                           | Fuel oil heater inlet temperature                     | Atomizing steam pressure  | Smoke periscope   | Fuel oil suction pressure   |         |

|    |     |   |  |  |  |   |   |         |
|----|-----|---|--|--|--|---|---|---------|
| 13 | 778 | A | The amount of fuel oil atomized by a steam atomization burner depends on the atomizing steam pressure, the fuel pressure and the _____.  | sprayer plate size   | oil return pressure  | furnace air pressure  | windbox pressure                              |         |
| 13 | 779 | A | Oil accumulation in boiler water would _____.  | cause foaming and carryover from the boiler  | increase the heat transfer rate                                      | prevent acid attack on the boiler tubes   | practically eliminate boiler sludge formation |         |
| 13 | 780 | D | Which steam plant watch operating condition will require priority attention over the other situations listed?  | Low level in lube oil sludge tank  | High level in lube oil in storage tank                               | Low level effluent in chlorination section of sewage tank                                     | High bilge water level throughout engineroom  |         |
| 13 | 781 | A | As found in a reduction gear drive system, thrust bearings serve to _____.   | transmit the force produced by the propeller to the structure of the ship                  | limit the radial movement of the shaft                               | increase the shaft speed  | hold the main engine in place                 |         |
| 13 | 782 | B | Proper bracing and support of the boiler safety valve escape piping is necessary to _____.   | prevent condensate from accumulating in lines  | prevent stressing of the safety valves                               | allow for back pressure formation in the line   | prevent scale from lodging on the valve seat  |         |
| 13 | 783 | C | The ability of the device illustrated to produce sound is greatly affected by the adjustments to "B". Another factor that can affect the proper operation of this device is the _____. | upward movement of "E"   | steam pressure being maintained at +/- 10% of design                 | changing of the orifice at "I"  | overall length of "K"                         | GS-0099 |
| 13 | 784 | C | If the steam flow input device to a two-element feedwater regulator valve fails, the regulator operates as a _____.  | constant pump pressure regulator   | remote manual control regulator                                      | single-element feedwater regulator  | local manual control                          |         |
| 13 | 785 | A | Which following condition could occur if the distilled water tank level indicator has been giving an erroneously high reading?   | It is possible to lose vacuum if the level drops below the make-up feed piping connection. | Past logbook entries must all be changed to indicate actual amounts. | The tank may overflow in the engine space causing unnecessary damage to electrical equipment. | All of the above are correct.                 |         |

|    |     |   |   |   |  |   |   |         |
|----|-----|---|---|---|--|---|---|---------|
| 13 | 786 | C | In a tubular-bowl type centrifugal lube oil purifier, any solids separated from the oil are _____.                                    | discharged with the water                                     | removed during the 'shoot' cycle   | retained in the bowl                                      | solidified on the upper cover                               |         |
| 13 | 787 | C | Efficient boiler operation is indicated when the percentage by volume of carbon dioxide present in combustion gases is between _____. | 1 and 10  | 10 and 11  | 12 and 14   | 15 and 17   |         |
| 13 | 788 | B | In a steam assist atomizer, the fuel oil/steam mix takes place entirely within the _____.   | tangential slots  | mixing chamber   | whirling chamber  | fuel oil swirliers  |         |
| 13 | 789 | A | Foaming and moisture carryover in a boiler can be caused by an _____.   | excessive amount of dissolved solids in the boiler water      | excessive acidity level in the boiler water                              | inadequate amount of dissolved oxygen in the boiler water | inadequate alkalinity content in the boiler water           |         |
| 13 | 790 | D | If the pressure control disk in the soot blower illustrated, is moved to a higher position, the result will _____.                    | cause the soot blower to rotate faster                        | cause the soot blower to rotate slower                                   | decrease the amount of steam valve travel                 | increase the steam pressure in the rotating blower element  | SG-0023 |
| 13 | 791 | B | In a reaction turbine, the axial thrust due to the reactive force on the rotor blading drives the rotor _____.                        | toward the high pressure end                                  | toward the low pressure end  | against the dummy piston                                  | toward the diaphragm squealer rings                         |         |
| 13 | 792 | C | Safety valves should be set to lift at or below the maximum working pressure allowed by the _____.                                    | Marine Power Plant Guide                                      | Marine Engineering Regulations   | Certificate of Inspection                                 | Marine Engineer's Manual                                    |         |
| 13 | 793 | B | If the feedwater flow input device to a multi-element feedwater regulator fails, the valve will be controlled as a _____.             | single element feedwater regulator                            | double element feedwater regulator                                       | triple element feedwater regulator                        | local manual control device                                 |         |
| 13 | 794 | B | The term 'shrink' relates to a change in boiler water level which _____.  | results when the feed rate becomes erratic during maneuvering | is due to the steam bubbles below the surface occupying a smaller volume | results in a rapid change of steam temperature            | indicates a high chloride concentration in the boiler water |         |
| 13 | 795 | B | The purpose of the air chamber at the discharge side of a steam reciprocating boiler feed pump is to _____.                           | facilitate draining of the cylinder                           | reduce pulsations in the feed line                                       | adjust the speed of the pump                              | provide for the addition of boiler compound                 |         |

|    |     |   |   |   |   |  |   |  |
|----|-----|---|---|---|---|--|---|--|
| 13 | 796 | A | Which steam plant watch operating condition will require priority attention over the other situations listed?   | Low level, lube oil gravity tank                                | High level, lube oil storage tank                               | Low level, chlorination section of the sewage tank                       | Low lube oil level to operating, chemical dosing pump             |  |
| 13 | 797 | C | Generally, a 12% to 14% content of carbon dioxide in boiler flue gases indicates .  | too much excess air   | a high vanadium content in the fuel oil                         | proper combustion of the fuel oil  | carbon deposits in the uptakes                                    |  |
| 13 | 798 | D | High temperature at the superheater outlet would be caused by .   | outer casing leakage  | improper turn down ration                                       | rapid fuel oil atomization   | excessive excess air  |  |
| 13 | 799 | B | Foaming in boiler water is a result of .  | carryover   | excessive suspended solids                                      | low water level  | excessive surface blows   |  |
| 13 | 800 | D | What physical changes will occur to the steam within a boiler that has been properly bottled up when additional heat is applied?                          | The steam pressure and it specific volume will remain constant. | The pressure will increase and the volume will remain constant. | The pressure will remain constant and the specific volume will increase. | The pressure will increase and the specific volume will decrease. |  |
| 13 | 801 | D | Which of the following types of main propulsion turbines is most likely to require a dummy piston or cylinder arrangement to counterbalance axial thrust? | Double flow impulse turbine.                                    | Multistage impulse turbine.                                     | Double flow reaction turbine.  | Single flow reaction turbine.                                     |  |
| 13 | 802 | C | The bottom blow valve should be used to remove sludge and solids which have settled out of circulation after the boiler .                                 | is at full load   | is at low load  | is secured   | is being brought up to steaming pressure                          |  |
| 13 | 803 | A | Which of the listed mediums should be used when water washing a boiler?   | Heated freshwater   | Cold freshwater   | Cold condensate  | Warm condensate   |  |
| 13 | 804 | B | If a boiler is brought on the line with its steam pressure much higher than that of the boiler already on the line, there is danger of .                  | thermal shock   | priming and carryover   | low water  | an overloaded superheater   |  |

|    |     |   |  |  |   |  |  |
|----|-----|---|--|--|---|--|--|
| 13 | 805 | B | What steps should be taken if excessive steaming and vigorous bubbling occurs in the first section of the drain inspection tank?                       | Systematically locate and isolate the faulty traps in the main steam piping to the turbogenerator. | Locate and secure any unnecessarily opened steam trap bypass valve.                                       | Secure the fuel oil heater currently in use.   | All of the above are correct and each step should be taken promptly.                         |
| 13 | 806 | C | When you are transferring fuel oil from one double bottom tank to another, precautions to be observed should include .                                 | plugging gooseneck tank vents to prevent accidental overflow                                       | maintaining a high transfer rate until a slight trickle of oil is observed flowing from the overflow line | sounding the tanks frequently and reducing the transfer rate while topping off       | maintaining a supply of chemical dispersant to cleanup minor oil spills adjacent to the ship |
| 13 | 807 | D | What percentage of CO2 in a boiler flue gas analysis would indicate perfect combustion?  | 0%   | 3%  | 6%   | 12%  |
| 13 | 808 | B | Compared to the return flow oil burner system, an internally mixed steam atomizer requires .   | higher fuel oil viscosity  | less excess air   | higher air velocity  | greater turbulence in the air/oil stream   |
| 13 | 809 | C | Foaming in boiler water is caused by .   | neutral water  | acidic contamination  | high boiler water alkalinity   | low boiler water alkalinity  |
| 13 | 810 | D | What will occur if the level of the atmospheric drain tank (fresh water collector) is permitted to continuously decrease while the vessel is underway? | The amount of condensate pumped to the contaminated evaporator will decrease.                      | The pressure of the contaminated steam system will drop once the tank is empty.                           | Make-up water will be automatically added to the tank via a vacuum drag arrangement. | There is a possibility of losing vacuum in the main condenser.                               |
| 13 | 811 | B | In which type of turbine does a pressure drop exist through the fixed blades and the moving blades?  | Impulse  | Reaction  | Rateau   | Curtis   |
| 13 | 812 | C | The purpose of the boiler bottom blow valve is to .  | remove scum from the steam drum during steaming  | control steam drum water level in an emergency  | remove heavy solids from the water drum  | all of the above   |
| 13 | 813 | D | Which of the conditions listed would cause the stern tube lube oil head tank level to decrease?  | An increase in sea water temperature.  | The entry of sea water into the system.   | The proper closure of a drain valve.   | A worn or damaged stern tube seal.   |

|    |     |   |  |   |   |   |   |  |
|----|-----|---|--|---|---|---|---|--|
| 13 | 814 | C | The distilled water tank has been determined to be 75% full. The tank connection to the pneumaticator has been disconnected for a maintenance check. If the pneumaticator operates correctly, the gage should indicate .   | a value equal to three fourths of the actual level                              | a false high reading possibly permitting the entry of air into the system | the minimum value display along the provided scales   | the absence of mercury in the system  |  |
| 13 | 815 | B | During an inport watch onboard a tank vessel while cargo operations are in progress, with the jacking gear engaged and running, you notice a 200 gallon drop in the reduction gear lube oil sump level. Which components or conditions should be checked immediately?                | Inspect proper line-up of lube oil service pumps.                               | Confirm with deck officer that there was a change in vessel trim.         | Verify the correct line-up of the lube oil transfer tank gravity overflow line.             | All of the above are correct.   |  |
| 13 | 816 | C | A steam propelled tank ship is operating at sea and despite troubleshooting the system by all the vessel's engineers, the transfer of fuel to the settler has not been possible and the settler will be empty in a few minutes. As the watch engineer, your NEXT step should be to . | repeat all the steps that have been taken to determine the cause of the problem | call out other engineers for assistance                                   | line up the diesel cold start system  | stop the main engine and secure the generator                               |  |
| 13 | 817 | A | In which order should the chemical test analysis of boiler flue gas samples be made?   | CO2, O2, CO   | CO, CO2, O2   | O2, CO, CO2   | CO, O2, CO2   |  |
| 13 | 818 | D | Which steam plant watch operating condition will require priority attention over the other situations listed?  | Low level of lube oil in cleansing tank   | High level of lube oil in storage tank                                    | Low level effluent in chlorination section of sewage tank                                   | High water level in main propulsion boiler                                  |  |
| 13 | 819 | D | Foaming in a boiler can be caused by .   | high total solids   | high alkalinity   | excessive phosphate   | all of the above  |  |
| 13 | 820 | C | What steps should be taken if excessive steaming and vigorous bubbling occurs in the first section of the drain inspection tank?   | Secure the fuel oil heater currently in use.                                    | Locate and open any unnecessarily closed steam trap bypass valves.        | Systematically locate and isolate any faulty traps in the contaminated steam system piping. | All of the above are correct and should be performed in the order as shown. |  |

|    |     |   |  |  |   |  |   |  |
|----|-----|---|--|--|---|--|---|--|
| 13 | 821 | A | Which steam plant watch operating condition requires priority attention over the other conditions listed?  | High level main condenser  | High lube oil storage tank level  | Low sewage tank chlorination section level   | Vapor issuing from deaerating heater vent   |  |
| 13 | 822 | D | The guarding valve installed in a boiler bottom blow line prevents _____.  | loss of steam and water from a steaming boiler due to a leaking bottom blow valve                          | leakage from the blow line back to an idle boiler                           | entry of seawater into idle boilers due to leaking skin and bottom blow valves         | all of the above  |  |
| 13 | 823 | B | Which steam plant operating condition requires priority attention over the other situations listed?  | High level of lube oil in the refrigeration compressor   | High water level in the deaerating feedwater heater                         | Low level effluent in chlorination section of sewage tank                              | High water level in the fuel oil sludge tank  |  |
| 13 | 824 | A | The steam soot blower piping should be thoroughly drained before operating to prevent _____.   | impinging of generating tube surfaces  | feedwater losses  | plugging of nozzles  | warping of soot blower elements   |  |
| 13 | 825 | B | A salinity indicator cell is located in the _____.   | seawater side of the main condenser  | main condenser hotwell  | evaporator brine suction line  | low pressure turbine casing drain   |  |
| 13 | 826 | A | A closed feedwater system when compared to an open feedwater system has the advantage(s) of _____. I. being capable of removing a greater percentage of dissolved oxygen II. having fewer components to maintain | I only   | II only   | Both I and II  | Neither I nor II  |  |
| 13 | 827 | D | A mechanical carbon dioxide recorder operates by detecting the difference between air and the _____.   | color of boiler flue gases   | temperature of the flue gases   | soot content of the flue gases   | specific weight of the flue gases   |  |
| 13 | 828 | B | Which of the following procedures represents the proper care of unused burners during low load conditions?   | They should be removed, cleaned, refitted with smaller tips and reinstalled to be ready for immediate use. | They should be removed, cleaned and stored in the rack on the burner bench. | They may be left in place, with fuel and steam secured as long as they are not fouled. | They may be left in place, but only if they are clean and if fuel oil is recirculated to provide cooling. |  |

|    |     |   |  |  |   |  |  |         |
|----|-----|---|--|--|---|--|--|---------|
| 13 | 829 | B | For a gravity type lube oil system, a remote pressure sensing device is installed at the point of highest static head pressure on the main unit to enable the watch engineer to _____. I. be certain that the bearings are being adequately lubricated II. determine if there is sufficient lube oil pressure to the main engine | I only   | II only   | Both I and II  | Neither I nor II   |         |
| 13 | 830 | C | Superheated steam is provided to operate the main steam turbine instead of saturated steam due to its _____. I. higher thermal energy per pound II. lesser erosive action on turbine blading   | I only   | II only   | Both I and II  | Neither I nor II   |         |
| 13 | 831 | D | Operating a steam turbine propulsion unit at medium speed, in an area with extremely cold seawater and the main circulating pump providing full cooling water flow to the condenser will result in _____.  | excellent plant efficiency due to higher attainable vacuum | increased plant efficiency due to increased condensate depression | increased effectiveness of the air ejectors due to the increased main condenser vacuum | increased condensate aeration due to the inability of the air ejectors to remove excessive air accumulation from the condenser |         |
| 13 | 832 | C | Before giving a boiler a bottom blow, it should be taken off the line and then the _____.  | water level initially lowered below normal                 | boiler steam pressure should be increased                         | water level initially raise above normal   | boiler air cock should be cracked  |         |
| 13 | 833 | B | During the operation of the illustrated device, water is observed in small quantities in chamber "M", this is _____.   | normal for this particular operation                       | a drawback in having 'wet oil' pass through a clarifier           | a result of using too large of a dam ring  | a result of using too small of a dam ring  | GS-0124 |
| 13 | 835 | C | Which of the following locations could desuperheated steam be consider to occur? I. spray attemporator II. main engine extractions   | I only   | II only   | Both I and II  | Neither I nor II   |         |

|    |     |   |   |   |   |  |  |         |
|----|-----|---|---|---|---|--|--|---------|
| 13 | 837 | A | When testing boiler flue gas with a chemical absorption apparatus, to obtain accurate results _____ .                                     | prevent any air from contaminating the gas sample | analyze for CO, O2 and CO2 in that order                        | run each analysis for at least 3 minutes                 | purge the apparatus with air before use                    |         |
| 13 | 838 | D | The primary function of burner atomization steam is to _____ .  | maintain a constantly high fuel pressure          | prevent overheating of the atomizer when secured                | maintain a constantly high fuel temperature              | impart swirling motion to the oil for efficient combustion |         |
| 13 | 839 | B | A thick dark colored ring three to four inches wide forming at the steaming level in the boiler steam drum is usually evidence of _____ . | turbine oil contamination of feedwater            | fuel oil contamination of feedwater                             | black iron oxide pitting                                 | alkaline sludge deposition                                 |         |
| 13 | 840 | C | How is a diaphragm type steam whistle protected from damage due to entrained condensate?  | High temperature steam is used in the whistle.    | Condensate drains from the horn each time the whistle is blown. | A water separator is installed in the steam supply line. | The diaphragm separates condensate from steam.             |         |
| 13 | 841 | D | An excessive power loss in a straight reaction turbine is commonly caused by _____ .  | improper nozzle angle                             | excessive fluid friction  | leaking diaphragm packing                                | abnormal tip leakage                                       |         |
| 13 | 842 | C | When is the best time to give a boiler a bottom blow?   | Just before placing it on the line.               | Just after placing it on the line.                              | Just after taking it off the line.                       | When the boiler pressure has dropped to zero.              |         |
| 13 | 843 | B | The sample of oil discharged from the device illustrated appears milky white, and is probably due to _____ .                              | normal operation                                  | worn or bad bearings in "C"                                     | weaken spring below "V"                                  | position of "P" is too high in the bowl                    | GS-0124 |
| 13 | 844 | D | Clean oil leaves the centrifuge illustrated through item _____ .  | K   | N   | V  | X  | GS-0124 |
| 13 | 845 | C | If the salinity indicator located in the main condensate pump discharge piping causes an alarm to sound there is a danger of _____ .      | low condensate depression                         | low condensate temperature                                      | salting up the boilers                                   | contaminating the distilled tank                           |         |

|    |     |   |   |  |  |   |   |         |
|----|-----|---|---|--|--|---|---|---------|
| 13 | 846 | A | The differential temperature of the main condenser circulating water during normal operation will be affected by _____ .I. Change in circulating pump speed II. The addition of make up feed      | I only   | II only  | Both I and II   | Neither I nor II  |         |
| 13 | 847 | A | The absence of carbon monoxide in the flue gas of a boiler indicates _____ .  | nearly complete combustion   | too much excess air  | contaminated fuel oil   | low carbon content of fuel  |         |
| 13 | 848 | A | A boiler has a steam delivery capacity of 100,000 pounds per hour, and is equipped with four steam atomizing burners. If the load range of the burners is 4 to 1, this means that _____ .         | the boiler may be operated down to 25,000 pounds per hour without securing any burners | the boiler may be operated down to 25,000 pounds per hour only after three burners are secured | if two burners are operating, steam output will be a minimum of 50,000 pounds per hour    | all four burners combined can supply up to 400,000 pounds of steam per hour |         |
| 13 | 849 | A | Excessive alkalinity of boiler water will cause _____ .   | caustic embrittlement  | scale formation  | calcium carbonate precipitation   | sodium sulfite reacting with dissolved oxygen                               |         |
| 13 | 850 | D | A vent line is provided on each water box of the main condenser in order to prevent _____ .I. excess pressure from being exerted on the tube sheet II. vapor binding of the main circulating pump | I only   | II only  | Both I and II   | Neither I nor II  |         |
| 13 | 852 | C | Which of the precautions listed should be taken prior to blowing down a boiler water wall header?   | Relieve the pressure and cool down the boiler.   | Raise the water level above the surface blow.  | Take the boiler out of service.   | Reduce the firing rate of the boiler to its minimum.                        |         |
| 13 | 853 | D | Which condition would cause an excessively high level in the deaerating feedwater tank (Direct Contact) heater during maneuvering?  | Excessive dumping of feedwater to the distilled water tank.                            | Excessive recirculation of condensate to the auxiliary condenser.                              | Improper operation of the live steam makeup valve supplying the auxiliary exhaust system. | Open bypass valve to the automatic makeup valve assembly.                   |         |
| 13 | 854 | A | As the saturation pressure of a fluid is increased, the relative values shown on the graph will change and _____ .  | decrease the length of line 4  | not affect the length of line 4  | decrease the amount of BTU's per pound per degree change for line 5                       | decrease the length of line 3   | SG-0001 |

|    |     |   |  |  |   |   |  |  |
|----|-----|---|--|--|---|---|--|--|
| 13 | 855 | B | If a salinity alarm system indicates 2.5 grains per gallon at the main condensate pump discharge, your first action should be to _____.  | blowdown the boilers and add make up water | chemically test the condensate for chloride content           | reduce main engine speed and line up the exhaust to the auxiliary condenser | calibrate the salinity cell for accuracy |  |
| 13 | 857 | C | The differential temperature of the main condenser circulating water will be affected by _____.I. change in sea temperature II. degree or amount of scaling or fouling   | I only                                     | II only   | Either I or II  | Neither I nor II                         |  |
| 13 | 858 | B | In a steam assist fuel oil atomizer, the steam pressure is higher than the oil pressure at _____.  | design boiler load                         | minimum boiler load   | high fuel viscosity   | low fuel viscosity                       |  |
| 13 | 859 | C | Babbitt metal is used to make _____.   | pump packing rings                         | shaft journals  | bearing surfaces  | nonsparking tools                        |  |
| 13 | 860 | B | A steam supplied heat exchanger will fail to maintain the designed quantity of heated liquid output if the _____.I. steam supply absolute pressure is increased II. tubes are leaking  | I only                                     | II only   | Both I and II   | Neither I nor II                         |  |
| 13 | 862 | D | If a boiler is being steamed at a high firing rate, blowing down a water wall header without taking any other precaution could result in _____.  | excessive strain on boiler blowdown lines  | erratic operation of the automatic feedwater regulating valve | load imbalance between other boilers on the line                            | interruption of water circulation        |  |
| 13 | 863 | B | Scavenging air lines are connected to stack periscopes to _____.I. keep the mirrors clean II. protect the optical devices from boiler combustion gases   | I only                                     | II only   | Both I and II   | Neither I nor II                         |  |
| 13 | 864 | C | A flue gas air heater, when installed in a boiler, would be accompanied by the operating characteristic(s) of _____.I. higher furnace temperatures than a boiler without an air heater II. greater heat absorption per pound of fuel | I only                                     | II only   | Both I and II   | Neither I nor II                         |  |

|    |     |   |   |   |  |  |   |  |
|----|-----|---|---|---|--|--|---|--|
| 13 | 865 | C | If a ship is to be laid up for an indefinite period, the steam side of the main condenser should be _____.  | filled with moist air                                     | left under a vacuum  | completely drained of water                        | pressurized to approximately 5 psig with nitrogen, 99.5% pure by volume |  |
| 13 | 866 | C | When required, the metal thickness of boilers can be tested by _____. I. non-destructive gauging II. drilling, followed by visual inspection  | I only  | II only  | Both I and II                                      | Neither I nor II  |  |
| 13 | 867 | C | The efficiency of boiler combustion can be measured by the relative proportions of certain elements in the flue gases. The elements measured are _____.   | nitrogen, carbon dioxide, and oxygen                      | nitrogen, carbon monoxide, and oxygen                          | carbon dioxide, oxygen, and carbon monoxide        | nitrogen, carbon dioxide, and carbon monoxide                           |  |
| 13 | 868 | B | Why should the fuel oil be recirculated before lighting off a cold boiler?  | To allow the fuel strainers to thoroughly clean the fuel. | To heat the fuel enough for proper atomization.                | To ensure that all water is removed from the fuel. | To allow fuel pressure to buildup gradually.                            |  |
| 13 | 869 | C | The formation of a pit in a boiler tube is most likely to occur when _____.   | waterside deposits are present                            | sludge is present  | dissolved oxygen is present                        | the tube metal acts as a cathode  |  |
| 13 | 872 | D | Blowing down a water wall header while steaming a boiler at a high firing rate could result in _____.   | excessive strain on boiler blowdown lines                 | the thermo-hydraulic feedwater regulator valve slamming closed | a load imbalance between other boilers on the line | an interruption in the water circulation                                |  |
| 13 | 873 | A | In order to test the lifting pressure of the deaerating feed heater relief valve, you would _____. I. close the auxiliary exhaust dump valves to the main and auxiliary condensers II. increase the set point of the reduced steam pressure to the auxiliary steam system | I only  | II only  | Both I and II                                      | Neither I nor II  |  |

|    |     |   |   |  |   |  |   |  |
|----|-----|---|---|--|---|--|---|--|
| 13 | 874 | D | For a gravity type lube oil system, a remote pressure sensing device is installed on the main unit to enable the watch engineer to _____. I. determine if there is sufficient lube oil flow to the main engine II. be certain that the bearings are being adequately lubricated | I only   | II only   | Both I and II  | Neither I nor II  |  |
| 13 | 875 | B | Electrolytic corrosion in the condenser circulating water system can be reduced by _____.   | decreasing the velocity of the circulating water through the waterboxes                  | using zinc plates in the waterboxes                                 | chemically treating the condensate formed in the hotwell           | decreasing the volume of water in the system                        |  |
| 13 | 876 | C | In order to prevent fires from occurring in drum type rotating air heaters _____ . I. soot blowers need to be used when boiler is operating at low loads II. stack gas temperatures should be maintained as low as possible   | I only   | II only   | Both I and II  | Neither I nor II  |  |
| 13 | 877 | A | Which condition would cause a dangerously low level in the deaerating feedwater tank (Direct Contact) heater during maneuvering?  | Excessive dumping of feedwater to the distilled water tank via the automatic dump valve. | Excessive recirculation of condensate to the drain inspection tank. | Improper operation of the auxiliary exhaust live steam dump valve. | Open bypass valve of the automatic/pneumatic makeup valve assembly. |  |
| 13 | 878 | D | Which test(s) are normally required to be performed on a propulsion boiler during an annual inspection? I. An accumulation test II. An evaporation rate test  | I only   | II only   | Both I and II  | Neither I nor II  |  |
| 13 | 879 | B | Dissolved oxygen entrained in the feedwater entering a boiler can cause _____.  | erosion  | localized pitting   | caustic embrittlement  | acid corrosion  |  |
| 13 | 880 | C | The differential temperature of the main condenser circulating water will be affected by _____. I. decrease in circulating pump pressure II. degree or amount of scaling or fouling   | I only   | II only   | Either I or II   | Neither I nor II  |  |

|    |     |   |   |   |   |  |   |
|----|-----|---|---|---|---|--|---|
| 13 | 881 | C | Which of the listed procedures should be followed in preparing a main propulsion plant for getting underway?  | Start the condensate and circulating pumps, check and start the lube oil system, engage the turning gear, then start the first-and second-stage air ejectors and the gland sealing. | Start the condensate and circulating pumps, check and start the lube oil system, start the air ejectors and the gland sealing system, then engage the turning gear. | Check and start the lube oil system, engage the turning gear, start the condensate and circulating pumps, start the gland sealing system and second-stage air ejector. | Check and start the lube oil system, start the second-stage air ejector and the gland sealing system, start the condensate and circulating pumps. |
| 13 | 882 | A | Under what operating conditions may water wall header drains be used for blowdown?  | Only if the fires are secured and no steam is being generated.  | During periods of carryover in the steam drum.  | When the water level is out of sight in the gage glass.  | When it is necessary for rapid drainage of the boiler.  |
| 13 | 883 | B | A water-tube type boiler is more efficient than a fire-tube type boiler as _____. I. a water-tube boiler requires less maintenance II. the water-tube boiler produces more pounds of steam per pound of boiler  | I only  | II only   | Both I and II  | Neither I nor II  |
| 13 | 884 | B | A water-tube type boiler when compared to a fire-tube type boiler has an advantage of _____. I. a water-tube boiler requiring less chemical compounding II. the fire-tube boiler providing a greater amount of heat transfer to the water as the hot gases pass through the tubes | I only  | II only   | Both I and II  | Neither I nor II  |
| 13 | 885 | A | Vapor blowing from the air ejector condenser vent may be caused by _____.   | insufficient condensate flow  | excess makeup feed being taken into the system  | low condensate temperature   | excessive condensate pump speed   |

|    |     |   |  |   |   |  |   |  |
|----|-----|---|--|---|---|--|---|--|
| 13 | 886 | B | A vent line is provided on each water box of the main condenser in order to prevent _____ . I. insufficient head pressure being developed on the circulating pump discharge II. inadequate heat transfer from developing during normal operation | I only  | II only   | Both I and II  | Neither I nor II  |  |
| 13 | 887 | A | When burning fuel oil in a boiler, a high CO2 content is desired in the stack gas because _____ .  | more heat is liberated by the production of CO2 than CO | less excess air is required to produce CO2 than CO                                  | efficient combustion is indicated even though the heat liberated is less than the heat produced by burning to CO | efficient combustion is indicated and the heat liberated is equal to the heat produced by the formation of CO |  |
| 13 | 888 | C | When recirculating fuel oil prior to cold boiler start-up, which of the listed actions should be carried out?  | Increase forced draft fan speed.                        | Decrease forced draft fan speed.  | Open the fuel oil meter bypass.  | Open the fuel oil heater bypass.  |  |
| 13 | 889 | A | Babbitt is a metal alloy commonly used for lining _____ .  | bearings  | cylinder liners   | bearing journals   | saltwater piping  |  |
| 13 | 890 | D | Machinery operating features are designed to help conserve energy. Which of the following will not contribute to energy conservation?  | Reduction of friction.                                  | Insulation of hot surfaces.   | Lubrication of moving parts.   | Elevation of condenser temperatures.  |  |
| 13 | 891 | D | Prior to rolling the main turbines in preparation for getting underway, you should _____ .   | secure the gland sealing steam regulator                | open the reduction gear casing access plates and inspect the lube oil spray pattern | circulate the lube oil through the emergency lube oil cooler   | disengage the turning gear  |  |
| 13 | 892 | D | Advances in metallurgy and improved methods of boiler tube fabrication has led to lighter tubes with wall thicknesses in the vicinity of 0.1 inches. A characteristic of these thin walled tubes is _____ .                                      | low tube metal temperatures                             | decreased probability of tube failure during normal operating conditions            | better heat transfer characteristics   | all of the above  |  |

|    |     |   |   |   |   |  |  |
|----|-----|---|---|---|---|--|--|
| 13 | 893 | A | A steam supplied heat exchanger will fail to maintain the designed quantity of heated liquid output if the _____ .I. steam side shell absolute pressure is decreased II. heat exchanger drain is leaking  | I only  | II only   | Both I and II                                      | Neither I nor II                                 |
| 13 | 894 | C | Which condition would cause an excessively high level in the deaerating feedwater tank (DC heater)?   | Excessive dumping of feedwater to the distilled water tank. | Excessive recirculation of condensate to the auxiliary condenser. | Improper operation of the condensate makeup valve. | Improper operation of the air ejector loop seal. |
| 13 | 895 | D | Scale in the air ejector first-stage nozzle could cause a decrease in the _____ .   | air ejector steam supply pressure                           | low pressure turbine exhaust temperature                          | condensing temperature in the condenser            | condenser vacuum                                 |
| 13 | 896 | B | A rapid loss of water from the deaerating feed tank and the sudden overflow of water from the distill tank would be caused by _____.I. a sudden increase in steam demand while maneuvering II. an unrestricted opening in the condensate spill line from the deaerating feed tank | I only  | II only   | Both I and II                                      | Neither I nor II                                 |
| 13 | 897 | D | A flue gas air heater, when installed in a boiler would be accompanied by the operating characteristic(s) of _____.I. higher uptake temperatures than a boiler without an air heater II. lower corrosion rates in the uptakes and economiser                                      | I only  | II only   | Both I and II                                      | Neither I nor II                                 |
| 13 | 898 | A | When preparing to light off a cold boiler, the fuel oil should be recirculated until it is _____ .  | heated enough for fine atomization                          | thoroughly cleaned by the fuel oil strainers                      | viscous enough for rapid pumping                   | entrained with air bubbles                       |
| 13 | 899 | B | In a water-tube boiler, waterside scale formation is caused by _____ .  | sodium phosphate  | calcium sulfate   | magnesium phosphate                                | sodium hydroxide                                 |

|    |     |   |   |  |  |   |  |  |
|----|-----|---|---|--|--|---|--|--|
| 13 | 900 | C | Excessive priming in a propulsion boiler can cause severe damage to the _____. I. integral superheater II. main steam turbine   | I Only   | II Only  | Both I and II   | Neither I nor II   |  |
| 13 | 901 | D | Which of the following problems can occur from improper main turbine warm-up?   | Distortion of the rotor  | Rubbing of blades  | Uneven casing heating   | All of the above   |  |
| 13 | 902 | B | If it becomes necessary to remove water from a pressurized main boiler, it should be directed _____.  | into the bilges  | overboard through the bottom blow line                           | into the cofferdam  | into the reserve feed tank   |  |
| 13 | 903 | C | Which condition would cause a dangerously low level in the deaerating feedwater tank (Direct Contact) heater as the vessel is increasing from maneuvering to sea speed? | Excessive dumping of feedwater to the drain inspection tank via the automatic dump valve | Excessive recirculation of condensate to the drain transfer tank | Internal collapse of a rubber expansion joint located in the condensate pump suction line | Clogged "Y" strainer at the condensate inlet of the pneumatically operated condensate recirculating valve assembly |  |
| 13 | 904 | D | Excessive priming in a propulsion boiler can lead to severe damage of the _____. I. downcomers installed in a "D" type boiler II. main steam turbine reduction gears    | I Only   | II Only  | Both I and II   | Neither I nor II   |  |
| 13 | 905 | A | Insufficient cooling water circulation through air ejector intercondensers and aftercondensers will cause _____.  | decreased vacuum in the main condenser   | overheating of the air ejector nozzles                           | flooding of the aftercondenser  | flooding of the loop seal  |  |
| 13 | 906 | C | The first and second stage air ejectors used with large sea water cooled steam, surface type condensers are designed to _____. I. establish vacuum II. maintain vacuum  | I only   | II only  | Both I and II   | Neither I nor II   |  |
| 13 | 907 | D | An explosion or flareback could occur in a boiler if _____.   | too much excess air were supplied for combustion   | the boiler firing rate exceeded the end point of circulation     | the fuel being burned had been heated to the flash point                                  | the firebox is not purged before attempting to light a fire  |  |

|    |     |   |   |  |   |   |   |  |
|----|-----|---|---|--|---|---|---|--|
| 13 | 908 | D | Boiler downcomers serve the purpose of _____. I. distributing water within the water or mud drum II. increasing the end point of carry-over   | I only   | II only   | Both I and II   | Neither I nor II  |  |
| 13 | 909 | B | Boiler water hardness is increased by _____.  | zero alkalinity in the water   | scale forming salts in the feedwater  | dissolved gases in the water  | improper operation of the DC heater   |  |
| 13 | 910 | D | A badly warped boiler water tube can be reworked and bent back into shape by _____. I. heating it with a torch and reforming it with a soft mallet II. cold pressing it back into shape with a hydraulic jack | I only   | II only   | Both I and II   | Neither I nor II  |  |
| 13 | 911 | D | Turbine throttling losses can best be described as a loss of energy occurring _____.  | as a result of friction created when steam passes through the nozzle block | whenever there is leakage of steam from one stage to another through the throttle valve packing gland | as a result of fluid friction caused by frequently throttling the turbine wheel and blade speed | as steam passes through the steam admission valve and there is a drop in pressure without the performance of work |  |
| 13 | 912 | A | Which of the following statements represents the advantage of using a small diameter boiler tube over a larger diameter tube?   | Small diameter tubes reduce gas turbulence in the tube banks.              | Small diameter tubes reduce the heating surface area.   | Small diameter tubes are less affected by the insulating properties of soot.                    | Small diameter tubes provide for greater heat transfer rates.   |  |
| 13 | 913 | C | The steam drum installed in "D" type boilers serve to provide _____. I. a water reserve necessary for proper boiler operation II. an area for steam and moisture to separate                                  | I only   | II only   | Both I and II   | Neither I nor II  |  |
| 13 | 914 | A | According to Coast Guard Regulations (46 CFR), periodic hydrostatic tests are required to be conducted without exception on all _____.  | main propulsion boilers  | auxilliary steam piping   | air receivers   | all of the above  |  |

|    |     |   |  |   |   |  |   |  |
|----|-----|---|--|---|---|--|---|--|
| 13 | 915 | D | If the cooling water flow through the air ejector intercondensers and aftercondensers is inadequate, which of the problems listed will occur?  | Air ejector nozzles will erode.                         | Aftercondenser will be flooded.               | DC heater level will rise                      | Main condenser absolute pressure will increase.         |  |
| 13 | 916 | D | In order to test the lifting pressure of the deaerating feed heater relief valve, you would _____. I. place a gag on the relief valve II. increase the set point of the reduced steam pressure to the auxiliary steam system   | I only  | II only                                       | Both I and II                                  | Neither I nor II  |  |
| 13 | 917 | D | Before an explosion can occur in a boiler furnace, there must be an accumulation of unburned fuel, sufficient air to form an explosive mixture, and a _____.   | space large enough for the explosion to occur           | ground in the burner ignition electrode       | high steam demand on the boiler                | source of ignition for the explosive mixture            |  |
| 13 | 918 | B | The vent line from the main condenser water boxes was not opened when the waterside was recharged. This would _____. I. lead to a build up of pressure on the tube sheet of greater than 40 psig. II. prevent the design vacuum from being attained under normal operating conditions at sea | I only  | II only                                       | Both I and II                                  | Neither I nor II  |  |
| 13 | 919 | A | Scale formation on the waterside of boiler tubes, is generally produced by _____.  | the salts of calcium and magnesium                      | metal oxides in the waterside                 | dissolved oxygen in the waterside              | accumulations of phosphates in the feedwater            |  |
| 13 | 921 | C | Which of the following statements represents an example of a throttling loss in a turbine?   | Friction as steam passes over the walls of the nozzles. | Steam leaving the last stages of the turbine. | Steam passing through a steam admission valve. | Steam leaking over the tips of fixed and moving blades. |  |
| 13 | 922 | C | The greatest resistance to heat transfer from the fireside to the waterside of a water-tube boiler takes place in the _____.   | steel tube wall itself                                  | soot buildup directly on the tube exterior    | gas film layer surrounding the tube            | moving water and steam inside the tube                  |  |

|    |     |   |   |   |   |  |  |         |
|----|-----|---|---|---|---|--|--|---------|
| 13 | 923 | D | Which condition would cause a dangerously low level in the deaerating feedwater tank (Direct Contact) heater as the vessel is increasing from maneuvering to sea speed? | Excessive dumping of feedwater to the drain inspection tank via the automatic dump valve. | Excessive recirculation of condensate to the drain transfer tank. | Improper operation of the auxiliary exhaust live steam dump valve. | Clogged "Y" strainer at the air supply of the pneumatically operated condensate makeup valve assembly. |         |
| 13 | 924 | C | According to Coast Guard Regulations (46 CFR), what is the maximum time interval for hydrostatically testing boilers on a cargo vessel having water-tube boilers?       | 1 year  | 2 years   | 5 years  | 8 years  |         |
| 13 | 925 | C | Excessively hot water returning to an atmospheric drain tank indicates .  | the condensate recirculating valve is open  | there is a loss of circulating water                              | a steam trap is hung open  | a heating coil has ruptured  |         |
| 13 | 926 | D | An accumulation of slag build up on the boiler furnace floor will cause _____. I. peeling of furnace brickwork II. overheating of the furnace floor                     | I only  | II only   | Both I and II  | Neither I nor II   |         |
| 13 | 927 | C | The most troublesome corrosive substances in boiler water are oxygen and .  | hydrogen sulfide  | sulfur dioxide  | carbon dioxide   | ammonia  |         |
| 13 | 928 | B | Throttling the burner air register of a lit burner could result in .  | carbon deposits on the register doors   | carbon deposits on the furnace walls                              | too much excess air for combustion                                 | excess combustion temperature in the furnace   |         |
| 13 | 929 | D | If the steam whistle shown in the illustration produces a poor, rattling tone when blown, the probable cause is a/an .  | insufficient steam pressure   | defective pilot valve   | excessive back cover tightness                                     | a loose back cover   | GS-0099 |
| 13 | 930 | A | Failure to remove calcium and magnesium from feedwater before it reaches the boiler can result in tube .  | scaling   | pitting   | sludging   | erosion  |         |
| 13 | 931 | B | Which of the effects listed describes the changes in the velocity and pressure of the steam as it passes through a nozzle?  | Velocity increases and pressure increases   | Velocity increases and pressure decreases                         | Velocity decreases and pressure increases                          | Velocity decreases and pressure decreases  |         |

|    |     |   |  |  |  |   |  |  |
|----|-----|---|--|--|--|---|--|--|
| 13 | 932 | B | In a watertube boiler, circulation is developed by the difference in the _____. I. tube length and various diameters II. densities of the hot and cold water   | I only   | II only  | Both I and II   | Neither I nor II   |  |
| 13 | 933 | A | A ruptured boiler tube should be removed by _____. I. splitting the remaining tube sections with a safety ripping chisel II. cutting out most of the tube and then allowing the remaining portion to disintegrate as the boiler is normally fired  | I only   | II only  | Both I and II   | Neither I nor II   |  |
| 13 | 934 | B | The maximum allowable working pressure of a particular boiler is 1050 psig (7340 kPa). The hydrostatic test pressure to be used during the Coast Guard required quadrennial inspection will be _____.  | 1050 psig (7340 kPa)   | 1312 psig (9146 kPa)                                       | 1575 psig (10959 kPa)   | 1850 psig (12855 kPa)                                      |  |
| 13 | 935 | A | Which of the conditions listed may be indicated by the lifting of the DC heater relief valve?  | A malfunctioning auxiliary exhaust make-up steam regulating valve. | Excessive deaeration of the feedwater.                     | Low back pressure in the auxiliary exhaust line.                  | Low water level continually maintained in the DC heater.   |  |
| 13 | 936 | B | A set of first and second stage air ejectors are used with a large sea water cooled steam condenser. If the first stage air ejector is not in operation _____. I. vacuum can not be established II. maximum operating vacuum can not be maintained | I only   | II only  | Both I and II   | Neither I nor II   |  |
| 13 | 937 | D | Sediment in fuel oil will cause _____.   | sputtering of atomizers  | panting in the furnace                                     | excessive white smoke   | clogged atomizer tips                                      |  |
| 13 | 938 | B | The distance piece in a boiler burner register assembly, provides for adjustment of the _____.   | diffuser to attain the desired amount of secondary air flow        | atomizer position to obtain the best mixing of air and oil | quantity of the primary and secondary air cones for best air flow | total volume of air and fuel admitted through the register |  |

|    |     |   |   |  |  |   |   |  |
|----|-----|---|---|--|--|---|---|--|
| 13 | 939 | B | The vent line from the main condenser water boxes was not opened when the waterside was recharged. This would _____ .I. lead to vapor binding of the main circulating pump II. contribute to a higher than normal condensate temperature entering the air ejector condenser | I only   | II only  | Both I and II   | Neither I nor II  |  |
| 13 | 940 | A | Which steam plant watch operating condition will require priority attention over the other situations listed?   | Low oil level in the steering gear sumps   | High lube oil level in all storage tanks                 | Low level effluent in chlorination section of sewage tank                   | Low bilge water levels throughout entire engineroom                       |  |
| 13 | 941 | B | An intermediate chamber is used in conjunction with labyrinth packing on a compound turbine for sealing steam .   | leak off during periods of internal vacuum   | supply during periods of low internal pressure           | supply during periods of high internal pressures                            | propulsion of peripheral water seals                                      |  |
| 13 | 942 | A | Before giving a boiler a surface blow, you should .   | raise the water level 2 or 3 inches above normal   | lower the water level to the normal level                | reduce the boiler firing rate to the minimum                                | take the boiler off the line and let it cool 1 hour                       |  |
| 13 | 943 | C | If flaking of a hard alloy tube is noticed while the tube is being expanded into the tube sheet, this would indicate that _____ .I. excessive pressure is being applied to the mandral II. the incorrect mandral is being used  | I only   | II only  | Both I and II   | Neither I nor II  |  |
| 13 | 944 | A | Coast Guard Regulations (46 CFR) require the duplex fuel oil discharge strainers installed in boiler fuel oil service systems to be .   | located so as to preclude the possibility of spraying oil on the burner or boiler casing | as close to the fuel oil service manifold as practicable | enclosed in a drip-proof vented enclosure to reduce the possibility of fire | a positive venting system that will return any vapors to the pump suction |  |
| 13 | 945 | B | If the DC heater relief valve lifts frequently, the cause can be excessive .  | condensate supplied to the DC heater   | auxiliary exhaust steam pressure                         | feedwater recirculated from the feed pump                                   | makeup feed introduced to the system                                      |  |
| 13 | 947 | D | Sediment in fuel oil will cause .   | wear in the fuel oil pumps   | clogging of the fuel oil heaters                         | wear in the sprayer plates  | all of the above  |  |

|    |     |   |   |  |  |  |   |  |
|----|-----|---|---|--|--|--|---|--|
| 13 | 948 | B | In an air register assembly, the largest quantity of air passes through the .   | diffuser or impeller   | stationary air foil or bladed cone   | air door operating ring  | atomizer assembly   |  |
| 13 | 949 | A | Carbon dioxide dissolved in boiler water is dangerous in a modern power boiler because the gas .  | forms carbonic acid which attacks the watersides   | breaks the magnetic iron oxide film inside boiler tubes  | combines with sulfates to cause severe waterside pitting             | combines with oxygen to cause severe waterside scaling                |  |
| 13 | 951 | B | A convergent-divergent nozzle functions to .  | reverse steam flow direction   | control turbulent steam expansion  | decrease steam velocity and increase steam pressure                  | decrease the specific volume of steam                                 |  |
| 13 | 952 | D | Before commencing a surface blow, the boiler .  | should be cold   | water level should be lowered to the surface blow line   | water drum should be checked for sludge                              | water level should be raised 2 to 3 inches (5 to 7.6 cm) above normal |  |
| 13 | 953 | B | The purpose of the boiler furnace corbel is to _____.I. protect the water drum from direct flame impingement II. support the furnace wall | I only   | II only  | Both I and II  | Neither I nor II  |  |
| 13 | 954 | B | Coast Guard Regulations (46 CFR) for boiler fuel oil service systems, require that .  | discharge piping from the service pumps to the burners must be of schedule 60 seamless steel | the return line from the burners must be arranged so that suction piping cannot be subject to discharge pressure | the fuel oil service pump relief valve must discharge to a wing tank | the suction strainer must be a simplex type                           |  |
| 13 | 955 | A | In a boiler equipped with an automatic feedwater regulator, erratic variations in the water level could be caused by .                    | high solids content and foaming in the drum  | ruptured feedwater control valve diaphragm   | low feedwater temperature  | high feedwater temperature  |  |
| 13 | 956 | A | A boiler water tube would burn out as a result of _____.I. direct flame impingement II. excessive soot accumulation                       | I only   | II only  | Both I and II  | Neither I nor II  |  |

|    |     |   |   |  |  |   |  |
|----|-----|---|---|--|--|---|--|
| 13 | 957 | A | Water washing of the water-tube boiler firesides is necessary to maintain efficient operation, but can lead to _____. I. sulfuric acid corrosion II. deterioration of the refractory                    | I only                                     | II only  | Both I and II                                 | Neither I nor II                                     |
| 13 | 958 | A | Boiler furnace brickwork can be fractured and broken by thermal shock caused by _____.  | leaving the registers open on a hot boiler | load changes on the boiler while answering bells | allowing the furnace to cool too slowly       | cold feedwater passing through the boiler economizer |
| 13 | 959 | B | The two most common causes of boiler corrosion attributable to boiler water are dissolved oxygen and _____.   | carbon monoxide                            | hydroxyl ions                                    | ammonia                                       | nitrogen   |
| 13 | 961 | B | In addition to causing erosion of turbine blades, slugs of water in the steam supply to a turbine driven pump can result in _____.  | thermal shock to the bearings              | erratic governor operation                       | loss of load with resultant turbine overspeed | overheating of the wearing rings                     |
| 13 | 962 | A | Before giving a boiler a surface blow, you must _____.  | open the skin valve on the blowdown line   | secure the fires in the furnace                  | lower the water level to a half glass         | increase the boiler steam pressure above normal      |
| 13 | 963 | B | The purpose of firebrick in a water tube boiler furnace is to _____. I. protect the tubes from direct flame impingement II. confine the combustion gases within the furnace                             | I only                                     | II only  | Both I and II                                 | Neither I nor II                                     |
| 13 | 964 | B | According to Coast Guard Regulations (46 CFR), a 1200 psig maximum allowable working pressure boiler, with external blowoff piping is required to have the blowoff piping withstand a minimum of _____. | 1200 psig                                  | 1425 psig  | 1500 psig                                     | 1575 psig  |
| 13 | 965 | D | The boiler water level is normal, the main condenser hotwell level is normal, and the DC heater shows a level 40% of full. You should _____.  | prime the condensate pump                  | bypass the vent condenser                        | slow the main unit                            | open the makeup feed vacuum drag line                |

|    |     |   |   |  |                                      |   |  |  |
|----|-----|---|---|--|--------------------------------------|---|--|--|
| 13 | 966 | C | Thin sheets of mica are installed in boiler gage glasses to _____. I. reduce the possibility of the glass from becoming etched II. limit the possibility of glass being blown out into the fire room  | I only   | II only                              | Both I and II                                   | Neither I nor II   |  |
| 13 | 967 | D | The depth of fuel oil in a double bottom tank is measured through the _____.  | vent line  | depth gage                           | manhole cover                                   | sounding tube  |  |
| 13 | 968 | A | Why are the burner registers closed a few minutes after a boiler has been secured to be cooled?   | To prevent cracking the furnace refractory.                  | To prevent further steam generation. | To allow more rapid furnace cooling.            | To allow continued steam generation.                         |  |
| 13 | 969 | A | In a boiler where the drum water level is automatically controlled, which of the following conditions could cause erratic variations in the water level?  | High total dissolved solids content and foaming in the drum. | Low pH boiler water value.           | Uncontrolled fluctuating deaerator water level. | Inability to maintain or correct high feedwater temperature. |  |
| 13 | 970 | C | Sliding contact bearings are classified into two general categories: journal bearings and _____.  | radial bearings  | needle bearings                      | thrust bearings                                 | roller bearings  |  |
| 13 | 971 | B | Most main propulsion reduction gear bearings are _____.   | self-lubricating   | rigidly mounted                      | spherical-seated                                | self-aligning  |  |
| 13 | 972 | B | When the rate of heat transfer through tube walls is so reduced that the metal becomes overheated, which of the following conditions will result in the boiler?                                       | Steam gouging  | Fireside burning                     | Fireside thinning                               | Steam binding  |  |
| 13 | 973 | A | The purpose of the water tube boiler furnace refractory is to _____. I. protect the water drum from direct flame impingement II. reinforce and strengthen the casing                                  | I only   | II only                              | Both I and II                                   | Neither I nor II   |  |
| 13 | 974 | B | According to Coast Guard Regulations (46 CFR), blowoff piping external to a boiler with a maximum allowable working pressure of 600 psig must be capable of withstanding a minimum pressure of _____. | 600 psig   | 750 psig                             | 825 psig  | 900 psig   |  |

|    |     |   |  |  |   |   |  |  |
|----|-----|---|--|--|---|---|--|--|
| 13 | 975 | C | Saltwater contamination of condensate could occur at which component?  | DC heater  | Aftercondenser  | Evaporator  | Intercondenser   |  |
| 13 | 976 | C | The internal feed pipe in a D-type marine boiler provides _____. I. distribution of feed water evenly throughout the steam drum II. guidance of the feedwater towards the downcomers as it enters the drum | I only   | II only   | Both I and II   | Neither I nor II   |  |
| 13 | 977 | C | When you are transferring fuel oil to the settling tanks, precautions to be observed should include _____.   | plugging gooseneck tank vents to prevent accidental overflow | maintaining a high transfer rate until a slight trickle of oil is observed flowing from the overflow line | sounding the tanks frequently and reducing the transfer rate as the level approaches maximum fill | maintaining a supply of chemical dispersant to cleanup minor oil spills adjacent to the ship |  |
| 13 | 978 | D | The main reason for keeping an operating boiler burner register fully open while steaming is to prevent _____.   | boiler explosions  | the fires being blown out   | boiler register warping   | improper fuel/air mixture  |  |
| 13 | 979 | C | In a steaming boiler, most dissolved chlorides tend to concentrate at, or near, the _____.   | tube joints  | mud drum  | water surface   | floor tubes  |  |
| 13 | 980 | B | A leaking boiler desuperheater may be determined by a/an _____. I. gradual, but continual rise in alkalinity II. hydrostatic test  | I only   | II only   | Both I and II   | Neither I nor II   |  |
| 13 | 981 | C | The turbine of a turbo-electric drive should be secured by _____.  | closing the main steam stops                                 | dynamic braking of the generator  | tripping the throttle trip by hand  | closing the throttle by hand   |  |
| 13 | 982 | A | In automatic combustion control systems, increasing or decreasing a loading pressure by a set amount is called _____.  | biasing  | loading   | relaying  | transmitting   |  |
| 13 | 983 | A | A boiler desuperheater is installed in high pressure boilers to _____. I. maintain flow through the superheater II. raise the steam temperature in the steam drum  | I only   | II only   | Both I and II   | Neither I nor II   |  |

|    |     |   |   |   |   |   |   |  |
|----|-----|---|---|---|---|---|---|--|
| 13 | 984 | B | Once a huddling chamber type safety valve has begun to initially open, it will then pop open due to the _____. I. expansion of tthe steam leaving the nozzle; II. forces exerted on the projecting lips                   | I only  | II only   | Both I and II                                     | Neither I nor II  |  |
| 13 | 985 | A | A common gas dissolved in water contributing to the greatest amount of corrosion in a condensate system is _____.   | carbon dioxide  | hydrogen  | carbon monoxide                                   | nitrogen  |  |
| 13 | 986 | C | In a water tube boiler, waterwall tubes are effectively used to _____. I. decrease the amount of refractory material necessary in non-waterwall installations II. allow for significant increases in the combustion rates | I only  | II only   | Both I and II                                     | Neither I nor II  |  |
| 13 | 987 | C | Fuel oil is transferred to the settling tanks for _____.  | filtering and purifing before being pumped to the burners | purging of any large air bubbles that have formed | heating to allow water and sediment to settle out | heating to the correct temperature for proper atomization |  |
| 13 | 988 | C | Shortly after shutting off the fuel to a boiler which is to be secured, the _____.  | air cock should be opened                                 | superheater vent may be closed                    | burner registers should be closed                 | feed stop must be closed                                  |  |
| 13 | 989 | D | A sudden increase in boiler water hardness or chloride content could indicate _____.  | a leaking condenser tube                                  | evaporator priming                                | bilge water leaking into the makeup feed tanks    | all of the above  |  |
| 13 | 990 | D | Thin sheets of mica are installed in boiler gage glasses to _____. I. reduce the effects of thermal exposure on the glass II. enhance the ability of the operator to observe the water level from a distance              | I only  | II only   | Both I and II                                     | Neither I nor II  |  |

|    |     |   |   |  |  |  |  |  |
|----|-----|---|---|--|--|--|--|--|
| 13 | 991 | B | The most critical period of main turbine operation is during cold start-up, rather than hot shutdown because .  | lubricant film thickness during start-up is considerably less than the dimensions of gear surface irregularities | differential expansion can result from the temperature difference between the rotor and rotor casing | the danger of blade erosion damage from dry steam impingement is greater during start-up | harmonic vibrations associated with critical speed can easily be reached during start-up |  |
| 13 | 992 | A | Coast Guard Regulations (46 CFR), require main propulsion lube oil systems to be designed to function satisfactorily when the vessel has a permanent .  | 15° list and a permanent 5°Trim  | 15° list and a permanent 10°Trim   | 22° list and a permanent 10° trim  | 30° list and a permanent 10° trim  |  |
| 13 | 993 | C | An accumulation test is performed on the boiler to determine the suitability of the safety valves and the set points _____. I. if the boiler normal operating pressure is permanently reduced II. when the steam generating capacity is increased | I only   | II only  | Both I and II  | Neither I nor II   |  |
| 13 | 994 | D | Coast Guard Regulations (46 CFR) require the temperature of the water leaving an oil fired, cast iron, low pressure, hot water heating boiler must not exceed .   | 190°F (87.8°C)   | 210°F (98.9°C)   | 230°F (110.0°C)  | 250°F (121.1°C)  |  |
| 13 | 995 | A | Carbon dioxide formed by improper chemical treatment in the boiler, may cause corrosion in the .  | condensate lines   | superheater tubes  | boiler tubes   | boiler desuperheater lines   |  |

|    |      |   |  |  |  |  |   |  |
|----|------|---|--|--|--|--|---|--|
| 13 | 996  | D | Which of the conditions listed should be attended to first upon taking over the watch and why should this step be taken?   | Excessive dumping of feedwater to the drain inspection tank. Failure to prevent will cause overflow and loss of distilled water. | Salted up evaporator draining to bilge. Must immediately be restarted to insure sufficient distilled and potable water quantities. | High level in fuel oil sludge tank. Necessary to pump contents to settler to prevent overflow of the tank into the bilges. | Broken air line to condensate makeup actuator. Repair or place in bypass control to insure proper levels throughout condensate and feedwater systems. |  |
| 13 | 997  | D | The main reason for having a low suction line on the fuel oil service or settling tanks is to _____.   | prevent loss of suction during rough weather   | decrease suction head on the pump  | increase the amount of fuel available for use  | facilitate water removal  |  |
| 13 | 998  | B | What is the purpose of the movable air doors in an air register?   | Regulate the temperature of air entering the furnace.  | Function to open and close the register.   | Maintain airflow across the forced draft fan.  | Support the burner distance piece.  |  |
| 13 | 999  | D | The internal feed pipe in a D-type marine boiler provides _____. I. distribution of feed water evenly throughout the water drum II. guidance and distribution of chemicals throughout the steam drum                   | I only   | II only  | Both I and II  | Neither I nor II  |  |
| 13 | 1000 | A | A leaking boiler desuperheater may be indicated by a/an _____. I. gradual, but continual rise in phosphate readings in only one boiler II. inability to maintain normal working pressure in the auxiliary steam system | I only   | II only  | Both I and II  | Neither I nor II  |  |
| 13 | 1001 | A | The diameter of a dummy piston installed in a reaction turbine is determined by _____.   | rotor design and the amount of thrust to be counteracted   | steam temperature and design RPM   | the length and diameter of the equalizing line   | the volume of the exhaust trunk and pressure drop over the last stage   |  |

|    |      |   |  |   |  |  |  |         |
|----|------|---|--|---|--|--|--|---------|
| 13 | 1002 | A | Coast Guard regulations require that the superheater safety valves _____. I. and the drum safety shall have a total rated capacity not less than the maximum generating capacity of the boiler II. be set and adjusted under pressure, regardless of the pilot pressure source | I only  | II only  | Both I and II  | Neither I nor II   |         |
| 13 | 1003 | A | The combustion air pressure is increased when using the steam soot blowers to 'blow tubes' in order to _____. I. aid in the process of removing soot deposits II. prevent the steam from extinguishing the fires   | I only  | II only  | Both I and II  | Neither I nor II   |         |
| 13 | 1005 | D | If the salinity indicator registers high salinity in the hotwell, you should suspect the cause to be _____.  | leaking air ejector condenser tubes               | leaking tubes in the third-stage heater              | high water pressure in the lube oil cooler           | leaking condenser tubes  |         |
| 13 | 1006 | C | Corrosion of the flue gas side of the economiser can be a result of the _____. I. stack gas temperature being lower than the dew point II. feedwater temperature being excessively cool  | I only  | II only  | both I and II  | neither I or II  |         |
| 13 | 1007 | A | Which of the following actions should be taken FIRST when water is found in the fuel oil settling tank?  | Shift pump suction to an alternate settling tank. | Shift to alternate or standby fuel oil service pump. | Sound the settling tank with water indicating paste. | Determine the extent of water contamination by reading the pneumerators. |         |
| 13 | 1008 | B | Identify the system shown in the illustration.   | Bleed steam                                       | Auxiliary steam                                      | High pressure drains                                 | Auxiliary condensate   | SG-0005 |
| 13 | 1009 | A | The illustrated burner atomizer assembly is _____.   | straight mechanical                               | used only for variable load steam atomization        | an example of a rotary cup type atomizer             | used in a return flow type burner management system                      | SG-0022 |

|    |      |   |   |  |   |   |  |  |
|----|------|---|---|--|---|---|--|--|
| 13 | 1010 | B | A boiler desuperheater is installed in high pressure boilers to _____.<br>I. maintain the essential flow of feedwater into the drum II. raise the feedwater temperature entering the steam drum   | I only   | II only   | Both I and II   | Neither I nor II   |  |
| 13 | 1011 | B | The axial position of a turbine rotor is controlled by the thickness of the _____.  | thrust bearing collar  | thrust bearing filler piece   | journal bearing shims   | labyrinth packing fins   |  |
| 13 | 1012 | B | Proper use of the boiler surface blow will _____.   | remove most precipitated solids  | remove floating impurities from boiler water  | disrupt circulation in a steaming boiler  | have no effect on boiler alkalinity                                  |  |
| 13 | 1013 | D | When starting a turbogenerator in an automated plant, you must provide lube oil pressure to the unit by means of _____.   | a line from the other generator  | a line from the gravity tank  | the main lube oil pump  | the hand operated or auxiliary lube oil pump                         |  |
| 13 | 1014 | A | When preparing to hydrostatically test water-tube boilers, you should _____.  | fill the boiler with water not less than 70°F (21.1°C), nor more than 160°F (71.1°C) | make arrangements for simultaneously testing main and auxiliary steam stops with water and steam pressure | remove all inspection plates and manhole covers as required by the marine inspector | have the boiler warmed to a temperature not exceeding 100°F (37.8°C) |  |
| 13 | 1015 | B | The relieving capacity of the superheater safety valves is considered to be insufficient when the working pressure of the boilers is _____. I. increased II. Decreased  | I only   | II only   | Both I and II   | Neither I nor II   |  |
| 13 | 1016 | B | The safety valve hand lifting gear should not be used if the boiler pressure is less than 75% of the safety valve popping pressure in order to _____. I. provide sufficient steam flow across the valve to prevent the collection of scale on the seat II. prevent cracking of the seat due to chattering of the feather and disc | I only   | II only   | Both I and II   | Neither I nor II   |  |

|    |      |   |  |   |  |   |  |  |
|----|------|---|--|---|--|---|--|--|
| 13 | 1017 | C | When heated, fuel oil will _____ .   | increase in specific gravity                          | have a higher specific heat  | expand in volume                              | increase in viscosity                            |  |
| 13 | 1018 | D | If one burner of a group of operating burners in a steaming boiler is cut out, the register doors for that burner should be _____ .  | left wide open  | left cracked open  | closed halfway                                | closed tightly                                   |  |
| 13 | 1019 | C | The proper oil inlet temperature for centrifuging lube oil should be _____ .   | 100° to 120°F<br>(37.8° - 48.9°C)                     | 130° to 150°F<br>(54.4° - 65.5°C)  | 160° to 180°F<br>(71.1° - 82.2°C)             | 190° to 210°F<br>(87.7° - 98.9°C)                |  |
| 13 | 1020 | B | A disk-type centrifuge is set up for continuous use on the main turbine lube oil system. In order to batch centrifuge a small quantity of diesel oil from a storage tank, _____ .  | the speed of the centrifuge must be increased         | another centrifuge should be used to avoid the possibility of contaminating the main lube oil system | the number of conical disks must be increased | the feed temperature must be decreased to 170°F  |  |
| 13 | 1021 | C | A rotor position micrometer measures rotor _____ .   | radial position relative to the casing                | radial position relative to the micrometer   | axial position relative to the casing         | axial position relative to the micrometer        |  |
| 13 | 1022 | A | Which of the listed methods can be used to blowdown a boiler without securing the fires?   | Steam drum surface blow.                              | Bottom blow from the mud drum.   | Blowdown the rear water wall header.          | Blowdown the front water wall header.            |  |
| 13 | 1023 | B | Scavenging air pressure is provided to the steam soot blowers to _____. I. keep steam from accumulating in the soot blowing element while another element is being operated II. prevent corrosive combustion gases from entering the elements when the system is secured | I only  | II only  | Both I and II                                 | Neither I nor II                                 |  |
| 13 | 1024 | B | Coast Guard Regulations (46 CFR) state that the temperature of the water for a hydrostatic test on a fire-tube boiler will be not less than 70° and not more than _____ .  | 90°F  | 100°F  | 130°F   | 160°F  |  |
| 13 | 1025 | B | Which of the conditions listed could prevent a centrifugal condensate pump from developing its rated capacity?   | Venting the pump to the vacuum side of the condenser. | Closing the water seal line to the packing gland.  | Flooding of the main condenser hotwell.       | Operating the pump with a positive suction head. |  |

|    |      |   |  |   |  |  |  |  |
|----|------|---|--|---|--|--|--|--|
| 13 | 1026 | B | As lube oil absorbs moisture its dielectric strength can be expected to .  | remain the same   | decrease   | increase with an increase in viscosity   | increase with a decrease in viscosity      |  |
| 13 | 1027 | C | Using an oil temperature-viscosity chart, you can determine the recommended .  | fuel oil flash point for best combustion                                  | fuel/air ratio for efficient combustion                        | oil temperature for proper atomization   | oil pressure for smokeless operation       |  |
| 13 | 1028 | C | While standing your engine room watch at sea, you notice the D.C. heater level is gradually dropping as indicated by the remote level indicator. Which of the following actions should you take? | Do nothing as this is a common marine plant occurrence.                   | Immediately open the automatic make-up feed bypass valve.      | Check the condensate level in both the main and auxiliary condenser hotwells.      | Immediately stop the main engine.          |  |
| 13 | 1029 | A | What steps should be taken if large quantities of fuel oil are found in the drain inspection tank?   | Change over to the standby fuel oil heater.                               | Open steam trap bypass of the fuel oil heater that is on line. | Secure the lube oil purifier and its associated heater.                            | All of the above                           |  |
| 13 | 1030 | A | After starting the main lube oil pump in a gravity-type lube oil system, you should verify that the gravity tanks are full by .  | looking at the overflow sight glass                                       | sounding the gravity tanks                                     | sounding the lube oil sump   | observing the flow from the bearings       |  |
| 13 | 1031 | A | Journal bearings used with modern turbine rotors are manufactured in two halves in order to .  | permit removal of the bearing without removing the rotor from the turbine | facilitate interchanging with other bearing halves             | maintain axial alignment and reduce thrust   | provide for positive oil flow at all loads |  |
| 13 | 1032 | D | The boiler gage glasses should be periodically blowdown to .   | test the feedwater stop-check valve                                       | provide water samples for the second assistant                 | maintain the proper water level in the steam drum                                  | remove any sediment from the glass         |  |
| 13 | 1033 | C | Which of the following conditions must be carried out before the superheating of saturated steam can occur in a boiler?  | The firing rate of the boiler must be increased.                          | The flow of feedwater to the boiler must be increased.         | The steam must be removed from contact with the water from which it was generated. | The boiler pressure must be raised.        |  |
| 13 | 1034 | B | The main condenser is losing 2" Hg vacuum every 5 minutes. In an hour, the absolute pressure will have increased by approximately .  | 6 psia  | 12 psia  | 16 psia  | 24 psia                                    |  |

|    |      |   |   |   |  |  |   |  |
|----|------|---|---|---|--|--|---|--|
| 13 | 1035 | B | Air in the main condenser is harmful because it will _____ .  | decrease the turbine exhaust steam pressure   | decrease the vacuum in the main condenser  | cause heat to be transferred too rapidly   | cause the turbine casing to warp and bow  |  |
| 13 | 1036 | B | The relieving pressure of the superheater safety valves is permitted to be reset without exchanging the valves when the working pressure of the boilers is _____ . I. increased II. Decreased | I only  | II only  | Both I and II  | Neither I nor II  |  |
| 13 | 1037 | C | Bunker "C" fuel oil is heated prior to atomization to _____ .   | increase the heating value  | increase its specific gravity  | reduce its viscosity   | reduce the flash point  |  |
| 13 | 1039 | D | A back pressure trip on an auxiliary turbine functions to secure the device if the _____ .  | oil pressure is too low   | discharge pressure of a turbine driven pump is excessive   | gland seal leakoff pressure is too high  | exhaust pressure rises above a preset limit   |  |
| 13 | 1040 | D | Which of the listed order of valves represents the proper installation of the main feedwater supply line to a marine propulsion boiler?   | Regulator, stop, stop-check   | Stop-check, stop, regulator  | Stop, regulator, stop-check  | Stop-check, regulator, stop   |  |
| 13 | 1041 | C | How is the axial clearance indicator used on a turbine?   | The axial clearance indicator is inserted in the depth gauge well until it rests on the reference boss, and the reading is noted. | After the axial clearance indicator is screwed into contact with the rotor, shims are placed in the clearance well, and the thickness is measured. | The arm of the axial clearance indicator is pushed so contact is made with a rotor, and the reading on the scale is noted. | A bridge gauge is placed across the bearing, and the gap between bridge and rotor is measured by the axial clearance indicator. |  |
| 13 | 1042 | A | The boiler water gage glasses should be blown down _____ .  | when you are in doubt about the water level   | twice each day on the midnight and afternoon watches   | every 12 hours of steady boiler steaming operation   | when the boiler water level changes in a steaming boiler  |  |

|    |      |   |   |   |   |  |   |         |
|----|------|---|---|---|---|--|---|---------|
| 13 | 1043 | D | Which of the listed items are the two most commonly used opposing forces involved in the operation of a constant pressure feed pump governor?                             | Steam inlet pressure and pump discharge pressure.                       | Pilot valve steam pressure and control valve spring pressure.                           | Steam inlet pressure and adjusting spring tension.   | Pump discharge pressure and adjusting spring compression. |         |
| 13 | 1044 | D | According to Coast Guard Regulations (46 CFR), what action should be taken if the metal thickness of a marine boiler is found to be thinner than original specifications? | Affected areas should be built up by welding.                           | Boiler should be condemned.   | Drum should be renewed before the next biennial inspection.  | Working pressure should be recalculated.                  |         |
| 13 | 1045 | B | If the condensate level in the loop seal of the intercondenser is lost,   | no condensate will flow through the system                              | some air will be drawn into the main condenser  | the air ejector will not operate   | the air ejector will become overheated                    |         |
| 13 | 1047 | A | The Butterworth heater (tank cleaning heater) shown in the illustration is designed to operate at a nominal steam pressure of approximately .                             | 130 psi   | 240 psi   | 450 psi  | 850 psi   | SG-0005 |
| 13 | 1048 | A | Fuel oil is heated before atomizing to .  | reduce the viscosity  | increase the viscosity  | raise the fire point   | lower the flash point                                     |         |
| 13 | 1049 | D | 46 CFR requires that .  | the OCMI be notified of repairs to boilers and unfired pressure vessels | the fuel burned in boilers of tankships shall have a flash point of not less than 140°F | a half-pint sample of each load of fuel be drawn and sealed at the time of supply and preserved until that fuel is exhausted | all of the above  |         |
| 13 | 1050 | B | Water circulation in a water-tube boiler is a result of the .   | difference between the area and length of the water-tubes               | differences in density within the circulated water                                      | velocity added to the water by the feed pump   | siphon action of steam leaving the drum                   |         |
| 13 | 1051 | B | Properly filing the ends of carbon ring segments removed from a turbine gland will .  | reduce the ring segment end clearance                                   | reduce the clearance between the assembled ring segments and shaft                      | increase the possibility of steam leakage past the rings   | increase the possibility of air leakage into the turbine  |         |

|    |      |   |  |   |  |  |  |  |
|----|------|---|--|---|--|--|--|--|
| 13 | 1052 | B | To properly blowdown a boiler gage glass, you should .   | blow through the top (steam) connection first   | blow through the bottom (water) connection first   | never disconnect the chains that connect the upper and lower cut out valves  | take up snugly on upper and lower gage glass packing nuts prior to blowing down  |  |
| 13 | 1054 | C | Coast Guard Regulations (46 CFR) state that a marine inspector may require a boiler to be drilled or gaged to determine actual thickness .   | at the first inspection for certification   | to preclude nondestructive testing methods   | at any time its safety is in doubt   | when boiler drum thickness has decreased by 5%   |  |
| 13 | 1055 | B | Noise caused by condensate striking bends or fittings in a pipe line is called .   | condensate depression   | water hammer   | piston slap  | hydraulic lock   |  |
| 13 | 1056 | B | Prior to taking on bunkers in a deep tank previously used to carry dry cargo, you should .   | test the fixed fire extinguishing system in that tank   | inspect and test the tank heating coils for damage   | install a quick-closing valve in the sounding tube   | chemically clean and gas free the tank   |  |
| 13 | 1057 | C | The double bottom tanks on your vessel are used to store heavy fuel oil. In general, there are six sets of tanks with the port/starboard outboard tanks being an average 33% to 50% capacity smaller than the port/starboard centerline tanks. Also, the tanks forward are smaller than those aft, with the 3's and 5's being relatively the largest double bottoms. In general, with a minimum amount of fuel oil on board, the bunkering process should be to fill the . | aft tanks, then the midship tanks, finally all forward tanks to use the increase in pressure to force the oncoming fuel forward | forward tanks, then the 3's and 5's, and finish with the aft tanks moving successively aft to bring the draft at the bow down as quickly as possible | forward tanks, then fill the aft tanks, and complete the bunkering by filling the outboard then centerline 3's and 5's to avoid high pressure in static overflow leg | forward then the aft tanks, and completing the process by filling the centerline, then the outboard 3's and 5's, as small tanks are easier to control when topping off |  |
| 13 | 1058 | A | The primary purpose of the heater used in a pressurized fuel oil system is to .  | reduce fuel oil viscosity for proper atomization  | reduce fuel oil specific gravity for better combustion   | increase the fire point of the fuel oil  | improve the flash point of the fuel oil  |  |

|    |      |   |  |   |   |  |  |
|----|------|---|--|---|---|--|--|
| 13 | 1059 | A | To test an automatic low lube oil pressure trip on an idling turbogenerator and at the same time prevent the chance of bearing damage, you should                | secure the steam supply valve to the throttle valve and observe the lube oil pressure reading when the throttle trips, while ensuring an adequate supply of oil with the hand or standby pump as the generator idles to a stop or drops below 3 psi | ensure the standby lube oil pump, if so equipped, is properly lined up and set in the "auto" mode, or the hand pump is being operated and then actuate the emergency trip | close the generator steam throttle valve and then ensure a supply of oil through the hand or standby pump when the pressure drops to 5-6 psi | actuate the overspeed trip, making a note at what pressure the oil is dumped from under the operating piston |
| 13 | 1060 | D | Coast Guard Regulations (46 CFR) state that main propulsion water-tube boilers are required to be fitted with a surface blow off valve if the design pressure is | less than 200 psig (1436 kPa)   | less than 250 psig (1795 kPa)   | less than 300 psig (2169 kPa)  | less than 350 psig (2513 kPa)  |
| 13 | 1061 | A | On a main propulsion turbine bearing, the readings obtained with a bridge gage represent the   | oil clearance and bearing wear  | babbitt thickness   | diaphragm tip clearance  | blade axial clearance  |
| 13 | 1062 | B | If the engineer on watch has reason to doubt the accuracy of the water level showing in the boiler gage glass, he should FIRST                                   | open the auxiliary feed line  | blowdown the gage glass   | replace the gage glass   | start the standby feed pump  |
| 13 | 1064 | C | According to Coast Guard Regulations (46 CFR), what is the highest steam temperature to which fusible plugs may be exposed?                                      | 290°F   | 375°F   | 425°F  | 500°F  |

|    |      |   |   |   |   |  |   |  |
|----|------|---|---|---|---|--|---|--|
| 13 | 1065 | D | A decrease in condenser vacuum is found to be caused by a loss of the air ejector loop seal. To reestablish the loop seal, you should _____.                    | crack open the recirculating line from the DC heater to the condenser hotwell   | close in on the recirculating line from the DC heater to the condenser hotwell      | bypass the regulating valve in the condensate recirculating line until the loop refills              | close the condenser loop seal valve until the loop refills and reopen slowly  |  |
| 13 | 1066 | D | While on watch aboard a 900 psi (6.2 MPa) steam vessel, you suddenly hear a loud, piercing, high-pitched noise. Which of the following actions should you take? | Vacate everyone from the engine room immediately, as this is the preliminary signal that CO2 is about to be released. | Rapidly move towards the direction of the noise to investigate the probable source. | Cautiously move towards the source of the noise, sweeping the beam of your flash light ahead of you. | Move away from the noise to find a broom, then cautiously advance, sweeping the handle ahead of you to locate the source. |  |
| 13 | 1067 | C | According to Coast Guard Regulations (46 CFR), fusible plugs are not permitted where the maximum steam temperature to which they are exposed exceeds _____.     | 206°F   | 218°F   | 425°F  | 850°F   |  |
| 13 | 1068 | B | Fuel oil is heated before it reaches the burners to _____.  | increase its heating ability  | make it atomize properly  | raise its ignition temperature   | boil off water contamination  |  |
| 13 | 1069 | A | Routine maintenance of boiler sliding feet should include _____.  | wire brushing to remove scale, rust, and dirt   | torquing retaining bolts on the stationary base                                     | removing all grease from around the bolts  | painting the sliding surfaces to prevent corrosion  |  |
| 13 | 1070 | A | If the bellows in a thermo-hydraulic feedwater control valve ruptures, the boiler water level will _____.   | decrease only   | increase only   | decrease initially and then increase   | increase initially and then decrease  |  |
| 13 | 1071 | D | Which of the devices listed can be used to determine bearing wear on a main propulsion turbine bearing?   | Bridge gage   | Soft lead wires   | Micrometer depth gages   | All of the above.   |  |
| 13 | 1072 | B | Steam baffles are installed in the steam drum of a water-tube boiler to _____.  | direct the flow of steam to the desuperheater inlet   | reduce the possibilities of carryover   | prevent water return   | increase the velocity of the steam and water mixture  |  |

|    |      |   |  |   |  |   |  |  |
|----|------|---|--|---|--|---|--|--|
| 13 | 1073 | B | Excessively hot water returning to an atmospheric drain tank indicates .   | a heating coil has ruptured                             | a steam trap is hung open                                | there is a loss of circulating water  | the condensate recirculating valve is open       |  |
| 13 | 1074 | C | During an inspection of the main turbine, you notice flow marks or discoloration across the diaphragm joints. This condition indicates .                                   | normal wear for a high temperature unit                 | water carryover between stages                           | improper seating of the diaphragm joint   | excessive chemical treatment of the boiler water |  |
| 13 | 1075 | A | While a vessel is underway, one of the FIRST indications of the failure of the gland leakoff exhaust fan motor is .  | excessive steam leakage at the turbine glands           | loss of vacume at the turbine                            | increased turbine exhaust temperature   | water knock on the turbin gland steam header     |  |
| 13 | 1076 | C | During a maintenance inspection of a turbogenerator, the integral turbine wheels are tapped with a hammer. What condition may be indicated by a dull non-resonating sound? | Improper rotor support                                  | Overstressed blade shrouding                             | A cracked turbine wheel   | Normal structural solidity                       |  |
| 13 | 1077 | B | All oil-fired main propulsion burners with automatic safety control systems must automatically close the burner valve when .   | flame in boiler furnace is confirmed                    | actuated by boiler safety trip                           | burner is properly seated   | starting trial for ignition occurs               |  |
| 13 | 1078 | C | Steam drains from fuel oil heating coils can be returned to the condensate and feedwater system .  | through a direct connection to the heating drain header | through a vacuum drag line connection to the fuel heater | after being collected in the drain inspection tank                              | after first passing through the DC heater        |  |
| 13 | 1079 | D | All oil-fired main propulsion burners with automatic safety control systems must automatically close the burner valve when .   | the flame in boiler furnace is confirmed                | starting "trial for ignition"                            | the burner is properly seated   | actuated by a boiler safety trip                 |  |
| 13 | 1080 | A | According to Coast Guard Regulations, bolier safety valves .   | shall not have valves on drain lines                    | will only be set and sealed by the Chief Engineer        | will be provided with a suitable lifting device operated only from the fireroom | all of the above                                 |  |
| 13 | 1081 | B | A bridge gage is used to measure .   | blade tip leakage                                       | rotor bearing wear                                       | axial clearances  | thrust bearing wear                              |  |

|    |      |   |  |   |   |   |   |         |
|----|------|---|--|---|---|---|---|---------|
| 13 | 1082 | B | The main feed check valve functions to .   | check pressure pulsations in the feed line                            | prevent backflow of water from the boiler in the event of a feed pump failure       | provide feed pump positive discharge head                 | reduce feed pump discharge pressure loading                               |         |
| 13 | 1083 | C | All oil-fired main boiler burners with automatic safety control systems must be provided with .  | a modulating pressuretrol, sensing both steam and temperature         | a pyrostat measuring decreased steam temperature                                    | one flame detector per burner                             | an electrode sensing high water level                                     |         |
| 13 | 1084 | D | Which normally closed valve would have to be at least partially open prior to actually lighting off a cold boiler as shown in the illustration?  | C   | D   | F   | J   | SG-0009 |
| 13 | 1085 | A | A malfunction in the DC heater is indicated by .   | the boiler requiring excessive amounts of oxygen scavenging chemicals | water and steam entering the DC heater at different temperatures                    | condensate coming in contact with steam inside the heater | air flowing from vent condenser vent                                      |         |
| 13 | 1086 | D | While standing watch in the engine room of a steam vessel while at normal sea speed, you notice that the condensate temperature outlet of the air ejector condenser is fluctuating by approximately 12°F. You should therefore . | call the Chief Engineer immediately                                   | only need to log the temperature and inform the watch engineer who will relieve you | only need to add make-up feed to the system               | first determine whether the main condenser level is normal and steady     |         |
| 13 | 1088 | B | When securing a fuel oil heater you should .   | open the fuel oil temperature regulator bypass, widely                | cut out the steam before securing the oil flow                                      | stop the oil flow and then cut out the steam              | remove all fuel oil pressure from the system by securing the service pump |         |

|    |      |   |   |   |  |  |   |         |
|----|------|---|---|---|--|--|---|---------|
| 13 | 1089 | D | While standing watch in the engine room, power is suddenly lost, but the main breaker has been observed to not have 'tripped'. The standby generator has automatically started, but when attempting to parallel it with the 'on-line unit' the synchroscope begins to rotate counterclockwise the more you increase generator speed. As the watch engineer you should . | attempt to re-establish power with the 'on-line' generator        | standby for orders from the bridge                                     | trip all non-critical breakers before trying to re-establish power | trip the 'on-line' generator and its breaker, before attempting to place the stand-by generator on line |         |
| 13 | 1090 | C | Why are two fuel oil heaters "E" provided in the fuel oil system shown in the illustration?   | Each heater supplies fuel to a different boiler.                  | To allow fuel of different temperatures to be provided to each boiler. | To provide a backup in case one of the heaters becomes inoperable. | To provide series operation at high firing rates.   | SG-0009 |
| 13 | 1091 | B | Thrust clearances indicated on a main propulsion turbine bearing clearance diagram are .  | normal clearances for operation under routine steaming conditions | cold clearances to which the bearing was initially set                 | minimum clearances that indicate when bearing renewal is necessary | maximum clearances which should not be exceeded when the turbine is warmed up                           |         |
| 13 | 1092 | C | On a boiler equipped with pilot actuated safety valves, which of the valves listed will be actuated first?  | Drum safety valve   | Superheater safety valve   | Pilot actuated safety valve for the superheater safety valve       | Pilot actuated safety valve for the drum safety valve   |         |
| 13 | 1093 | C | While standing watch underway at sea in the engine room, there is a complete loss of electrical power. When power is restored, the steering gear pump motor will .  | have to be restarted from the steering gear room                  | have to be reset before restarting                                     | restart automatically  | trip via the overload relay   |         |
| 13 | 1094 | B | While standing watch underway in the engineroom, failure of the normal power supply will cause the emergency generator to provide power through the .   | main bus tie feeder   | automatic bus transfer device  | line connection feeder   | power failure alarm bus   |         |

|    |      |   |   |  |  |   |  |  |
|----|------|---|---|--|--|---|--|--|
| 13 | 1095 | C | Excessive condensate depression can result in _____ .   | overheated air injectors   | high condensate discharge temperature  | decreased plant operating efficiency  | insufficient condensate subcooling   |  |
| 13 | 1097 | A | While on watch at sea with only one ship's service turbogenerator on line, the entire plant suddenly blacks out without warning. After restoring power, which of the following faults would most likely have attributed to this casualty?   | The turbogenerator throttle valve position "micro switch" vibrated open, allowing the main breaker to trip open according to its protection circuitry. | Someone pushed the trip button to the 'shore power' breaker.   | The main air compressor suddenly stopped.   | The standby generator started automatically and became motorized.  |  |
| 13 | 1098 | D | The fins on the tubes of a fin type fuel oil heater are provided to _____ .   | clean the fuel oil   | prevent tube erosion   | decrease fuel flow  | increase heater efficiency   |  |
| 13 | 1099 | B | While underway at sea, a mechanical malfunction in one of the ship's service generators operating in parallel, requires that you must secure that generator. In order to prevent a possible overload to the remaining generator, which of the following sequential courses of action should be taken? | Trip the malfunctioning generator's circuit breaker and prime mover throttle trip.   | Trip all nonvital distribution feeder circuit breakers, decrease the load on that generator by using the governor, trip the malfunctioning generator's circuit breaker, and trip the prime mover throttle. | Trip the malfunctioning generator's circuit breaker and distribution feeder circuit breakers. | Trip all nonvital distribution feeder circuit breakers, the malfunctioning prime mover turbine throttle trip, and the generator circuit breaker. |  |
| 13 | 1101 | B | The thrust bearing wear on a turbine may be determined by checking the _____ .  | bearing drop   | rotor axial position   | rotor expansion rate  | casing movement  |  |
| 13 | 1102 | C | One of the important functions of the superheater safety valves is to _____ .   | maintain a constant steam flow in the desuperheater  | protect the desuperheater from overheating   | protect the superheater from overheating  | maintain a constant steam flow in the auxiliary steam line   |  |

|    |      |   |   |   |  |  |  |  |
|----|------|---|---|---|--|--|--|--|
| 13 | 1103 | C | While standing watch in the engine room which of the following actions should be taken to reestablish a 'blown' air ejector loop seal?  | Decrease the steam pressure to the air ejector nozzels.     | Shut off the steam to the second stage air ejector momentarily then open it again. | Momentarily close the valve in the loop seal line, then reopen slowly. | Increase the condensate flow through the air ejector.        |  |
| 13 | 1104 | D | While underway, the boiler water level in a steaming boiler begins dropping rapidly and cannot be kept at the normal level by standard practices. As the watch engineer you should .                      | continue to speed up the feed pump to raise the water level | blowdown the gage glass to find the true water level                               | secure the steam stop and then secure the fires                        | secure the fires and then secure the feed stop to the boiler |  |
| 13 | 1105 | D | Excessive condensate depression will result in .  | increased oxygen rejected in the condenser                  | decreased steam consumption  | excessive condensate temperatures                                      | increased air absorption by the condensate                   |  |
| 13 | 1106 | A | While on watch in the engine room and steaming at a steady rate, the water level begins to decrease and suddenly drops out of sight in the boiler gage glass. Your FIRST corrective action should be to . | secure the fires  | slow down the engines  | blowdown the boiler gage glass   | open the feedwater regulator bypass                          |  |
| 13 | 1107 | B | The consideration that is MOST important when determining the minimum temperature of fuel oil in storage tanks is the .   | fire point of the oil                                       | pumpability of the oil   | expansion of the oil   | size of the vents  |  |
| 13 | 1108 | A | You are standing watch in the engine room of a steam vessel. You should blow down a gage glass periodically to .  | remove any sediment that has accumulated                    | maintain the proper water level in the steam drum                                  | provide water samples for the second assistant                         | test the feedwater stop-check valve                          |  |
| 13 | 1109 | D | You are standing watch in the engine room of a steam vessel. If the entire pneumatic control to a multi-element feedwater regulator fails, the feedwater valve can be controlled by the .                 | constant pump pressure regulator                            | remote manual control regulator  | single-element feedwater regulator                                     | local manual hand control                                    |  |

|    |      |   |   |   |   |  |  |  |
|----|------|---|---|---|---|--|--|--|
| 13 | 1110 | B | While underway on watch in the engine room of a steam vessel, the proper valve positions for controlling feedwater to the boiler using the auxiliary feed system should be .  | the auxiliary check valve fully open and the stop valve used to regulate the amount of flow | the stop valve fully open and the auxiliary check valve used to regulate the amount of flow | the stop and check valves fully open and the feed pump speed used to regulate the amount of flow | the check valve fully open and the stop valve regulated by the feedwater regulator |  |
| 13 | 1111 | D | In order to operate the main engine with only the high pressure turbine in service, the unit should be arranged .   | to secure only the gland sealing steam to the low pressure turbine                          | with a blank installed in the high pressure turbine steam inlet                             | with the valve closed in the crossover pipe between the high pressure and low pressure turbine   | with the high pressure turbine exhausting directly to the main condenser           |  |
| 13 | 1112 | A | If a boiler superheater safety valve is leaking at normal working pressure, the quickest method of determining and possibly solving the problem is to .   | blow out the valve by several short lifts with the hand lifting gear                        | fully open the superheater safety drain valve for several seconds                           | lower the firing rate until the leakage stops  | raise the firing rate until the leakage stops                                      |  |
| 13 | 1113 | A | Your main propulsion boilers are equipped with a two element feedwater regulating control system. While on watch, you are required to respond to a 'stop' bell from full sea speed. With the shaft now stopped, the automatic feedwater regulator will have . | closed down on the feedwater valve due to the decrease in steam flow demand                 | opened the feedwater valve wide due to the effect of shrink                                 | partially closed down on the feedwater valve due to the effect of swell                          | fully opened the feedwater valve due to the increase in steam flow                 |  |
| 13 | 1114 | C | You are standing watch in the engine room of a steam vessel. Fine adjustments to a boiler combustion control system, to bring about near perfect combustion, should be made by manually adjusting the .   | fuel oil back pressure  | air volume regulators   | fuel/air ratio knob  | forced draft fan damper positions  |  |
| 13 | 1115 | C | On a steam vessel, if a centrifugal main feed pump were operating at shutoff head with the recirculating line closed, which of the following conditions could occur?  | Water level in the DC heater would decrease.  | An increased water level in the steam drum.   | Flashing at the suction side of the pump.  | Excessive diaphragm seal wear in the feedwater regulator.                          |  |

|    |      |   |   |  |   |   |  |  |
|----|------|---|---|--|---|---|--|--|
| 13 | 1116 | D | During initial starting of the standby turbine-driven boiler feed pump, which of the listed valves should remain closed?  | Turbine exhaust valve                    | Turbine steam supply valve  | Pump suction valve  | Pump discharge check valve   |  |
| 13 | 1117 | D | Fuel oil settling tanks are used to .   | store oil for immediate use              | precipitate out water and solids  | facilitate the stripping of sludge and water                                      | all of the above   |  |
| 13 | 1118 | C | In the majority of marine power plants, the fuel oil heater installations are divided into several units because .  | more heating is required for lower loads | auxiliary steam is better utilized in this system   | plant operation can be continued while repairs are being made to a defective unit | oil leakage into the condensate system is less likely with multiple system |  |
| 13 | 1119 | D | While standing watch in the engine room you hear a 'crackling' sound coming from within a general service system centrifugal pump. The most probable cause for this occurrence would be due to an abnormal condition at the . | shaft sleeves                            | discharge volutes   | wearing rings   | pump suction   |  |
| 13 | 1120 | C | If you hear a 'crackling' sound coming from a salt water centrifugal pump casing, the most probable cause of the noise would be .   | insufficient packing                     | an oversized lantern ring   | excessive suction lift  | reversed pump rotation   |  |
| 13 | 1121 | A | While a vessel is underway the low pressure turbine high-speed pinion is damaged. The pinion is then removed from the gear train. Under these circumstances, the main unit is capable of which speed and direction?           | Reduced speed ahead only                 | Reduced speed astern only   | Reduced speed ahead and full speed astern   | Reduced speed astern and full speed ahead                                  |  |
| 13 | 1122 | C | Which of the conditions will occur FIRST if the steam flow to the main engine, from a boiler with mechanical atomization, when at full power is suddenly stopped?   | Drum safety valves will open.            | Dual element automatic feedwater regulator will admit additional water to compensate for shrinkage. | Superheater safety valve will open.   | Combustion control system will automatically secure all of the burners.    |  |

|    |      |   |   |  |   |   |   |  |
|----|------|---|---|--|---|---|---|--|
| 13 | 1123 | B | If you hear a 'crackling' sound coming from a salt water centrifugal pump casing, the most probable cause of the noise would be _____.  | insufficient speed   | cavitation  | excessive discharge pressure  | excessive net positive suction head   |  |
| 13 | 1124 | A | According to Coast Guard Regulations (46 CFR), which of the following steam piping conditions, subjected to main boiler pressure, is exempted from hydrostatic testing?   | All piping with a nominal size of 3 inches or less.                    | All piping from the main steam stop to the throttle valve.  | All piping to the ship's service generators.  | All piping equipped with a safety or relief valve.  |  |
| 13 | 1125 | C | Which of the conditions listed should be immediately reported to the engineering officer on watch?  | Steam leaving the vent of the gland exhaust condenser.                 | Lube oil passing through the bull's eye of the gravity tank overflow line.  | Oil in the drain inspection tank.   | Water trickling in through the stern gland.   |  |
| 13 | 1126 | A | The usual symptoms of cavitation in a centrifugal pump would be _____.  | noise and vibration  | an increase in discharge pressure   | an increase in suction pressure   | lifting of the relief valve   |  |
| 13 | 1127 | A | Cavitation is a term commonly used with centrifugal pumps to describe _____.  | the formation and subsequent collapse of vapor pockets in the impeller | excessive clearances produced on the impeller wearing rings   | the laminar flow of the fluid being pumped  | water hammer in the pump suction line   |  |
| 13 | 1128 | A | The advantage of a counterflow fuel oil heater, as compared to a parallel flow fuel oil heater, is that the counterflow heater _____.   | produces a higher oil temperature at any given steam temperature       | has a larger heat transfer area providing greater heat transfer   | has thinner tube walls providing greater heat transfer  | is not subject to coking if overheated  |  |
| 13 | 1129 | B | While underway at sea, one of three available centrifugal salt water service pumps is in operation with a sea water temperature of 50°F. The operating temperature of all the systems supplied by this pump appear to be high. Your next proper course of action would be to _____. | start a second pump and operate it in parallel                         | start a second pump and place it on line, close the discharge valve on the original pump and watch for a rise in the discharge pressure | start the second pump, open the casing vent valve of the first pump, then secure the first pump | start the second pump, secure the first pump and do nothing else with the salt water service system |  |

|    |      |   |   |  |   |  |  |
|----|------|---|---|--|---|--|--|
| 13 | 1130 | D | On watch aboard ship, which of the following conditions will prevent a general service shipboard pump from achieving its maximum suction lift?  | Leaks developed in the suction piping. | Friction losses as a result of improperly sized pipe.               | Gases or vapors released in the liquid as a result of greater than normal pressure drops.                      | All of the above.  |
| 13 | 1131 | D | During an inspection of the main turbine, you notice flow marks or discoloration across the diaphragm joints. This condition indicates .  | water carryover between stages         | normal wear for a high temperature unit                             | excessive chemical treatment of the boiler water   | improper seating of the diaphragm joint  |
| 13 | 1132 | B | Standing watch in the engine room, what would be the result of throttling the suction valve on a general service centrifugal pump to the point where the flow was less than that recommended by the manufacturer?I. The designed discharge head would be reduced.II. The packing life would be reduced. | I only                                 | II only   | Both I and II  | Neither I nor II   |
| 13 | 1134 | D | When conducting a hydrostatic test of a boiler, Coast Guard Regulations (46 CFR) prohibit .   | gagging the safeties                   | removing the safety valves in order to perform the hydrostatic test | a test pressure of less than 1 1/2 times the maximum allowable working pressure if testing a water-tube boiler | the auxiliary stop valve from simultaneously having hydrostatic pressure on one side of the valve and steam pressure on the other side |
| 13 | 1135 | A | Excessive recirculation of condensate should be avoided, as it can cause .  | excessive cooling of the condensate    | overheating of the air ejectors                                     | the condenser hotwell to be completely drained at low speeds   | overheating of the vent condenser  |

|    |      |   |  |   |   |  |  |         |
|----|------|---|--|---|---|--|--|---------|
| 13 | 1137 | D | The results of a flue gas analysis indicate a very high percentage of oxygen, and a low percentage of carbon dioxide. This condition coincides with which area on the graph shown in the illustration?                             | A   | B and C   | D  | E  | SG-0021 |
| 13 | 1138 | C | The boiler fuel oil service pump normally takes suction from the _____.  | fuel oil heater discharge                                     | contaminated drain inspection tank  | fuel oil settler tank                          | double bottom fuel tanks                                 |         |
| 13 | 1139 | A | If a severe leak develops in the electro-hydraulic steering gear, which of the listed conditions could result?   | Loss of vessel steering                                       | Overheating of the gyrocompass  | Jamming of the six-way valve                   | Jamming of the follow-up device                          |         |
| 13 | 1141 | D | Which of the following construction methods would apply to the babbitt lined, split-type, reduction gear bearings?   | They are always mounted with the split in a horizontal plane. | They are secured in their housing so pressure points will occur at the joint faces. | They are split into four equal sized segments. | They are rigidly mounted and dowelled in their housings. |         |
| 13 | 1143 | B | A power failure in the hydraulic system of a compact type steering gear would cause the rudder to _____.   | swing 35° right or left                                       | remain locked in its last position  | move to the midship position automatically     | jam against the rudder emergency stops                   |         |
| 13 | 1144 | D | Coast Guard Regulations (46 CFR) require that the final setting of boiler safety valves be conducted in presence of the _____.   | Chief Engineer  | COTP  | OCMI   | Marine Inspector   |         |
| 13 | 1145 | C | If the main condenser were operating at a vacuum of 28.5"Hg, a condensate discharge temperature of 86°F, a seawater inlet temperature of 72°F, and a seawater outlet temperature of 79°F, what would be the condensate depression? | 0.2 inches Hg   | 0.7 inches Hg   | 4 degrees Fahrenheit                           | 7 degrees Fahrenheit                                     | SG-0026 |
| 13 | 1146 | B | Air trapped in the hydraulic fluid of a steering system would be indicated by _____.   | the pump overspeeding   | erratic rudder response   | bubbles in the sight glass                     | ram relief valves lifting                                |         |

|    |      |   |  |  |   |   |  |         |
|----|------|---|--|--|---|---|--|---------|
| 13 | 1147 | C | Results of the flue gas analysis indicate a high percentage of carbon dioxide and a low percentage of carbon monoxide, approaching maximum efficiency. This condition coincides with which area(s) on the graph shown in the illustration? | A  | D   | B and C   | E  | SG-0021 |
| 13 | 1148 | B | Which of the pumps listed takes fuel oil suction from the double bottom tanks and discharges it to the settling tanks?   | Fuel oil service pump                      | Fuel oil transfer pump                                      | Centrifugal type general service pump           | Settler service pump                                     |         |
| 13 | 1149 | D | Air trapped in the hydraulic fluid of a steering system would be indicated by  | an improper rudder response                | hammering noises in the equipment or transmission lines     | popping or sputtering noises                    | all the above  |         |
| 13 | 1150 | A | When air becomes trapped in the hydraulic fluid of a steering system, the  | rudder will respond erratically            | hydraulic ram movement will overspeed                       | sight glass will show bubbles                   | ram relief valves will lift                              |         |
| 13 | 1151 | C | Which of the following conditions is indicated by the necessity of providing excessive gland sealing steam pressure to maintain the normal operating conditions of the main propulsion unit?   | Vacuum leak in the condenser shell.        | Flooded main condenser hotwell.                             | Worn or damaged labyrinth packing.              | Restriction in the gland leak off piping.                |         |
| 13 | 1152 | D | Damaging scale can form on the interior of superheater tubes as a result of  | leaks from the desuperheater               | high superheater outlet temperature                         | insufficient steam flow through the superheater | boiler water carryover                                   |         |
| 13 | 1153 | D | While standing watch in the engine room, irregular feeding or surging of the feedwater supply to a flash evaporator may be attributed to   | erratic water flow through the air eductor | a clogged vent line from the air eductor condenser          | excessive pressure in the seawater feed heater  | a dirty strainer in the saltwater feed pump suction line |         |
| 13 | 1154 | B | Salinity cells are strategically installed in distilling units to indicate the   | quantity of the distillate produced        | quality of the distillate produced                          | presence of leaks in the flash chambers         | all of the above   |         |
| 13 | 1155 | B | While underway on watch, you notice that you need to constantly increase the coil pressure in the high pressure contaminated evaporator to maintain capacity. Which of the following may be the cause?                                     | The brine density is improper.             | The heating transfer surfaces are being layered with scale. | Impure distillate is being produced.            | Shell vapor pressure is constantly decreasing.           |         |

|    |      |   |  |  |  |   |   |         |
|----|------|---|--|--|--|---|---|---------|
| 13 | 1156 | D | If the rated distillate production of a submerged tube type evaporator cannot be maintained with the supplied maximum steam pressure, the evaporator .   | chemical feed must be increased  | has a serious brine leak   | temperature switch is defective   | heating surfaces are scaled   |         |
| 13 | 1157 | A | Results of the flue gas analysis indicate a high percentage of carbon monoxide and an extremely low percentage of carbon dioxide. This condition coincides with which area on the graph shown in the illustration? | A  | B and C  | D   | E   | SG-0021 |
| 13 | 1158 | B | Which of the following statements is true concerning the operation of the solenoid valve in the fuel oil manifold of an automatically fired boiler?  | The valve should secure the fires if the main propulsion turbine overspeeds. | The valve must be manually reset to the open position prior to relighting burners. | The valve will automatically reopen from a low water shutdown once water level is restored. | The valve will automatically close if atomizing steam pressure varies more than 2 psig. |         |
| 13 | 1159 | C | Indicated high salinity of the distillate discharged from a flash-type distilling plant will be a result of .  | operating at reduced vacuum conditions                                       | carrying the brine level below normal  | leaks in the demister baffles   | reduced feedwater heater temperatures   |         |
| 13 | 1160 | C | If a higher than normal water level is observed through the inspection port of a flash evaporator, you should suspect .  | a leak in the feedwater heater   | improper vacuum  | a malfunctioning brine pump   | a clogged desuperheater water strainer  |         |
| 13 | 1161 | C | Which of the following statements about gravity type lube oil systems is correct?  | Any lube oil pump failure causes immediate damage to turbine bearings.       | The discharge from the gravity tanks flows to the lube oil pump suction.           | Gravity tank overflow lines are lead directly to the lube oil sump.                         | Gravity tanks are fitted with an overflow alarm.  |         |
| 13 | 1162 | B | Why are scale deposits on the inside of boiler tubes objectionable?  | Flow of water within the tube is restricted.                                 | Poor heat transfer due to scale deposits overheats tubes.                          | The metal of the tube interior is eaten away by scale.                                      | Hydroxyl ions liberated by the scaling process form acid in the boiler water.           |         |
| 13 | 1163 | C | An excessively high brine level in a flash evaporator can be caused by .   | excessive vacuum in the first effect shell                                   | an excessive brine blowdown rate   | failure of the brine pump   | excessive distillate pump speed   |         |

|    |      |   |  |  |  |  |  |         |
|----|------|---|--|--|--|--|--|---------|
| 13 | 1164 | D | While standing watch in the engine room, if you suspect air leaking into a flash type distilling plant. The most probable cause(s) of the air leak could occur through .   | gasketed joints  | valve stems  | gage glass packing   | all of the above   |         |
| 13 | 1165 | D | While standing watch in the engine room, you notice a high reading at a salinity cell located in the loop seal between two stages of a flash type evaporator. This would indicate .                                  | chill shocking is necessary to remove scale                  | leakage at the second-stage condenser  | faulty operation of the brine overboard pump                       | carryover in the first-stage   |         |
| 13 | 1166 | B | Standing watch in the engine room, a high reading is only indicated at the salinity cell labeled "6" shown in the illustration. This would be the probable result of .   | a minor tube leak in the distillate condenser in section III | a faulty cell at this location   | the compensating temperature is set too low for this cell location | All of the above   | GS-0053 |
| 13 | 1167 | A | While standing watch underway at sea, you notice carryover in a flash type distilling plant. This can be a result of .   | faulty operation of the brine overboard pump                 | a pressure drop through the loop seal  | low first stage vacuum   | low distillate conductivity  |         |
| 13 | 1168 | C | A solenoid valve in the boiler fuel oil supply line will close when the .  | main turbine throttle valve is closed                        | boiler is operating at low pressures   | forced draft fan fails   | fuel oil temperature exceeds 150°F   |         |
| 13 | 1169 | B | While standing watch underway at sea, you notice that the brine level in the second effect of a double effect soloshell evaporator is nearly out the top of the sight glass. Which action should be taken initially? | The feed rate should be increased to the first effect.       | The feed rate should be reduced and the brine discharge valve opened slightly. | The brine overflow weir should be raised to allow greater outflow. | The brine section should be drained down a minimum of 6 inches below the seawater heater bundle. |         |
| 13 | 1170 | C | Prior to relieving the watch you should first check the fireroom status by verifying the boiler water level and .  | prepare to blow tubes  | economizer inlet temperature   | boiler steam pressure  | port and starboard settling tanks  |         |
| 13 | 1171 | D | Which of the following types of packing is commonly used to seal the glands of an auxiliary turbine?   | Flax   | Asbestos   | Rubber   | Carbon   |         |
| 13 | 1172 | B | High temperature at the superheater outlet would NOT be caused by .  | outer casing leakage   | high feedwater temperature   | poor fuel oil atomization  | too much excess air  |         |

|    |      |   |  |   |   |  |  |  |
|----|------|---|--|---|---|--|--|--|
| 13 | 1173 | A | When relieving the watch in the fireroom, you should first check the boiler steam pressure and .   | boiler water level  | prepare to blow tubes   | stack temperature  | port and starboard settling tanks                        |  |
| 13 | 1174 | B | When relieving the watch in the fireroom, you should first check the boiler water level and .  | port and starboard settling tank temperatures   | condition of furnace fires  | steam atomization to the mechanical atomizers                                    | feed pump lube oil level                                 |  |
| 13 | 1175 | D | When relieving the watch in the fireroom, you should first check the fuel pressure to the boiler and .   | port and starboard settling tank levels   | economizer outlet temperature   | empty all oil drip pans  | boiler water level                                       |  |
| 13 | 1176 | B | In a gravity type lube oil service system, with no lube oil appearing in the sight flow glass (bull's eye) while underway, is a positive indication of . | no oil flowing to the bearings  | no oil is overflowing the gravity tank                                | failure of all lube oil pumps  | the gravity tanks being empty                            |  |
| 13 | 1177 | A | Prior to relieving the watch you should first check the fireroom status by verifying the fuel oil pressure to the boilers and .                          | boiler steam pressure   | make up feed tank level   | prepare to blow tubes  | port and starboard settling tanks                        |  |
| 13 | 1178 | C | The fuel oil meter in the fuel oil service system should be bypassed when .  | transferring fuel from storage to settler tank to avoid erroneous fuel consumption readings | conducting programmed routine maintenance of the meter while underway | warming the oil in the burner headers by recirculation prior to boiler light off | finished with engines is given by the bridge             |  |
| 13 | 1179 | D | When relieving the watch in the fireroom, you should first check the boiler water level and .  | the port and starboard settling tank temperatures   | make up feed tank level   | empty all oil drip pans  | the condition of the furnace fires                       |  |
| 13 | 1180 | D | Prior to relieving the watch at sea, you notice black smoke coming from the stack. What would this indicate?   | Insufficient excess air   | Dirty burner  | Soot blowers need to be operated   | All of the above   |  |
| 13 | 1181 | B | When a turbine bearing shows signs of overheating, you should .  | stop the turbine  | immediately reduce speed  | increase the lube oil pump discharge pressure                                    | increase the cooling water supply to the lube oil cooler |  |

|    |      |   |   |                              |                                      |                                 |   |  |
|----|------|---|---|------------------------------|--------------------------------------|---------------------------------|---|--|
| 13 | 1182 | A | Underway on watch in the fireroom, the bridge reports black smoke coming from the stack. This would indicate .  | fuel oil temperature too low | excessive steam atomization pressure | excessive air-fuel turbulence   | All of the above                        |  |
| 13 | 1183 | B | Underway on watch in the fireroom, the bridge reports white smoke coming from the stack. This would indicate .  | high fuel oil viscosity      | excessive excess air                 | low fuel oil temperature        | insufficient steam atomization pressure |  |
| 13 | 1184 | B | When standing watch at sea, steaming full ahead, reducing the boiler forced draft pressure would also have a tendency to correct which discrepancy?     | Low superheat temperature.   | High stack temperature.              | High atomizing steam pressure.  | High DC heater level.                   |  |
| 13 | 1185 | D | While standing watch at sea and steaming full ahead, reducing the boiler forced draft pressure would also have a tendency to correct which discrepancy? | High superheat temperature.  | White smoke from the stack.          | High stack temperature.         | All of the above.                       |  |
| 13 | 1186 | C | The source of metal particles adhering to the magnets in a lube oil strainer is probably from the .   | shaft journal                | bearing shell                        | reduction gears                 | babbitt material                        |  |
| 13 | 1187 | A | When standing watch at sea, steaming full ahead, reducing the boiler forced draft pressure would also have a tendency to correct which discrepancy?     | High superheat temperature.  | Black smoke from the stack.          | Low boiler pressure.            | High fuel oil temperature.              |  |
| 13 | 1188 | C | When standing watch at sea, steaming full ahead, reducing the boiler forced draft pressure would also have a tendency to correct which discrepancy?     | Low fuel oil temperature.    | High desuperheat steam pressure.     | White smoke from the stack.     | Low furnace air pressure.               |  |
| 13 | 1189 | D | When standing watch at sea, steaming full ahead, adding make-up feedwater would also have a tendency to change which of the following parameters?       | Decrease DC heater pressure. | Increase DC heater level.            | Increase condensate depression. | All of the above.                       |  |
| 13 | 1190 | B | When standing watch at sea, steaming full ahead, adding make-up feedwater would also have a tendency to change which of the following parameters?       | Increase DC heater pressure. | Increase DC heater level.            | Increase boiler water level.    | All of the above.                       |  |

|    |      |   |  |   |   |   |   |  |
|----|------|---|--|---|---|---|---|--|
| 13 | 1191 | A | If you are notified that one of the turbine bearings is overheated, which of the following actions should you take as the watch engineer?  | Immediately reduce speed.   | Immediately stop the turbine.   | Increase lube oil pump discharge pressure and check the strainer for metal particles. | Increase cooling water supply to the lube oil cooler.                       |  |
| 13 | 1192 | D | Air leaks through the inner or outer casings of a boiler will _____.   | improve fuel combustion   | decrease stack temperatures   | cause boiler panting  | reduce boiler efficiency  |  |
| 13 | 1193 | A | When standing watch at sea, steaming full ahead, adding large amounts of make-up feedwater would also have a tendency to change which of the following parameters?                                     | Lower DC heater temperature.  | Decrease DC heater level.   | Increase air ejector condenser main condensate outlet temperature.                    | All of the above.   |  |
| 13 | 1194 | A | Coast Guard Regulations (46 CFR) require that new fuel oil service piping between pumps and burners be subjected to _____.   | a hydrostatic test of 1.5 times the maximum allowable pressure but not less than 500 psi (3447 kPa) | a hydrostatic test of 1.25 times the maximum allowable pressure with the relief valves closed | spot radiographic examination of portions of the finished weld joints                 | a hydrostatic leak test to the design pressure specified by the Coast Guard |  |
| 13 | 1195 | C | When standing watch at sea, steaming full ahead, adding make-up feedwater from reserve feed double bottom tanks would also have a tendency to change which of the following parameters?                | Increase DC heater temperature.   | Decrease DC heater level.   | Decrease air ejector condenser main condensate outlet temperature.                    | Increase main condensate discharge temperature.                             |  |
| 13 | 1196 | A | Excessive water in an operating lube oil system can be detected by _____.  | the amount of water discharging from the lube oil purifier  | sounding the lube oil settling tank   | examining the lube oil strainers  | checking oil for unusually low temperature                                  |  |
| 13 | 1197 | C | While underway on watch, you notice that you need to constantly increase the coil pressure in the high pressure contaminated evaporator to maintain capacity. Which of the following may be the cause? | The water level is too high.  | Excessive distillate is being produced.   | The heating coils have excessive scale buildup.                                       | Shell pressure is excessive.  |  |

|    |      |   |  |  |  |  |  |  |
|----|------|---|--|--|--|--|--|--|
| 13 | 1198 | D | Condensate from fuel oil heating coils return to the .   | feedwater heater   | engine room bilge  | reserve feed tank  | drain inspection tank  |  |
| 13 | 1199 | C | Operating a steam turbine propulsion unit at medium speed, in an area with extremely cold seawater, and the main circulating pump providing full cooling water flow to the condenser will result in .  | decreased plant efficiency due to higher attainable vacuum | increased plant efficiency due to increased condensate recirculation | reduced plant efficiency due to excessive condensate depression                        | increased effectiveness of the air ejectors due to the increased main condenser vacuum |  |
| 13 | 1200 | B | To provide emergency feedwater supply to a steaming boiler if it becomes necessary to secure the DC heater, suction should be taken on the distilled water tank using the .                            | emergency injector discharge                               | emergency feed pump  | feed booster pump  | main condensate pump   |  |
| 13 | 1201 | B | The FIRST adverse effect resulting from main bearing wear in an impulse turbine is .   | wear of radial dummy piston packing strips                 | wear of gland seal and diaphragm labyrinth packing                   | loosening of bearing cap bolts   | lower steam exhaust temperatures   |  |
| 13 | 1202 | B | Operating a steam turbine propulsion unit at medium speed, in an area with extremely cold seawater, with the main circulating pump providing full cooling water flow to the condenser will result in . | excellent plant efficiency due to higher attainable vacuum | increased requirements for condensate deaeration                     | increased effectiveness of the air ejectors due to the increased main condenser vacuum | increased plant efficiency due to increased condensate depression                      |  |
| 13 | 1203 | D | All ships with periodically unattended machinery plants shall, in addition to the general alarm required by Coast Guard Regulations (46 CFR), be provided with a/an .                                  | engineer's assistance-needed alarm                         | accommodation space communication system                             | personnel alarm  | all of the above   |  |

|    |      |   |   |  |  |   |   |  |
|----|------|---|---|--|--|---|---|--|
| 13 | 1204 | B | Which of the following statements represents the Coast Guard Regulation regarding a boiler installation in which the superheater outlet temperature exceeds 850°F?                | Safety valves are to be set at 110% of the highest setting of the safety valves on the drum. | Visible and audible alarms indicating excessive superheat shall be provided. | All mountings, fittings, valves, or other superheater attachments must be of malleable cast iron. | A device, actuated by inlet static pressure and designed to function by the bursting of a pressure retaining disk, must be fitted at the outlet of the superheater. |  |
| 13 | 1205 | D | All ships with periodically unattended machinery plants shall, in addition to the general alarm required by Coast Guard Regulations (46 CFR), be provided with a/an .             | accommodation space communication system   | engineer's assistance-needed alarm   | remote vital system alarm   | all of the above  |  |
| 13 | 1206 | C | The entrance of water into the main propulsion lube oil system is undesirable because .   | the flash point of the lube oil is raised to a dangerously high level                        | water causes oil to clog in journal bearings                                 | emulsification occurs with resultant loss of lubricating qualities                                | oil additives break down into amino acids and polyglycerides when in contact with water   |  |
| 13 | 1207 | C | Engineering Control Centers for minimally attended machinery plants shall, in addition to the general alarm required by Coast Guard Regulations (46 CFR), be provided with a/an . | gyrocompass system alarm   | satellite telecommunication s alarm  | personnel alarm   | all of the above  |  |
| 13 | 1208 | B | Why are the condensate drains from the fuel oil heaters and fuel oil tank heating coils returned to the drain inspection tank?  | To allow any oil to be separated from the steam.   | To detect and prevent oil from getting in the boiler water.                  | As a safety precaution to prevent oil leaks from these coils.                                     | As a safety precaution to prevent oil leaks into the bilges.  |  |
| 13 | 1209 | B | Engineering Control Centers for minimally attended machinery plants shall, in addition to the general alarm required by Coast Guard Regulations (46 CFR), be provided with a/an . | satellite telecommunication s alarm  | remote vital system alarm  | gyrocompass system alarm  | all of the above  |  |

|    |      |   |   |   |   |   |   |         |
|----|------|---|---|---|---|---|---|---------|
| 13 | 1210 | D | In accordance with Coast Guard Regulations (46 CFR) for vessels propelled by steam turbines, the navigation bridge primary control system must include safety limit controls for .                                | high boiler water levels  | low boiler water levels   | low steam pressure  | All of the above  |         |
| 13 | 1211 | A | Engineering Control Centers for minimally attended machinery plants shall, in addition to the general alarm required by Coast Guard Regulations (46 CFR), be provided with a/an .                                 | engineer's assistance-needed alarm  | gyrocompass system alarm  | satellite telecommunication s alarm   | all of the above  |         |
| 13 | 1212 | B | In addition to being hazardous to personnel, gas leaks through the boiler casing can also .   | cause overheating of the uptakes  | impair the effectiveness of the air purge cycle                             | cause improper atomization of fuel oil  | impair the operation of the high steam pressure limit switch        |         |
| 13 | 1213 | C | In what classification of turbines are the moving blades and the adjacent fixed rows of blades shaped to act as nozzles?  | Impulse   | Radial flow   | Reaction  | Helical flow  |         |
| 13 | 1214 | A | If the maximum steam generating capacity of a boiler is increased, Coast Guard Regulations (46 CFR) require that the safety valves' .   | relieving capacity be checked   | lifting pressure be increased   | reseating pressure be increased   | blowdown be reduced   |         |
| 13 | 1215 | D | A ship is equipped with the illustrated turbine gear set and a right hand turning propeller. When steam is admitted to the astern element, with sternway on, the high-speed gear on the high pressure side is .   | rotating in the opposite direction as the low-speed pinion on the low pressure side as viewed from the aft end of the reduction gear. | turning clockwise as viewed from the forward end of the reduction gear.     | turning opposite to the rotation of the high-speed gear on the low pressure side. | turning clockwise as viewed from the aft end of the reduction gear. | SE-0016 |
| 13 | 1216 | B | A ship is equipped with the illustrated turbine gear set and a right hand turning propeller. When steam is admitted to the astern element, with sternway on, the high-speed pinion on the high pressure side is . | rotating in the same direction as the low-speed pinion on the low pressure side.  | turning counter clockwise as viewed from the aft end of the reduction gear. | turning the same direction as the high-speed gear on the low pressure side.       | turning the opposite direction as the low speed reduction gear.     | SE-0016 |

|    |      |   |   |   |  |  |   |  |
|----|------|---|---|---|--|--|---|--|
| 13 | 1217 | D | Which condition could cause a low level in the deaerating feedwater tank (DC heater) as the vessel is increasing from maneuvering to sea speed? | Maintaining the water levels of both boilers excessively high                         | Excessive recirculation of main condensate   | Insufficient flow of make-up feed to the condenser   | All of the above  |  |
| 13 | 1218 | B | In a propulsion boiler, diesel oil is generally supplied to the burners when .  | heavy smoking persists  | lighting off a cold ship   | a heavy fuel must be blended   | it is necessary to compensate for overload capacity   |  |
| 13 | 1221 | D | Turbine blade erosion is accelerated by .   | high blade speed  | high moisture content  | high vacuum  | all of the above  |  |
| 13 | 1222 | B | In an oil fired water-tube boiler, inner casing air leaks can cause .   | oxidation of the exposed furnace walls  | chilling of the combustion gases   | excessive feedwater consumption  | localized overheating of tube surfaces  |  |
| 13 | 1224 | C | Which of the Coast Guard publications listed contain the information regarding allowable repairs to boilers installed on cargo vessels?         | Rules and Regulations for Cargo and Miscellaneous Vessels                             | Manufacturer's Instruction Manual  | Marine Engineering Regulations   | Modern Marine Engineer's Manual   |  |
| 13 | 1228 | B | Many steam plants are designed so that diesel oil can be provided to the burners when .   | heavy smoking persists  | lighting off a cold ship   | a heavy fuel must be blended   | overload capacity is required   |  |
| 13 | 1231 | D | Which of the journal bearings listed most easily accommodates the minor turbine shaft misalignment?   | Ball bearings   | Roller bearings  | Spring bearings  | Spherically seated bearings   |  |
| 13 | 1232 | D | Foaming in a lube oil system can cause .  | oil overflow  | loss of cooler effectiveness   | inadequate lubrication   | all of the above  |  |
| 13 | 1234 | C | What is the policy regarding repairs to a cracked superheater header in a power boiler?   | If the reverse side of the weld is inaccessible, complete penetration is unnecessary. | After excavation is completed, and prior to welding, the excavated area shall be examined by spot radiography. | No repairs by welding shall be made, except temporary emergency repairs, without prior approval of the Officer in Charge, Marine Inspection. | Post weld heat treatment of repaired cracks is only required if the pressure part is fabricated of alloy steel. |  |

|    |      |   |  |  |   |   |   |         |
|----|------|---|--|--|---|---|---|---------|
| 13 | 1235 | C | In order to test the lifting pressure of the deaerating feed heater relief valve, you would _____. I. close the auxiliary exhaust dump valves to the main and auxiliary condenser II. increase the set point of the reduced steam pressure to the auxiliary steam system | I only   | II only   | Both I and II   | Neither I nor II  |         |
| 13 | 1237 | A | After starting the main lube oil pump in a gravity-type lube oil system, you should verify that the gravity tanks are full by _____.   | observing the overflow sight glass                       | sounding the gravity tanks                          | sounding the lube oil sump                              | observing the flow from the bearings                            |         |
| 13 | 1238 | C | Boiler fuel oil atomizer parts should be cleaned by soaking in 'tip cleaner' or diesel fuel and _____.   | polished with emery cloth                                | brushed with a steel brush                          | scraped with a nonabrasive tool                         | scraped with a modified table knife                             |         |
| 13 | 1239 | A | A leaking boiler desuperheater may be indicated by a/an _____. I. gradual, but continual rise in phosphate readings in only one boiler II. inability to maintain normal working pressure in the auxiliary steam system   | I only   | II only   | Both I and II   | Neither I nor II  |         |
| 13 | 1240 | C | In a double articulated reduction gear system, the component labeled "2" would be identified as the _____?   | high speed pinion  | low speed pinion                                    | quill shaft   | high speed gear   | SE-0005 |
| 13 | 1241 | A | Which of the following statements concerning the design of balanced throttle valves is correct?  | They use a conventional valve disc and a balance piston. | They use two parallel seats and a balance cylinder. | The valve has a positive opening tendency at all times. | The piston is secured below the valve disc to prevent movement. |         |
| 13 | 1242 | D | Air leaks through the inner or outer casing of a boiler could result in _____.   | high superheater outlet temperature                      | low superheater outlet temperature                  | higher fuel consumption for normal steaming conditions  | all of the above  |         |
| 13 | 1243 | D | In a double articulated reduction gear system, the component labeled "3" would be identified as the _____?   | high speed pinion  | low speed gear                                      | quill shaft   | high speed gear   | SE-0005 |

|    |      |   |  |  |  |   |   |         |
|----|------|---|--|--|--|---|---|---------|
| 13 | 1244 | D | Your vessel has a fractured superheater header. In preparation for conducting the emergency repairs, where could one find information regarding the correct welding procedure and welder qualification to be used? | ASME Welding Qualifications Section IX                 | 46 CFR Parts 50-63 Marine Engineering Regulations                | ABS Rules                               | All of the above                              |         |
| 13 | 1245 | B | In a double articulated reduction gear system, the component labeled "1" would be identified as the _____ ?  | high speed pinion                                      | low speed pinion   | quill shaft                             | high speed gear                               | SE-0005 |
| 13 | 1246 | B | Prior to relieving the watch you should first check the fireroom status by verifying the boiler water level and _____ .  | steam atomization pressure to the mechanical atomizers | fuel pressure to the burners                                     | fuel oil viscosity                      | water drum level                              |         |
| 13 | 1247 | A | When relieving the watch in the fireroom, you should first check the boiler water level and then _____ .   | check the fuel pressure to the burners                 | empty all oil drip pans  | prepare to blow tubes                   | check port and starboard settling tank levels |         |
| 13 | 1248 | B | To properly clean a burner tip, you should use _____ .   | light sand blast grit                                  | a soft metal tool  | a jack knife                            | a wire brush                                  |         |
| 13 | 1249 | D | Prior to relieving the watch you should first check the fireroom status by verifying the fuel oil pressure to the burners and _____ .  | DC heater temperature                                  | prepare to blow tubes  | check port and starboard settling tanks | boiler water level                            |         |
| 13 | 1250 | C | When relieving the watch in the fireroom, you should first check the _____ .   | boiler water drum level                                | boiler steam drum temperature                                    | fuel pressure to the burners            | port and starboard settling tank levels       |         |
| 13 | 1251 | D | Which of the conditions listed would indicate water carryover to a turbine?  | Loss of condenser vacuum.                              | High steam temperature in the high pressure turbine steam chest. | Decreased condensate salinity.          | Noise and vibration in the turbine.           |         |
| 13 | 1252 | C | Desuperheated steam can be found at the _____ .  | main steam stop  | generator steam stop   | spray attemperator outlet               | high pressure turbine steam chest             |         |
| 13 | 1254 | D | According to Coast Guard Regulations (46 CFR), the studs and bolts on marine boiler mountings must be removed for examination at least every _____ .   | 3 years  | 4 years  | 5 years                                 | 10 years                                      |         |

|    |      |   |  |   |  |   |  |  |
|----|------|---|--|---|--|---|--|--|
| 13 | 1261 | B | An unusual vibration in the main propulsion turbine unit, accompanied by a rumbling sound in the reduction gear, could be caused by _____.                   | overloading of the condenser  | a carryover from the boiler                                      | a reduction in condenser vacuum   | a labyrinth seal failure                                       |  |
| 13 | 1262 | B | Spray attemperators are commonly used to _____.  | deerate condensate  | reduce steam temperatures  | cool the intercondenser   | aerate makeup distillate                                       |  |
| 13 | 1264 | D | During each two and one-half year inspection, which test or examination of a cargo vessel water tube boiler is required by Coast Guard Regulations (46 CFR)? | Accumulation test   | Uptakes structural survey  | Hydrostatic test  | Fireside inspection  |  |
| 13 | 1268 | C | To properly remove the burner tip nut from the burner barrel, the barrel should be _____.  | clamped in a machinist's vice on the work bench   | fixed in the burner stowage rack                                 | held by the fixture on the burner cleaning bench  | removed from the gooseneck before removing the tip nut         |  |
| 13 | 1271 | B | The main propulsion turbine can be damaged by _____.   | operating at slow speeds  | water carryover from the boilers                                 | maintaining vacuum too high   | using the jacking gear when there is no vacuum                 |  |
| 13 | 1272 | C | The primary purpose of a control desuperheater installed in the steam drum of a boiler is to _____.  | assure a constant volume of steam flow through the entire superheater under all load conditions | regulate the temperature of superheated steam by adding moisture | regulate the superheater outlet temperature by cooling a portion of the superheated steam | regulate saturated steam temperature through the desuperheater |  |
| 13 | 1278 | C | If oil is observed in the steam drains from a fuel oil heater, you should _____.   | increase the fuel oil pressure to the heater  | shift the drains to the atmospheric drain tank                   | transfer operation to another heater and secure the original heater                       | increase the steam pressure to that heater                     |  |
| 13 | 1281 | A | Moisture erosion in the last stages of the low pressure turbine will result from _____.  | low inlet steam temperature   | excessive gland sealing steam                                    | a leaking astern guardian valve   | All of the above are correct.                                  |  |
| 13 | 1282 | D | The control desuperheater of most boilers functions to control _____.  | superheated steam flow  | desuperheated steam temperature                                  | superheater inlet temperature   | superheated steam temperature                                  |  |
| 13 | 1288 | B | A leaky fuel oil heater relief valve could be indicated by an increase in the _____.   | sludge tank level   | discharge piping temperature                                     | contaminated drain tank level   | fuel oil service pump pressure                                 |  |

|    |      |   |  |  |  |   |   |  |
|----|------|---|--|--|--|---|---|--|
| 13 | 1291 | B | Water entrained in the steam entering a turbine could result in .  | excessive rotor shaft wear   | blade erosion  | turbine overspeed   | fracturing of the carbon packing                  |  |
| 13 | 1292 | C | One function of the desuperheater installed in a boiler steam drum is to .   | raise the temperature of the steam in the dry pipe   | distribute feedwater within the boiler                       | provide steam for auxiliary machinery   | add moisture to superheated steam                 |  |
| 13 | 1294 | B | The MAWP of a boiler is 900 psi and the normal drop across the superheater is 20 psi. If the superheater safety valve is set to lift at 825 psi, what are the minimum settings of the drum safety valves allowed by Coast Guard Regulations (46 CFR)?    | 825 psi  | 850 psi  | 875 psi   | 900 psi   |  |
| 13 | 1296 | D | Which of the following statements defines the term 'axial float' in reference to reduction gears?  | The gears are not subject to excessive tooth loads due to mismatching of the journal bearing halves. | The gears are double-helical and axial thrust is eliminated. | The gears are capable of free motion, neither supporting nor being supported radially by other gears. | The pinion gears are capable of free axial motion |  |
| 13 | 1298 | C | What will occur if the fuel oil heater condensate returns are not opened or are partially plugged?   | Fuel will become overheated.   | Fuel consumption will decrease.                              | Fuel may not be heated sufficiently for proper combustion.  | Fuel pump slippage will result.                   |  |
| 13 | 1299 | A | Main reduction and pinion gears are double helically cut to .  | balance axial thrust and reduce vibration  | decrease reduction gear radial bearing loads                 | increase tooth deflection at high speeds  | decrease the number of teeth in contact           |  |
| 13 | 1301 | C | A common cause of the babbitt linings cracking in a turbine journal bearing is .   | prolonged operation at low speed   | prolonged operation at full speed                            | vibration generated by the rotor  | excessive thrust bearing wear                     |  |
| 13 | 1304 | D | A boiler superheater safety valve is set to lift at 450 psi (3102 kPa). Coast Guard Regulations (46 CFR) require that if there is a pressure drop of 10 psi (69 kPa) across the superheater, the drum safety valve should set to lift at a pressure of . | 450 psi (3102 kPa)   | 455 psi (3137 kPa)   | 460 psi (3171 kPa)  | 465 psi (3206 kPa)                                |  |

|    |      |   |   |   |   |   |  |  |
|----|------|---|---|---|---|---|--|--|
| 13 | 1308 | B | If the fuel oil temperature flowing to the burners is too low, the _____ .  | fuel service pump will lose suction   | boiler will produce heavy black smoke   | boiler will produce dense white smoke   | fuel service strainers will become clogged   |  |
| 13 | 1311 | D | If the main propulsion turbine begins to vibrate severely while you are increasing speed, you should _____ .  | open the throttle wider to pass through the critical speed                                      | hold the turbine at that speed until vibration stops                                      | stop the turbine and not answer any more bells  | immediately slow the turbine to see if the vibration will stop                               |  |
| 13 | 1314 | D | Coast Guard Regulations (46 CFR) require that alarm systems be provided for superheaters whose operating outlet temperature is capable of exceeding _____ . | 550°F (288°C)   | 650°F (343°C)   | 750°F (399°C)   | 850°F (454°C)  |  |
| 13 | 1318 | C | What causes carbon to adhere to the inside surfaces of a fuel oil heater?   | Too much carbon in the fuel   | Deteriorated zinc strips  | Excessive fuel oil temperature  | Vanadium in the fuel   |  |
| 13 | 1321 | A | Vibration in main propulsion turbines could be caused by _____ .  | uneven heating of the rotors  | high pressure steam in the first-stage  | high vacuum in the main condenser   | thrust developed in the turbines   |  |
| 13 | 1322 | A | Desuperheated steam from the control desuperheater is returned to the main superheater to control the outlet temperature by the action of _____ .           | the superheater temperature control valve   | the superheater flow valves   | an orifice in the superheater inlet header  | a diaphragm type pressure controller   |  |
| 13 | 1328 | B | Carbon deposits in a fuel oil heater are caused by _____ .  | low fuel oil temperature  | high fuel oil temperature   | low fuel oil viscosity  | high fuel oil pressure   |  |
| 13 | 1331 | B | Which of the conditions listed is the most common source of torsional vibration in a geared turbine drive?  | Gear excited critical vibrations  | Propeller excited vibrations  | Turbine rotor imbalance   | Changing shaft thrust  |  |
| 13 | 1332 | A | The main function of a desuperheater is to _____ .  | maintain uniform steam flow through the superheater while providing auxiliary steam as required | heat the water in the drum while maintaining sufficient flow through the generating tubes | provide the boiler with additional steam generating surface while providing a sufficient reservoir for surface blow | heat the water in the drum while providing additional steam generating surface in the boiler |  |

|    |      |   |   |  |   |  |  |
|----|------|---|---|--|---|--|--|
| 13 | 1338 | C | Carbonization of the conductive surfaces of a fuel oil heater results in reduced heating capacity because .               | a fluid film layer covers the solid contaminants and increases heat transfer | the relative velocities of the fluids must be decreased causing a corresponding loss of heat transfer | the thermal conductivity of solidified contaminants is poor      | radiational heat transfer becomes severely impaired        |
| 13 | 1341 | B | What should you do if you detect an abnormal vibration in the operating main propulsion turbine?                          | Notify the chief engineer and stand by the throttles.                        | Immediately slow the turbine until the vibration ceases.  | Immediately stop the turbine.                                    | Open the turbine drains until the vibration ceases.        |
| 13 | 1342 | A | One purpose of a desuperheater installed in a boiler steam drum is to .   | protect the superheater from overheating                                     | increase the boiler efficiency  | add moisture to superheated steam                                | remove all superheat from generated steam                  |
| 13 | 1348 | B | The overheating of fuel oil in the fuel oil heaters may result in .   | excessive atomization  | clogged fuel oil heaters  | ineffective straining of the fuel oil                            | low fuel oil service pump discharge pressure               |
| 13 | 1351 | C | The slight wavy appearance of the tips of reduction gear teeth is a result of .   | insufficient lube oil pressure   | high lube oil temperatures  | the method of manufacture and does affect normal operation       | uneven bearing wear due to gross misalignment              |
| 13 | 1352 | C | A boiler fitting used to protect the superheater and to provide reduced temperature steam for use by auxiliaries is the . | reducing station   | feedwater injector  | desuperheater  | dry pipe   |
| 13 | 1358 | A | If the fuel oil temperature in the fuel oil heater attains an excessive temperature, what will happen?                    | Carbon deposits will build up on the heating surfaces.                       | The fuel heater relief valve will open immediately.   | The fuel oil pump will lose suction.                             | The fuel oil recirculating valve will automatically close. |
| 13 | 1361 | D | A pressure drop occurs across both the moving and fixed blades of a reaction turbine as a result of the .                 | reversing blades causing a velocity drop with resultant pressure drop        | conversion of the thermal energy to pressure energy always resulting in a pressure drop               | interstage diaphragms creating a nozzle effect in the steam flow | moving and fixed blades being shaped to act as nozzles     |

|    |      |   |   |   |   |   |   |  |
|----|------|---|---|---|---|---|---|--|
| 13 | 1362 | D | Water-tube boilers having integral uncontrolled superheaters are equipped with internal desuperheaters to .   | lower the temperature of bleed steam in a reheat type plant         | add moisture to superheated steam                                       | lower superheated steam pressure for use in auxiliary machinery   | provide desuperheated steam for auxiliary machinery     |  |
| 13 | 1368 | B | An internal leak in a fuel oil heater can result in .   | water contamination of the fuel oil                                 | oil contamination of the heater drains                                  | carbon buildup in the heater                                      | fluctuating fuel oil pressure                           |  |
| 13 | 1371 | B | The pressure drop existing across the diaphragm of a pressure compounded impulse turbine necessitates .   | installation of a dummy piston and equalizing line to reduce thrust | installation of a diaphragm packing seal to minimize interstage leakage | circumferential dovetailing to secure the rotor blades            | Seal stripping the tips of the turbine blades           |  |
| 13 | 1372 | B | Under steady steaming conditions, the superheater outlet temperature is regulated by the .  | integral superheater  | control desuperheater   | auxiliary desuperheater   | radiant superheater                                     |  |
| 13 | 1378 | B | The contaminated steam system is secured for repairs. Live steam is supplied to the fuel oil heating system and its returns are directed to the drain tank. Considering these circumstances, an undetected leak in an idle fuel oil heater could eventually lead to . | secondary combustion  | boiler tube failures  | low stack gas temperatures  | sputtering burners and possible loss of fires           |  |
| 13 | 1381 | A | The packing ring in an interstage diaphragm of a turbine is prevented from rotating by .  | a horizontal joint key extending into a slot                        | spring tension exerted on retaining rings                               | steam pressure exerted on the packing segments                    | the weight of the diaphragm acting on the packing ring  |  |
| 13 | 1382 | B | Steam leaving the desuperheater is used to .  | operate the ship service turbogenerator                             | operate auxiliary equipment   | supply additional steam for propulsion during overload conditions | provide steam for propulsion during low speed operation |  |
| 13 | 1388 | C | Condensate accumulation in the steam side of a fuel oil heater could result in .  | scale accumulation in an operating heater                           | water contamination of the fuel oil                                     | reduced heating capacity in an operating heater                   | annealing of the heater tube bundles                    |  |

|    |      |   |   |   |   |  |   |         |
|----|------|---|---|---|---|--|---|---------|
| 13 | 1390 | D | While making your rounds, you notice the main lube oil temperature to be higher than normal. To remedy this situation, you should . | speed up the main lube oil pump   | open the lube oil cooler seawater inlet valve wider                         | throttle in on the lube oil cooler seawater discharge valve                                      | increase the opening of the lube oil cooler seawater discharge valve      |         |
| 13 | 1391 | B | Shrouding, with regards to steam turbines, is rolled to the curvature of the blade ends and fitted to the blade .                   | roots   | tenons  | seal strips  | dovetails   |         |
| 13 | 1392 | B | Overheating of the generating tubes will occur when a boiler reaches its end point of .   | evaporation   | circulation   | combustion   | moisture carryover  |         |
| 13 | 1398 | C | Condensate accumulating in the steam side of a fuel oil heater could result in .  | overheating   | scale accumulation  | corrosion  | immediate oil contamination of the condensate                             |         |
| 13 | 1401 | D | Which turbine blade is best suited for high pressure installations?   | Pot-brazed oval shrouded type   | Gaged type  | Wire-lashed type   | Shrouded segmental type   |         |
| 13 | 1402 | A | Reaching which 'end point' will result in the most severe damage to the boiler?   | Circulation   | Carryover   | Combustion   | Atomization   |         |
| 13 | 1411 | C | Which of the following statements is true concerning the turbine shown in the illustration?   | The low pressure turbine is designed with reaction type stages            | The astern element is of the Curtis type consisting of two three-row stages | A steam deflector is provided between the astern element and the ahead stages of the LP turbine. | The ahead rotor can be classified as a helical flow, Parsons type turbine | SE-0016 |
| 13 | 1412 | A | Which of the following statements about boilers is correct?   | A hot boiler will continue to generate steam after the fires are secured. | No boiler will continue to generate steam after the fires are secured.      | The water level in a properly operated boiler will not shrink or swell.                          | Loss of water will not harm a boiler if the water level can be restored.  |         |
| 13 | 1418 | B | The rate of fouling on the oil side of a fuel oil heater is inversely related to the .  | quality of steam flowing through the heater                               | flow rate of fuel oil through the heater                                    | shape of the heating coils in the heater   | pressure on the oil in the heater   |         |

|    |      |   |   |  |  |   |  |         |
|----|------|---|---|--|--|---|--|---------|
| 13 | 1421 | C | During maneuvering, a vessel has just reached full ahead from a dead slow condition. Which of the following actions reflects the first operation of the gland seal regulator shown in the illustration? | Pilot valve bushing would move downward.   | Valve "D" would move upward.                         | Bellows and connecting link would move upward.                                | Needle valve would automatically become seated.                      | SE-0004 |
| 13 | 1422 | A | When increasing the firing rate of a boiler, which of the following should be carried out FIRST?  | Increasing of the forced draft air pressure.                                       | Increasing the fuel pressure.                        | Increasing the feedwater flow.  | Decreasing the steam pressure.                                       |         |
| 13 | 1424 | C | Which of the items listed is required by Coast Guard Regulations (46 CFR) to be stamped on a pressure vessel?   | Hydrostatic test pressure  | Pneumatic test pressure                              | Coast Guard Symbol  | Minimum wall thickness   |         |
| 13 | 1428 | D | Which of the conditions listed would indicate a dirty fuel oil strainer?  | Decreasing fuel oil temperature  | Dirt and sediment deposits in the atomizers          | Decreasing pressure drop across the strainer                                  | Decreasing fuel oil pressure at the burner manifold                  |         |
| 13 | 1431 | D | Guardian valves are installed on main propulsion turbines to  | prevent steam from leaking into the astern element while the vessel is maneuvering | provide an emergency means of quick throttle closing | provide a means to supply steam directly to the astern element of the turbine | prevent steam from leaking into the astern element at full sea speed |         |
| 13 | 1432 | A | To safely increase the firing rate of a boiler, you should always increase the forced draft pressure  | before increasing the fuel pressure  | after increasing the fuel pressure                   | by opening the burner register wider  | by opening additional burner registers                               |         |
| 13 | 1438 | B | If one fuel oil strainer of a duplex unit becomes clogged while the vessel is steaming at sea, the FIRST action should be to  | clean the dirty strainer as quickly as possible                                    | change the oil flow over to the clean side           | stop the fuel oil service pump  | open the strainer bypass valve                                       |         |
| 13 | 1441 | C | In the turbine and gear set shown in the illustration, when going astern, the minimum tolerable clearance between the rotor and intermediate or guide blading is  | .025 inch  | .070 inch  | .090 inch   | .150 inch  | SE-0016 |
| 13 | 1442 | B | To safely decrease the boiler firing rate, you should always reduce the fuel pressure   | after reducing the forced draft pressure   | before reducing the forced draft pressure            | by opening the oil recirculating valve  | by opening the fuel pump relief valve                                |         |

|    |      |   |   |   |   |  |   |         |
|----|------|---|---|---|---|--|---|---------|
| 13 | 1444 | C | According to 46 CFR, which of the following statements is true concerning safety and relief valve escape piping?  | Expansion joints or flexible pipe connections are prohibited.     | The piping shall be led as near vertical as possible to the atmospheric drain tank. | The piping should be supported and installed so that no stress is transmitted to the valve body. | All of the above.   |         |
| 13 | 1448 | C | If you noted a large difference in the pressures indicated by a duplex pressure gage to the fuel oil system strainer, you should .  | increase the fuel pump discharge pressure                         | reduce the firing rate of the boilers   | shift to a clean fuel oil strainer   | secure the fuel oil service pump  |         |
| 13 | 1451 | D | If the gland assembly, shown in the illustration, is located at the forward end of the high pressure turbine, and the vessel is operating at full speed ahead, .  | A slight vacuum would exist at "E"                                | sealing steam would only enter at "F"   | sealing steam would enter at "E" and "F" from the LP turbine                                     | this gland would be self sealing and provide sealing steam to the other glands      | SE-0006 |
| 13 | 1454 | D | In accordance with Coast Guard Regulations (46 CFR), all vessels having oil fired main propulsion boiler(s) must be equipped with .   | at least two fuel service pumps                                   | at least two fuel oil heaters   | a suction and discharge duplex strainer  | all of the above  |         |
| 13 | 1458 | D | If a fuel oil solenoid valve fails to secure the fuel oil supply to the starboard boiler upon loss of the forced draft air supply, you should immediately .   | open the crossover damper manually from the port forced draft fan | reset the starboard forced draft fan circuit breaker on the main switchboard        | stop the fuel oil service pump   | manually close the quick-closing valve in the fuel oil line to the starboard boiler |         |
| 13 | 1461 | C | While maneuvering out of port, you answer a stop bell. You notice a lot of steam coming out of the gland exhaust condenser vent, in addition to the main condenser hotwell level being low. For this condition you should . | decrease gland sealing steam pressure                             | speed up the condensate pump  | manually recirculate condensate and add some makeup feed   | increase steam pressure to the air ejectors   |         |
| 13 | 1464 | B | Coast Guard Regulations (46 CFR) require that quick-closing valves on a fuel oil service system should be installed as close as is practicable to the .   | suction side of the fuel oil pump                                 | boiler front header   | fuel oil settling tanks  | fuel oil service heaters  |         |

|    |      |   |  |   |   |  |  |         |
|----|------|---|--|---|---|--|--|---------|
| 13 | 1471 | B | When securing a main propulsion turbine equipped with carbon packing glands, the vacuum should always be broken before securing gland seal steam because .   | turbine rotor well will expand faster than the casing           | cold air drawn across the carbon packing will damage it         | jacking gear will be unable to be engaged                                  | gland seal leak off lines will fill with water               |         |
| 13 | 1472 | C | When raising steam on a cold boiler under normal conditions, you should always .   | raise steam within one hour or less                             | take 24 hours to raise steam                                    | use a small orifice burner sprayer plate to start                          | use a large orifice burner sprayer plate to start            |         |
| 13 | 1481 | D | With vacuum up and the main propulsion turbine standing by while awaiting engine orders, it is necessary to roll the unit alternately ahead and astern every five minutes to .   | distribute the gland sealing steam evenly throughout the glands | slowly bring the lube oil and bearings to operating temperature | warm the astern guarding valve and the low lube oil pressure throttle trip | reduce the possibility of warping the turbine rotors         |         |
| 13 | 1482 | A | The time taken to raise steam on a cold boiler should always be .  | the time specified by the boiler manufacturer                   | not less than a full 24 hour                                    | not more than 1 full hour  | as short as possible to avoid over expansion                 |         |
| 13 | 1484 | B | Coast Guard Regulations (46 CFR) require that the design pressure of an economizer integral with the boiler and connected to the boiler drum without intervening stop valves shall be at least equal to .  | the feed pump shut off head pressure                            | 110% of the drum safety valves highest set pressure             | 125% of the boiler hydrostatic test pressure                               | 150% of the boiler design test pressure                      |         |
| 13 | 1488 | A | If the boiler fires are extinguished by water entrained in the fuel oil, you should FIRST .  | secure the burner valves  | secure the settler tank suction                                 | reduce the load on the boiler  | purge the boiler furnace                                     |         |
| 13 | 1489 | D | Any abnormal condition or emergency that occurs in the engine room must be reported immediately to the .   | first assistant engineer  | fireman on watch  | Chief engineer   | engineer on watch  |         |
| 13 | 1491 | D | When a reference input signal from the bridge to the engine room takes place, the signal is inverted in the amplifiers and function generators. A negative signal from the amplifier, shown in the illustration, labeled "M", will result in a . | positive signal to the ahead hydraulic actuator pilot motor     | negative signal to the ahead hydraulic actuator pilot motor     | positive signal to the astern hydraulic actuator pilot motor               | negative signal to the astern hydraulic actuator pilot motor | SE-0002 |

|    |      |   |  |  |  |   |  |  |
|----|------|---|--|--|--|---|--|--|
| 13 | 1492 | C | After the steam pressure has risen to about 5 pounds more than the pressure of the boilers already on the line, you can .  | close the air cock   | close the superheater vent   | put the boiler on the line                                      | increase the boiler firing rate                                    |  |
| 13 | 1494 | B | When a boiler economizer is fitted with a valved bypass, Coast Guard Regulations (46 CFR) require which of the following devices to be installed?                      | A sentinel valve is to be fitted to a by-passed economizer.                                | A stopcheck valve is to be located at the economizer outlet.       | A check valve is to be located at the economizer inlet.         | An emergency drain line must be provided to the reserve feed tank. |  |
| 13 | 1498 | B | Water in the fuel supply to a steaming boiler can be detected by .   | observation of the fuel oil heater drains  | sputtering of the fires  | panting of the casing   | dense white smoke being observed in the periscope                  |  |
| 13 | 1501 | B | How many pinion gears are required in an articulated, double reduction gear set for a cross-compounded turbine?  | Two  | Four   | Six   | Eight  |  |
| 13 | 1508 | D | Water emulsified in the fuel oil when supplied to a boiler is indicated by .   | sputtering of the fires  | lower than normal fuel oil pressure                                | excessive white smoke   | all of the above   |  |
| 13 | 1511 | C | Coast Guard Regulations (46 CFR) concerning lubricating oil systems for main propulsion turbines, require .  | the lube oil system to function satisfactorily when the vessel has a permanent list of 25° | lube oil coolers to have three separate means of circulating water | lube oil piping to be independent of other piping systems       | two standby auxiliary lube oil pumps be provided                   |  |
| 13 | 1512 | A | In a regenerative air heater, air is bypassed around the heater while .  | operating at low steaming rates  | blowing tubes  | crossing over forced draft fans                                 | giving a surface blow  |  |
| 13 | 1518 | D | If the fires in a boiler furnace begin sputtering or hissing, you should suspect .   | excessive fuel pressure at the burners   | loss of fuel pump suction  | low fuel oil temperature  | water contamination of the fuel oil                                |  |
| 13 | 1521 | D | Which of the following statements represents the reason why the babbitt of a turbine journal bearing is relieved at the point of oil entry along the horizontal joint? | To prevent oil from backing up in the supply line.   | To permit oil to discharge through the rear of the bearing.        | To prevent hydraulic pressure buildup when the journal rotates. | To permit the rotor journal to draw oil around the shaft.          |  |

|    |      |   |   |   |  |  |   |  |
|----|------|---|---|---|--|--|---|--|
| 13 | 1522 | C | Stack type air heaters are bypassed when a vessel is in port in order to prevent .  | insufficient air supply to the fires due to the pressure drop across the heater | interference with the operation of the soot blowers        | corrosion of the heater due to the low stack temperatures                            | localized heat stressing of air heater surfaces                 |  |
| 13 | 1524 | C | Coast Guard Regulations (46 CFR) concerning superheater safety valves require that the valve be .   | set at a pressure higher than the drum safety valves                            | operated by a pilot valve                                  | set at a pressure not exceeding the design pressure of the superheater outlet flange | set at the design pressure of the turbogenerator steam chest    |  |
| 13 | 1528 | C | When boiler fires begin sputtering, indicating water in the fuel oil settling tank, you should .  | start the alternate fuel oil service pump                                       | shift to the service pump low suction                      | change suction to the alternate settling tank  | reduce the fuel pump operating speed                            |  |
| 13 | 1529 | A | The following information was recorded after a recent L.P. turbine bearing installation. The bearing temperature was logged at the indicated time intervals as:1200-110°F(43°C)1210-123°F(51°C)1220-136°F(58°C)1230-149°F(65°C)1240-153°F(67°C)1250-155°F(68°C)1300-155°F(68°C) The shaft RPM and lube oil cooler outlet temperature remained constant. The readings indicate . | normal temperature during wear in   | water in the lube oil system                               | wiping of the bearing material   | excessive bearing preload conditions                            |  |
| 13 | 1531 | B | In an emergency, an auxiliary turbine can be stopped by .   | closing the exhaust valve slightly  | actuating the throttle hand tripping device                | rotating the hand lube oil pump backwards  | increasing the load on the driven unit                          |  |
| 13 | 1532 | A | One function of the air and flue gas bypass dampers installed in regenerative type air heaters is to .  | avoid excessive cooling of the stack gases during low load operation            | regulate combustion air temperature at normal firing rates | reduce the load on the element drive motor   | reduce the temperature of the double undulated heating elements |  |

|    |      |   |  |   |   |   |   |  |
|----|------|---|--|---|---|---|---|--|
| 13 | 1534 | C | The safety valve nominal size for propulsion boilers and superheaters must be not less than 1 1/2 inches and not more than 4 inches. The term 'nominal size' refers to the . | free spring length  | diameter of the feather   | diameter of the inlet opening   | diameter of the huddling chamber  |  |
| 13 | 1537 | C | Which of the following statements is NOT one of Newton's laws?   | A body at rest tends to remain rest and a body in motion tends to remain in motion. | For every action there is an equal and opposite reaction.   | If the pressure is constant, the volume of an enclosed dry gas varies directly with the absolute temperature. | An imbalance of force on a body tends to produce an acceleration in the direction of that force which is directly proportional to the applied force and inversely proportional to the mass of the body. |  |
| 13 | 1538 | C | When the fires begin to sputter, you should .  | decrease the manifold pressure  | increase the manifold pressure  | take suction from another settling tank   | switch the duplex strainer elements   |  |
| 13 | 1539 | B | A theoretical engine cycle is a process that .   | takes place in the combustor of the engine  | begins with certain conditions, progresses through a series of additional conditions and returns to the original conditions | begins with certain conditions, progresses to a steady state and stays there                                  | None of the above.  |  |

|    |      |   |  |   |  |   |  |  |
|----|------|---|--|---|--|---|--|--|
| 13 | 1540 | A | Boyle's law can best be defined as .   | The volume of an enclosed gas varies inversely with the applied pressure, provided the temperature remains constant | If the pressure is constant, the volume of an enclosed gas varies directly with absolute temperature | A body at rest tends to remain at rest.   | None of the above.                                 |  |
| 13 | 1542 | C | A regenerative type air heater should be bypassed at low load in order to .  | prevent chipping of the ceramic coating   | prevent condensation in the steam baffling   | avoid excessive cooling and condensation of the exhaust gases                             | maintain a positive seal on the replaceable basket |  |
| 13 | 1544 | D | Coast Guard Regulations (46 CFR) for boiler safety valves, require that .  | no valves of any type shall be installed in the leak off from drains or drain headers                               | all safety valve gags or clamps must be carried on board the vessel at all times                     | the final setting of the safety valves shall be checked and adjusted under steam pressure | All of the above are correct.                      |  |
| 13 | 1548 | C | If the fires in both boilers start to sputter, you should immediately .  | shift feed suction to the double bottom   | speed up the fuel oil pump   | shift settlers  | shift to the low suction                           |  |
| 13 | 1551 | A | Rotating flyweights acting against a spring force makes up a simple type of .                                      | governor  | reducing valve   | safety valve  | feedwater regulator                                |  |
| 13 | 1552 | D | Air for combustion is bypassed around the boiler air heater when the .   | soot blowers are operating  | control desuperheater is operating   | combustion control system is in manual  | boiler is steaming at low rates                    |  |
| 13 | 1558 | D | If the fires start sputtering while steaming under steady conditions, which of the actions listed should be taken? | Start the standby fuel oil service pump.  | Increase the fuel oil pressure.  | Shift over to another fuel strainer.  | Shift suction to another settling tank.            |  |
| 13 | 1561 | C | The main throttle valve on a turbine admits steam directly into the .  | nozzle diaphragm  | turbine blades   | steam chest   | crossover connection                               |  |
| 13 | 1562 | B | When a vessel is in port, stack type air heaters are bypassed in order to prevent .                                | insufficient air supply to the fires due to the pressure drop across the heater                                     | corrosion of the heater due to low stack temperatures  | excessive back pressure in the furnace due to low flow rates                              | localized heat stressing of air heater surfaces    |  |

|    |      |   |  |   |  |  |   |  |
|----|------|---|--|---|--|--|---|--|
| 13 | 1564 | C | According to Coast Guard Regulations (46 CFR), which of the following is classified as a boiler mounting?  | Main feed check valve                             | Soot blower element                            | Blowoff valve  | Escape piping drain valve   |  |
| 13 | 1566 | B | A steam vessel is operating at sea and despite troubleshooting the system by all the vessel's engineers, the transfer of fuel to the settler has not been possible and the settler will be empty in a few minutes. As the watch engineer, your NEXT step should be to _____. | activate the "engineer needs assistance" alarm    | line up the diesel cold start system           | warm up the emergency generator  | repeat all the steps that have been taken to determine the cause of the problem         |  |
| 13 | 1567 | B | The downcomer tubes installed in modern watertube boilers would normally be located _____.   | outside of the boiler double casing               | between the inner and outer boiler casings     | inside of the boiler inner casing  | in the furnace gas passages   |  |
| 13 | 1568 | C | Oil in the contaminated drain inspection tank results from _____.  | a defective relief valve on the fuel oil heater   | improper drainage of the fuel oil heater coils | a leaking heating coil in a fuel oil settling tank                               | operating the fuel oil heater at excessive temperatures                                 |  |
| 13 | 1571 | C | If a turbine bearing high temperature alarm sounds, you should immediately _____.  | increase lubricating oil flow                     | increase cooling water flow                    | slow the turbine   | stop the turbine  |  |
| 13 | 1572 | B | Accumulation tests are conducted in order to determine the _____.  | steam generating capacity of an individual boiler | steam relieving capacity of safety valves      | maximum combined oil consumption of all oil burners installed on a single boiler | maximum combined steam generating capacity for all propulsion boilers of a single plant |  |
| 13 | 1574 | C | In accordance with Coast Guard Regulations (46 CFR) all fuel oil service piping in the vicinity of the burners must _____.   | utilize leak proof gaskets in all joints          | have all joints seal welded                    | have wrap around deflectors on all bolted flanged joints                         | be provided with coamings or drip pans  |  |
| 13 | 1577 | B | Steam drains from the potable water system hot water heater would be collected in the _____.   | deaerating feedwater heater                       | contaminated drain inspection tank             | gland exhaust condenser  | first stage heater  |  |
| 13 | 1578 | C | Which of the listed conditions would indicate a dirty atomizer sprayer plate?  | Fluctuating pressure in the windbox.              | Carbon deposits on the register doors.         | Dark streaks in the burner flame.  | Dazzling white incandescent burner flame.   |  |

|    |      |   |  |   |                                  |                                   |  |  |
|----|------|---|--|---|----------------------------------|-----------------------------------|--|--|
| 13 | 1584 | D | Coast Guard Regulations (46 CFR) concerning marine boilers, require the installation of a safety valve on the .  | auxiliary steam outlet                                    | desuperheated steam outlet       | preheated steam outlet            | superheated steam outlet                             |  |
| 13 | 1591 | C | Where three gear trains, i.e. high pressure first reduction, low pressure first reduction, and second reduction are each contained in a separate and sequential portion of the gear housing, the reduction gear unit is known as . | nested  | locked train                     | articulated                       | none of the above                                    |  |
| 13 | 1592 | A | Before blowing tubes in a boiler equipped with steam soot blowers, you should .  | increase the boiler water level                           | decrease the boiler water level  | reduce the forced draft fan speed | lower the boiler steam pressure                      |  |
| 13 | 1598 | A | If the fuel oil service piping was leaking upstream of the quick-closing valve, you should be able to stop the leak by closing the .   | master oil valve  | root valve                       | burner valve                      | recirculating valve                                  |  |
| 13 | 1599 | D | An overheated bearing in the main propulsion unit is indicated by .  | bubbles in the sight flow glasses                         | sludge in the lube oil strainers | high level in the lube oil sump   | high temperature of the lube oil leaving the bearing |  |
| 13 | 1601 | C | Rotating flyweights, acting against a spring force, will provide a simple type of .  | feedwater regulator                                       | safety valve                     | governor                          | reducing valve                                       |  |
| 13 | 1602 | A | Before using the steam soot blowers to blow tubes at sea, you should .   | raise the water level                                     | lower the water level            | increase the firing rate          | decrease the firing rate                             |  |
| 13 | 1604 | D | In accordance with Coast Guard Regulations (46 CFR), which of the following materials may be used in short lengths between the fuel oil boiler front header manifold and the atomizer head to provide flexibility?                 | Copper tubing   | Annealed copper nickel           | Nickel copper                     | All of the above                                     |  |
| 13 | 1608 | C | Which of the conditions listed can cause the flame of a mechanically atomized burner to be blown away from the burner tip when you are attempting to light off?  | Insufficient excess air is being supplied to the furnace. | Fuel oil viscosity is too low.   | The diffuser is burned out.       | The secondary air cone is improperly adjusted.       |  |

|    |      |   |   |   |   |   |   |  |
|----|------|---|---|---|---|---|---|--|
| 13 | 1609 | D | Hot running bearings can be caused by .   | inadequate lube oil supply                                    | contaminated lube oil   | excessive loading   | all of the above  |  |
| 13 | 1611 | A | A constant speed hydraulic governor would more than likely be installed on a .  | turbogenerator  | main propulsion turbine   | main feed pump  | main condensate pump  |  |
| 13 | 1612 | C | In preparing to blow tubes at sea, you should .   | increase the firing rate                                      | decrease the firing rate  | increase the forced draft speed   | decrease the forced draft speed   |  |
| 13 | 1619 | A | Poor atomization accompanied by an elongated flame from a steam atomization burner is MOST likely caused by .                                   | the fuel oil temperature being too low                        | improper operation of traps in atomizing steam return piping  | the forced draft fan too slow for the boiler load   | an improper cetane number   |  |
| 13 | 1621 | B | An excess pressure governor should be used on a .   | main circulator pump  | turbine-driven feed pump  | low pressure propulsion turbine   | forced draft fan  |  |
| 13 | 1622 | B | Boiler forced draft pressure should be increased before blowing tubes to .  | prevent condensation in the uptakes                           | aid in removing loosened soot   | maintain a clear stack  | prevent a drop in steam pressure  |  |
| 13 | 1624 | A | According to Coast Guard Regulations (46 CFR), which of the following is permitted in boiler fuel oil service system discharge piping?          | Screwed bonnet valves of the union bonnet type.               | Pipe unions one inch or greater in diameter.  | Bushings made of seamless steel.  | Street ells made of carbon steel.   |  |
| 13 | 1634 | C | Coast Guard Regulations (46 CFR) for boiler fuel oil service systems require .  | fuel oil heaters for boilers burning fuels with low viscosity | fuel oil service tanks to overhang boilers to utilize heat radiated from the boilers for greater efficiency | machinery driving fuel oil service pumps to be fitted with remote controls so that they may be stopped in the event of a fire | all piping between service pumps and burner fronts to be located below the floor plates to eliminate fire hazards |  |
| 13 | 1638 | A | Fluctuations in the atomizing steam pressure at the burners could be caused by a/an .   | malfunctioning steam trap in the atomizing steam system       | incorrectly assembled air register  | partially closed atomizing fuel valve   | partially opened recirculating valve  |  |
| 13 | 1641 | D | The constant pressure governor of a turbine-driven feed pump maintains which of the following pressures at a constant value for all capacities? | Turbine inlet   | Turbine exhaust   | Pump suction  | Pump discharge  |  |

|    |      |   |  |  |  |   |  |  |
|----|------|---|--|--|--|---|--|--|
| 13 | 1642 | B | After routine blowing of tubes at sea, there should be a decrease in the .   | fuel oil temperature   | stack temperature  | excess air required for complete combustion                                   | CO2 in the stack gas   |  |
| 13 | 1647 | D | A triple element, main propulsion, boiler feedwater regulating system commonly used aboard ship utilizes .   | two-position differential gap action   | proportional action  | proportional plus reset action  | proportional plus reset plus rate action                                   |  |
| 13 | 1648 | A | When slight sputtering is detected at the boiler atomizer, you should .  | check for water in the fuel supply   | increase furnace air supply                                | shut off the oil supply and purge the furnace                                 | close burner register shutters and increase fuel oil service pump speed    |  |
| 13 | 1651 | D | Guardian valves are installed on main propulsion turbines to .   | prevent steam from leaking into the astern element while the vessel is maneuvering | provide an emergency means of quickly closing the throttle | provide a means to supply steam directly to the astern element of the turbine | prevent steam from leaking into the astern element while at full sea speed |  |
| 13 | 1652 | D | Which of the listed operational precautions is necessary before blowing tubes?   | Increase forced draft fan speed.   | Open all drains in soot blower steam supply piping.        | Thoroughly warm all soot blower steam supply piping.                          | All of the above.  |  |
| 13 | 1657 | C | A pneumatic dual element, main propulsion, boiler feedwater regulating system commonly used aboard ship utilizes .   | two-position differential action   | proportional action  | proportional plus reset action  | on off reset action  |  |
| 13 | 1661 | A | In any governor there is a small range of speed in which no corrective action occurs. This speed range is called the governor dead band and is caused by . | friction in the governor linkage and control valve                                 | excessive sensitivity in the governor control valve        | speed droop designed into the governor system                                 | hydraulic slippage in the governor servomotor system                       |  |
| 13 | 1662 | D | Scavenging air is supplied to steam soot blower elements to .  | provide cooling air when soot blower elements are rotating through blowing arcs    | prevent buildup of soot on the element                     | prevent overheating of adjacent tubing  | prevent the backup of combustion gases into soot blower heads              |  |

|    |      |   |  |   |  |   |  |  |
|----|------|---|--|---|--|---|--|--|
| 13 | 1667 | B | A single element boiler feedwater regulating system used aboard ship utilizes _____.   | two position differential gap action  | proportional action  | proportional plus reset action  | proportional plus reset plus rate action                           |  |
| 13 | 1671 | C | Lube oil coolers are necessary in most engine lubricating systems because _____.   | engine oil is used continuously and cooling prevents the oil from wearing out | harmful acids will be condensed and then removed by the centrifuge | cooling increases viscosity and aids in maintaining the oil film strength | cooling decreases viscosity and improves engine thermal efficiency |  |
| 13 | 1672 | D | The arc through which a steam soot blower element blows is regulated by the _____.   | control air pressure  | direction of element rotation                                      | steam supply pressure   | cam profile  |  |
| 13 | 1673 | C | Downcomers are installed between the boiler inner and outer casing to _____. I. increase circulation rates II. decrease the amount of heat that they can absorb from the furnace | I only  | II only  | Both I and II   | Neither I or II  |  |
| 13 | 1674 | B | Downcomers are installed between the inner and outer boiler casings to _____. I. increase the end point of combustion II. increase the end point of circulation                  | I only  | II only  | Both I and II   | Neither I or II  |  |
| 13 | 1675 | D | Downcomers are installed between the inner and outer boiler casings to _____. I. increase the end point of carry over II. decrease the end point of circulation                  | I only  | II only  | Both I and II   | Neither I or II  |  |
| 13 | 1676 | D | Downcomers are installed between the inner and outer boiler casings to _____. I. increase the end point of combustion II. increase the end point of carry over                   | I only  | II only  | Both I and II   | Neither I or II  |  |
| 13 | 1677 | A | As steam first enters the main propulsion turbine, which of the following energy conversions takes place?  | potential to kinetic  | mechanical to thermal  | electrical to thermal   | thermal to electrical  |  |

|    |      |   |   |  |  |  |  |  |
|----|------|---|---|--|--|--|--|--|
| 13 | 1678 | B | In a multi-burner firebox, a burner tip with a worn and enlarged orifice will .   | have no effect on the flow of oil if the proper pressure is maintained     | result in an uneven flow of oil through the burner                 | cause a high fuel oil return line back pressure                          | cause smokeless and flameless combustion                       |  |
| 13 | 1680 | A | When on watch in the engine room, a main turbine bearing high temperature alarm is indicated and remotely displayed as 145 degrees Fahrenheit, you should .                                   | assume, but verify that the circuit has malfunctioned                      | notify the bridge that you will be slowing down the main turbine   | change over to the standby main lube oil supply pump                     | increase the speed of the operating main lube oil supply pump  |  |
| 13 | 1681 | A | Which of the following types of bearings are used for the reduction gears in a marine steam turbine installation?   | Babbitt lined split shell  | Lignum vitae lined precision                                       | Bronze lined cutless   | Sintered bronze bushings                                       |  |
| 13 | 1682 | C | The primary purpose of the boiler internal dry pipe is to .   | prevent priming and foaming in the boiler drum                             | remove all moisture from steam leaving the boiler                  | permit a flow of nearly dry saturated steam                              | prevent foreign materials from entering the steam drum         |  |
| 13 | 1688 | C | Excessive accumulation of carbon deposits on a boiler burner throat ring and diffuser could result in .   | too much excess combustion air   | a reduced boiler fuel oil pressure                                 | a decrease in boiler efficiency  | increased heat transfer and overheating                        |  |
| 13 | 1689 | A | You have just been notified by the watchstander in the engine room, a main turbine bearing high temperature alarm is indicated and remotely displayed as 145 degrees Fahrenheit, you should . | assume, but verify that the circuit has malfunctioned                      | notify the bridge that you will be slowing down the main turbine   | change over to the standby main lube oil supply pump                     | increase the speed of the operating main lube oil supply pump  |  |
| 13 | 1691 | D | To accurately measure the amount of wear on a high speed pinion journal bearing with a bridge gage, you must .  | be sure that the area of greatest wear is at 90° to the measuring pin      | shift the journal to position the pinion off center in the bearing | raise the journal to a height equal to the oil clearance                 | roll the bearing shell until the wearing zone is at the bottom |  |
| 13 | 1692 | B | Which of the following statements represents one operational characteristic of a cyclone steam separator?   | Unit reduces the circulation of the steam and water mixture in the boiler. | Unit imparts a rotational motion to the steam and water mixture.   | Steam is forced to the outer side of the separator by centrifugal force. | Water is forced upward by centrifugal force.                   |  |

|    |      |   |   |   |   |  |  |  |
|----|------|---|---|---|---|--|--|--|
| 13 | 1694 | C | According to Coast Guard Regulations (46 CFR), feedwater nozzles shall be fitted with sleeves, or have other suitable means employed to reduce the effects of temperature differentials on all boilers designed for operating pressures of .  | 250 psig (1825 kPa) or over   | 300 psig (2169 kPa) or over   | 400 psig (2859 kPa) or over  | 600 psig (4238 kPa) or over  |  |
| 13 | 1696 | A | For a gravity type lube oil system, a remote pressure sensing device is installed on the main unit lube oil header to enable the watch engineer to _____. I. determine if there is sufficient lube oil pressure to the main engine II. be certain that the bearings are being adequately lubricated | I only  | II only   | Both I and II  | Neither I nor II   |  |
| 13 | 1698 | C | Carbon deposits on the boiler burner throat ring is usually caused by .   | too much excess combustion air  | a faulty ignition electrode   | a dirty atomizer sprayer plate   | the burner cycling on and off  |  |
| 13 | 1700 | D | Bi-color remote water level indicators, operate on the principle of .   | different refractive properties of steam and water  | increased feed rates at higher steam demand                                     | different chemical properties of steam and water                           | different pressures which result from the comparison of the varying water level in the drum with that of a constant head |  |
| 13 | 1701 | A | As steam first enters the main propulsion turbine, which of the following energy conversions takes place?   | thermal to mechanical   | mechanical to thermal   | electrical to thermal  | thermal to electrical  |  |
| 13 | 1702 | C | Circulation of boiler water to the water wall tubes is maintained by the .  | water screen tubes  | risers  | downcomers   | generating tubes   |  |
| 13 | 1703 | A | Which of the following statements is true regarding lube oil coolers used for main steam propulsion systems?  | Regulating the inlet water flow to a lube oil cooler may result in air binding of the water side. | A lube oil cooler is typically constructed as a cross-flow type heat exchanger. | The coolers may be bypassed when operating in warm sea water temperatures. | The lube oil usually flows thru the tubes and the cooling water around the tubes.  |  |

|    |      |   |   |   |  |  |   |  |
|----|------|---|---|---|--|--|---|--|
| 13 | 1704 | D | Coast Guard Regulations (46 CFR) state that main propulsion water-tube boilers are not required to be fitted with a surface blow off valve if the design pressure is .                              | more than 200 psig (1436 kPa)   | more than 250 psig (1795 kPa)  | more than 300 psig (2169 kPa)  | more than 350 psig (2513 kPa)                                 |  |
| 13 | 1706 | A | Which of the following statements represents the advantage of using a small diameter boiler tube over a larger diameter tube?   | Small diameter tubes have a greater ratio of generating surface area to the volume of contained water | Small diameter tubes reduce the heating surface area.                  | Small diameter tubes are less affected by the insulating properties of soot. | Small diameter tubes provide for greater heat transfer rates. |  |
| 13 | 1707 | A | What is the main constituent in fuel oil which determines its heat value?   | Hydrocarbons  | Oxygen   | Nitrogen   | Sulphur   |  |
| 13 | 1708 | C | Failure of the fuel oil service pump to maintain fuel oil flow to the burner could be caused by .   | a high relief valve setting   | excessive return line oil pressure                                     | dirty fuel oil strainers   | excessive fuel pump speed                                     |  |
| 13 | 1709 | B | A secondary function of burner atomization steam is to .  | maintain a constantly high fuel pressure  | prevent overheating of the atomizer when not firing during maneuvering | maintain a constantly high fuel temperature                                  | vary the viscosity of the fuel oil                            |  |
| 13 | 1710 | A | Air accumulated in the intercondenser of the air ejector assembly is discharged directly to the .   | aftercondenser  | high pressure turbine  | main condenser   | atmosphere  |  |
| 13 | 1711 | D | Precautions to be observed prior to starting a turbine driven cargo pump, should include .  | assuring that the turbine casing drains are wired closed  | observing the operation of the overspeed trip                          | open all governor oil relay drains   | checking the hand tripping device for proper operation        |  |
| 13 | 1712 | C | When preparing to cut a boiler in on the line, you determine that the steam pressure of the incoming boiler is about 5 psig above line pressure. Which of the following steps should you take next? | Open the superheater vent.  | Light off additional burners.  | Open the main steam stop.  | Test the hand relieving gear.                                 |  |

|    |      |   |  |   |  |  |   |         |
|----|------|---|--|---|--|--|---|---------|
| 13 | 1713 | D | Leakage over the ends of the blade tips, as a result of the pressure differential between each row of blades in a reaction turbine, can be reduced by .                                  | thin tipping  | end-tightening   | seal stripping   | All of the above are correct.                               |         |
| 13 | 1714 | C | An energy loss associated with a reaction turbine, but not an impulse turbine, is .  | throttling loss   | windage loss   | tip leakage loss   | leaving loss  |         |
| 13 | 1715 | C | An increase in clearance between reaction blade tips and the turbine casing will result in .   | an increase in rotor thrust load  | an increased pressure drop across the blades                       | steam leakage over the blade tips                            | increased blade erosion                                     |         |
| 13 | 1716 | D | Thin tipping is a type of turbine blade design primarily used to .   | increase the effective blade surface area without increasing blade weight | prevent any pressure drop from occurring through the moving blades | provide a means for mounting the shrouding on the blade tips | reduce losses due to blade tip leakage in reaction turbines |         |
| 13 | 1717 | C | What is used to compensate for the increased possibility of blade vibration occurring with impulse turbine blading?  | The decreased pressure drop across the blade due to the thin tip design.  | Tuned vibration dampers.   | Securing the blade tips with shrouding.                      | Seal stripping the groove within the turbine casing.        |         |
| 13 | 1718 | C | Failure of the fuel oil service pump to maintain fuel oil flow to the burners of the boiler could result from .  | incorrect burner linkage adjustment                                       | carbon deposits on the ignition electrode                          | leaks in the pump suction line                               | excessive fuel return pressure                              |         |
| 13 | 1719 | D | According to the data given in illustration SG-0026, which of the following would be the physical state of the fluid at a gage vacuum of 25.03 inches Hg, and 138.79 degrees Fahrenheit. | Subcooled liquid  | Saturated liquid   | Mixture of saturated liquid and vapor                        | Superheated vapor   | SG-0026 |
| 13 | 1720 | D | According to the data given in illustration SG-0026, which of the following would be the physical state of the fluid at a gage vacuum of 23.81 inches Hg, and 166.30 degrees Fahrenheit. | Subcooled liquid  | Saturated liquid   | Mixture of saturated liquid and vapor                        | Superheated vapor   | SG-0026 |

|    |      |   |  |                    |   |                                       |                                |         |
|----|------|---|--|--------------------|---|---------------------------------------|--------------------------------|---------|
| 13 | 1721 | D | According to the data given in illustration SG-0026, which of the following would be the physical state of the fluid at a gage vacuum of 28.09 inches Hg, and 117.99 degrees Fahrenheit. | Subcooled liquid   | Saturated liquid                                  | Mixture of saturated liquid and vapor | Superheated vapor              | SG-0026 |
| 13 | 1722 | C | Which of the listed tubes provides circulation to the water wall tubes?  | Water screen tubes | Risers  | Downcomers                            | Generating tubes               |         |
| 13 | 1723 | A | According to the data given in illustration SG-0026, which of the following would be the physical state of the fluid at a gage vacuum of 25.03 inches Hg, and 126.08 degrees Fahrenheit. | Subcooled liquid   | Saturated liquid                                  | Mixture of saturated liquid and vapor | Superheated vapor              | SG-0026 |
| 13 | 1724 | A | According to the data given in illustration SG-0026, which of the following would be the physical state of the fluid at a gage vacuum of 23.81 inches Hg, and 126.08 degrees Fahrenheit. | Subcooled liquid   | Saturated liquid                                  | Mixture of saturated liquid and vapor | Superheated vapor              | SG-0026 |
| 13 | 1725 | A | According to the data given in illustration SG-0026, which of the following would be the physical state of the fluid at a gage vacuum of 29.00 inches Hg, and 85.21 degrees Fahrenheit.  | Subcooled liquid   | Saturated liquid                                  | Mixture of saturated liquid and vapor | Superheated vapor              | SG-0026 |
| 13 | 1726 | D | According to the data given in illustration SG-0026, which of the following would be the physical state of the fluid at a gage vacuum of 29.31 inches Hg, and 76.38 degrees Fahrenheit.  | Subcooled liquid   | Saturated liquid                                  | Mixture of saturated liquid and vapor | Superheated vapor              | SG-0026 |
| 13 | 1727 | A | According to the data given in illustration SG-0026, which of the following would be the physical state of the fluid at a gage vacuum of 10.58 inches Hg, and 182.86 degrees Fahrenheit. | Subcooled liquid   | Saturated liquid                                  | Mixture of saturated liquid and vapor | Superheated vapor              | SG-0026 |
| 13 | 1728 | B | If oil is found in the fuel oil heating drain system when using live steam directly to the heating coils, which of the actions listed should be taken?                                   | Secure the boiler. | Shift contaminated drains to proper holding area. | Bottom blow the boiler.               | Shift to low fuel oil suction. |         |

|    |      |   |  |   |   |  |  |  |
|----|------|---|--|---|---|--|--|--|
| 13 | 1729 | A | Which of the following reaction turbine components listed converts thermal energy into kinetic energy.   | Fixed and moving blades   | Fixed blades only   | Moving blades only   | None of the above  |  |
| 13 | 1730 | D | A steam plant is operating at 100% power when the atmospheric drain tank runs dry allowing a large air leakage into the main condenser. Which of the following will occur as a result of this air leakage?   | Decreased condensate temperature                                      | Decreased pressure in the main condenser                                    | Decreased suction pressure at the condensate pump                            | Decreased condenser cooling water outlet temperature               |  |
| 13 | 1732 | C | Why does air entry into the main condenser reduce the efficiency of the steam cycle?   | Steam flow rate through the main turbine increases                    | Condensate subcooling in the main condenser increases                       | Low pressure turbine exhaust steam enthalpy value increases                  | The air mixes with the steam and enters the condensate             |  |
| 13 | 1733 | A | What affect will the emergency plugging of leaking condenser tubes have on the condenser pressure and hotwell temperature when returning to normal steam plant sea speed operation?  | Absolute pressure and hotwell temperature will increase               | Absolute pressure will decrease and hotwell temperature will increase       | Absolute pressure will increase and hotwell temperature will decrease        | Absolute pressure and hotwell temperature will decrease            |  |
| 13 | 1734 | A | Which of the following statements represents the advantage of using a small diameter boiler tube over a larger diameter tube?  | Small diameter tubes result in lower outside tube metal temperatures. | Small diameter tubes reduce the heating surface area.                       | Small diameter tubes are less affected by the insulating properties of soot. | Small diameter tubes provide for greater heat transfer rates.      |  |
| 13 | 1736 | B | Your main propulsion boilers are equipped with a two element feedwater regulating control system. While on watch, you are required to respond to a 'slow' bell from full sea speed. Under these conditions the automatic feedwater regulator will have . | opened the feedwater valve wide due to the effect of shrink           | closed down on the feedwater valve due to the decrease in steam flow demand | partially closed down on the feedwater valve due to the effect of swell      | fully opened the feedwater valve due to the increase in steam flow |  |
| 13 | 1737 | D | The net positive suction head of a boiler centrifugal feed pump should be calculated to include the feedwater vapor pressure and the .   | impeller ratio of the pump  | speed of the impeller   | pump capacity in gpm   | height of the DC heater  |  |
| 13 | 1738 | B | Fuel oil may be discovered in the contaminated drain inspection tank when the .  | steam atomizer leaks  | fuel oil heater leaks   | DC heater leaks  | steam operated fuel oil pump leaks                                 |  |

|    |      |   |  |   |   |   |   |         |
|----|------|---|--|---|---|---|---|---------|
| 13 | 1739 | C | A strong, well defined sound developed by the steam whistle, shown in the illustration, is obtained by adjusting the _____.  | operating lever stroke  | whistle valve travel  | position of the back cover                                | number of diaphragms  | GS-0099 |
| 13 | 1740 | C | Modern day boiler automation allows bypassing the "flame safeguard" system to permit a burner to have a "trial for ignition" period during burner light-off. This period may not exceed _____. | 5 seconds   | 10 seconds  | 15 seconds  | 30 seconds  |         |
| 13 | 1741 | D | A back pressure trip on an auxiliary turbo-generator functions to secure the device if the _____.  | oil pressure is too low   | discharge pressure of a turbine driven pump is excessive        | gland seal leakoff pressure is too high                   | turbine exhaust pressure rises above a preset limit         |         |
| 13 | 1742 | A | The function of downcomers installed in water-tube boilers is to _____.  | accelerate of water circulation   | decrease the end point for moisture carryover                   | distribute feedwater within the drum                      | decrease the rate of steam generation                       |         |
| 13 | 1743 | D | The designed 'end point for combustion' for a boiler furnace is reached when _____.  | the amount of heat being transferred to the tubes reaches a maximum no matter how much the firing rate is increased | panting of the furnace accompanied with black smoke takes place | the maximum rate the boiler can generate steam is reached | the boiler is operating at its maximum fuel oil firing rate |         |
| 13 | 1744 | B | If boiler priming occurs, you should immediately _____.  | increase the steaming rate  | reduce speed and open throttle drains                           | lift the safety valves with the hand easing gear          | open the boiler bottom blow valve                           |         |
| 13 | 1745 | B | The minimum design height of the DC heater is determined by the _____.   | dew point temperature of the stack gases  | minimum net positive suction head required by the main feedpump | maximum condensate pump discharge pressure                | desuperheater outlet temperature                            |         |
| 13 | 1746 | C | While underway at sea, the feedwater inlet temperature to a boiler economizer is determined by the _____.  | dew point temperature of the stack gases  | superheater inlet temperature                                   | temperature of the HP turbine bleed                       | desuperheater outlet temperature                            |         |

|    |      |   |   |  |  |   |   |         |
|----|------|---|---|--|--|---|---|---------|
| 13 | 1747 | C | Which of the listed statements is true concerning the application and use of plastic fireclay furnace refractory?   | The plastic fireclay refractory is especially resistant to slag buildup. | The plastic fireclay must be allowed to be completely air dry to achieve maximum strength. | Vent holes should be punched on approximately two-inch centers to provide for ready escape of trapped vapor during heating. | All of the above.   |         |
| 13 | 1748 | B | A leak in the heating coils of a fuel oil heater will first show up as _____.   | water in the fuel oil supply   | oil in the drain inspection tank   | sputtering and hissing furnace fires  | an intense white furnace flame  |         |
| 13 | 1749 | B | According to U. S. Coast Regulations (46 CFR), water-tube boilers shall be hydrostatically tested on passenger vessels every _____.   | year   | 2 .5 years   | 5 years   | 8 years   |         |
| 13 | 1750 | A | If the gland assembly, shown in the illustration, is located at the forward end of the high pressure turbine, and the vessel is operating at minimum maneuvering speeds, which of the following statements is true? | Sealing steam would enter at "E".  | Sealing steam would enter at "F".  | Sealing steam would enter at "E" and "F".   | This gland would be self sealing and provide sealing steam to the other glands. | SE-0006 |
| 13 | 1751 | A | When a main propulsion turbine throttle malfunction develops, affecting both the main and secondary control stations, you should _____.   | override the automated circuit and manually control the engine           | override the automated circuit and shut down the engine                                    | allow the automatic shutdown circuit to shut down the engine, then locate the problem                                       | immediately make an entry in the engine log                                     |         |
| 13 | 1752 | D | Downcomers installed in water-tube boilers function to _____.   | distribute feedwater within the water drum                               | decrease the end point for moisture carryover  | accelerate the generation of superheated steam  | accelerate water circulation in the boiler                                      |         |
| 13 | 1753 | B | Circulation of water and the steam/water mixture within a natural circulation boiler is retarded by _____.  | large changes in steam density   | fluid friction in the downcomers, drums, generating tubes, and headers                     | high feedwater pressure   | back pressure in the steam drum acting on the user tubes                        |         |

|    |      |   |   |   |   |   |   |         |
|----|------|---|---|---|---|---|---|---------|
| 13 | 1754 | B | A vent line is provided on each water box of the main condenser in order to prevent _____ . I. insufficient head pressure being developed on the circulating pump discharge II. inadequate heat transfer from developing due to air bound tubes | I only  | II only                                       | Both I and II   | Neither I nor II  |         |
| 13 | 1755 | D | Machinery operating features are designed to help conserve energy. Which of the following will not contribute to a systems thermal efficiency?  | Reduction of friction.                                  | Insulation of hot surfaces.                   | Lubrication of moving parts.                                    | Elevation of heat sink temperatures.                          |         |
| 13 | 1756 | C | Coast Guard Regulations (46 CFR) concerning superheater safety valves require that the valve _____ .  | be set at a pressure higher than the drum safety valves | can only be operated by a pilot valve         | nominal size is not less than 1.5 inches nor more than 4 inches | is not set at a pressure less than the feed pump relief valve |         |
| 13 | 1757 | C | Which of the devices listed is used to convert thermal energy into rotor kinetic energy in a reaction turbine?  | Nozzle diaphragms                                       | Labyrinth nozzles                             | Moving blades   | None of the above   |         |
| 13 | 1758 | D | A suspected leak in an operating fuel oil heating coil is normally confirmed by _____ .   | checking the pH of heating coil returns                 | conducting a soap test                        | conducting a blotter spot test                                  | checking the drain inspection tank                            |         |
| 13 | 1759 | C | An increase in clearance between reaction blade tips and the turbine casing will result in _____ .  | an increase in rotor thrust load                        | an increased pressure drop across the blades  | decrease in rotor torque  | increase in rotor vibration                                   |         |
| 13 | 1760 | D | In the illustration of a typical ship service turbogenerator control system, the handle labeled "B" is used to _____ .  | roll over the high speed pinion                         | pump up the lube oil manifold                 | bypass the governor control                                     | reset the overspeed trip                                      | SE-0009 |
| 13 | 1761 | A | In steam turbine and reduction gear units, lube oil coolers installed in the lube oil system are located between the _____ .  | lube oil pumps and gravity tanks                        | gravity tanks and main unit                   | gravity tanks and lube oil sump                                 | lube oil sump and lube oil pumps                              |         |
| 13 | 1762 | D | Downcomers installed in water-tube boilers function to _____ .  | distribute feedwater within the water drum              | decrease the end point for moisture carryover | cool the tubes adjacent to the burner throats                   | ensure proper circulation to the water wall headers           |         |

|    |      |   |  |   |   |   |  |         |
|----|------|---|--|---|---|---|--|---------|
| 13 | 1763 | B | In the illustration of a typical ship service turbogenerator control system, the device that monitors turbine exhaust pressure is labeled _____.   | K   | J   | M   | F  | SE-0009 |
| 13 | 1764 | C | You would not see a flow through the bull's-eye of the lube oil gravity tank overflow line when the _____.   | main engines are stationary at a stop bell                  | main engines are secured and the turning gear is engaged              | the lube oil gravity tanks are being drained    | main engines are turning at normal sea speed |         |
| 13 | 1765 | C | While standing watch, what immediate action should you take if you are running at sea speed and notice a sudden and significant drop in lube oil pressure to the operating main turbine?   | Immediately increase cooling water flow to lube oil cooler. | Slow the turbine to minimum speed and watch the bearing temperatures. | Stop the main shaft using astern steam.         | Shift strainers and gravity tanks.           |         |
| 13 | 1766 | C | If the main condenser were operating at a vacuum of 28.7"Hg, a condensate discharge temperature of 81°F, a seawater inlet temperature of 72°F, and a seawater outlet temperature of 79°F, what would be the condensate depression? | 0.2 inches Hg   | 0.3 inches Hg   | 4.0 degrees Fahrenheit                          | 12 degrees Fahrenheit                        | SG-0026 |
| 13 | 1767 | B | The component labeled "II", as shown in the illustration, is called the _____.   | first reduction gear  | high speed pinion   | second reduction gear                           | second reduction pinion                      | SE-0013 |
| 13 | 1768 | C | A leak in a heating coil in a fuel oil storage tank should be detected quickly by _____.   | an increase in fuel oil temperature                         | observing oil on the contaminated evaporator steam coils              | the presence of fuel oil in the inspection tank | the sputtering of burners in the boilers     |         |
| 13 | 1769 | D | The component shown in the illustration, labeled "III", is the _____.  | first reduction gear  | high speed pinion   | second reduction gear                           | low speed pinion                             | SE-0013 |
| 13 | 1770 | C | The component shown in the illustration, labeled "IV", is the _____.   | first reduction gear  | high speed pinion   | bull gear                                       | low speed pinion                             | SE-0013 |
| 13 | 1771 | C | In a segmental pivoted-shoe thrust bearing, the thrust load among the shoes is equalized by the _____.   | base ring   | oil wedge   | leveling plates                                 | thrust collar                                |         |
| 13 | 1772 | A | Downcomers are used in modern boilers to _____.  | circulate water to the mud drum                             | cool the superheater  | preheat the feedwater                           | remove soot from the firesides               |         |

|    |      |   |  |   |   |  |  |         |
|----|------|---|--|---|---|--|--|---------|
| 13 | 1773 | B | Which type of energy conversion is associated with an operating steam boiler?  | Chemical  | Thermal   | Mechanical   | Specific   |         |
| 13 | 1774 | A | The automatic recirculating valve in the main condensate recirculating line is designed to be controlled by which method?  | Thermostatic control  | Main condenser salt water pressure controller   | Exhaust steam pressure controller  | Preset electric timing device  |         |
| 13 | 1775 | D | The rate of fouling on the oil side of fuel oil heaters is mostly affected by the _____.   | quality of the steam flow through the heater  | shape of the heating coils in the heater  | pressure on the oil in the heater  | rate of oil flow through the heater  |         |
| 13 | 1776 | C | Magnets are installed in the main propulsion turbine lube oil strainers to attract metal particles released through wearing of _____.  | turbine labyrinth   | turbine blades  | reduction gears  | all of the above   |         |
| 13 | 1777 | C | If the main lube oil pump fails to build up discharge pressure, the cause could be the _____.  | bypass valve is closed  | discharge valve is open   | shaft packing gland requires adjustment  | suction pressure is high   |         |
| 13 | 1778 | B | Accumulation of fuel oil in the boiler double casing could be caused by _____.   | leaking fuel oil strainers  | dripping atomizers  | high atomizing steam pressure  | faulty steam atomizer return traps   |         |
| 13 | 1779 | B | One of the functions of a boiler desuperheater installed in a high pressure boiler is to _____. I. maintain the essential flow of feedwater into the drum II. heat the boilerwater in the steam drum | I only  | II only   | Both I and II  | Neither I nor II   |         |
| 13 | 1780 | A | If water hammer develops while opening the valve in a steam line, which of the following actions should be taken?  | Shut the steam valve at once, open the drain valve until all moisture is drained, shut the drain line valve, and slowly open the steam valve again. | Continue to fully open the steam valve and throttle open the drain line valve until all moisture is drained and then shut the drain line valve. | Stop opening the steam valve, open the drain line valve, resume opening the steam valve slowly, and shut the drain line valve after the steam valve is open fully. | Increase the speed of opening the steam valve to rapidly heat the line to stop the water hammer. |         |
| 13 | 1781 | D | Regarding the bearing shown in the illustration, "X" represents the _____.   | template used for bearing offset  | lower bearing half  | upper bearing half   | vacated bearing shell space  | SE-0017 |

|    |      |   |   |  |  |   |  |  |
|----|------|---|---|--|--|---|--|--|
| 13 | 1782 | A | Downcomers are frequently mounted outside the boiler casing on a water-tube boiler for the purpose of .                     | reducing heat in the downcomers and improving water circulation          | improving the cooling of the lower tube banks            | causing suspended solids in the boiler water to settle in the water drums | providing for easy maintenance and repair                        |  |
| 13 | 1783 | D | In a marine boiler equipped with mechanically atomized burner assemblies, proper combustion depends on the .                | fuel oil pressure  | speed of the forced draft fan and quantity of excess air | temperature of the fuel oil   | all of the above   |  |
| 13 | 1784 | B | Discharging an excessive amount of make-up feed water into the DC heater during normal steaming conditions could cause .    | loss of feed pump suction  | decreased auxiliary exhaust pressure                     | water hammer in the economizer  | increased air ejector discharge temperature                      |  |
| 13 | 1785 | D | A boiler feed stop-check valve would be located at the .  | DC heater outlet   | first stage feedwater heater outlet                      | boiler water drum   | economizer discharge   |  |
| 13 | 1786 | C | If a boiler is smoking black and increasing the boiler front air box pressure does not reduce the smoke, the cause can be . | forced draft fan failure   | heavy soot on tubes                                      | low fuel oil temperature  | high air heater temperature                                      |  |
| 13 | 1787 | B | Waterboxes on main condensers are vented to .   | prevent excessive pressure on tube sheets                                | liberate air pockets and reduce waterside oxidation      | provide a minimum condensate level in the hot well                        | prevent vapor binding of the circulating pump                    |  |
| 13 | 1788 | C | Fuel oil accumulation in a boiler double front is caused by .   | leaking fuel oil strainers   | mismatch sprayer plates                                  | dripping atomizers  | insufficient air   |  |
| 13 | 1789 | B | The distance piece in a boiler burner register assembly, provides for adjustment of the .                                   | burner throat opening to attain the desired amount of secondary air flow | diffuser position with relation to the atomizer tip      | fuel oil flame cone angle   | total volume of air admitted through the register                |  |
| 13 | 1790 | C | Fuel oil is transferred to the settling tanks for .   | the purpose of removing any volatile gases present in the fuel           | purging of any large air bubbles that have formed        | heating to allow water and sediment to settle out                         | heating to the correct temperature for proper burner atomization |  |

|    |      |   |   |   |   |  |  |         |
|----|------|---|---|---|---|--|--|---------|
| 13 | 1791 | D | Because of the pressure drop existing across each diaphragm, the flow of steam between the nozzle diaphragm and the rotor of the turbine is held to a minimum by _____. | a fluid seal  | deflector rings   | a babbitt liner  | a labyrinth packing ring                         |         |
| 13 | 1792 | D | The boiler economizer provides additional heat to the _____.  | fuel oil entering the furnace   | air supply entering the furnace                             | steam leaving the superheater  | feedwater entering the boiler                    |         |
| 13 | 1793 | A | If a boiler is being operated with the economizer bypassed, which of the following is true?   | The fuel consumption will increase for the same boiler load.                                  | There is always the danger of burning the economizer tubes. | Less heat is actually being transferred to the superheated steam because of the decrease in feedwater flow | all of the above                                 |         |
| 13 | 1794 | C | Which of the following conditions will occur when a glassy film forms on the furnace wall due to the burning of fuel oil contaminated with salt water?                  | Formation of the protective coating will increase the overall life of the furnace refractory. | The average furnace temperature will increase.              | The slagged sections will eventually peel off the surface of the wall.                                     | Cracks will begin to occur in the furnace floor. |         |
| 13 | 1795 | D | According to the illustration of a typical boiler furnace rear wall, which item number would best represent "insulating block"?   | 1   | 2   | 3  | 7  | SG-0003 |
| 13 | 1796 | A | According to the illustration of a typical boiler furnace rear wall, which item number would best represent "insulating brick"?   | 1   | 2   | 3  | 7  | SG-0003 |
| 13 | 1797 | C | According to the illustration of a typical boiler furnace rear wall, which item number would best represent "standard fire brick"?                                      | 1   | 2   | 3  | 4  | SG-0003 |

|    |      |   |  |   |  |  |  |         |
|----|------|---|--|---|--|--|--|---------|
| 13 | 1798 | A | Carbon deposits on the diffuser and register throat ring of a burner .   | interfere with air flow around the burner               | cause pre-ignition of the atomized fuel            | allow heat loss to the boiler casing                 | are of no consequence and may be left in place until a fireside inspection allows time for removal |         |
| 13 | 1799 | C | According to the illustration, what part number identifies the "diffuser"?   | 1   | 3  | 9  | 7  | SG-0016 |
| 13 | 1800 | B | According to the illustration, what part number identifies the "air doors"?  | 1   | 3  | 9  | 4  | SG-0016 |
| 13 | 1801 | B | Most auxiliary turbines do not require an external source of gland sealing steam because they .                                  | operate at relatively low pressures                     | exhaust to pressures above atmospheric pressure    | utilize carbon packing rings at the low pressure end | operate with only a small amount of axial thrust   |         |
| 13 | 1802 | D | A check valve is located between the economizer and the steam drum to .  | assure a positive feedwater flow through the economizer | assure a positive feedwater flow to the steam drum | prevent the feed pump from becoming vapor bound      | prevent steam and water flow reversal from the drum should an economizer casualty occur            |         |
| 13 | 1803 | D | According to the illustration, what part number identifies the "air door handle"?  | 4   | 6  | 7  | 12   | SG-0016 |
| 13 | 1804 | A | In the illustration of a hydraulically operated turbine gland seal regulator, the gland seal pressure sensing line is labeled .  | G   | C  | D  | A  | SE-0019 |
| 13 | 1805 | D | Serious tube leaks in the air ejector condenser assembly may cause .   | clogged steam strainers                                 | fouled nozzles                                     | an overflow of the drain inspection tank             | an overflow of the atmospheric drain tank  |         |
| 13 | 1806 | B | High pressure steam drains, such as those coming from the main steam line, and throttle block, are generally discharged to the . | contaminated drain tank                                 | main condenser                                     | vent condenser                                       | atmospheric drain tank   |         |

|    |      |   |  |  |  |  |   |  |
|----|------|---|--|--|--|--|---|--|
| 13 | 1807 | A | The purpose of the steam control valves installed in the auxiliary exhaust line is to .  | control steam admission and maintain the proper steam spray pattern in the DC heater | regulate back pressure in the desuperheater line | preheat the condensate before it enters the vent condenser | seal the vent condenser to prevent the escape of condensate |  |
| 13 | 1808 | C | Which of the conditions listed could be responsible for the flame of a mechanical atomizer to blow out when attempting to light off? | The openings in the diffuser are improperly adjusted.                                | The radial air doors are closed.                 | The distance piece is improperly adjusted.                 | The viscosity of the fuel oil is too low.                   |  |
| 13 | 1809 | D | The boiler main feed stop check valve is located nearest the .   | DC heater feedwater outlet   | first stage feedwater heater outlet              | boiler water drum inlet                                    | main feedwater regulator inlet                              |  |
| 13 | 1810 | A | The rate of fouling on the oil side of fuel oil heaters is directly related to the .   | steam pressure in the heater   | shape of the heating coils in the heater         | oil pressure in the heater                                 | rate of oil flow through the heater                         |  |
| 13 | 1811 | C | Which type of bearing lining material is most commonly used in modern precision split type bearings?                                 | Zinc   | Monel  | Babbitt  | Copper  |  |
| 13 | 1812 | A | One factor for determining the minimum feedwater inlet temperature to a boiler economizer is the .                                   | dew point temperature of the stack gases   | superheater inlet temperature                    | temperature of steam bled off the LP turbine               | desuperheater outlet temperature                            |  |
| 13 | 1813 | C | In addition to a orifice plate, a fuel oil atomizer uses which of the listed parts?  | Ignition electrode   | Burner cone                                      | Sprayer plate  | Air cone  |  |
| 13 | 1814 | C | When preparing water-tube boilers for hydrostatic testing, they shall be filled with water at not .                                  | more than 100°F  | less than 80°F                                   | more than 160°F  | less than 100°F   |  |
| 13 | 1815 | C | The most serious fireside burning of the boiler superheater tubes can be indirectly attributed to .                                  | combustion gases impinging on the tubes  | fuel droplets striking the hot tubes             | excessive boiler water carryover                           | the tubes being subjected to excessive vibration            |  |

|    |      |   |  |  |   |  |   |         |
|----|------|---|--|--|---|--|---|---------|
| 13 | 1816 | C | A boiler with a water capacity of 10 tons, generates steam at the rate of 30 tons per hour. If the feedwater concentration of solids was initially 0.5 PPM, and will increase at a rate of 1.5 ppm every hour, what would be the increase in the feedwater concentration of solids after 24 hours? | 12 ppm   | 24 ppm  | 36 ppm   | 48 ppm  |         |
| 13 | 1817 | C | Dissolved oxygen in the condensate can result from _____.  | steam leaks into the gland leakoff   | improper operation of the gland exhauster   | adding make up feed  | vapor lock in the condensate pump   |         |
| 13 | 1818 | C | Which of the following statements is true concerning the burner atomizer shown in the illustration?  | The annular groove imparts the initial swirling motion to the oil.                     | The operating range, or 'turndown ratio', of this type of burner is almost unlimited.   | The bore of the sprayer plate orifice has a standard drill size of "38". | All of the above.   | SG-0022 |
| 13 | 1819 | D | Heating the fuel oil to an excessively high a temperature in a fuel oil heater will cause _____.   | a loss of fuel oil suction   | overfiring the boiler   | leakage at the burners   | fouling of the heater   |         |
| 13 | 1820 | D | In a steam turbine and reduction gear main propulsion plant, the sensor for low turbine oil pressure is usually installed _____.   | at a point on the inlet side of the main bearings as close to the bearings as possible | at a point on the outlet side of the main bearings as close to the bearings as possible | at the outlet of the main thrust bearing                                 | at the end of the supply line header to the bearings                        |         |
| 13 | 1821 | D | Large temperature and pressure drops in the first stage of a combination impulse and reaction turbine are caused by _____.   | two rows of moving blades  | steam passing through a single row of blades more than once                             | using a dummy piston and cylinder to offset axial thrust                 | a velocity-compounded impulse stage at the high pressure end of the turbine |         |
| 13 | 1823 | A | What is the significance of pinion deflection in the operation of reduction gears?   | Pinion deflection causes unequal tooth loading.  | Deflection is minimal because a longer pinion is more rigid                             | Deflection causes excessive wear at the center of the pinion.            | Deflection causes excessive wear at both ends of the pinion                 |         |

|    |      |   |   |  |  |   |  |         |
|----|------|---|---|--|--|---|--|---------|
| 13 | 1824 | C | To comply with Coast Guard Regulations (46 CFR), which type of boiler listed shall be subjected to a hydrostatic test at one and one half times maximum allowable working pressure?                     | All water-tube boilers once a year.                              | All water-tube boilers once every 4 years.   | All water-tube boilers to which extensive repairs have been made.                                     | All fire-tube boilers once every 2 years.  |         |
| 13 | 1831 | A | A sequential lift, nozzle valve control bar utilizes which of the following operating principles?   | A lifting beam mechanism engages valve stems of varying lengths. | A hydraulic piston raises or lowers groups of valves according to pressure received from a governor. | A hydraulic piston raises or lowers individual valves according to pressure received from a governor. | A servomotor, mechanically connected to nozzle valve handwheels, opens or closes the valves in accordance with the type of electrical signal received. |         |
| 13 | 1836 | D | When the boiling temperature of a steam boiler is increased, which of the following effects will occur with relation to the pressure and the specific volume of the steam?                              | The steam pressure and specific volume will remain constant.     | The steam pressure will increase and the specific volume will remain constant.                       | The steam pressure will remain constant and the specific volume will increase.                        | The steam pressure will increase and the specific volume will decrease.  |         |
| 13 | 1837 | B | To insure that boiler water contains sufficient chemicals to transform hard scale forming salts into harmless sludge which would be removed with blowdowns, which type of water test would be required? | alkalinity test  | phosphate test   | chloride test   | hydrozine test   |         |
| 13 | 1838 | B | Valve "H" shown in the illustration, functions to _____.  | regulate the amount of fuel burned                               | provide a quick shut off of fuel to the boiler   | prevent a backflow from the manifold  | recirculate fuel oil during start-up   | SG-0009 |
| 13 | 1839 | B | Which system should be tested and used when required to raise the water level in an idle boiler?  | Chemical feed system   | Auxiliary feed system  | Desuperheated steam system  | Superheated steam system   |         |

|    |      |   |  |   |  |  |   |  |
|----|------|---|--|---|--|--|---|--|
| 13 | 1840 | A | Which of the following represents a significant system limitation to be aware of when a burner management system is operated in the "Manual" mode? | Some boiler safety interlocks are bypassed when the boiler is being fired in "Manual" mode. | The burner is not capable of maintaining a high firing rate when the boiler is in "Manual" mode. | The flame failure alarm cannot function when the boiler is in "Manual" mode.                                     | The burner sequence control is fully automatic even in the "Manual" mode. |  |
| 13 | 1841 | A | What part of the turbine assembly is used to relieve strain on the turbine caused by thermal stress?   | Flexible I-beam supports  | Rigid mountings  | Curved steam lines   | Babbitt lined bearings  |  |
| 13 | 1842 | A | Whenever operating a boiler, whose economizer is bypassed, always keep in mind that _____.   | it is necessary to fire more fuel to maintain the required evaporative rating               | there is always the danger of metal oxidation in the economizer                                  | less heat is actually being transferred to the steam because of the decrease in the ratio of gas to steam weight | all of the above  |  |
| 13 | 1843 | B | The boiler fuel oil service pump normally takes suction from the _____.  | fuel oil heater discharge   | fuel oil settler tank high suction   | fuel oil settler tank low suction  | fuel oil storage tanks  |  |
| 13 | 1845 | B | In a multi-burner firebox, a burner tip with a worn and enlarged orifice will _____.   | have no effect on the flow of oil if the proper pressure is maintained                      | result in an uneven heating of the furnace   | cause a high fuel oil return line back pressure  | cause smokeless and flameless combustion                                  |  |
| 13 | 1846 | D | Which of the listed conditions can cause high superheater outlet steam temperature in an automated boiler?   | High water level in the steam drum.   | Excessive heat transfer in the control desuperheater.  | Insufficient excess air.   | Operating with a bypassed economizer.                                     |  |
| 13 | 1847 | D | If a lube oil pump fails to build up discharge pressure, the cause could be the _____.   | bypass valve is closed  | discharge valve is open  | suction vacuum is high   | shaft packing gland is worn   |  |
| 13 | 1848 | D | When sputtering is detected in the boiler fires indicating water in the fuel, which of the procedures listed should be followed?                   | Start the standby fuel service pump.  | Increase the fuel service pump speed.  | Increase the furnace air supply pressure.  | Shift to the settler high suction.  |  |
| 13 | 1850 | A | Contaminated steam generators in a contaminated drain system are usually _____.  | single effect   | double effect  | triple effect  | multistage flash type   |  |

|    |      |   |   |  |  |   |  |  |
|----|------|---|---|--|--|---|--|--|
| 13 | 1852 | B | When forced draft blowers are provided with high and low speed controls, it is advisable to run the blowers at high speed during maneuvering to . | keep the forced draft discharge dampers open wide  | permit full maneuvering capability without the necessity of changing blower speed  | maintain a constant air/fuel ratio  | ensure that all burners will remain ignited at low load  |  |
| 13 | 1854 | D | Coast Guard Regulations (46 CFR) require unfired pressure vessels with manholes to be hydrostatically tested .                                    | every four years   | every eight years  | at each certification inspection  | at the discretion of the marine inspector  |  |
| 13 | 1858 | C | In the operation of a lube oil clarifier, the position of the oil-water interface should be .   | maintained by the ring dam   | maintained by the number of disks in the disk stack  | nonexistent   | maintained by the diaphragm-type, weir control valve   |  |
| 13 | 1860 | B | The purpose of a contaminated steam system is to .  | distill water from a harbor  | ensure fouled heating coil returns from fuel tanks do not contaminate boiler feedwater   | distill makeup feed for use as potable water  | ensure an uncontaminated source of feed for the makeup evaporator  |  |
| 13 | 1861 | A | Which component of a Kingsbury thrust bearing assembly transmits the thrust from the line shaft to the oil film and shoes?                        | Collar   | Lower leveling plate   | Upper leveling plate  | Base ring  |  |
| 13 | 1862 | A | The purpose of the prerotation vane damper installed in a boiler forced draft blower is to .  | control the air volume to a steaming boiler  | prevent air from entering an idle boiler furnace   | provide a natural draft when the blower is secured  | equalize the forced draft air between steaming boilers   |  |
| 13 | 1864 | D | Which of the following statements is true concerning the inspection of water-tube boilers?  | All mountings shall be opened up and examined by a Coast Guard inspector at eight year intervals after the initial inspection. | All boiler mounting studs or bolts shall be removed for examination by a Coast Guard inspector every 4 years after initial inspection. | Boiler mountings attached to boiler nozzles must be opened and removed for examination every 8 years. | Boiler mountings attached directly to the boiler plating by screwed studs and nuts shall be removed and examined every 10 years. |  |

|    |      |   |   |  |   |   |   |  |
|----|------|---|---|--|---|---|---|--|
| 13 | 1870 | C | A contaminated steam generator is used to produce saturated vapor from collected .  | bilge water  | sanitary water  | fuel oil heating return drains  | condenser cooling water   |  |
| 13 | 1871 | C | Failure to use the turning gear prior to warming up a main turbine will damage the .  | thrust bearings  | gland sealing system  | rotor assembly  | nozzle located in the diaphragm   |  |
| 13 | 1872 | B | What is the advantage of a forced water circulation boiler over a natural circulation boiler?   | The circulating pump need not operate when low pressure steam is required.                           | Boiler tubes are less likely to overheat.   | A steam accumulator is not required.  | All of the above.   |  |
| 13 | 1874 | A | Coast Guard Regulations (46 CFR) require that main steam piping must be hydrostatically tested at specified intervals. If the pipe insulation cannot be removed during this test, the piping shall be tested at . | 1 1/4 times the maximum allowable working pressure and the pressure maintained for 10 minutes        | 1 1/2 times the maximum allowable working pressure and the pressure maintained for 20 minutes | operating pressure and temperature and the pressure maintained for 1 hour   | a pressure and temperature specified by a Coast Guard marine inspector                |  |
| 13 | 1881 | B | Why is a flexible I-beam rigidly mounted at the forward end of the main turbine?  | To relieve stress on the hull.   | Allow for turbine casing expansion and contraction.   | To relieve stress at the light end of the turbine.                          | Prevent the reaction developed within the turbine from being transmitted to the hull. |  |
| 13 | 1882 | B | If a feed pump failure causes the boiler water to drop out of sight in the gage glass, the engineer should FIRST .  | secure the fires, steam stops and then add water   | secure the fires, reduce steam load and start standby feed pump                               | reduce the steaming rate and then cool the boiler with the force draft fan  | reduce the steaming rate and then add water   |  |
| 13 | 1884 | C | Steam piping subject to main boiler pressure must be hydrostatically tested at specified intervals. Therefore, which of the following statements is true?   | The piping must be tested at a pressure and temperature specified by a Coast Guard marine inspector. | The piping must be tested at 1 1/2 times working pressure every 4 years.                      | Piping under 3 inches nominal pipe size need not be hydrostatically tested. | The piping must be tested at 1 1/2 times maximum allowable pressure every 4 years.    |  |

|    |      |   |  |  |   |   |  |         |
|----|------|---|--|--|---|---|--|---------|
| 13 | 1891 | D | When starting a turbogenerator, you must provide lube oil pressure to the governor power piston by means of _____ .  | a line from the other generator  | a line from the gravity tank  | the main lube oil pump  | the hand operated or auxiliary lube oil pump             |         |
| 13 | 1892 | C | Lower than normal steam pressure in an operating boiler may be caused by _____ .   | a sudden drop in superheater outlet temperature  | high feedwater temperature  | a low water level in the steam drum                             | boiler water contamination                               |         |
| 13 | 1902 | B | Which action should be taken if the water level in the gage glass drops out of sight and the burner fails to secure automatically?   | Blowdown the gage glass.   | Trip the master solenoid.   | Increase the feed pump speed.                                   | Repair the feedwater regulator.                          |         |
| 13 | 1904 | B | Coast Guard Regulations (46 CFR) require that boiler mountings shall be removed and studs examined by a Coast Guard inspector _____ .  | every 4 years  | every 10 years  | when the boiler is hydrostatically tested                       | at each inspection for certification                     |         |
| 13 | 1907 | A | The water seal used in a tubular bowl centrifugal purifier is kept in the bowl during normal operation by _____ .  | an inclined port or passage rising from the bowl side towards the center                   | an inclined port or passage rising from the center towards the bowl side          | baffled orifice   | top cover  | GS-0124 |
| 13 | 1911 | B | A hydraulic governing system for a turbogenerator unit maintains constant turbine speed by using a governor flyweight-actuated pilot valve to control oil flow and to directly _____ . | change the position of the turbine throttle valve  | change the position of the governor lever   | vary steam pressure in the steam chest                          | regulate back pressure                                   |         |
| 13 | 1912 | A | The water level in one boiler of a two boiler plant rapidly falls out of sight, which of the following actions should be carried out FIRST?  | Secure the fuel oil to the low water boiler.   | Raise the feed pump pressure.   | Blowdown the gage glass.  | Have the engineer on watch wait for help                 |         |
| 13 | 1917 | D | The rotating speed of the tubular bowl centrifuge is more than twice that of the disk type. The reason for this is _____ .   | a narrow diameter bowl is not effected as much by windage losses as a larger diameter bowl | the friction affecting rotation is not as significant with a narrow diameter bowl | the drag bushing is used to permit the higher speed of rotation | to produce a nearly equal magnitude of centrifugal force |         |
| 13 | 1921 | D | The reversing turbine is normally used for which of the following operations?  | Emergency stopping   | Backing   | Maneuvering   | All of the above.  |         |

|    |      |   |  |  |  |  |  |  |
|----|------|---|--|--|--|--|--|--|
| 13 | 1924 | A | Which of the following statements is true concerning boiler inspections?   | The marine inspector may require any boiler to be drilled to determine its actual thickness any time its safety is in doubt. | At the first inspection for certification after a water-tube boiler has been installed for ten years, it shall be gaged by drilling to determine the actual extent of deterioration. | If the thickness found as a result of gaging is less than original thickness, the boiler must be condemned.                          | Any user of a nondestructive testing device must demonstrate that results with an accuracy of plus or minus one percent are consistently obtainable. |  |
| 13 | 1927 | A | When a lube oil purifier has been cleaned, but a small amount of sludge remains in one spot of the bowl side, the  | seal will be gradually lost after being placed into operation  | through put will be reduced  | temperature of the oil input will have to be lowered   | dirty oil pump discharge pressure will need to be increased  |  |
| 13 | 1931 | B | Which of the devices listed is used to compensate for the expansion and minor misalignments occurring between the main turbines and the reduction gears?                         | Sliding sleeve   | Flexible coupling  | Expansion gear   | Quill shaft  |  |
| 13 | 1934 | A | In accordance with Coast Guard Regulations (46 CFR), which of the following statements is true concerning safety valve construction and/or operation used on propulsion boilers? | Not have threaded inlets for valves larger than 2".  | Gagging a safety valve by means of a set screw through the cap when gags are unavailable is acceptable only when conducting a hydrostatic test.                                      | After the valve is set and adjusted, the tolerance in popping and reseating pressures shall not vary more than plus or minus 1 1/2%. | All of the above.  |  |
| 13 | 1937 | C | The disk stack and tubular shaft used in a lube oil centrifugal purifier, is forced to rotate at bowl speed by   | the use of an acme thread screw  | wire springs   | the locating pin   | the drive pin  |  |
| 13 | 1941 | D | Reduction gears for main propulsion turbines are lubricated by   | grease cups and gravity feed lines   | oil flinger rings mounted on the shaft   | leak off lines from the lube oil cooler  | spray nozzles at the gear meshing points   |  |

|    |      |   |  |                                      |  |  |  |  |
|----|------|---|--|--------------------------------------|--|--|--|--|
| 13 | 1944 | B | If the maximum steam generating capacity of a boiler is increased Coast Guard Regulations (46 CFR) require that the safety valves' .                                   | lifting pressure be increased        | relieving capacity be checked  | reseating pressure be increased  | blowdown be reduced  |  |
| 13 | 1951 | D | Which of the listed parts of a Kingsbury thrust bearing tilts to permit the formation of a wedge shaped film of oil?   | Collar                               | Base ring  | Dowel disk   | Shoes  |  |
| 13 | 1954 | B | Coast Guard Regulations (46 CFR) state that main propulsion water-tube boilers are not required to be fitted with a surface blow off valve if the design pressure is . | 300 psig (2169 kPa) or over          | 350 psig (2413 kPa) or over  | 500 psig (3548 kPa) or over  | 550 psig (3893 kPa) or over  |  |
| 13 | 1957 | B | If the bowl of a centrifugal purifier is improperly reassembled with O-ring seals that have become hard and flat, the centrifuge .                                     | bearings will be permanently damaged | will begin to lose its water seal  | will discharge oil to the main sump as dirty as the input  | bowl will rotate at a lower speed                                    |  |
| 13 | 1961 | D | Why are convergent-divergent nozzles used in high-pressure turbine applications?   | They are easy to manufacture.        | They are less susceptible to steam erosion than other nozzle types due to their shape. | They produce a larger pressure drop and therefore are more efficient than other nozzle types.            | They direct the steam flow more efficiently than other nozzle types. |  |
| 13 | 1967 | D | When water is removed from lube oil passing through a centrifugal purifier, the water removed will .   | be retained in the bowl              | force the diameter of the oil column within the bowl to be narrowed                    | displace water from the heavy phase discharge port, but of an amount less than that removed from the oil | displace an equal amount of water from the bowl seal                 |  |
| 13 | 1971 | D | Which of the parts listed for a reaction turbine serve the same function as the nozzles of an impulse turbine?   | Fixed nozzles                        | Moving nozzles   | Moving blades only   | Fixed blades and moving blades                                       |  |

|    |      |   |  |  |   |   |  |
|----|------|---|--|--|---|---|--|
| 13 | 1981 | C | Which of the following statements would best describe the purpose of operating the hand lube oil pump on an auxiliary turbo-generating unit? | It supplements the main lube oil pump flow while paralleling the generators.     | It empties the governor control reserve prior to shutting down.                       | It assists in opening the governor control valve while starting the unit.   | It permits the changeover of lube oil filters.   |
| 13 | 1987 | B | Which of the following statements is true concerning the centrifuging of lubricating oil?  | Centrifuging is more effective with inhibited oils than straight mineral oils.   | Centrifuging is more efficient when the oil is preheated prior to centrifuging.       | Silicones are water soluble and easily removed by centrifuging.   | Centrifuging will purge the oil of various contaminants, including acids and alkalis.                        |
| 13 | 1991 | D | In addition to the direction of steam flow, which of the descriptions listed may also be used to classify turbines?                          | The method in which the steam causes the turbine rotor to rotate.                | The type of staging and compounding of steam pressures and velocities.                | The division of the steam flow.   | All of the above   |
| 13 | 2001 | C | Which of the following statements describes how the main propulsion turbine overspeed relay initiates closing of the throttle valve?         | Excessive centrifugal force causes a spring loaded weight to trip a valve latch. | Excessive centrifugal force causes spring loaded flyballs to actuate a control lever. | Excessive speed causes an oil pump to develop sufficient pressure to open a spring loaded relay valve which tends to close the steam control valve. | Excessive speed causes an increase in lube oil control temperature which actuates a solenoid oil dump valve. |
| 13 | 2002 | C | If the engineer on watch has reason to doubt the accuracy of the water level shown in the boiler gage glass, he should                       | speed up the main feed pump  | open the auxiliary feed line  | blowdown the gage glass   | start the standby feed pump  |
| 13 | 2011 | B | In the operation of a main propulsion turbine, using bar-lift throttle valve control, the successive opening of the valves                   | admits more steam to the steam chest   | increases the steam flow to the HP turbine first stage                                | increases the pressure of steam in the steam chest  | bypasses the flow of steam directly to the later turbine stages  |
| 13 | 2014 | C | According to Coast Guard Regulations (46 CFR), what is the minimum flash point of oil to be used as fuel for the boilers?                    | 80°F (26.7°C)  | 110°F (43.3°C)  | 140°F (60.0°C)  | 150°F (65.6°C)   |

|    |      |   |  |  |   |   |  |  |
|----|------|---|--|--|---|---|--|--|
| 13 | 2017 | B | In a disk type centrifugal purifier, the contaminated oil enters the centrifuge .  | at the bottom through the oil inlet  | at the top through the regulating tube  | through the neck of the top disk  | through the funnel body  |  |
| 13 | 2021 | B | Which of the descriptions listed applies to a Rateau stage?  | One set of nozzles and two rows of moving blades.                                  | One set of nozzles and one row of moving blades.  | Two sets of nozzles and two rows of moving blades.  | Two sets of nozzles and one row of moving blades.  |  |
| 13 | 2022 | C | One boiler of a two boiler plant has ruptured a tube and the water cannot be maintained in sight in the gage glass. After securing the fires, your next action should be to .          | secure the forced draft fans   | stop the fuel oil service pump  | secure the feedwater supply to the boiler   | close the main steam stop  |  |
| 13 | 2024 | A | 46 CFR Parts 59 and 35 require that .  | the OCMI be notified of emergency repairs to boilers and unfired pressure vessels  | the fuel burned in boilers of tankships shall have a flash point of not less than 130°F | a one pint sample of each load of fuel be drawn and sealed at the time of supply and preserved until that fuel is exhausted | all of the above   |  |
| 13 | 2031 | B | Which of the following methods is used to lubricate main propulsion turbine reduction gears?   | The gears run through an open oil sump and oil is carried along on the gear teeth. | Oil is sprayed through nozzles at the point of gear mesh.                               | Oil is pressure fed through internal drilled passages which force oil to the gear's periphery.                              | Oil rings in channels outside the gears dip into oil in the sump and carry it to the gear teeth. |  |
| 13 | 2032 | C | If a tube failure results from low water level and you cannot maintain water in sight in the gage glass, you should .  | immediately secure the forced draft fans   | increase the feed pump speed to maximum   | immediately secure the fuel oil supply to the burners   | blowdown the gage glass to verify a low water condition  |  |
| 13 | 2034 | C | Should one boiler on a two boiler vessel suffer serious tube damage, the Officer-in-Charge, Marine Inspection may issue a permit (Form CG-948) to proceed to another port for repair . | only if the vessel's Certificate of Inspection is valid and has not expired        | as long as no cargo or passengers are being carried                                     | only upon written application of the master, owner, or agent of the vessel  | all of the above   |  |

|    |      |   |   |   |   |   |   |
|----|------|---|---|---|---|---|---|
| 13 | 2041 | C | Which of the following enables a Kingsbury, or any pivot shoe type thrust bearing, to bear a much greater load per square inch of working surface than parallel surface bearings? | The thickness of the filler piece behind the pivotal-shoes is adjusted to obtain a more accurate fit. | Clearances are automatically adjusted to the correct value when wear occurs.        | The shoes tilt slightly thereby allowing the formation of a wedge shaped oil film under a thrust load.  | The shoes pivot, thus remaining parallel with the collar when thrust loads are applied.                           |
| 13 | 2042 | A | Which of the following actions should be carried out if the boiler water level is falling due to a tube failure?  | Secure the fires and try to maintain the water level.   | Speed up the feed pump to keep the water level up while firing the boiler.          | Open the auxiliary feed stop and check for extra feed.  | Start the standby feed pump and feed the boiler using two feedpumps.  |
| 13 | 2044 | B | According to Coast Guard Regulations (46 CFR) a 'oil fuel unit' is correctly described by which of the following statements?  | The amount of heat released by burning a 'unit' amount of fuel oil.                                   | Equipment used for the preparation of fuel oil for delivery to an oil fired boiler. | The amount of thermal units required to raise the temperature to the flash point in an open cup tester. | The amount of thermal units necessary to cause a liquefied flammable gas to exceed a certain Reid vapor pressure. |
| 13 | 2049 | B | The maximum temperature rise of oil passing through any reduction gear set, or bearing, should not exceed _____.  | 30°F (16.7°C)   | 50°F (27.8°C)   | 70°F (38.9°C)   | 90°F (44.5°C)   |
| 13 | 2051 | B | During a maintenance inspection of a turbogenerator, the integral turbine wheels are tapped with a hammer. What condition may be indicated by a dull, non resonating sound?       | Normal structural solidity  | A cracked turbine wheel   | Overstressed blade shrouding  | Improper rotor support  |
| 13 | 2061 | D | Which of the following designs is an essential feature of the Rateau type turbine?  | A large pressure and temperature drop occurring in the first stage.                                   | The use of alternate rows of fixed and moving blades.                               | The use of a velocity-compounded impulse stage installed at the high pressure end of the turbine.       | Two or more simple impulse stages aligned in tandem in one casing.  |

|    |      |   |   |   |  |   |   |
|----|------|---|---|---|--|---|---|
| 13 | 2062 | B | The fireman/watertender secures the fires because there is no visible water level in the gage glasses of a steaming boiler. Upon inspection, you observe condensate trickling down the inside of the gage glass. This indicates . | high water level  | low water level  | priming   | steam binding of the feedwater regulating valve sensing line from the top of the steam drum |
| 13 | 2071 | A | A turbogenerator back pressure trip can be actuated as a result of .  | insufficient circulating water flow through the condenser                   | a steam inlet valve being partially open   | an excessive pressure drop through the turbine  | excessively low exhaust pressure  |
| 13 | 2091 | A | A pilot valve and servomotor are utilized in mechanical-hydraulic governing systems in order to .   | provide sufficient force to operate large steam control valves              | provide a means of operational hunting   | attain 100% of regulation with zero speed droop   | All of the above are incorrect.   |
| 13 | 2092 | C | After the main engine has reached full sea speed, which of the following conditions could cause the water level in the boiler steam drum to keep falling?   | Open cutout valves on the boiler gage glasses.                              | Condensate recirculating line is excessively open.   | Feed pump discharge pressure is set too low.  | Feed pump recirculating valve is closed.  |
| 13 | 2101 | D | Which of the following statements represents the significance of the differential pressure existing between the nozzle block and steam chest of a turbogenerator equipped with a lifting beam mechanism?                          | The pressure differential necessitates the use of a special balance piston. | The pressure differential eliminates the possibility of valve binding in the lifting beam. | The pressure differential requires the installation of a special biasing spring to open the valves. | The pressure differential assists in seating the valves when the lifting beam is lowered.   |
| 13 | 2121 | B | Fine metallic particles, which may originate from wear or failure of the lube oil service pump internal parts, are prevented from contaminating the bearings served by the lube oil system by .                                   | the settling action of solid matter in the gravity tank                     | use of the magnetic strainers in the lube oil service pump discharge piping                | the change of direction and settling action within the lube oil coolers                             | batch centrifuging the lube oil at least once a week  |
| 13 | 2131 | C | In a double reduction gear, the function of a quill shaft is to provide flexibility between the second reduction pinion and the .   | bull gear   | second reduction gear  | first reduction gear  | first reduction pinion  |

|    |      |   |   |  |  |   |  |  |
|----|------|---|---|--|--|---|--|--|
| 13 | 2141 | A | One of the most effective methods of improving purification in tubular and disk type centrifugal purifiers is to .  | decrease the viscosity of the oil by heating | increase the pressure at which the oil is fed through the purifier | match the discharge ring size outside diameter with the lube oil's specific gravity | use the smallest inside diameter of the discharge ring size without a loss of oil with the discharge water |  |
| 13 | 2142 | C | The internal feed pipe of a power boiler distributes the feed water into the .  | mud drum                                     | water drum   | steam drum  | economizer   |  |
| 13 | 2150 | B | While making engine room rounds at sea, you observe excessive steam leaking from the forward gland on the high pressure turbine. This may indicate that the . | turbine is operating at low speed            | gland seal leakoff line is obstructed                              | main condenser vacuum is too high   | drains were left open  |  |
| 13 | 2151 | C | Which of the following is used to hold the poppet valves closed in the turbine nozzle control valves?   | Lifting beam                                 | Springs  | Steam pressure  | Oil pressure   |  |
| 13 | 2152 | A | Which of the devices listed is used to convert thermal energy to useful mechanical work?  | Turbine                                      | Condenser  | Air ejector   | Each of the above  |  |
| 13 | 2161 | A | When starting a turbine driven boiler feed pump with the recirculating valve open, which of the following valves should be closed?                            | Pump discharge valve                         | Pump suction valve   | Turbine steam supply valve  | Turbine exhaust valve  |  |
| 13 | 2171 | A | Which of the turbines listed is part of a cross-compound system and when operating receives steam that has passed through another turbine?                    | Low pressure turbine                         | High pressure turbine  | Back pressure turbine   | Astern turbine   |  |
| 13 | 2172 | C | The greatest heat loss in an oil fired boiler is from .   | blowdown                                     | radiation in the furnace casing                                    | uncontrolled escape of combustion gases up the stack                                | incomplete combustion  |  |

|    |      |   |   |  |   |   |  |  |
|----|------|---|---|--|---|---|--|--|
| 13 | 2175 | B | The three-wing device used in the tubular bowl purifier, is held in place and forced to rotate at bowl speed by the . | vertical shallow grooves machined into the bowl surface      | flexible wire springs secured to the edge of each 'wing'          | locating pin pressed into the top edge of the three-wing device                   | drive pin pressed into the interior surface of the bowl                                  |  |
| 13 | 2181 | D | The overspeed tripping device installed on an auxiliary turbine is automatically actuated by .                        | pneumatic force  | hydraulic pressure  | high back pressure  | centrifugal force  |  |
| 13 | 2183 | C | A centrifugal oil purifier should be shut down if the .   | presence of oil is indicated in the gravity tank bull's-eye  | observation cover clamp needs tightening                          | purifier is vibrating badly   | trapped water is discharged from the overflow line                                       |  |
| 13 | 2188 | B | If one fuel strainer of a duplex strainer unit becomes clogged while your vessel is underway, you should first .      | secure the engine immediately                                | change the oil flow over to the clean side                        | stop the fuel oil pump  | open the strainer bypass valve   |  |
| 13 | 2191 | C | The valve opening sequence for bar-lift nozzle control valves in a marine steam turbine is determined by .            | the turbine idle speed                                       | pilot valves which initiate movement of each individual valve bar | the distance between the top of the bar and the adjusting nuts on the valve stems | electro-hydraulic servomotors attached to individual valve stems                         |  |
| 13 | 2192 | D | The proper way to quickly reduce high water level in a steaming boiler is to use the .                                | bottom blow valve  | safety valve  | water column valve  | surface blow valve   |  |
| 13 | 2201 | C | Axial thrust developed in a reaction turbine is the result of a steam pressure drop in .                              | the nozzles  | the stationary blades   | the moving blades   | both the moving and stationary blades  |  |
| 13 | 2211 | A | What type of strainer is used in a turbine lube oil system to remove metallic particles?                              | Magnetic basket strainer                                     | Simplex filter  | Metal edge strainer   | Fuller's earth filter  |  |
| 13 | 2221 | D | The function of a quill shaft used on a double reduction gear main propulsion unit is to .                            | allow for gross radial misalignment of the high-speed pinion | reduce backlash in the reduction gear                             | allow for flexibility between the high-speed pinion and first reduction gear      | allow for axial flexibility between the first reduction gear and second reduction pinion |  |

|    |      |   |  |   |   |   |   |  |
|----|------|---|--|---|---|---|---|--|
| 13 | 2231 | C | Why do double flow reaction turbines produce very little axial thrust?   | Because there is never any axial thrust developed.              | Because partially expanded steam is exhausted to another low pressure turbine where the expansion is completed. | Because the axial thrust is developed at each end in opposite directions to counterbalance each other.                                  | Because equalizing holes are provided in the turbine wheels.          |  |
| 13 | 2241 | A | The labyrinth seals used on rotating steam turbine shafts reduces external leakage by causing _____.   | successive pressure drops through the seal stages               | successive temperature drops through the seal stages  | pressure increases through successive seal stages   | increased turbulence through successively larger labyrinth clearances |  |
| 13 | 2251 | D | Why are geared turbine installations equipped with turning mechanisms?   | For jacking the main engine over periodically when secured.     | For turning the main engine during routine inspections.   | For turning the main engine during warm-up and securing operations.   | For all of the above purposes.  |  |
| 13 | 2252 | C | According to 46 CFR Part 56, which of the following statements is true concerning the main steam stop valves on multiple boiler installations incorporating uncontrolled superheaters? | When only one valve is used, it must be of the stop-check type. | The resistance to closing increases as the cross-sectional area of the valve seat opening decreases.            | A six inch main steam stop must be fitted with a bypass for heating of the line and equalizing the pressure before the valve is opened. | All of the above.   |  |
| 13 | 2261 | B | To prevent damage to the turning gear mechanism, which of the following procedures must be carried out before the turning gear is engaged?   | The brake on the first reduction worm shaft must be set.        | The propeller shaft must be stopped and held stationary until the clutch is engaged.                            | The engine order telegraph must be on 'stop'.   | The speed of the astern turbine must be reduced.                      |  |

|    |      |   |  |  |   |   |  |         |
|----|------|---|--|--|---|---|--|---------|
| 13 | 2271 | B | If two turbo-generators with the same no-load speed settings are operating in parallel, the unit whose governor has the lesser speed droop will .                                      | assume the smaller share of the load                 | assume the larger share of the load                   | have poor sensitivity characteristics                               | have poor power response                               |         |
| 13 | 2272 | C | Water circulates within a natural circulation boiler as a result of the .  | difference in the tube length and diameter           | angle of tube inclination                             | differences in density within the circulating medium                | difference between the heights of the boiler drums     |         |
| 13 | 2281 | C | The turning gear mechanism of a geared turbine installation is designed to turn the main engine at a rate of speed that is .   | approximately equal to their normal operating speeds | approximately equal to their maximum operating speeds | very slow in relation to their normal operating speeds              | very fast in relation to their normal operating speeds |         |
| 13 | 2291 | B | Which of the devices listed is used to engage the main engine turning gear to the high pressure turbine high-speed pinion?   | Manually operated band brake                         | Manually operated jaw clutch                          | Sleeve coupling   | Quill shaft  |         |
| 13 | 2301 | B | Main steam turbine lubricating oil systems are fitted with .   | floating strainers                                   | magnetic strainers                                    | centrifugal strainers   | cestus strainers                                       |         |
| 13 | 2302 | C | Water circulates in a natural circulation boiler due to the .  | difference in tube length and diameter               | angle of inclination                                  | difference in density between the water and the steam/water mixture | difference between the heights of the boiler drums     |         |
| 13 | 2311 | A | Flexible couplings used in modern turbine reduction gear installations would include .   | gear type  | grid type   | nonmetallic star type   | labyrinth type   |         |
| 13 | 2321 | A | In which type of turbine does the steam pass through reversing chambers machined on the inner surface of the casing, causing the steam to be redirected back to the turbine wheel rim? | Helical flow turbine                                 | Axial flow turbine                                    | Combination axial and radial flow turbine                           | Cross compound flow turbine                            |         |
| 13 | 2331 | B | As indicated in the graph, what percentage of rated horsepower is being used to operate the main propulsion turbine at 30% speed?  | 1%   | 4%  | 10%   | 40%  | SE-0018 |

|    |      |   |  |                                    |                             |                                   |   |         |
|----|------|---|--|------------------------------------|-----------------------------|-----------------------------------|---|---------|
| 13 | 2332 | C | The proportion of downcomers installed in relation to riser tubes in a vertical tube type of boiler, is dependent upon the _____.  | degree of superheat                | type of water level control | steam output of the boiler        | position of the mud drum                              |         |
| 13 | 2341 | B | A steam driven 750 KW turbogenerator has a rated speed of 1200 RPM. The overspeed setting for this unit must have a maximum limit of _____.  | 1320 RPM                           | 1380 RPM                    | 1440 RPM                          | 1500 RPM  |         |
| 13 | 2351 | B | If the main propulsion turbine speed percentage is increase from 30% to 60%, what percentage of horsepower is required when the new speed is attained as shown in the illustrated graph? | 10%                                | 20%                         | 30%                               | 40%   | SE-0018 |
| 13 | 2352 | D | Which of the following precautions should be taken prior to lighting off a boiler?   | Secure the main steam line drains. | Close the air register.     | Bottom blow the mud drum.         | Purge the furnace of combustibile gases.              |         |
| 13 | 2361 | D | Inefficient operation or a faulty condition of turbine components will be indicated by an abnormal variation of which condition?   | Speed                              | Vibration                   | Lubricating oil temperature       | All of the above conditions are individually correct. |         |
| 13 | 2371 | A | The safety device provided on a turbogenerator which closes the throttle automatically when exhaust pressure reaches a preset maximum is called a/an _____.                              | back pressure trip                 | low pressure trip           | emergency hand trip               | overspeed trip  |         |
| 13 | 2381 | C | Constant speed governors are normally employed with _____.   | cruising turbines                  | high pressure turbines      | turbogenerator units              | variable speed turbines                               |         |
| 13 | 2391 | B | The steady frequency required from a ship service generator for electrical power is maintained by means of a _____.  | throttle control mechanism         | constant speed governor     | speed limited governor            | cam operated nozzle control valve                     |         |
| 13 | 2401 | A | On main turbine propulsion units, flexible couplings are used between the _____.   | rotor shaft and pinion shaft       | rotor shaft and quill shaft | quill shaft and high speed pinion | second reduction and the shaft thrust bearing         |         |

|    |      |   |   |  |  |  |  |         |
|----|------|---|---|--|--|--|--|---------|
| 13 | 2402 | D | The primary purpose of screen tubes installed in a marine boiler is to .  | act as internal downcomers                   | protect the furnace casing and retain furnace heat | protect the generating tube bank from the convectional heat transfer | protect the superheater from radiation heat transfer |         |
| 13 | 2411 | C | Regarding the governor shown in the illustration, what would occur as the result of a speed increase by a ship's service turbogenerator?                          | The governor weights will move inward.       | The lifting beam is raised.                        | The pilot valve bushing is lowered.                                  | Oil is pumped into the operating cylinder.           | SE-0009 |
| 13 | 2412 | B | Which of the following problems can occur when an excessive number of water screen tubes are plugged?   | Superheater outlet pressure will rise.       | Superheater outlet temperature will rise.          | Steam pressure leaving the drum will increase.                       | Steam temperature in the drum will decrease.         |         |
| 13 | 2421 | C | Which of the listed actions will occur when there is an increase in load on a ship service generator equipped with a centrifugal type hydraulic governor?         | The governor weights move outward.           | The operating piston is forced to move lower.      | More oil will enter the operating cylinder (O).                      | Steam flow to the turbine decreases.                 | SE-0009 |
| 13 | 2431 | C | The adjustable spherically seated self-aligning bearing housings used in main turbines are provided with oil deflector rings. The function of these rings is to . | ensure efficient lubrication of the bearing  | prevent the leakage of main steam into the oil     | prevent the external leakage of oil out of the bearing housing       | direct the flow of oil through the bearing           |         |
| 13 | 2432 | C | Which of the listed components is used to protect the boiler superheater against the radiant heat of the furnace?   | Superheater support tubes                    | Control desuperheater                              | Screen tubes   | Generating tubes                                     |         |
| 13 | 2441 | B | In the reduction gearing for a typical ship service turbogenerator, the oil pump and governor drive gear are mounted on the turbine end of the .                  | high speed pinion shaft                      | reduction gear wheel shaft                         | medium speed generator shaft   | low speed turbine shaft                              | SE-0009 |
| 13 | 2451 | C | In a modern main propulsion turbine installations, lube oil system strainers are usually located in the .   | bearing supply line                          | gravity tank overflow line                         | pump suction line  | gravity tank discharge line                          |         |
| 13 | 2461 | B | In steam turbine main engine installations, how are the main reduction gear bearings identical to other radial bearings?  | They are of the single casting type bearing. | They are babbitt-lined bearings.                   | They are self-aligning bearings.                                     | They are spherical seated bearings.                  |         |

|    |      |   |   |   |   |  |  |         |
|----|------|---|---|---|---|--|--|---------|
| 13 | 2469 | C | Using a dry uncoated sounding rod or tape to measure the depth of water in a reserve feed water tank will .   | always be 100% accurate                           | thoroughly contaminate the feed water                     | be very inaccurate                                 | be satisfactory if a small amount of oil is floating on the surface      |         |
| 13 | 2471 | A | Which of the following types of bearings are used as line shaft bearings?   | Ring-oiled, babbitt-faced, spherical seat, shell  | tapered roller, split type radial                         | Segmental, pivoted-shoe thrust                     | Rigidly mounted, radial sleeve   |         |
| 13 | 2481 | C | Which of the devices listed are used to rigidly mount reduction gear bearings in their housings?  | Keyways and keys                                  | Spherical housings  | Dowels or locking screws                           | Notched construction   |         |
| 13 | 2491 | C | The most likely result of water slugging in the steam supply to a ship service turbogenerator is .  | excessive shaft seal wear                         | contamination of the lube oil                             | damage to the turbine blades                       | rapid erosion of labyrinth packing                                       |         |
| 13 | 2492 | C | Which of the conditions listed occurs when glassy slag, formed by the burning of fuel oil contaminated with salt water, melts and runs over the furnace wall?                           | Formation of a protective coating.                | Increased furnace temperature.                            | Damage to the furnace refractory.                  | Cracks through the furnace floor.  |         |
| 13 | 2501 | D | The splits located in the halves of main reduction gear bearings are aligned at an angle to the horizontal in order to resist .   | oil loss  | steam loss  | axial stress                                       | wiping   |         |
| 13 | 2506 | B | To properly sound a reserve feed water tank, you should use a/an .  | innage sounding tape                              | chalk coated calibrated metal rod                         | manila line with an attached weight                | fuel oil settler ullage tape   |         |
| 13 | 2511 | B | A motor driven synchronizing device, figure "D" shown in the illustration, operated from the generator switchboard, initiates fine adjustments to the steam turbine speed by directly . | raising or lowering the nozzle block lifting beam | changing the vertical location of the pilot valve bushing | increasing or decreasing operating spring pressure | varying the pivot rod stroke length on the governor weight eccentric pad | SE-0009 |

|    |      |   |   |   |   |   |   |
|----|------|---|---|---|---|---|---|
| 13 | 2520 | A | Which possible condition has occurred if a vacuum is present at the atmospheric drain tank vent while the vessel is underway?                             | The control valve regulating flow to the main condenser is stuck in an open position.                 | The control valve ball float has been holed causing the ball to remain in a lowered position.                                       | There is a definite possibility of the tank overflowing causing loss of distilled water.  | There will be an increase of vacuum in the main condenser within a short period of time.                                    |
| 13 | 2521 | C | The transfer of the heat produced by friction in the bearings to the lube oil is assisted through the use of _____.                                       | rollers   | monel linings   | babbitt linings   | a dowel   |
| 13 | 2530 | D | The level of the drain inspection tank continually decreases after steam is admitted to a double bottom tank fuel oil heating coil. You can expect _____. | proper heating of the fluid   | higher than normal temperatures   | a leaking makeup feed regulator   | a perforated heating coil   |
| 13 | 2531 | C | Which of the following statements describes the function of a ship's propulsion plant main reduction gear thrust bearing?                                 | Support the weight of the reduction gears.  | Absorb the transmitted power when radial thrust is developed.   | Absorb the axial thrust transmitted through the shaft from the propeller.   | To absorb only the thrust developed by the high pressure turbine.   |
| 13 | 2541 | A | Turbine lube oil suction strainer baskets have _____.   | course perforations   | fine perforations   | frame lined with wire cloth   | self-cleaning design  |
| 13 | 2551 | C | Which of the following operational practices is helpful in avoiding the accumulation of condensate in the main reduction gear casing?                     | Always ensure that the lubricating oil pressure is 14-17 psi when operating in unusually cold waters. | The temperature of the lubricating oil should not exceed the manufacturer's recommendation when the unit is operating at full load. | After the main unit is secured, lubricating oil should be circulated until the temperature of the oil and reduction gear casing approximates the engine room temperature. | Avoid applying gland sealing steam to the low pressure turbine until you are ready to start up the first-stage air ejector. |

|    |      |   |   |   |   |   |   |         |
|----|------|---|---|---|---|---|---|---------|
| 13 | 2561 | A | Which of the bearings listed is used in some turbines to limit axial movement?  | Pivoted-shoe type thrust bearing  | Self-adjusting, spherically-seated, self-aligning bearing | Journal bearing   | Cylindrical bearing   |         |
| 13 | 2571 | D | The Kingsbury bearing is equipped with pivoted shoes in order to _____.   | absorb radial stress  | compensate for shaft misalignments                        | keep the sleeve from turning  | maintain a wedge-shaped oil film  |         |
| 13 | 2581 | D | Which of the listed parts illustrated in the turbogenerator governing system, provides the follow-up to prevent the nozzle valves from cycling between the fully open and fully closed positions, with each variation in turbine speed? | D   | O   | H   | E   | SE-0009 |
| 13 | 2591 | D | Which of the features listed, regarding the Kingsbury thrust bearing, prevents the base ring from turning and secures it to its housing?  | Pin   | Dowel   | A combination of pin and dowel  | Keyed construction  |         |
| 13 | 2601 | D | In a reduction gear train, a quill shaft of high torsional flexibility provides _____.  | self-adjustment of the pinion gear shaft  | rigidity between the elements of the gear train           | efficient distribution of oil to the various elements of the gear train | equal distribution of the load among the various elements of the gear train |         |
| 13 | 2602 | C | The steam drum in a D-type marine boiler _____.   | maintains circulation by forcing steam bubbles downward in the generating tubes | supports the superheater tube bank                        | provides a space for moisture to separate from the steam                | acts as a receptacle for heavy suspended solids in boiler feedwater         |         |
| 13 | 2611 | B | Which of the flexible coupling types listed is used in most turbine reduction gear installations?   | Friction clutch   | Gear  | Bend  | Flange  |         |
| 13 | 2612 | B | When two or more boilers provide steam flow to a common main steam line, each boiler main steam line shall be fitted with a main steam stop valve and a/an _____.   | auxiliary steam stop valve  | stop-check valve  | swing check valve   | gate valve  |         |

|    |      |   |   |                                   |  |   |  |  |
|----|------|---|---|-----------------------------------|--|---|--|--|
| 13 | 2621 | B | Which of the following factors determines the type of construction used for gear hubs in shipboard reduction gear units?            | Size of the gear wheel            | Type of reduction gear unit                                  | Type of ship using installation   | Type of steam turbine installation                         |  |
| 13 | 2622 | B | Which of the conditions listed could cause steam formation in the economizer?   | Excessive water flow rates.       | Sudden large increase in the firing rate.                    | Soot buildup on the gill rings.   | An open main feed pump recirculating line.                 |  |
| 13 | 2631 | D | In which of the following lube oil lines should you expect to find an illuminated sight glass (bull's-eye)?                         | Lube oil pump suction             | Lube oil pump discharge                                      | Gravity tank discharge  | Gravity tank overflow                                      |  |
| 13 | 2632 | A | The phenomenon called 'shrink' causes an apparent drop in the water level of a steaming boiler. This phenomenon is caused by a/an . | collapse of steam bubbles         | excessive formation of steam bubbles                         | sudden decrease in steam pressure   | rapid increase in feed rate                                |  |
| 13 | 2641 | A | Fresh water accumulating in the reduction gear sump may be directly attributed to a/an .  | inefficient gland sealing system  | faulty turbine casing drain valve                            | lube oil cooler tube leak   | fractured main condenser support sheet                     |  |
| 13 | 2642 | D | Before using a boiler compressed air soot blower system, you should .   | reduce the boiler pressure        | lower the water level  | decrease the forced draft fan speed                                       | drain the soot blower pneumatic operating lines            |  |
| 13 | 2651 | C | The pinion gears used in main propulsion reduction gear mechanisms are generally constructed of .                                   | aluminum                          | bronze   | forged steel  | cast steel   |  |
| 13 | 2652 | A | Which of the listed conditions causes shrinkage in boiler water levels?   | Collapse of steam bubbles         | Excessive steam bubbles                                      | Sudden increase in feedwater temperature                                  | Sudden decrease of drum pressure                           |  |
| 13 | 2661 | B | In main propulsion systems, which metal is used in the construction of the shafts for a main reduction gear unit?                   | Aluminum-bronze                   | Forged steel   | Aluminum  | Cast steel   |  |
| 13 | 2662 | C | The effects of shrink and swell on boiler water levels can be minimized by .  | providing a constant surface blow | rapidly opening and closing the throttles during maneuvering | avoiding rapid opening and closing of the throttles while answering bells | installing an automatic single-element feedwater regulator |  |

|    |      |   |   |  |   |   |  |  |
|----|------|---|---|--|---|---|--|--|
| 13 | 2671 | B | Why are the gear teeth of large reduction gears usually cut in a temperature controlled room?   | To prevent stress buildup.   | To prevent ambient conditions from affecting the tolerances of the machining process. | To control the size of the journals.  | To control cutting machine vibration.  |  |
| 13 | 2672 | C | The superheater vents should always be open when _____.   | blowing down the boiler  | using the steam soot blowers  | lighting off or securing the boiler   | the water level is lower than normal   |  |
| 13 | 2681 | D | Which of the following statements defines the term 'axial float' in reference to reduction gears?   | The gears are not subject to excessive tooth loads due to mismatching of the journal bearing halves. | The gears are double-helical and axial thrust is eliminated.                          | The gears are capable of free motion, neither supporting nor being supported radially by other gears. | The gears are capable of free motion, neither supporting nor being supported axially by other gears. |  |
| 13 | 2682 | B | The scavenging air for soot blowers is supplied by the _____.   | low pressure air compressor  | forced draft blowers  | control air regulator   | all of the above   |  |
| 13 | 2691 | B | Which of the following represents one of the designed functions of reduction gears?   | Change rotary motion into linear motion.   | Combine multiple speed inputs into a single low speed output.                         | To amplify low speed to high speed.   | Utilize a single engine input and convert to multiple propeller output.                              |  |
| 13 | 2701 | D | When securing the main engine, which of the listed procedures should be carried out to remove or reduce condensation from the interior of the main reduction gear casing? | Circulate oil until oil and gear casing have reached ambient temperatures.                           | Continue to operate the lube oil purifier until there is no water discharge.          | Continue to operate the lube oil cooler and rotate the engine with the turning gear.                  | All of the above.  |  |
| 13 | 2711 | D | In a gravity lube oil system, a sight glass is installed in a line near the operating platform. This line connects the _____.   | bottom of the gravity tank and the lube oil headers  | bottom of the gravity tank and the sump   | gravity tank overflow and the lube oil headers  | gravity tank overflow and the sump   |  |

|    |      |   |  |   |   |   |   |
|----|------|---|--|---|---|---|---|
| 13 | 2721 | C | A Kingsbury, or pivot shoe type thrust bearing, can bear much greater loads per square inch of working surface than can parallel surface bearings because provisions are made in the Kingsbury bearing . | for adjusting the filler piece thickness behind the pivotal-shoes to give a more accurate fit | for automatically adjusting clearances to the correct value when wear occurs              | for the shoes to tilt slightly, thereby allowing the formation of a wedge shaped oil film under a thrust load | to allow the leveling plates to pivot on the collar when thrust loads are applied                       |
| 13 | 2731 | D | If saltwater leaks into and contaminates the main lubricating oil system, which of the following remedial actions should be taken?   | Locate the leak and seal it off when time permits.  | Disengage the jacking gear and allow contaminated oil to cool to engine room temperature. | Run the engines at idle and prevent the circulation of contaminated oil.                                      | Seal off the leak and promptly remove and replace all contaminated oil from the system.                 |
| 13 | 2741 | D | Which of the following statements represents the principle of operation of the Kingsbury type thrust bearing?  | A flat film of oil is more readily formed and maintained than a wedge shaped oil film.        | A flat film of oil can carry heavier loads than a wedge shaped oil film.                  | A wedge shaped film of oil absorbs less heat than a flat oil film.  | A wedge shaped film of oil is more readily formed and maintained than a flat oil film.                  |
| 13 | 2751 | B | Which of the following statements represents the function of the center groove machined on a double-helical gear?  | It allows the gears slight axial movement without gear damage.                                | It allows a path for oil to escape regardless of the direction of rotation.               | It prevents excessive axial thrust loads from developing on the teeth.  | It is used to distribute oil to the gear teeth.   |
| 13 | 2752 | B | As the rate of combustion is increased in a boiler, more steam is generated because the _____ .  | fires are hotter  | weight rate of hot gas flow increases   | furnace becomes hotter  | flue gas turbulence decreases   |
| 13 | 2761 | A | By which of the following means can rotating parts of the main reduction gear be examined?   | Inspection covers   | Bull's eyes or sight glasses  | RT junction boxes   | Tachometer drives   |
| 13 | 2762 | D | When raising steam on a boiler, the superheater drains should _____ .  | be opened to remove condensate, and then closed when the first burner is lit                  | be closed until just before line pressure is reached, and then given a short blow period  | be closed until after the air cock is closed, and then opened until the boiler is placed on line              | remain open or partially open until steam blows through the lines, and then the valves should be closed |

|    |      |   |  |   |  |  |   |  |
|----|------|---|--|---|--|--|---|--|
| 13 | 2771 | C | The maintenance of reduction gear units is principally concerned with attention to keeping the .   | reduction ratio constant between the speed of the turbine and the speed of the driven element | upper half of the gear casing secured to the lower half                            | gears supplied with clean oil at the proper operating pressure and temperature | drive gears aligned with drive shaft                        |  |
| 13 | 2772 | D | After steam has been raised and a boiler is being placed on the line, the superheater vent can be closed when .  | main and auxiliary steam line drains are opened   | the boiler steam stops have been warmed up   | boiler pressure is 5 psi above line pressure                                   | the boiler is supplying auxiliary steam                     |  |
| 13 | 2781 | C | Which immediate action should you take when the temperature of one line shaft bearing increases above its normal operating temperature?                                  | Stop the unit and carefully inspect the bearing.  | Stop the unit and replace the bearing.   | Check the bearing for proper lubrication.                                      | Check for proper water circulation to the lube oil coolers. |  |
| 13 | 2782 | C | When a boiler is up to pressure and is being placed on the line, you should secure the .   | air cock  | economizer drain   | superheater vent   | air heater vent   |  |
| 13 | 2791 | D | Which of the following problems is likely to occur if the lube oil level in the sump is too high?  | Aeration of the oil.  | A rise in oil temperature.   | The main engine could not be operated at full speed.                           | All of the above.   |  |
| 13 | 2792 | D | Which of the listed conditions can cause excessively high superheater outlet steam temperature in an automated boiler?   | High water level in the steam drum.   | Excessive heat transfer in the control desuperheater.                              | Insufficient excess air.   | A malfunction of the windbox airflow transmitter.           |  |
| 13 | 2801 | B | Sludge tanks are used in an oil lubricating system to receive .  | makeup oil that is to be added to the system after settling                                   | foreign liquid matter, discharged from the lube oil purifier or the stripping pump | bilge slops that can be reclaimed after clarification                          | all of the oil that passes through the lube oil coolers     |  |
| 13 | 2802 | A | On a boiler equipped with an uncontrolled interdeck superheater, reducing the feedwater temperature to the steam drum will cause the superheater outlet temperature to . | rise  | decrease   | rise momentarily then decrease   | remain constant   |  |

|    |      |   |  |  |   |   |  |  |
|----|------|---|--|--|---|---|--|--|
| 13 | 2811 | C | Dirt and/or metallic particles in a reduction gear lubricating oil system may cause which of the following problems to occur?                    | Uniform polishing of the journals.   | Clogging of the spray nozzles.                            | Spalling of the gear teeth.   | All of the above.  |  |
| 13 | 2841 | D | In herringbone helical gear sets, the tooth contact loading .  | is both a sliding and rolling action   | is distributed over several teeth simultaneously          | is distributed between two opposing helices                             | all of the above   |  |
| 13 | 2851 | D | A cloudy or milky appearing lube oil sample, taken from the main lubricating oil system could be caused by .                                     | insufficient cooling water to the lube oil cooler                                      | excessive cooling water to the lube oil cooler            | insufficient gland sealing steam  | excessive gland sealing steam  |  |
| 13 | 2861 | B | Reduction gears on main propulsion turbines are double helical cut to .  | reduce torque  | eliminate gear tooth thrust                               | increase pinion deflection  | reduce the size and weight of the bull gear  |  |
| 13 | 2862 | D | The steam generating capacity of a boiler depends upon the .   | number of burners  | relative size of tubes and downcomers                     | amount of heat absorbing surface  | all of the above   |  |
| 13 | 2871 | D | In a disk type lubricating oil centrifuge .  | the centrifuge driving gears are lubricated by the reclaimed oil as it leaves the bowl | all dirt and sludge are discharged with the cooling water | sealing water must never be supplied until after oil is fed to the unit | deterioration of the bowl ring gasket will cause the purifier to lose its water seal |  |
| 13 | 2872 | A | Under otherwise normal steaming conditions, an abnormally high temperature at the superheater outlet of a single furnace boiler would indicate . | poor heat transfer in feedwater heaters  | high steam demand   | insufficient combustion air   | excessive steam supply to fuel oil heaters   |  |
| 13 | 2881 | A | Main reduction and pinion gears are double helically cut to .  | reduce end thrust and noise  | decrease reduction gear radial bearing loads              | increase tooth deflection at high speeds                                | decrease the number of teeth in contact  |  |
| 13 | 2882 | B | When answering a full astern bell from half ahead, the superheater outlet temperature on a single furnace boiler will .                          | increase sharply with the increased firing rate  | decrease due to the increase steam volume used            | decrease momentarily and then increase proportionately with load demand | remain the same  |  |

|    |      |   |  |  |   |  |   |         |
|----|------|---|--|--|---|--|---|---------|
| 13 | 2892 | B | The purpose of the pressure control disk installed in the multi-nozzle soot blower, as shown in the illustration, is to .                  | control the pressure exerted on the steam valve disk when the cam secures the steam supply | reduce the steam supply pressure to the soot blower element | control the pressure exerted on the valve spring retainer    | increase the pressure in the steam supply line for proper soot blower operation | SG-0023 |
| 13 | 2901 | D | Most main reduction gear units employ double helical cut gears, rather than single helical cut gears, because double helical cut gears .   | eliminate the need for a turbine dummy piston  | eliminate the need for spherically seated bearings          | prevent unequal tooth contact                                | prevent end thrust  |         |
| 13 | 2911 | B | Lube oil temperature leaving the lube oil coolers is regulated by throttling the .   | cooling water inlet valve  | cooling water outlet valve                                  | lube oil return flow valve                                   | lube oil outlet valve   |         |
| 13 | 2912 | C | In an automatically fired boiler, increasing the temperature of the feedwater entering the steam drum will ultimately result in a/an .     | increase in the quality of superheated steam   | increase in fuel consumption                                | decrease in the degree of superheat                          | decrease in the quality of steam entering the superheater                       |         |
| 13 | 2921 | B | The purpose of the main reduction gears is to .  | transmit vibration and thrust to the ship's hull   | reduce high turbine RPM to an efficient propeller RPM       | reduce engine room noise levels during high speed operations | provide a means of reversing the main engines in an emergency                   |         |
| 13 | 2931 | D | If a tube should leak in an operating main steam turbine lube oil cooler, the water will not immediately contaminate the oil because the . | second-stage discharge valve will open   | plug type bypass valve will open                            | cooling pump would automatically shut off                    | oil pressure is greater than the water pressure                                 |         |
| 13 | 2941 | B | An air vent is installed on some reduction gear casings to .   | avoid the accumulation of flammable oil vapors   | release air pressure buildup                                | admit cooling air to the gearing                             | decrease the possibility of corrosion   |         |
| 13 | 2951 | D | During high speed operation of the main turbine propulsion unit, the heat absorbed by the lubricating oil is removed by the .              | lube oil purifier  | sump vents  | distillate cooler  | lube oil cooler   |         |
| 13 | 2961 | D | Which of the following bearings is designed to take loads applied to the axis of the shaft?  | Radial   | Spring  | Strut  | Thrust  |         |

|    |      |   |  |  |  |   |   |  |
|----|------|---|--|--|--|---|---|--|
| 13 | 2971 | A | In some lube oil systems, the temperature of the lube oil downstream from the lube oil cooler is directly regulated by _____.                            | a thermostatically controlled valve which bypasses oil around the cooler                                     | the amount of latent heat that the oil carries away from the bearings  | the ambient sea water temperature   | The operating speed range of the equipment  |  |
| 13 | 2981 | C | When the temperature of the main steam turbine lubricating oil is lowered, an increase will occur in the _____.  | pour point   | concentration of contaminants  | viscosity   | flash point   |  |
| 13 | 2991 | B | Thrust bearings are installed in main propulsion turbines to _____.  | cancel centrifugal thrust force  | control rotor axial movement   | eliminate the need for dummy piston   | maintain radial clearances  |  |
| 13 | 3001 | C | To test an automatic low lube oil pressure trip on an idling turbogenerator and at the same time prevent the chance of bearing damage, you should _____. | actuate the overspeed trip, making a note at what pressure the oil is dumped from under the operating piston | close the generator steam throttle valve and then ensure a supply of oil through the hand or standby pump when the pressure drops to 5-6 psi | secure the steam supply valve to the throttle valve and observe the oil pressure as the throttle trips during the slowdown and ensure a supply of oil through the hand or standby pump when the pressure drops to 2-3 psi | ensure the standby lube oil pump, if so equipped, is properly lined up and set in the 'auto' mode, or the hand pump is being operated and then actuate the emergency trip |  |
| 13 | 3002 | C | In a steadily steaming boiler, carryover is indicated by a/an _____.   | inability to maintain boiler chemistry   | sudden increase in superheater outlet temperature  | sudden decrease in superheater outlet temperature   | sudden decrease in drum level   |  |
| 13 | 3011 | A | Which of the following methods provides for axial movement in a gear type flexible coupling?   | External teeth on the floating member are allowed to slide between internal teeth on the shaft rings.        | Each gear is allowed to slide on its shaft between retaining collars.  | A coupling permits free relative radial motion of the gear and pinion, thereby allowing axial movement.   | Opposing helices act to balance axial thrust with the coupling.   |  |

|    |      |   |   |   |   |   |   |  |
|----|------|---|---|---|---|---|---|--|
| 13 | 3012 | B | The plugging of an excessive number of superheater tubes will result in .   | high superheater outlet temperature   | low superheater outlet temperature                                | high boiler water level   | low superheater outlet pressure                           |  |
| 13 | 3021 | B | After a prolonged shutdown of a main propulsion turbine, and before the turning gear is operated, the lube oil temperature should be at least . | 60°F  | 90°F  | 110°F   | 120°F   |  |
| 13 | 3022 | A | A rapid fluctuation of the superheater outlet temperature on a steady steaming boiler could indicate .  | water carryover into the superheater  | excessive steam flow through the superheater                      | leaks in the superheater element                                      | failure of the internal auxiliary desuperheater           |  |
| 13 | 3032 | A | At a given pressure, erosion of steam piping and machinery will be minimized by utilizing .   | superheated steam   | desuperheated vapor   | wet steam   | saturated steam   |  |
| 13 | 3042 | A | A heavy accumulation of soot on the fireside of the superheater can cause a .   | low superheater outlet temperature because of the insulating effect of soot | high superheater outlet temperature because of reduced steam flow | high superheater inlet temperature because of decreased heat transfer | high superheater outlet temperature because of gas laning |  |
| 13 | 3051 | D | Why is a high lube oil level in the main engine reduction gear sump undesirable?  | Oil churning may result.  | The oil may become aerated.                                       | Oil temperature may rise.   | All of the above.   |  |
| 13 | 3061 | D | Which of the listed operational checks should be continuously made on the main propulsion reduction gears?                                      | Check radial bearing wear.  | Inspect alignment between gears and turbine.                      | Check teeth for pitting and scuffing.                                 | Check lube oil bearing temperatures.                      |  |
| 13 | 3071 | C | After the housing has been bolted down, the final check of reduction gear tooth contact is usually made by .                                    | alignment gauges  | dial indicators   | bluing the teeth  | bridge gauges   |  |
| 13 | 3072 | A | Boiler superheaters are designed to .   | raise the sensible heat of the steam  | increase the overall mechanical efficiency of the plant           | provide continuous steam flow to the control desuperheater            | raise the latent heat of the steam                        |  |
| 13 | 3081 | D | Excessive thrust bearing wear in a main propulsion turbine should FIRST become apparent by .  | rubbing noises when jacking over the main unit                              | metal particles in the lube oil purifier                          | an intermittent vibration when changing speed                         | taking rotor position indicator readings                  |  |

|    |      |   |   |   |  |  |  |  |
|----|------|---|---|---|--|--|--|--|
| 13 | 3082 | B | Increasing the amount of excess air to a boiler equipped with an uncontrolled interdeck superheater will cause the steam temperature at the superheater outlet to . | decrease  | increase   | decrease momentarily   | increase momentarily                               |  |
| 13 | 3091 | A | Oil flowing through the sight glass in the line between the lube oil gravity tank and main sump indicates the .   | gravity tank is overflowing                         | lube oil pump is stopped   | lube oil suction strainer is clogged   | lube oil sump is full                              |  |
| 13 | 3101 | D | Gear surface failure caused by exceeding the endurance limit of the surface material is characterized by .  | initial or corrective pitting                       | destructive pitting  | spalling   | All of the above are correct.                      |  |
| 13 | 3102 | A | An excessively high superheater temperature could be the result of .  | excessive air                                       | high feedwater temperature   | soot accumulation on the superheater   | excessive steam demand                             |  |
| 13 | 3111 | B | Which of the following conditions is indicated by oil flowing through a lube oil gravity tank overflow bull's eye?  | Excessive oil is stored in the gravity tank.        | Sufficient oil flow is being supplied to the gravity tank.             | Insufficient oil is being pumped to the gravity tank.  | Turbine bearing failure has occurred.              |  |
| 13 | 3112 | C | If a pressure drop does not exist across the superheater in a steaming boiler .   | this is a normal condition                          | the drum safety valve is about to lift ahead of the superheater safety | there is no steam flow through the superheater   | the feedwater temperature is too low               |  |
| 13 | 3121 | C | If a spring bearing begins to run at an abnormally high temperature, you should .   | increase the water flow to the main lube oil cooler | immediately stop the shaft to prevent seizing                          | slow the shaft, if possible and supply emergency cooling water to the spring bearing housing | alternate the shaft speed to flush out the bearing |  |
| 13 | 3122 | C | Superheaters of the convection type are heated .  | by direct contact with the flame                    | by hot brick work  | by gases passing over them   | from the fuel bed                                  |  |

|    |      |   |   |  |  |  |  |         |
|----|------|---|---|--|--|--|--|---------|
| 13 | 3131 | C | You would not see a flow through the bull's-eye of the lube oil gravity tank overflow line when the _____ .   | main engines are stationary at a stop bell   | main engines are secured and the turning gear is engaged   | the lube oil service pumps are secured   | main engines are turning at normal sea speed   |         |
| 13 | 3132 | D | Under operating conditions of constant load and rate of combustion, which of the following conditions will happen to the superheater when the amount of excess air to the furnace is increased? | The superheater outlet temperature decreases.  | The rate of heat transfer is decreased.  | The rate of steam flow is increased regardless of all other firing conditions.   | The superheater outlet temperature increases.  |         |
| 13 | 3141 | C | The base ring shown in the illustration is identified by the letter _____ .   | A  | C  | D  | E  | SE-0012 |
| 13 | 3142 | D | The temperature of steam at the superheater outlet is effected by the _____ .   | temperature of the feed water  | amount of excess air   | amount of moisture contained in the steam  | all of the above   |         |
| 13 | 3151 | C | The lube oil cooler will be used as a heater for the main propulsion unit _____ .   | when the vessel is operating at full speed   | if the oil temperature is below 120°F  | when warming up a cold plant   | when lube oils of different viscosities are used   |         |
| 13 | 3152 | D | Which statement is true concerning operational factors affecting the degree of superheat in a single furnace boiler?  | As the rate of combustion increases, the degree of superheat increases throughout the entire firing range. | With a constant firing rate and steam consumption equal to generation, a decrease in the incoming feedwater temperature results in a superheat temperature decrease. | With large amounts of excess air, superheater outlet temperature will decrease due to the lack of sufficient time for heat transfer to take place. | Carrying boiler water total dissolved solids higher than normal could result in a decrease in the degree of superheat. |         |
| 13 | 3161 | A | In the diagrammatic arrangement of the thrust bearing, shown in the illustration, the direction of shaft rotation and the direction of thrust are indicated respectively by arrows _____ .      | F and J  | F and H  | G and J  | G and H  | SE-0012 |

|    |      |   |  |   |   |   |   |         |
|----|------|---|--|---|---|---|---|---------|
| 13 | 3162 | A | Rapid fluctuation in the superheater temperature of a steady steaming boiler indicates _____ . | moisture carryover  | improper positioning of superheater fires                       | leaky desuperheater tubes                     | leaky superheater tubes   |         |
| 13 | 3171 | C | The reduction gear shown in the illustration is a/an _____ .                                   | nested double reduction gear                                  | nested four-step reduction gear                                 | articulated double reduction gear             | locked-train double reduction gear  | SE-0013 |
| 13 | 3172 | B | Rapid fluctuation of the superheater outlet temperature is caused by _____ .                   | a dirty economizer  | intermittent carryover  | excess air                                    | dirty watersides  |         |
| 13 | 3181 | B | The purpose of oil deflector rings for turbine shafts include _____ .                          | directing the lube oil spray                                  | preventing oil leakage along the shaft                          | forming the lube oil spray pattern            | removing emulsified lube oil from the sump  |         |
| 13 | 3182 | B | The primary purpose of the refractory in a marine boiler is to _____ .                         | conduct the heat of combustion away from the water wall tubes | protect the furnace casing and retain furnace heat              | support the outer casing                      | protect the superheater from convectional heat transfer                                   |         |
| 13 | 3191 | B | Which type of reduction gear arrangement is shown in the illustration?                         | Locked train, double reduction.                               | Articulated, double reduction.                                  | Nested, double reduction.                     | Two-pinion, single reduction.   | SE-0013 |
| 13 | 3192 | B | The purpose of the refractory lining of a water-tube boiler furnace is to _____ .              | prevent flames from impinging on tubes                        | assist in maintaining the heat of combustion within the furnace | support the outer casing                      | protect the superheater from convectional heat transfer                                   |         |
| 13 | 3201 | A | The component shown in the illustration, labeled "I", is the _____ .                           | first reduction gear  | first reduction pinion  | second reduction gear                         | second reduction pinion   | SE-0013 |
| 13 | 3202 | B | A secondary function of the refractory installed in a marine boiler is to _____ .              | support the boiler casing                                     | direct the flow of combustion gases                             | maintain air flow through the burner diffuser | support the burner distance piece   |         |
| 13 | 3211 | D | The gravity tank in a gravity lube oil system serves to _____ .                                | store heated lube oil   | supply the lube oil service pump with a positive suction head   | settle lube oil prior to purifying            | maintain oil supply for several minutes to bearings should the lube oil service pump fail |         |

|    |      |   |   |   |   |  |   |         |
|----|------|---|---|---|---|--|---|---------|
| 13 | 3212 | D | Which of the problems listed will reduce boiler efficiency?   | Using worn sprayer plates.  | Steaming with a clear stack.                                      | Tolerating unacceptable levels of carbon monoxide in flue gas.   | All of the above.   |         |
| 13 | 3221 | A | The disassembled thrust bearing, shown in the illustration, which of the listed parts is labeled "I"?   | Base ring.  | Leveling plates.  | Thrust shoes.  | Collar.   | SE-0014 |
| 13 | 3222 | C | As compared with a typical front fired boiler, which of the listed conditions represents an advantage of a top fired boiler?                                  | No division tube wall separating the convection and radiant sections of the furnace is ever required.   | Superheating diaphragms may be omitted.                           | More uniform heat distribution and gas dwell is obtained within the furnace.                                       | A lower fuel flow rate can be allowed, thus increasing economy.                         |         |
| 13 | 3231 | B | On a ship equipped with a gravity type lube oil system, which of the conditions listed will occur FIRST if the main lube oil pump discharge pressure is lost? | All bearing oil pressure will be lost.  | An alarm will sound.  | The astern throttle will immediately open.   | Lube oil will be provided to the bearings and gears via the gravity tank overflow line. |         |
| 13 | 3232 | D | Which of the listed absorbing agents could be used in a boiler during a dry lay up period?  | Sodium hydroxide  | Sodium chloride   | Deactivated hydrazine  | Silica gel  |         |
| 13 | 3241 | A | Which of the following statements is true concerning the turning gear rotor arrangement shown in the illustration?  | The second reduction worm gear always rotates whenever the turning gear motor is in operation; regardless of the position of the engaging handle. | The turning gear motor coupling is engaged by the locking device. | In order for the 'turning gear engaged' indicating lamp to be lit, the switch must be of the normally closed type. | The first reduction gear meshes directly with the bull gear.                            | SE-0015 |

|    |      |   |   |  |  |  |   |         |
|----|------|---|---|--|--|--|---|---------|
| 13 | 3242 | B | A water-tube boiler can be laid up either wet or dry. If it is to be laid up wet, you should .  | completely fill the boiler with water, then blowdown to steaming level | completely fill the boiler with deaerated feedwater and maintain a slight pressure | drain and refill the boiler each week                                | drain and refill the boiler when the pH goes above 6      |         |
| 13 | 3251 | B | Which of the following conditions is the engineer's FIRST warning that the main lube oil pump has stopped?  | Gravity tank low level alarm will sound.                               | Lack of oil in the overflow bull's-eye is observed.                                | High main engine bearing temperatures will be noted.                 | Low main sump level alarm will sound.                     |         |
| 13 | 3252 | A | When a propulsion boiler is removed from service for an extended period, why should the firesides be thoroughly cleaned and dried?  | Reduce the probability of corrosion.                                   | Prevent flarebacks on lighting off.  | Prevent cracking of the brickwork.                                   | Reduce the possibility of thermal spalling.               |         |
| 13 | 3261 | D | Because the entire thrust bearing assembly is normally submerged in oil, the pivoting shoe arrangement allows the formation of a continuous wedge shaped oil film shown in the illustration by arrow "B", between the . | leveling plates and collar   | base ring and pivoted shoes  | leveling plates and buttons  | collar and pivoted shoes                                  | SE-0012 |
| 13 | 3262 | A | Which of the listed actions should be carried out if a ship is to be laid up for an indefinite period of time?  | Boilers to be laid up wet should be completely filled.                 | All fuel tanks should be cleaned and gas freed.                                    | All potable water tanks should be cleaned and disinfected.           | All of the above.   |         |
| 13 | 3272 | A | When you are installing a new furnace floor in an oil fired boiler, the clearance between the firebricks should be large enough to .  | allow for expansion without subjecting the joint to flame penetration  | facilitate rebricking at required maintenance intervals                            | allow for proper filling with slag under normal operating conditions | allow for installation of plastic chrome ore after drying |         |

|    |      |   |  |   |  |  |   |         |
|----|------|---|--|---|--|--|---|---------|
| 13 | 3281 | A | Supply pressure to the main lube oil header of a gravity feed lube oil system is .   | the result of the height of the gravity tank above the manifold | the sum of the lube oil static head pressure and service pump discharge pressure | the difference between the lube oil static head pressure and service pump discharge pressure | merely the service pump discharge pressure, since the static heads of the lines to and from the gravity tank cancel out one another |         |
| 13 | 3282 | D | To assure a long service life for boiler refractory materials after installation, the most effective method is to .  | maintain a high furnace temperature at all times                | patch refractory with plastic chrome ore   | properly secure refractory with anchor bolts   | avoid rapid temperature changes and follow recommended operating procedures   |         |
| 13 | 3291 | B | Magnets located in lube oil strainers serve to .   | remove all metallic particles from the lube oil                 | remove ferrous metallic particles from the lube oil                              | remove nonferrous metallic particles from the lube oil                                       | hold the strainer cover in place when removing or installing the cover bolts  |         |
| 13 | 3292 | C | Which of the listed procedures is the most important factor to take into consideration when making repairs to the refractory surrounding the burner openings?      | All cracks must be completely filled.                           | Finished repair surfaces must be smooth.   | Design refractory cone angle must be maintained.   | Plastic firebrick must be used.   |         |
| 13 | 3301 | C | In the thrust bearing assembly illustrated the total oil clearance can be correctly decreased by .   | increasing the thickness of the adjusting ring                  | increasing the thickness of the filler piece                                     | decreasing the thickness of the adjusting ring   | decreasing the thickness of the filler piece  | SE-0007 |
| 13 | 3302 | B | A furnace wall in which there are open spaces around the brick as a result of firebrick shrinkage, is .  | normal and need only be cleaned                                 | loose and should be repaired   | cracked and must be patched  | spalled and must be replaced  |         |
| 13 | 3311 | B | In a pressure type main propulsion turbine lubrication system, the lube oil service pumps normally take suction from the main sump and discharge directly to the . | gravity feed tank   | lube oil coolers   | lube oil header  | main thrust bearing   |         |

|    |      |   |   |  |  |  |   |  |
|----|------|---|---|--|--|--|---|--|
| 13 | 3312 | C | When drying and baking are impractical, or time is not available, which of the listed materials could be used to repair both burner openings and gas baffles? | Plastic chrome ore   | Plastic fire clay  | High temperature castable refractory                                     | Baffle mix  |  |
| 13 | 3321 | D | Water can enter the lube oil system of a main propulsion turbine unit from .  | leaky tubes in secured lube oil coolers  | steam sealed turbine glands                                  | vents on tanks and gear casings  | all of the above  |  |
| 13 | 3322 | A | When cleaning the waterside of boiler tubes with a powered rotary brush, the brush should kept in motion to .   | avoid tube damage  | prevent it from seizing                                      | reduce tube pitting  | reduce wear to brush bristles   |  |
| 13 | 3331 | C | The temperature of emulsified lubricating oil entering a purifier from a preheater should range between .   | 110°-120°F   | 140°-150°F   | 160°-180°F   | 190°-210°F  |  |
| 13 | 3332 | D | Maximum heat transfer rates in a marine boiler can be obtained by .   | maintaining the recommended boiler water pH  | treating the boiler water with oxygen scavenging chemicals   | maintaining the feedwater temperature of 212°F                           | keeping the watersides free from scale deposits                           |  |
| 13 | 3341 | A | Water retained in the lube oil system of a main propulsion turbine installation is undesirable because it .   | causes pitting of the gear teeth   | causes the turbine to overspeed                              | raises the flash point of the oil to a dangerously high level            | results in excessive cooling of bearing surfaces                          |  |
| 13 | 3342 | B | The correct method of expanding a generating tube at the boiler drum tube sheet is to roll .  | to a depth less than the thickness of the drum tube sheet  | to a depth greater than the thickness of the drum tube sheet | heavily at the tube end prior to welding the tube to the drum tube sheet | slightly at the tube end prior to welding the tube to the drum tube sheet |  |
| 13 | 3351 | A | If the main and standby lube oil service pumps of the main engine fail while underway at sea, .   | an emergency supply of oil in the gravity tank will provide time to crash stop the turbine and gears | the reduction gear bearings will immediately fail            | the turbine bearings will immediately fail                               | emergency lubrication can be supplied through the use of the hand pump    |  |

|    |      |   |  |  |   |  |  |  |
|----|------|---|--|--|---|--|--|--|
| 13 | 3352 | D | Which of the listed conditions is the cause of heavy flaking of an alloy tube being rolled or expanded into a tube header?                                 | Tube is brittle as a result of long storage time at high temperatures. | Tube has a flaw at the point of tube sheet entry. | Diameter of the tube roller is too large.        | Excessive tube roller pressure is being applied.                     |  |
| 13 | 3361 | D | If lube oil pressure to the main turbines is lost while underway at sea speed, the rotor should be stopped immediately. This is accomplished by _____.     | applying the pony brake  | tightening the stern tube packing gland           | securing all steam to the turbines               | admitting astern steam to the turbines after securing ahead steam    |  |
| 13 | 3371 | A | What is the FIRST thing that will happen if both the main and standby lube oil pumps fail on a geared main propulsion turbine operating at full sea speed? | Ahead throttle will close.   | Lube oil sump will overflow.                      | Vacuum will be lost.                             | HP turbine bearings will overheat.                                   |  |
| 13 | 3372 | C | The process of flaring the section of a boiler tube extending beyond the tube sheet into the drum is known as _____.                                       | safe ending  | expanding   | belling  | breeching  |  |
| 13 | 3381 | B | Which of the conditions listed could cause an oil flow sight glass, of a main turbine bearing, to be completely filled with oil?                           | An increase in oil temperature.  | A restriction in the oil drain line to the sump.  | Excessive air trapped in the lube oil system.    | Increasing the amount of oil through the gravity tank overflow line. |  |
| 13 | 3382 | A | Proper lagging of a single-element feedwater regulator is accomplished by applying the insulation material _____.  | to the steam connection, but not water connection                      | to the water connection, but not steam connection | to both connections, including finned areas      | only as necessary to prevent possible injury                         |  |
| 13 | 3391 | A | Magnets are installed in the main propulsion turbine lube oil strainers to attract metal particles released through wearing of the _____.                  | reduction gears  | turbine blades                                    | babbit bearings                                  | turbine labyrinth  |  |
| 13 | 3392 | A | When testing boiler safeties, those valves not being tested are prevented from lifting by _____.   | installing gags  | securing the lifting arms                         | temporarily increasing the valve spring pressure | closing the actuating pilot valve                                    |  |

|    |      |   |  |   |  |  |  |  |
|----|------|---|--|---|--|--|--|--|
| 13 | 3401 | A | If the main turbine bearing lube oil pressure drops to 'zero' and cannot be restored immediately, you should .   | notify bridge and crash stop the engine                                     | reduce turbine rotor speed until lube oil sump level returns to normal   | reduce turbine rotor speed and pump lube oil with the hand emergency pump                    | strike down makeup lube oil from the gravity tanks                                   |  |
| 13 | 3402 | D | To prevent safety valves from lifting when a boiler is being hydrostatically tested, you should .  | tie down the hand lifting gear  | increase the valve spring pressure   | decrease the valve spring pressure   | install gags on the valves   |  |
| 13 | 3411 | B | If you are underway at full speed on a vessel fitted with a main propulsion turbine pressure lubrication system, which of the following actions will be necessary upon complete loss of lube oil pressure? | Slow the main engines and strike down additional oil from the gravity tank. | First close the ahead throttle valve, then open the astern guardian valve, and then open the astern throttle to admit astern steam as quickly as possible. | Secure main steam to the turbines immediately and engage jacking gear.                       | Secure main steam to the turbines and break vacuum on the main plant immediately.    |  |
| 13 | 3412 | D | Which of the precautions listed should be taken when gagging a boiler safety valve?  | Do not allow the gag to contact the safety valve stem.                      | Tighten the gag only with the special wrench supplied with the gag.  | Ensure that all moving parts of the safety valve are free to move before installing the gag. | Tighten the gag only finger tight to prevent damage to the valve stem, disc or seat. |  |
| 13 | 3421 | C | What immediate action should you take if you are on watch and note 'zero' lube oil pressure for the operating main turbine?  | Immediately increase cooling water flow to lube oil cooler.                 | Slow the turbine to minimum speed and watch the bearing temperatures.  | Stop the shafts.   | Shift strainers and gravity tanks.   |  |
| 13 | 3422 | B | Safety valve gags should only be installed hand tight in order to prevent .  | compression of the valve spring   | bending of the valve stem  | damage to the gag  | overpressurizing the valve body  |  |
| 13 | 3431 | D | If a lube oil pump fails to build up discharge pressure, the cause could be the .  | bypass valve is closed  | discharge valve is open  | suction vacuum is high   | suction valve is closed  |  |

|    |      |   |  |  |  |  |   |  |
|----|------|---|--|--|--|--|---|--|
| 13 | 3432 | D | When using the universal color contrast-type dye penetrant to examine a boiler weldment, any surface defect will appear .                    | black against a white background                                   | white against a black background                           | white against a dull red background                | bright red against a white background         |  |
| 13 | 3441 | B | Abnormally low lube oil service pump pressure may be the result of .   | a defective cooler bypass valve                                    | excessively high lube oil temperature                      | wasted lube oil cooler zincs                       | all of the above                              |  |
| 13 | 3451 | A | An excessive pressure differential across a lube oil strainer could indicate .   | the strainer needs cleaning  | the filter elements are installed upside down              | the relief valve is stuck open                     | all of the above                              |  |
| 13 | 3452 | B | When installing new safety valve escape piping, precautions should include assuring that .   | bends or elbows in the line do not exist                           | no stress is transmitted to the valve                      | the quick-closing valve operates freely            | the piping leads directly to the bilge        |  |
| 13 | 3461 | A | While a vessel is underway, which of the conditions listed would indicate a leak in the lube oil cooler?                                     | Excessive lube oil consumption.                                    | Excessive water discharge rate from the lube oil purifier. | Contamination of the lube oil.                     | Corrosion of the journals and bearings.       |  |
| 13 | 3462 | B | Which of the listed operating practices is considered as safe, and should be followed when opening and inspecting the waterside of a boiler? | Open the water drum manhole before opening the steam drum manhole. | Wire all valves closed that connect to other boilers.      | Remove handhole plate dogs with a slugging wrench. | Ventilate the waterside until completely dry. |  |
| 13 | 3471 | A | When a sudden increase in pressure occurs in a forced lubrication system, you should check for a .   | loss of oil flow across one of the bearings                        | clogged lube oil pump suction                              | ruptured tube in the lube oil cooler               | high lube oil sump level                      |  |
| 13 | 3472 | A | Oil deposits can be removed from the waterside of boilers by 'boiling out' with a/an .   | alkaline solution  | acid solution  | salt solution                                      | kerosene solution                             |  |
| 13 | 3481 | C | When there is a sudden increase of lubricating oil pump discharge pressure in a force feed lubricating system, you should FIRST check the .  | pump relief valve  | lubricating oil cooler outlet temperature                  | lubricating oil flow from the bearings             | lubricating oil suction strainers             |  |
| 13 | 3482 | C | Which type of waterside deposits can normally be removed by chemically boiling out a boiler?   | Corrosion deposits   | High temperature oxide                                     | Oil  | Sludge  |  |
| 13 | 3491 | B | A sudden increase in lube oil pressure to the main turbine would indicate .  | a leak in the gravity tank   | debris clogging the system                                 | a leaking lube oil cooler                          | excessively cool lube oil                     |  |

|    |      |   |   |  |  |   |  |         |
|----|------|---|---|--|--|---|--|---------|
| 13 | 3501 | B | What should be done when foreign matter is found in a lube oil strainer?  | Immediately stop the main engine and inspect all strainers.                          | Examine the foreign matter and determine its source.           | Back flush the strainer to the lube oil sludge tank.  | All of the above.  |         |
| 13 | 3502 | D | Which of the listed refractory materials should be used for patching a burner front formed of plastic, castable, or tile?   | Plastic chrome insulation  | Chrome castable insulation                                     | Air-setting mortar  | Plastic fireclay   |         |
| 13 | 3511 | C | Which of the following conditions may exist if you detect an excessive amount of metal particles on a main engine lube oil strainer magnet?   | Journal bearing damage.  | Turbine shrouding damage.                                      | Reduction gear damage.  | Main shaft bearing damage.   |         |
| 13 | 3522 | A | To make temporary emergency repairs to brickwork in a boiler furnace, which of the materials listed should be used?   | Plastic refractory   | Air setting mortar   | Insulating block  | Calcined diatomaceous earth  |         |
| 13 | 3531 | B | Which of the components listed is indicated by the "X" shown in the illustration?   | Strainer   | Sight glass  | Drain   | Branch line  | SE-0010 |
| 13 | 3541 | C | How is the lube oil temperature controlled in the pressurized lube oil system shown in the illustration?  | Sea water flow through the cooler is adjusted by opening or closing the inlet valve. | A thermostatic valve diverts sea water flow around the cooler. | A thermostatic valve sensor determines temperature downstream of the L.O. coolers and the valve diverts lube oil flow through or around the cooler accordingly. | Lube oil flow through the cooler is adjusted by changing the speed of the lube oil pump. | SE-0011 |
| 13 | 3542 | A | Tubes may be seal welded into fittings or headers of boilers and superheaters after they have been expanded and flared, provided the material in the fitting or header does not contain carbon in excess of | 0.35%  | 0.40%  | 0.45%   | 0.50%  |         |

|    |      |   |   |   |   |   |  |         |
|----|------|---|---|---|---|---|--|---------|
| 13 | 3552 | B | In a single furnace boiler, fitted with a U-tube horizontal superheater, renewing the entire transverse support/seal plates usually involves _____.   | removal of all screen tubes to gain access  | removal of all superheater tubes to facilitate fitting  | only replacing the dog-bone type supports that appear burnt   | removal of all furnace refractory  |         |
| 13 | 3561 | D | Which of the following statements is true concerning the lube oil system shown in the illustration?   | The gravity tanks supply emergency lube oil to the turbines and gears in the event of failure to the main, standby, and emergency lube oil pumps. | The battery-powered emergency lube oil pump supplies oil to the turbines and gears for four hours in the event of failure of the main and standby lube oil pumps. | The three-way temperature control valve bypasses cooling water around or through the lubricating oil cooler to maintain the desired oil supply temperature to the turbines. | The lube oil cooler, lube oil filters, and lube oil system pressure relief valves all drain to the lube oil sump tank. | SE-0011 |
| 13 | 3562 | D | Routine maintenance of boiler sliding feet should include _____.  | painting the sliding surfaces to prevent corrosion  | removing all grease from around bolts   | torquing retaining bolts on the stationary base   | wire brushing to remove scale, rust, and dirt  |         |
| 13 | 3572 | C | To increase the blowdown of a nozzle reaction safety valve, _____.  | lower the nozzle ring   | raise the blowdown ring   | lower the adjusting ring  | raise the blowdown ring and then lower the nozzle ring   |         |
| 13 | 3581 | C | To assure the main propulsion turbine bearings are receiving the proper lube oil supply, you should check the _____.  | bull's-eye in the gravity tank overflow   | lube oil temperature at the cooler outlet   | flow through the sight glass at the bearing   | lube oil strainer magnets  |         |
| 13 | 3582 | A | Which of the test pressures listed is considered to be satisfactory when conducting a hydrostatic test on a desuperheater, which has undergone a welding repair, and has been reinstalled in a boiler having a MAWP of 900 psi? | 250 psi   | 900 psi   | 1125 psi  | 1350 psi   |         |
| 13 | 3591 | B | The astern guarding valve must be open when a vessel is _____.  | at full sea speed   | maneuvering into port   | running with a warm bearing   | loading cargo  |         |

|    |      |   |   |  |   |  |   |         |
|----|------|---|---|--|---|--|---|---------|
| 13 | 3592 | D | Increasing the blowdown of a boiler nozzle reaction safety valve is normally accomplished by _____.   | increasing the valve spring compression  | decreasing the valve spring compression   | raising the adjusting ring   | lowering the adjusting ring   |         |
| 13 | 3601 | D | While a vessel is underway, one of the FIRST indications of the failure of the gland leakoff exhaust fan motor is _____.  | loss of vacuum at the turbine  | increased turbine exhaust temperature   | water knock in the turbine gland steam header  | excessive steam leakage at the turbine glands   |         |
| 13 | 3602 | D | When installed, the economizer relief valve should always be set _____.   | at the same pressure as the superheater safety valve                                   | at the same pressure as the drum safety valve   | 50 pounds higher than the superheater safety valve plus the water pressure drop through the economizer | 50 pounds higher than the drum safety valve plus the water pressure drop through the economizer |         |
| 13 | 3611 | B | Some turbines used for high temperature and pressure service utilize special casing flange bolts having internal axial holes. The purpose for these cavities is to _____. | permit axial movement of the casing due to expansion                                   | provide access for heating elements used to expand the bolts                          | act as a witness mark for properly tightening the nuts   | provide access for a clamp dial indicator during tightening                                     |         |
| 13 | 3612 | D | Warping of superheater screen tubes can be caused by _____.   | high superheater temperatures  | high furnace temperatures   | installing baffles of excessive length   | sudden cooling of tubes after being overheated  |         |
| 13 | 3621 | C | Which of the coupling types listed is shown in the illustration?  | Claw   | Pin   | Gear   | Solid   | SE-0001 |
| 13 | 3622 | A | When you are installing a new furnace floor in an oil fired boiler, the clearance between each firebrick should be enough to _____.                                       | allow for expansion without subjecting the joint to flame penetration                  | facilitate rebricking at required maintenance intervals                               | allow for proper filling with slag under normal operating conditions                                   | allow for installation of plastic chrome ore after drying                                       |         |
| 13 | 3631 | D | Which of the following statements is true concerning the coupling shown in the illustration?  | It allows for any misalignment between the main turbine and the second reduction gear. | It is commonly used between the first reduction pinion and the second reduction gear. | It is suitable for use on small auxiliary turbines only.   | It can be used to connect the main turbine to the high-speed pinion.                            | SE-0001 |

|    |      |   |  |  |   |  |   |         |
|----|------|---|--|--|---|--|---|---------|
| 13 | 3632 | A | When you are installing a new furnace floor in an oil fired boiler, enough clearance should be left between firebrick to allow for _____.      | expansion when the boiler is fired   | flame penetration of the joint  | proper filling of the joint with slag  | ramming with plastic chrome ore   |         |
| 13 | 3641 | D | The part shown in the illustration would be located between which of the following components of a modern geared turbine main propulsion unit? | Between the bull gear and line shaft on the thrust bearing side of the gear. | Between the bull gear and line shaft on the side of the gear opposite the thrust bearing. | Between the first reduction gears and high-speed pinions of the high pressure and low pressure turbines. | Between the rotors and high-speed pinions of the high pressure and low pressure turbines. | SE-0001 |
| 13 | 3651 | A | The type of turbine shown in the illustration is a _____.  | velocity-compounded impulse turbine  | pressure-compounded impulse turbine   | pressure-compounded reaction turbine   | combination impulse and reaction turbine  | SE-0003 |
| 13 | 3652 | A | The burner front refractory should be replaced when the slag accumulation causes _____.  | the burner flame pattern to be distorted                                     | slight radial cracking around the burner cones  | the flame scanners to sense false signals from the glowing brickwork                                     | overheating of the burner atomizer tips   |         |
| 13 | 3661 | B | The type of turbine shown in the illustration is classified as a _____.  | pressure-compounded impulse  | velocity-compounded impulse   | pressure-velocity compounded impulse   | pressure-compounded reaction  | SE-0003 |
| 13 | 3662 | B | When water washing the firesides of a boiler, which of the listed procedures should be followed?   | Begin water washing while the brickwork is still warm.                       | Begin the washing above the economizer and work down.                                     | Assure that the water stream impinges directly on the refractory to avoid tube damage.                   | Dry the boiler by firing all burners at high rates to evaporate moisture rapidly.         |         |
| 13 | 3671 | A | How many Curtis stages are contained in the turbine shown in the illustration?   | 1  | 2   | 3  | only a reaction turbine stage is shown  | SE-0003 |
| 13 | 3672 | C | Which of the tools listed is used to remove a boiler tube from a header?   | Swaging tool   | Laminating tool   | Backing out tool   | Expanding tool  |         |

|    |      |   |   |   |  |  |   |         |
|----|------|---|---|---|--|--|---|---------|
| 13 | 3681 | A | A ship is equipped with the illustrated turbine gear set and a right hand turning propeller. When steam is admitted to the astern element, with sternway on, the high-speed gear on the high pressure side is . | rotating the same direction as the low-speed pinion on the low pressure side.                       | turning the same rotation of the high-speed pinion on the low pressure side.             | turning opposite to the rotation of the high-speed gear on the low pressure side.        | turning counter clockwise as viewed from the aft end of the reduction gear.           | SE-0016 |
| 13 | 3682 | C | Which of the statements represents an advantage of the 'bent tube' method of installing boiler tubes?   | Removal and replacement of tubes is easier than with other methods.                                 | Cleaning of tubes is easier than other methods.  | A comparatively greater number of holes can be placed in a given area of the tube sheet. | A minimum number of spare tubes must be carried.                                      |         |
| 13 | 3691 | B | Which of the statements listed applies to the quill shaft shown in the illustration?  | It provides torsional rigidity to help maintain alignment between gear train and the turbine rotor. | It permits axial movement between the high speed gear and low speed pinion.              | It compensates for high speed pinion radial misalignment.                                | It absorbs the axial thrust generated by the meshing gears.                           | SE-0005 |
| 13 | 3692 | A | Which of the listed mediums should be used when water washing a boiler?   | Heated freshwater   | Cold freshwater  | Heated saltwater   | Cold saltwater  |         |
| 13 | 3701 | A | How many pressure drops occur in the turbine stage shown in the illustration?   | One   | Two  | Three  | Four  | SE-0003 |
| 13 | 3702 | B | Which procedure should be followed to dry out the fireside of a boiler after water washing?   | Place trays of silica gel in the furnace.   | Alternate firing of one burner at a time for 15 minute intervals during a 5 hour period. | Open the furnace registers and run the forced draft fans for 3 hours.                    | Use a wire reinforced steam hose to put superheated steam in the furnace for 6 hours. |         |
| 13 | 3711 | C | How is an excess of turbine gland seal steam remedied?  | It exhausts to atmosphere.  | It drains to the makeup feed tank.   | It is directed to the gland exhaust condenser.   | It is recirculated via the loop seal.   |         |
| 13 | 3712 | A | Improper water washing of the water-tube boiler firesides can cause .   | sulfuric acid corrosion   | decreased heat transfer capabilities   | erosion of tubes and drums   | loss of ductility in boiler tubes   |         |

|    |      |   |   |  |   |   |  |         |
|----|------|---|---|--|---|---|--|---------|
| 13 | 3721 | B | Which of the listed conditions could occur if during start-up the rotor illustrated shifts radially?  | The teeth in segments "A" could be sheared off as they rubbed against the sides of the machined rotor lands.     | No appreciable damage would result as the segments "A" would simply move outward against spring compression.                  | Enough frictional heat would be produced, even in that short period of time, to cause distortion and ultimate scoring of the shaft.                       | None of the above as the operator would be fore warned of this situation through the action of the squealer ring "D".                                      | SE-0006 |
| 13 | 3722 | A | In the absence of the manufacturer's instructions, a good procedure in reassembling a high pressure boiler gage glass is to tighten the nuts in pairs and . | begin with the center bolts and work toward the ends   | begin with the end bolts and work toward the center   | start at the top and work down  | start at the bottom and work up  |         |
| 13 | 3731 | B | An interference fit between the coupling bolts and coupling assembly shown in the illustration is produced by .   | applying expansionary heat to the coupling hole surface, while at the same time contracting the bolt by chilling | using a hydraulic device to elongate the bolt, decreasing proportionately its diameter until the applied pressure is released | line boring accompanied with precision reaming until the bolt can be pneumatically driven into place without any abrasive damage resulting to the threads | line boring accompanied with precision reaming until the bolt can be hydraulically pressed into place without any abrasive damage resulting to the threads | SE-0008 |
| 13 | 3732 | C | Which of the following actions, if any, should be taken if the water gage glass on a steaming boiler breaks?  | Reduce the firing rate.  | Close in on the feed stop-check valve.  | Close the gage glass cutout valves.   | No action is necessary since checks in the cutout valves automatically seat to stop loss of steam and water.   |         |
| 13 | 3741 | B | In order to reduce the oil clearance between the collar and the astern thrust element shown in the illustration, you would .                                | increase the thickness of the adjusting ring   | decrease the thickness of the adjusting ring  | increase the thickness of the filler piece  | decrease the thickness of the filler piece   | SE-0007 |

|    |      |   |   |  |  |   |  |         |
|----|------|---|---|--|--|---|--|---------|
| 13 | 3742 | A | A hole should be made in the sagged tube occurring in a water-tube boiler, prior to plugging the tube to prevent a .  | pressure buildup in the tube                   | quick burnout of the tube                              | complete sagging failure of the tube        | crack failure of the tube                    |         |
| 13 | 3751 | D | After setting the allowable end play of the thrust bearing shown, you would establish the axial position of the turbine shaft by .  | increasing the thickness of the adjusting ring | decreasing the thickness of the adjusting ring         | changing the thickness of the thrust collar | changing the thickness of the filler piece   | SE-0007 |
| 13 | 3752 | B | If a water-tube boiler tube has sagged and must be plugged, a hole must be made in the tube wall to prevent .   | quick burnout of that tube                     | pressure buildup in that tube                          | a complete sagging failure                  | tube cracking due to overheating             |         |
| 13 | 3761 | C | Helical gears are preferred over spur gears for reduction gear units due to they fact that they .   | prevent torsional stress                       | eliminate pinion deflection                            | produce less noise and vibration            | be easier to lubricate at high speeds        |         |
| 13 | 3762 | A | After a boiler generating tube has been plugged, .  | a hole should be made in the defective tube    | the firing rate should be reduced                      | the steam flow rate must be increased       | all of the above                             |         |
| 13 | 3771 | B | The purpose of a thrust bearing, mounted between the engine and the propeller of a steam plant power train, is to .   | dampen torsional vibrations                    | transmit propeller thrust to the hull                  | maintain crankshaft radial alignment        | absorb gear thrust in double helical gears   |         |
| 13 | 3772 | B | An obstruction in the top connection of a boiler gage glass will cause the .  | water level to remain constant in the glass    | water level to rise slowly in the glass                | gage glass to overheat and break            | gage glass to be blown empty                 |         |
| 13 | 3782 | B | While the vessel is rolling in heavy seas, the level in the boiler gage glass remains steady, this is an indication that .  | the gage glass is functioning normally         | there is most likely an obstruction in the lower valve | the steam drum is adequately baffled        | the water level in the steam drum is too low |         |
| 13 | 3792 | A | Which of the following conditions is indicated by an external bulge or bowed area of the boiler furnace wall?   | The brickwork has failed in that area.         | The brickwork has become slagged.                      | The insulation block has become slagged.    | The corbels have failed.                     |         |
| 13 | 3802 | D | Radial cracks have developed in the castable refractory of the burner cones after the first firing since the installation of new furnace front refractory. This is an indication of . | a need for plastic firebrick patchwork         | inadequate cone angle                                  | a need for castable refractory patchwork    | relieved stresses                            |         |

|    |      |   |  |  |  |  |   |  |
|----|------|---|--|--|--|--|---|--|
| 13 | 3812 | B | Coast Guard Regulations (46 CFR) require that in preparing a water-tube boiler for a hydrostatic test, you should fill the boiler with water at a temperature of not less than . | 50°F and more than 100°F   | 70°F and more than 160°F   | 60°F and more than 120°F                                 | 100°F and more than 200°F   |  |
| 13 | 3822 | C | If the burner throat refractory does not fit tightly against the boiler inner casing, the casing plates can overheat and warp causing .  | a combustion gas leakage through the outer casing                                    | a combustion air leakage through the inner casing                                | the burner register doors to bind                        | the burner air cone to bind   |  |
| 13 | 3832 | C | Waterside grooving is usually very difficult to locate in a boiler tube before leakage occurs because .  | detection and confirmation of this type of corrosion requires laboratory examination | it occurs only on the interior surfaces of desuperheater tubes                   | it usually occurs in the tube bends near the water drum  | it occurs in narrow bands along the top of horizontal floor tubes exposed to the products of combustion |  |
| 13 | 3842 | D | Which of the conditions listed could cause a boiler economizer to leak?  | High feedwater temperatures.   | Low feedwater pressure.  | High stack gas temperatures.                             | Water hammer.   |  |
| 13 | 3852 | A | When a soot fire occurs, damage to an economizer can be minimized if you .   | maintain feedwater flow through the economizer while extinguishing the fire          | secure the economizer and open the drain valve to prevent steam pressure buildup | increase the forced draft fan speed to blow out the fire | secure the fires and inject CO2 into the furnace  |  |
| 13 | 3862 | C | Which of the conditions listed would indicate excessive soot buildup on the economizer?  | High feedwater temperature entering the boiler                                       | Low air temperature entering the boiler  | High superheater temperature                             | Lower than usual air pressure in the furnace  |  |
| 13 | 3872 | C | Which of the problems listed will occur when the economizer temperature is below the acid dew point of the flue gases?   | Hairline fractures   | Efficiency loss  | External corrosion                                       | Hydrogen embrittlement  |  |
| 13 | 3882 | B | Which of the following would indicate a moderate leak in the desuperheater?  | Higher than normal auxiliary steam pressure  | Lower than normal auxiliary steam temperature                                    | Higher than normal fuel oil consumption                  | Lower than normal fuel oil consumption  |  |
| 13 | 3892 | B | An indication of a moderate leak existing in a desuperheater is .  | high auxiliary steam pressure  | low auxiliary steam temperature  | reduced feedwater consumption                            | sudden rise in superheater outlet pressure  |  |

|    |      |   |   |   |   |   |  |  |
|----|------|---|---|---|---|---|--|--|
| 13 | 3902 | D | A leak in a desuperheater could be indicated by an .  | increased boiler water compound level in the boiler with the affected desuperheater | increased concentration of dissolved oxygen in boiler water                 | inability to maintain control of boiler water suspended solids                              | inability to maintain proper boiler water pH or phosphate levels |  |
| 13 | 3912 | D | A small leak in the desuperheater of an operating boiler could cause an .   | immediate increase in superheater outlet pressure                                   | immediate decrease in superheater outlet temperature                        | immediate drop in boiler water level  | inability to maintain required boiler water chemistry            |  |
| 13 | 3922 | A | A leak in the internal desuperheater located in one of the two main boilers on a ship can be indicated by a/an .                                  | decrease in the amount of feed treatment chemicals remaining in that boiler         | increase in the amount of feed treatment chemicals contained in that boiler | decrease in the amount of feed treatment required for proper water chemistry of that boiler | increase in the amount of time necessary for priming that boiler |  |
| 13 | 3932 | B | Leakage into an internal desuperheater may be caused by .   | steam scrubbers carrying away   | external corrosion penetrating the desuperheater tube walls                 | chemical feed pipe leaking  | excess lifting of safety valves                                  |  |
| 13 | 3942 | B | Which of the conditions listed could be the cause of chattering in a boiler safety valve?   | Excessive spring tension.   | Loose blowdown ring.  | Excessive blowdown adjustment.  | Scale in the escape piping.                                      |  |
| 13 | 3952 | A | While your vessel is underway at normal speed, a steam drum safety valve develops a significant leak. Your first corrective action should be to . | attempt to reseal the valve using the hand releasing gear                           | secure the boiler and check the valve spring compression                    | inspect the escape piping for binding on the valve body                                     | secure the boiler and blank off the valve flange                 |  |
| 13 | 3962 | A | The MOST common cause of heat blisters developing on boiler generating tubes is due to .  | waterside deposits  | flame impingement   | gas laning  | insufficient water circulation                                   |  |
| 13 | 3972 | D | Blisters developing on boiler tubes can be caused by .  | air in the feedwater  | cold feedwater  | hot feedwater   | waterside scale deposits   |  |
| 13 | 3982 | D | Heat blisters forming on the first row of the generating tubes are caused by .  | fireside deposits   | low water level   | flame impingement   | waterside deposits   |  |

|    |      |   |   |  |  |   |  |  |
|----|------|---|---|--|--|---|--|--|
| 13 | 3992 | A | If a large number of tubes has failed, you can minimize damage to a boiler by .   | securing the fires, steam stops, and relieving boiler pressure | securing the fires, feed stops, and leaving the boiler cut on the line | increasing the feedwater supply to keep the boiler cool                                     | speeding up the forced draft fans to blow steam up the stack |  |
| 13 | 4002 | C | The boiler water level begins to fall very slowly due to the sudden failure of a water wall tube. In response to this situation, you should continue the feedwater supply and immediately . | reduce the firing rate of the boiler                           | secure the forced draft fans   | secure the boiler   | gag the drum safety valves to prevent loss of steam          |  |
| 13 | 4012 | C | If a large number of tubes fail in a steaming boiler, the .   | steam pressure will rise rapidly                               | fires will always be extinguished                                      | water level will drop rapidly   | fires will hiss and sputter                                  |  |
| 13 | 4022 | D | Steam escaping from the boiler casing is a good indication of .   | a leaking tube   | a leaking water wall header  | a leaking handhole gasket   | all of the above are individually correct                    |  |
| 13 | 4032 | B | What is the cause of 'laning' in a boiler tube bank?  | Insufficient airflow   | Excessive slag accumulation on the tubes                               | Low fuel oil pressure   | Reduced furnace volume                                       |  |
| 13 | 4042 | B | Fireside burning of boiler tubes is usually the direct result of .  | soot accumulations on a tube bank                              | overheating due to poor heat transfer                                  | oxygen corrosion  | slag accumulation on the firesides                           |  |
| 13 | 4052 | D | Which of the following repairs should be made to a badly warped boiler tube?  | Heat the tube and use a soft mallet to straighten it.          | Use a hydraulic jack to cold bend the tube.                            | Assure that the warped tube does not touch adjacent tubes and then reroll it in the header. | Replace the tube with a spare, if available, or plug it.     |  |
| 13 | 4062 | D | Waterside abrasion of boiler tubes can be caused by .   | entrained impurities in the boiler water                       | improper bends in the tubes  | oxygen corrosion  | mechanical tube cleaning                                     |  |
| 13 | 4072 | B | The development of pinhole leaks where the boiler tubes enter the water drums and headers, may be evidence of .   | gas laning   | soot corrosion   | excess alkalinity   | excess hydrazine   |  |

|    |      |   |   |   |   |   |   |  |
|----|------|---|---|---|---|---|---|--|
| 13 | 4082 | D | The generating tubes in an operating boiler will overheat and possibly fail when the boiler reaches the end point of .            | evaporation                                 | generation                              | combustion  | circulation   |  |
| 13 | 4092 | D | Boiler tube failures can result from .  | corrosion                                   | overheating                             | mechanical stress                                     | all of the above  |  |
| 13 | 4102 | D | Cratering and water tracking in boiler tubes is caused by .   | burning a fuel with a high vanadium content | baked on slag deposits                  | soot corrosion  | water trapped between tubes and refractory              |  |
| 13 | 4112 | C | If a tube failure results from low water level and the water level can not be maintained in sight in the gage glass, you should . | immediately secure the forced draft fans    | increase the feed pump speed to maximum | immediately secure the fuel oil supply to the burners | blowdown the gage glass to verify a low water condition |  |
| 13 | 4122 | A | Oil or scale deposits on boiler tube walls will cause .   | those tubes to overheat                     | decreased boiler steam pressure         | increased boiler steam pressure                       | an explosion in the boiler                              |  |
| 13 | 4132 | D | Fireside burning of boiler tubes is usually the direct result of .  | high furnace temperatures                   | gas laning in tube banks                | oxygen corrosion of metallic surfaces                 | overheating due to poor heat transfer                   |  |
| 13 | 4152 | D | Fireside burning of boiler superheater tubes is a direct result of .  | combustion gases impinging on the tubes     | fuel droplets striking the hot tubes    | heating carbon steel tubes above 750°F                | tubes becoming steam bound                              |  |
| 13 | 4162 | D | Fireside burning of boiler tubes can be a result of .   | slag deposit                                | improper atomization                    | soot accumulations                                    | waterside deposits                                      |  |
| 13 | 4172 | C | The formation of a pit in the surface of a boiler tube is most likely to occur when .   | waterside deposits are present              | sludge is present                       | the tube metal acts as an anode                       | dissolved minerals are present                          |  |
| 13 | 4182 | B | If a boiler tube bank baffle carries away, or burns through, there will be .  | incomplete combustion                       | localized overheating of the water drum | excessive gas turbulence in the furnace               | fireside burning of boiler tubes                        |  |
| 13 | 4192 | D | If a steaming boiler begins 'panting,' the probable cause is .  | too much air for proper combustion          | excessively high furnace temperature    | excessively cold fuel oil                             | insufficient air for proper combustion                  |  |
| 13 | 4202 | D | Vibration or panting of a boiler can be caused by .   | insufficient air                            | poor mixing of air and oil              | excessive fuel oil temperature                        | all of the above  |  |
| 13 | 4212 | D | Pulsating boiler furnace fires can be caused by .   | low fuel temperature                        | too much air                            | low fuel pressure                                     | too little air  |  |
| 13 | 4222 | B | Panting or rumbling in a boiler furnace is usually caused by .  | too much air                                | not enough air                          | low fuel temperature                                  | low fuel pressure                                       |  |

|    |      |   |   |  |   |   |   |  |
|----|------|---|---|--|---|---|---|--|
| 13 | 4232 | C | If a boiler begins to pant and vibrate you should _____ .   | check the fuel oil service pumps   | secure the fires                                      | increase the air  | reduce the steam demand   |  |
| 13 | 4242 | B | Which actions listed should be taken if a boiler is panting?  | Decrease the air pressure to the burners.  | Increase the air pressure to the burners.             | Decrease the boiler water level.                              | Increase the boiler water level.  |  |
| 13 | 4252 | B | If a boiler is panting, which of the following actions should be taken?                                       | Decrease the air pressure to the burners.  | Increase the air pressure to the burners.             | Increase the fuel oil pressure.                               | Increase the fuel oil temperature.  |  |
| 13 | 4262 | A | To avoid pulsations of the burner flame after rebuilding the boiler burner front tile refractory, _____ .     | the burner tile should be fitted to the throat ring rather than the surrounding brick work | the tile surface should be stippled with a wire brush | the tile surface should be coated with a thin layer of mortar | the vertical face of the tile should be perpendicular to the front casing |  |
| 13 | 4272 | D | Panting in an oil fired marine boiler can be caused by _____ .  | excessive combustion air supply  | low fuel oil temperature                              | fouled burner sprayer plates                                  | insufficient combustion air supply  |  |
| 13 | 4282 | A | If a steaming boiler is not supplied with sufficient air for proper combustion, the _____ .                   | boiler will pant and rumble  | fires will hiss and sputter                           | boiler will smoke white                                       | fires will be too hot   |  |
| 13 | 4292 | C | If a boiler fire is blown out by a flareback, you should immediately _____ .                                  | increase the forced draft blower speed   | start the standby fuel oil pump                       | secure the fuel supply to the boiler burners                  | relight the fires with a torch  |  |
| 13 | 4302 | B | If a major flareback occurs to a boiler, which of the following actions should be immediately taken?          | Secure the forced draft fan.   | Secure the fuel to the burners.                       | Secure all fireroom ventilation.                              | Purge the fuel oil system.  |  |
| 13 | 4312 | B | When a boiler flareback occurs, you should _____ .  | reduce the forced draft blower speed   | close the master fuel oil valve                       | take the boiler off the line                                  | increase the fuel oil supply pressure                                     |  |
| 13 | 4322 | D | Gasket leakage around boiler handholes may be caused by _____ .   | improper positioning of the gasket   | pitted seating surfaces                               | loose dogs  | all of the above  |  |
| 13 | 4332 | D | If while filling the boiler a newly installed gasket on a water-tube handhole plate weeps, you should _____ . | coat the gasket with graphite  | retighten the stud nut with an air wrench             | use a double gasket   | center and tighten with correct size wrench                               |  |

|    |      |   |  |   |  |  |  |  |
|----|------|---|--|---|--|--|--|--|
| 13 | 4342 | A | Which of the listed methods would be MOST effective when repairing a steam cut on a seating surface of a superheater handhole plate? | Filling the cut by welding and then grinding it smooth.                   | Filling the cut with iron cement or plastic steel.                   | Grinding the seating surface and installing an oversized gasket.   | Refacing the surface and over torquing the handhole plate.                   |  |
| 13 | 4352 | B | An indication of a faulty superheater soot blower element is a _____.  | low stack temperature   | low superheater outlet temperature                                   | high superheater outlet temperature  | low fuel oil consumption   |  |
| 13 | 4362 | C | If a soot blower element does not revolve freely, the most likely cause would be _____.  | a seized blower head bearing  | an improper blowing arc cam setting                                  | warpage  | insufficient steam pressure to the soot blower element                       |  |
| 13 | 4372 | C | If an oil fire occurs in the double casing of a steaming boiler, you should _____.   | increase the forced draft fan speed                                       | secure the feedwater supply to the boiler                            | secure the fuel oil supply to the burners  | apply water with a smooth bore nozzle  |  |
| 13 | 4382 | A | Excessive soot accumulations on boiler generating tube surfaces can result in _____.   | high superheater outlet temperature                                       | incomplete combustion in the furnace                                 | reverse circulation of the steam and water mixture   | low stack gas temperature  |  |
| 13 | 4392 | D | Boiler firesides must be kept free of soot accumulations because _____.  | soot interferes with the flow of feedwater                                | the steam drum internals will become clogged                         | the fuel oil heaters will become overloaded  | soot insulates the boiler heating surfaces                                   |  |
| 13 | 4402 | B | An indication of excessive soot accumulation on boiler water tubes and economizer surfaces is _____.                                 | low stack temperature   | high stack temperature   | lower feedwater flow   | high feedwater temperature   |  |
| 13 | 4412 | C | Which of the listed actions should be carried out with the superheater vent valve during the time steam is being raised in a boiler? | The valve must be wide open all the time until the boiler is on the line. | The valve may be closed when all air is vented.                      | The valve may be partially throttled as the pressure increases until the boiler is on the line at which time it is closed. | The valve need only be open if the superheater temperature approaches 850°F. |  |
| 13 | 4422 | C | The terms 'swell' and 'shrink' relate to a change in boiler water level which _____.   | results when the feed rate becomes erratic during maneuvering             | is due to steam bubbles below the surface occupying a smaller volume | results from a change in steam flow or firing rate   | indicates a high chloride concentration in the boiler water                  |  |

|    |      |   |   |   |  |   |  |         |
|----|------|---|---|---|--|---|--|---------|
| 13 | 4432 | B | The boiler wrapper sheet, shown in the illustration, is indicated by arrow .                                      | A   | B  | H   | I  | SG-0007 |
| 13 | 4437 | A | During initial starting of the standby turbine-driven feed pump, which of the listed valves should remain closed? | Pump discharge check valve                                      | Turbine steam supply valve   | Turbine exhaust valve   | Pump suction valve   |         |
| 13 | 4438 | B | No lube oil appearing in the sight glass (bull's eye) of a gravity type system is a positive indication of .      | no oil flowing to the bearings                                  | no oil is overflowing the gravity tank                                 | failure of all lube oil pumps   | the gravity tanks being empty                                  |         |
| 13 | 4442 | C | The boiler superheater shown in the illustration is a/an .  | horizontal U-type   | overdeck convection-type   | vertical U-type   | overdeck integral-type   | SG-0007 |
| 13 | 4452 | A | Regarding the boiler shown in the illustration, the burners are to be placed at .                                 | arrow "F"   | arrow "K"  | arrow "L"   | none of the above  | SG-0007 |
| 13 | 4462 | D | The boiler shown in the illustration, arrow "O" indicates the .   | main generating tubes   | superheater tubes  | screen tubes  | soot blower elements   | SG-0007 |
| 13 | 4472 | A | The components lettered "O" shown in the illustration function to .   | clean soot off the surrounding tubes                            | support the surrounding tubes  | provide viewing of the generating tubes   | acid clean the surrounding tubes during cold plant maintenance | SG-0007 |
| 13 | 4482 | C | The component lettered "J" shown in the illustration serves as a .  | water drum  | support beam   | side water wall header  | screen tube header   | SG-0007 |
| 13 | 4492 | B | The boiler superheater vent, shown in the illustration, is connected to the part labeled ' ' .                    | C   | M  | D   | J  | SG-0007 |
| 13 | 4502 | C | The component labeled "F" as shown in the illustration is .   | one of the retractable soot blower elements                     | a regenerative air heater  | one of the main burner assemblies   | a permanently installed Orsat apparatus                        | SG-0007 |
| 13 | 4512 | B | Component "B" shown in the illustration is properly identified as the .   | drumhead  | wrapper sheet  | tube sheet  | drum crown   | SG-0007 |
| 13 | 4522 | D | The purpose of boiler tube curvature shown in the illustration in the area labeled "L" is to .                    | accommodate an oil burner for separately firing the superheater | compensate for the greater degree of expansion in the superheater area | accommodate an inspection port used to view superheater conditions while steaming | allow for access to the superheater cavity                     | SG-0007 |

|    |      |   |   |  |  |  |   |         |
|----|------|---|---|--|--|--|---|---------|
| 13 | 4532 | A | Which of the devices listed is indicated by arrow "H" shown in the illustration?                                  | Economizer                                       | Steam soot blowers   | Overdeck superheater   | Air heater  | SG-0008 |
| 13 | 4542 | C | The tubes projecting horizontally through the generating tube bank shown in the illustration are .                | through stays                                    | generator support tubes  | soot blower elements   | steam smothering lines  | SG-0008 |
| 13 | 4552 | C | Arrow "B" shown in the illustration indicates the .   | regenerative air heater                          | retractable soot blower opening  | combustion air inlet   | uptakes   | SG-0008 |
| 13 | 4562 | D | The tube sheet shown in the illustration is indicated by the letter ' ' .   | A  | B  | I  | K   | SG-0008 |
| 13 | 4572 | A | Where is the superheater located in the boiler shown in the illustration?   | G  | H  | I  | J   | SG-0008 |
| 13 | 4582 | D | Which of the devices listed is shown in the boiler illustration?  | Retractable soot blower                          | Separately fired superheater   | Regenerative air heater  | Integral or interdeck superheater                               | SG-0008 |
| 13 | 4592 | A | The boiler shown in the illustration has its screen tubes connecting the steam drum and the component label ' ' . | I  | G  | F  | D   | SG-0008 |
| 13 | 4602 | D | What type of boiler superheater is shown in the illustration?   | Overdeck convection tube                         | Vertical U-tube  | Overdeck integral tube   | Horizontal U-tube   | SG-0008 |
| 13 | 4612 | D | In the boiler shown in the illustration, the arrow "E" indicates a .  | water wall tube                                  | recirculating tube   | support tube   | downcomer   | SG-0008 |
| 13 | 4622 | B | The screen tubes shown in the illustration are indicated by arrow ' ' .   | F  | J  | H  | D   | SG-0008 |
| 13 | 4632 | D | The boiler screen tubes shown in the illustration connect the .   | upper front header and water drum                | upper front header and steam drum                                      | lower front header and steam drum                                  | steam drum and mud drum   | SG-0008 |
| 13 | 4642 | B | In the boiler shown in the illustration, the arrow "C" indicates a .  | downtake nipple                                  | water wall header  | sliding foot   | recirculating header  | SG-0008 |
| 13 | 5702 | C | Why are two fuel oil heaters "E" provided in the fuel oil system shown in the illustration?                       | Each heater supplies fuel to a different boiler. | To allow fuel of different temperatures to be provided to each boiler. | To provide a backup in case one of the heaters becomes inoperable. | Two heaters are necessary when both boilers steam at full load. | SG-0009 |

|    |      |   |  |  |   |  |   |         |
|----|------|---|--|--|---|--|---|---------|
| 13 | 5712 | A | The fuel oil has been raised to the proper temperature for the straight mechanical atomization system of the boiler shown in the illustration, and is ready to light off. Which of the valves listed must be closed just prior to igniting the fuel? | J  | G   | A  | H   | SG-0009 |
| 13 | 5722 | C | What type of boiler is shown in the illustration?  | A downfired two furnace boiler with a vertical superheater, economizer, waterwalls and downcomers. | A Scotch boiler with a horizontal superheater, economizer, waterwalls and downcomers. | A two drum single furnace boiler with an interdeck superheater, an economizer, water walls and downcomers. | A sectional header boiler with a superheater, economizer, and water walls and downcomers. | SG-0008 |
| 13 | 5732 | B | One function of the component labeled "C" shown in the illustration is to  | act as a foundation beam to support the weight of the boiler                                       | provide a collecting area for sediment and sludge                                     | cool the refractory  | form a soot seal in the lower corner of the boiler casing                                 | SG-0008 |
| 13 | 5742 | D | The fittings labeled "P" shown in the illustration are known as the  | main steam stops   | main steam outlets  | desuperheater outlets  | safety valve nozzles  | SG-0011 |
| 13 | 5752 | B | One function of the internal fitting labeled "C" shown in the illustration is to   | reduce high water level in an emergency  | pass generated steam to the superheater   | remove scum from the water surface   | distribute feedwater throughout the drum  | SG-0011 |
| 13 | 5772 | A | Which of the listed types of safety valves is shown in the illustration?   | Huddling chamber type  | Jet flow type   | Nozzle reaction type   | Pressure-loaded type  | SG-0018 |
| 13 | 5782 | C | What is the function of valve "H" of the system shown in the illustration?   | To regulate the amount of fuel burned.   | To prevent fuel backflow from the manifold.   | To provide for quick fuel shut off.  | To recirculate fuel when lighting off.  | SG-0009 |
| 13 | 5792 | C | At which point of the blistered boiler tube shown in illustration will the temperature be the greatest?  | A  | B   | C  | D   | SG-0012 |
| 13 | 5802 | C | The device shown in the illustration is a/an   | air ejector  | deaerator   | desuperheater  | eductor   | SG-0013 |
| 13 | 5812 | D | Which of the symbols shown in the illustration is used to identify a stop-check valve?   | A  | B   | C  | D   | SG-0014 |

|    |      |   |  |   |   |   |   |         |
|----|------|---|--|---|---|---|---|---------|
| 13 | 5822 | B | Which of the problems listed could occur if the sliding-foot bearing surfaces, shown in the illustration, are not properly lubricated? | Deformation of the tank top.  | Failure of pressure parts.  | Corrosion of the pedestal.  | Failure of main steam piping due to misalignment.   | SG-0015 |
| 13 | 5832 | B | In the system illustrated the valves at point "A" are .  | swing check/ stop valves  | stop-check/ stop valves   | gauge valves/ drain valves  | globe valves/ gate valves                           | SG-0005 |
| 13 | 5842 | D | The popping pressure of the safety valve, shown in the illustration, is controlled by the .  | seat bushing adjustment   | feather guide retaining ring  | adjusting ring position   | amount of spring compression                        | SG-0018 |
| 13 | 5852 | B | The boiler downcomers shown in the illustration are .  | exposed to the radiant heat of the furnace                            | located away from furnace heat  | installed directly adjacent to the superheater  | supported by refractory                             | SG-0008 |
| 13 | 5862 | D | Which of the following statements concerning the safety valve shown in the illustration is correct?                                    | When the drop lever is raised, the safety valve spring is compressed. | When a gag is placed on the valve, it should be installed only finger tight to prevent damage to the spindle. | The adjusting ring should be firmly locked by the ring pin at all times except when blowdown is being adjusted. | All of the above.                                   | SG-0018 |
| 13 | 5872 | B | To adjust the amount of safety valve blowdown, as shown in the illustration, you would reposition the part indicated by arrow ' .'     | A   | B   | C   | D   | SG-0018 |
| 13 | 5873 | A | When starting a turbogenerator in an automated plant, you must provide lube oil pressure to the unit by means of a/an .                | auxiliary lube oil pump   | line from the other generator   | line from the gravity tank  | line from the main lube oil pump                    |         |
| 13 | 5882 | C | To change the lifting pressure of the safety valve shown in the illustration, you must readjust the part labeled .                     | A   | B   | C   | D   | SG-0018 |
| 13 | 5891 | D | Boiler efficiency and its ability to absorb heat is limited by the need to .   | maintain an excess of CO during transient firing rates                | prevent excess air density at low load conditions   | protect the safety valves from excessive temperature  | maintain uptake gas temperature above the dew point |         |

|    |      |   |   |   |   |  |   |         |
|----|------|---|---|---|---|--|---|---------|
| 13 | 5892 | B | To change the amount of blowdown of the safety valve shown in the illustration, you must change the position of the .   | feather guide                             | adjusting ring                                  | compression screw                            | huddling chamber  | SG-0018 |
| 13 | 5902 | D | To increase the popping pressure of the safety valve shown in the illustration, .   | raise the adjusting ring                  | lower the adjusting ring                        | loosen the compression screw                 | tighten the compression screw                             | SG-0018 |
| 13 | 5912 | C | On a boiler with a 775 MAWP, the drum safety valve shown in the illustration is set to lift at 650 psi and reseal at 630 psi. To increase the lifting pressure to 700 psi, but maintain the previous amount of blowdown, turn the compression screw . | in the clockwise direction only           | in the counterclockwise direction only          | clockwise and lower adjusting ring           | counterclockwise and lower the adjusting ring             | SG-0018 |
| 13 | 5922 | B | When placing a gag on the safety valve shown in the illustration, it is necessary to remove the .   | compression screw                         | cap   | upper spring washer                          | all of the above  | SG-0019 |
| 13 | 5932 | B | The principal means of increasing the amount of blowdown for safety valve shown in the illustration, remove the set screw labeled .   | "A" and raise the position of the ring    | "A" and lower the position of the ring          | "B" and raise the position of the ring       | "B" and lower the position of the ring                    | SG-0019 |
| 13 | 5952 | A | Which area shown in the illustration will offer the most resistance to heat transfer from the fireside to the waterside of a boiler tube?   | B   | C   | D  | E   | SG-0017 |
| 13 | 5962 | B | After patching refractory with plastic firebrick, holes are poked in the patch on 1 1/2 inch centers in order to .  | prevent spalling                          | vent moisture                                   | allow for expansion                          | prevent slag buildup                                      |         |
| 13 | 5972 | D | To prevent a small plastic refractory wall patch repair from falling into the furnace of a D-type boiler, you should .  | attach anchor bolts to the furnace casing | reinforce the patch with fine mesh metal screen | mix the plastic with concrete prior to using | undercut the existing brick around the area to be patched |         |
| 13 | 5978 | B | Circulation in a water-tube boiler is caused by the difference in the .   | area and length of the water-tubes        | densities of the circulating water              | heights of the boiler drum                   | angle of inclination of the tubes                         |         |

|    |      |   |  |  |  |  |  |  |
|----|------|---|--|--|--|--|--|--|
| 13 | 5979 | D | To stop the rotor of a main turbine while underway at sea you should _____ .                                       | apply the pronny brake                             | tighten the stern tube packing gland               | secure all steam to the turbine                      | admit astern steam to the turbine after securing the ahead steam |  |
| 13 | 5980 | C | If an operating propulsion unit requires excessive quantities of gland sealing steam, you should suspect a _____ . | vacuum leak in the condenser shell                 | flooded main condenser hotwell                     | worn or damaged labyrinth packing                    | restriction in the gland leak off piping                         |  |
| 13 | 5982 | D | When water washing a boiler, the proper sequence for washing the sections should be the _____ .                    | generating tubes, superheater, and then economizer | superheater, economizer, and then generating tubes | screen tubes, generating tubes, and then superheater | economizer, superheater, generating, and then screen tubes       |  |